



1/5



VS8111

VISTO WI-FI EXTERNAL UNIT. VIP SYSTEM



Wi-Fi video entry external unit for use in Comelit ViP systems, complete with adapter allowing use of the power supply for the existing bell (12-20 VAC or 12-33 VDC) and allowing interfacing with the existing bell. Depending on the system configuration, you can receive video entry phone calls on ViP monitors or directly on smartphones and tablets via the Comelit app. With the Comelit app, you are always in touch with what is going on at your home, whether you are in town or even in another country.



Maximum absorption (W)

2/5



VS8111

VISTO WI-FI EXTERNAL UNIT. VIP SYSTEM	
	GENERAL DATA
Туре	Monoblock
Height (mm)	136
Width (mm)	47
Depth (mm)	32
Product color	Dark Graphite RAL9011
Wall-mounted	Yes
COMPATIBLE SYSTEMS	
ViP	Yes
AUDIO FEATURES	
Technologies implemented	Full-Duplex, Echo canceling, Noise reduction
CAMERA FEATURES	
Camera	Colours
Sensor type	1/4" CMOS
Lens optical dimensions (mm)	1.6
Angle of view (H x V - °)	170 (diagonal)
Sensitivity (lux)	2
Video resolution (H x V - pixel)	
Video resolution (H x V - pixel) Video compression	H.264
Video compression	H.264 CTRICAL CHARACTERISTICS
Video compression	
Video compression	CTRICAL CHARACTERISTICS

HARDWARE FEATURES	
Call type	Push-buttons
Type of buttons	Mechanical

Technical specifications are subject to change without prior notice and refer to the latest version of the product released.

6





VS8111

VISTO WI-FI EXTERNAL UNIT. VIP SYSTEM

HARDWARE FEATURES		
Number of push-buttons (n°)	1	
Clamps	+ - NO C	
Removable terminals	Yes	
Number of outputs (n°)	1	
Type of outputs	Relay (C-NO, 1A@30VDC)	

NETWORK AND COMMUNICATION PROTOCOLS

Type of Wi-Fi connection

2.4 GHz

ENVIRONMENTAL AND COMPLIANCE FEATURES		
IP protection rating	IP54	
Operating temperature (°C)	-25 ÷ 55	
Operating humidity (RH max) (%)	0 ÷ 75	
Environmental class	III	
CE certifications	RoHS II - 2011/65/UE (EN 50581:2012), RED 2014/53/UE (EN 60950-1:2006+A11:2009+A1:2010+A12:2011, +A2:2013, EN 62311:2008, EN 61000-6-1:2007, EN 61000-6-3:2007 + A1:2011, ETSI EN 301 489-1 V2.2.0, ETSI EN 301 489-17 V3.2.0, ETSI EN 300 328 V2.1.1)	

MAIN FUNCTIONS		
Visual indications of system status	Yes	
GENERAL FEATURES		





VS8111

VISTO WI-FI EXTERNAL UNIT. VIP SYSTEM		
		ACCESSORIES
	3534	24VDC POWER SUPPLY UNIT WITH EU-UK-US PLUG
		Power supply for Visto smart doorbell, input voltage 110÷240 VAC, output voltage 24 VDC. Interchangeable plugs for the European, English and American markets supplied.
	3528	ADAPTER PLATE FOR VISTO KIT
		Plate for the installation of the Visto smart doorbell on existing recessed boxes type 503 (horizontal and vertical) with interaxis of 83.5mm, square boxes with interaxis of 62mm, box type 502/German/round with interaxis of 60mm. Made of PMMA, white color.
1	3526	UP-DOWN ADJUSTABLE BRACKET FOR VISTO
		Up/down adjustable bracket for Visto smart doorbell, 10° vertical inclination, plastic material, silver mist RAL9006 colour.
	3532	ADDITIONAL WIRELESS BELL FOR VISTO KIT
<i>₽.9.9</i>		Wireless additional bell for Visto smart doorbell, 433 MHz operating frequency, adjustable volume, various selectable melodies, powered by 2 batteries (size AA, 1.5V, not included), wall mounting, white/silver color.
	3527W	CLOUD WHITE COVER FOR VISTO EXTERNAL UNIT
		Cover replacement for Visto smart doorbell. Plastic material, cloud white RAL9003 color.

Technical specifications are subject to change without prior notice and refer to the latest version of the product released.



5/5



VS8111

VISTO WI-FI EXTERNAL UNIT. VIP SYSTEM		
		ACCESSORIES
	3527S	SILVER MIST COVER FOR VISTO EXTERNAL UNIT Cover replacement for Visto smart doorbell. Plastic material,silver mist RAL9006 color.
	3527B	DARK GRAPHITE COVER FOR VISTO EXTERNAL UNIT Cover replacement for Visto smart doorbell. Plastic material, dark graphite RAL9011 color.
	3525	LEFT-RIGHT ADJUSTABLE BRACKET FOR VISTO Left/right adjustable bracket for Visto smart doorbell, 20° horizontal inclination, plastic material, silver mist RAL9006 colour.
	3522	ADAPTER FOR WI-FI VISTO KIT Voltage adapter for Visto smart doorbell. Input voltage 12÷20 VAC, output for powering the Visto smart doorbell. It is possible to control already existing bells. Case in plastic material, dark graphite RAL9011 color. Dimensions (W x H x D): 59 x 40 x 14mm.
	CONAL02A	Power supply connector w/ female terminals/jack Connector for power supply, 2 screw terminals, female jack type

connector.