



3001NA

ALUMINIUM AUDIO ENTRANCE PANEL, 1 BUTTON



Door-entry phone entrance panel with front plate in 4 mm thick anodised aluminium, buttons with 16 mm diameter, impact-proof grille. Complete with flush-mounted box and anti-intrusion screws. Equipped with a module holder and bulb socket for festoon bulbs (not supplied), diameter 6.3 x 39 mm. The entrance panel should be finished with a door-entry phone audio speaker unit depending on the wiring system used. 1 button, 1 wire. Plate dimensions 135x224x4 mm. Box dimensions 115x204x55 mm. 1 bulb socket



3001NA

ALUMINIUM AUDIO ENTRANCE PANEL, 1 BUTTON

MAIN FEATURES

| | |
|------------------------------------|------|
| Audio system: | Yes |
| Audio/video system: | Yes |
| Flush-mounted: | Yes |
| Vandal Resistant rating (IK code): | IK08 |

HARDWARE SPECIFICATIONS

| | |
|-----------------------------|----|
| Sensitive Touch technology: | No |
|-----------------------------|----|

GENERAL DATA

| | |
|----------------------|--------|
| Product height (mm): | 224,03 |
| Product width (mm): | 134,87 |
| Product depth (mm): | 4,06 |

COMPATIBILITY

| | |
|-----------------------------------|-----|
| Simplebus Top audio/video system: | Yes |
| Simplebus 2 audio system: | Yes |
| Vip system: | Yes |
| Traditional system: | Yes |



3001NA

ALUMINIUM AUDIO ENTRANCE PANEL, 1 BUTTON

ACCESSORIES



1250IA

ACCESSORY FOR MOUNTING IKALL AUDIO UNITS ON SING.-PLATE PAN.

Accessory allowing the installation and use of Ikall audio modules part. 1622, 1622VC, 1622VCF and 1682 on single-plate panels and N, AV/4 series. Fitted with a voltage reducer for powering festoon lamps if used with power supply unit 1595 or 1207.