



3008NV

ALUMINIUM VIDEO ENTRANCE PANEL, 8 BUTTONS



Door-entry monitor entrance panel with front plate in 4 mm thick anodised aluminium, buttons with 16 mm diameter, impact-proof grille. Complete with flush-mounted box and anti-intrusion screws. Equipped with a module holder and bulb socket for festoon bulbs (not supplied), diameter 6.3 x 39 mm. The entrance panel should be finished with a door-entry monitor speaker unit depending on the wiring system used. 8 buttons, 2 wires. Plate dimensions 180x293x4 mm. Box dimensions 156x275x55 mm. 1 bulb socket



3008NV

ALUMINIUM VIDEO ENTRANCE PANEL, 8 BUTTONS

MAIN FEATURES

Audio system:	Yes
Audio/video system:	Yes
Flush-mounted:	Yes

HARDWARE SPECIFICATIONS

Sensitive Touch technology:	No
-----------------------------	----

GENERAL DATA

Product height (mm):	293,12
Product width (mm):	180,09
Product depth (mm):	4,06

COMPATIBILITY

Simplebus Top audio/video system:	Yes
Simplebus 2 audio system:	Yes
Vip system:	Yes
Traditional system:	Yes



3008NV

ALUMINIUM VIDEO ENTRANCE PANEL, 8 BUTTONS

ACCESSORIES



1250IV

ACCESSORY FOR A/V IKALL GROUP ASSEMBLING

Accessory allowing the installation and use of Ikall audio/video modules part. 4680, 4680C, 4680K, 4680KC, 4681, 4682C, 4682HC, 4682KC, 4682HKC, 4675 and 4673 on single-plate entrance panels. Fitted with a voltage reducer for powering festoon lamps if used with power supply unit 1595 or 1207.