



3010NA

ALUMINIUM AUDIO ENTRANCE PANEL, 10 BUTTONS



Door-entry phone entrance panel with front plate in 4 mm thick anodised aluminium, buttons with 16 mm diameter, impact-proof grille. Complete with flush-mounted box and anti-intrusion screws. Equipped with a module holder and bulb socket for festoon bulbs (not supplied), diameter 6.3 x 39 mm. The entrance panel should be finished with a door-entry phone audio speaker unit depending on the wiring system used. 10 buttons, 2 wires. Plate dimensions 180x316x4 mm. Box dimensions 155x298x55 mm. 1 bulb socket



3010NA

ALUMINIUM AUDIO ENTRANCE PANEL, 10 BUTTONS

MAIN FEATURES

Audio system:	Yes
Audio/video system:	Yes
Flush-mounted:	Yes
Vandal Resistant rating (IK code):	IK08

HARDWARE SPECIFICATIONS

Sensitive Touch technology:	No
-----------------------------	----

GENERAL DATA

Product height (mm):	315,98
Product width (mm):	180,09
Product depth (mm):	4,06

COMPATIBILITY

Simplebus Top audio/video system:	Yes
Simplebus 2 audio system:	Yes
Vip system:	Yes
Traditional system:	Yes



3010NA

ALUMINIUM AUDIO ENTRANCE PANEL, 10 BUTTONS

ACCESSORIES



1250IA

ACCESSORY FOR MOUNTING IKALL AUDIO UNITS ON SING.-PLATE PAN.

Accessory allowing the installation and use of Ikall audio modules part. 1622, 1622VC, 1622VCF and 1682 on single-plate panels and N, AV/4 series. Fitted with a voltage reducer for powering festoon lamps if used with power supply unit 1595 or 1207.