



### 3014NV

## ALUMINIUM VIDEO ENTRANCE PANEL, 14 BUTTONS



Video entry phone entrance panel with 4 mm thick anodised aluminium front plate, 16 mm diameter buttons, impact-proof grille. Complete with flush-mount box and anti-intrusion screws. Equipped with module holder and bulb sockets (without bulb) for festoon bulbs with a diameter of 6.3 x 39 mm. The keypad should be completed with an audio/video unit appropriate for type of the wiring system. 14 buttons, 2 rows. Plate dimensions: 180x362x4 mm. Box dimensions: 156x344x55 mm. 1 lamp socket



## 3014NV

# ALUMINIUM VIDEO ENTRANCE PANEL, 14 BUTTONS

### MAIN FEATURES

Audio system:	Yes
Audio/video system:	Yes
Flush-mounted:	Yes

### HARDWARE SPECIFICATIONS

Sensitive Touch technology:	No
-----------------------------	----

### GENERAL DATA

Product height (mm):	361,95
Product width (mm):	180,09
Product depth (mm):	4,06

### COMPATIBILITY

Simplebus Top audio/video system:	Yes
Simplebus 2 audio system:	Yes
Vip system:	Yes
Traditional system:	Yes



**3014NV**

## ALUMINIUM VIDEO ENTRANCE PANEL, 14 BUTTONS

### ACCESSORIES



#### **1250IV**

#### ACCESSORY FOR A/V IKALL GROUP ASSEMBLING

Accessory allowing the installation and use of Ikall audio/video modules part. 4680, 4680C, 4680K, 4680KC, 4681, 4682C, 4682HC, 4682KC, 4682HKC, 4675 and 4673 on single-plate entrance panels. Fitted with a voltage reducer for powering festoon lamps if used with power supply unit 1595 or 1207.