



## 3020NA

# ALUMINIUM AUDIO ENTRANCE PANEL, 20 BUTTONS



Entry phone entrance panel with 4 mm thick anodised aluminium front plate, 16 mm diameter buttons, impact-proof grille. Complete with flush-mount box and anti-intrusion screws. Equipped with module holder and bulb sockets (without bulb) for festoon bulbs with a diameter of 6.3 x 39 mm. The keypad should be completed with an audio/video unit appropriate for type of the wiring system. 20 buttons, 2 rows. Plate dimensions: 180x431x4 mm. Box dimensions: 156x413x55 mm. 1 lamp socket



## 3020NA

# ALUMINIUM AUDIO ENTRANCE PANEL, 20 BUTTONS

### MAIN FEATURES

|                                    |      |
|------------------------------------|------|
| Audio system:                      | Yes  |
| Audio/video system:                | Yes  |
| Flush-mounted:                     | Yes  |
| Vandal Resistant rating (IK code): | IK08 |

### HARDWARE SPECIFICATIONS

|                             |    |
|-----------------------------|----|
| Sensitive Touch technology: | No |
|-----------------------------|----|

### GENERAL DATA

|                      |        |
|----------------------|--------|
| Product height (mm): | 431,04 |
| Product width (mm):  | 180,09 |
| Product depth (mm):  | 4,06   |

### COMPATIBILITY

|                                   |     |
|-----------------------------------|-----|
| Simplebus Top audio/video system: | Yes |
| Simplebus 2 audio system:         | Yes |
| Vip system:                       | Yes |
| Traditional system:               | Yes |



**3020NA**

## ALUMINIUM AUDIO ENTRANCE PANEL, 20 BUTTONS

### ACCESSORIES



#### **1250IA**

ACCESSORY FOR MOUNTING IKALL AUDIO UNITS ON SING.-PLATE PAN.

Accessory allowing the installation and use of Ikall audio modules part. 1622, 1622VC, 1622VCF and 1682 on single-plate panels and N, AV/4 series. Fitted with a voltage reducer for powering festoon lamps if used with power supply unit 1595 or 1207.