



3036NA

ALUMINIUM AUDIO ENTRANCE PANEL, 36 BUTTONS



Entry phone entrance panel with 4 mm thick anodised aluminium front plate, 16 mm diameter buttons, impact-proof grille. Complete with flush-mount box and anti-intrusion screws. Equipped with module holder and bulb sockets (without bulb) for festoon bulbs with a diameter of 6.3 x 39 mm. The keypad should be completed with an audio/video unit appropriate for type of the wiring system. 34 buttons, 4 rows. Plate dimensions: 340x385x4 mm. Box dimensions: 320x365x55 mm. 1 lamp socket

The technical specifications are subject to variations without warning.



3036NA

ALUMINIUM AUDIO ENTRANCE PANEL, 36 BUTTONS

MAIN FEATURES	
Audio system:	Yes
Audio/video system:	Yes
Flush-mounted:	Yes
Vandal Resistant rating (IK code):	IK08

HARDWARE SPECIFICATIONS

Sensitive Touch technology:	
-----------------------------	--

GENERAL DATA	
Product height (mm):	385,06
Product width (mm):	340,11
Product depth (mm):	4,06

No

COMPATIBILITY	
Simplebus Top audio/video system:	Yes
Simplebus 2 audio system:	Yes
Vip system:	Yes
Traditional system:	Yes



3036NA

ALUMINIUM AUDIO ENTRANCE PANEL, 36 BUTTONS

ACCESSORIES

1250IA

ACCESSORY FOR MOUNTING IKALL AUDIO UNITS ON SING.-PLATE PAN.

Accessory allowing the installation and use of Ikall audio modules part. 1622, 1622VC, 1622VCF and 1682 on single-plate panels and N, AV/4 series. Fitted with a voltage reducer for powering festoon lamps if used with power supply unit 1595 or 1207.