



3048NA











Entry phone entrance panel with 4 mm thick anodised aluminium front plate, 16 mm diameter buttons, impact-proof grille. Complete with flush-mount box and anti-intrusion screws. Equipped with module holder and bulb sockets (without bulb) for festoon bulbs with a diameter of 6.3 x 39 mm. The keypad should be completed with an audio/video unit appropriate for type of the wiring system. 48 buttons, 4 rows. Plate dimensions: 340x454x4 mm. Box dimensions: 320x434x55 mm. 1 lamp socket





3048NA

ALUMINIUM AUDIO ENTRANCE PANEL, 48 BUTTONS

MAIN FEATURES	
Audio system:	Yes
Audio/video system:	Yes
Flush-mounted:	Yes
Vandal Resistant rating (IK code):	IK08

HARDWARE SPECIFICATIONS	
Sensitive Touch technology:	No

GENERAL DATA	
Product height (mm):	453,9
Product width (mm):	340,11
Product depth (mm):	4,06

COMPATIBILITY	
Simplebus Top audio/video system:	Yes
Simplebus 2 audio system:	Yes
Vip system:	Yes
Traditional system:	Yes





3048NA

ALUMINIUM AUDIO ENTRANCE PANEL, 48 BUTTONS

ACCESSORIES

1250IA

ACCESSORY FOR MOUNTING IKALL AUDIO UNITS ON SING.-PLATE PAN.



Accessory allowing the installation and use of lkall audio modules part. 1622, 1622VC, 1622VCF and 1682 on single-plate panels and N, AV/4 series. Fitted with a voltage reducer for powering festoon lamps if used with power supply unit 1595 or 1207.