



4680CW

D&N WIDE COLOUR A/V UNIT. IKALL SERIES SIMPLEBUS



Audio/video unit with terminal block, Simplebus Color system, complete with colour camera with 2.3 mm lens and IR illumination. Digital audio management system with Echo-cancelling, watertight loudspeaker and electret microphone, loudspeaker volume can be adjusted from the front. Complete with microprocessor and dip-switch with 8 positions for programming calls to users. Programmable audiovisual indications to comply with DDA. 33 VDC power supply via power supply unit part. 1595. On-board electronic lock-release function (3A), plus C-NC-NO 10A relay contacts. Compatible with all SBTOP functions and products. Allows call addressing up to 120000 users. Timed door opening and door open visualization. To add in the audio-video modules with 0, 1 and 2 buttons. Dimensions: 102x55x38 mm.


4680CW
D&N WIDE COLOUR A/V UNIT. IKALL SERIES SIMPLEBUS
MAIN FEATURES

Audio/video system:	Yes
Audio/video system:	Yes
Camera:	Colors
Diagonal viewing angle (°):	105
Type of sensor:	
Horizontal resolution (TVL):	520
Minimum illumination (lux):	0,07
Lens size (mm):	2,3
Clamps:	L L V+V- RTE DO PR GND SE COM NC NO
Microphone:	Yes
Microphone volume control:	Yes
Loudspeaker volume control:	Yes
Signal/noise ratio (dB):	53

FUNCTIONS

Key button function:	Yes
----------------------	-----

HARDWARE SPECIFICATIONS

Visual signalling:	Yes
Acoustic signalling:	Yes
Speech synthesis:	Yes

SETTINGS

Loudspeaker volume control:	Yes
Microphone volume control:	Yes

GENERAL DATA

Product height (mm):	55
Product width (mm):	104
Product depth (mm):	35

COMPATIBILITY

Simplebus Top audio/video system:	Yes
-----------------------------------	-----

ELECTRICAL SPECIFICATIONS

Door release (dry contact bridge):	Yes
------------------------------------	-----



4680CW

D&N WIDE COLOUR A/V UNIT. IKALL SERIES SIMPLEBUS

ELECTRICAL SPECIFICATIONS

Door release (direct current output):

Yes