



#### 4682HC



Audio-video unit for ViP system including terminal block complete with front-adjustable mini lens colour camera, LED camera lighting. Complete with terminal block and digital audio management system with Eco-cancelling, watertight loudspeaker and electret microphone, loudspeaker volume adjustable from the front. For fitting in modules: art. 33410, 33411 and 33412. Dimensions: 102x55x38 mm.



#### 4682HC

## COL.AUD/VID UNIT FOR VIP SYST., IKALL SERIES.H264

MAIN FEATURES	
Audio/video system:	Yes
Camera:	Colors
Video encoding:	H.264
Type of sensor:	1/3" CCD
Minimum illumination (lux):	0,23
Lens size (mm):	3,6
Camera orientation:	Yes
Power supply voltage:	÷ 33
Clamps:	TX- TX+RX- RX+V- V+RTE GND SE COM NC NO
Microphone:	Yes
Microphone volume control:	Yes
Loudspeaker:	Yes
Loudspeaker volume control:	Yes
Operating temperature (°C):	-25 ÷ 55

	FOIFICATIONS.
SOFTWARE/FIRMWARE SPI	ECIFICATIONS

Video resolution HxV (mm): 500x582

## FUNCTIONS

Speech synthesis:

Key button function:

HARDWARE SPECIFICATIONS	
Visual signalling:	Yes
Acoustic signalling:	Yes

Yes

GENERAL DATA	
Product height (mm):	55
Product width (mm):	102
Product depth (mm):	38

## COMPATIBILITY

Vip system:

CONNECTIVITY	
Ethernet ports:	1



### 4682HC

# COL.AUD/VID UNIT FOR VIP SYST., IKALL SERIES.H264

ELECTRICAL SPECIFICATIONS	
Door release (dry contact bridge):	Yes
Door release (direct current output):	Yes