

VIDEO DOOR ENTRY SYSTEMS & KITS KIT VIDEO IP

1/3 - OVERVIEW



4894HIM





Single-family video door entry external unit for ViP system with Ikall Metal entrance panel. The kit comprises: 1 flush-mounted box Art. 3110/1, 1 silver coloured frame Art. 3311/1S, 1 module with 1 button art. 33411M and 1 colour audio/video unit Art. 4682HKD. The external unit is coded with ViP address 100 and the button on module Art. 33411M sends the call to ViP address 1. Compatible with H264 video format



VIDEO DOOR ENTRY SYSTEMS & KITS KIT VIDEO IP

4894HIM

EXTERNAL UNIT FOR VIP KIT - IKALL METAL H264

MAIN FEATURES		
Audio/video system:	Yes	
Flush-mounted:	Yes	
Type of sensor:	1/3" CCD	
Lens size (mm):	3,6	
Minimum colour lighting (lux):	0,23	
Video resolution (H x V - pixel):		
Video encoding:	H.264	
Power supply:	33VDC	
Microphone volume control:	Yes	
Loudspeaker volume control:	Yes	
Operating temperature (°C):	-25 ÷ 55	
IP protection rating (IP code):	IP54	

SUFTWARF/FIRMWARL SELVITUATION	SOFTW	ARE/FIRMWARE SPECIFICATIONS
--------------------------------	-------	-----------------------------

IP assignment: AutoIP,	, DHCP, Static IP
------------------------	-------------------

FUNCTIONS

Key button function:

HARDWARE SPECIFICATIONS		
Visual signalling:	Yes	
Acoustic signalling:	Yes	
Speech synthesis:	Yes	

GENERAL DATA	
Height (mm):	125
Width (mm):	125
Depth (mm):	37,5

COMPATIBILITY Vip system: Yes

CONNECTIVITY	
Ethernet ports:	1



VIDEO DOOR ENTRY SYSTEMS & KITS KIT VIDEO IP

4894HIM

EXTERNAL UNIT FOR VIP KIT - IKALL METAL H264

ACCESSORIES

4682HKD

HD COLOR AV UNIT FOR IKALL KIT. VIP



ViP system audio/video unit complete with colour video camera. Maximum resolution 1280x720 pixels. Recording angle 110° (H) - 80° (V). LED camera lighting. Complete with terminal block and digital audio management system with Echo-cancellation, watertight loudspeaker and electret microphone; loudspeaker volume can be adjusted via software programming. Programmable audiovisual functions for users with disabilities. Standard POE audio/video unit but if necessary 33 Vdc power supply can be used via Art. 1595. Compatible with H.264 video format. Audio/video unit pre-programmed with ViP address 100 and call button with ViP address 1. Dimensions (W x H x D): 102x55x38 mm.

33411M

IKALL METAL VIDEO MODULE - 1 BUTTON



Module designed for audio/video speaker unit, with stainless steel finish. Nameplates with LED lighting (options: blue, white or off). To be fitted with a suitable video entry speaker unit depending on the cabling system used. Dimensions 112x89.5x32 mm.

3311/1\$

IKALL SERIES 1-MODULE HOLDER FRAME, SILVER FRAME

Made of die-cast aluminium and coated with special weather-resistant paint. 1 module. Silver colour. Dimensions 125x125x37,5mm



3110/1

MODULE-HOLDER FRAME WITH FINISHING FRAME

Module-holder frame with finishing frame. 1 module. Dimensions 118x118x45 mm