



6228W

EASYCOM SIMPLEBUS UNIT - WHITE



Hands-free door-entry phone with electronic call, call volume adjustment, privacy service, loudspeaker volume adjustment and conversation privacy. Fitted as standard with 3 buttons for audio operation, with audio active indicator LED, lockrelease command and command for actuator Art. 1256. The buttons can be configured differently for switchboard call and actuator functions. Allows floor door call and call repetition management. Complete with dip-switch with 8 positions for selection of the desired user code. Door-entry phone for use in mixed audio/video Simplebus 1 and Simplebus 2 systems or in Simplebus KITS. Intercom function (to devices with the same address) in kit and Simplebustop systems. Fitted with distribution terminal art. 1214/2C. It is compatible with all SBTOP functions and products. Allows direct intercommunication between users with the same address (without the aid of an interface or porter switchboard), separate call to main switchboard, secondary switchboard and guardian door-entry phone. Colour: white. Dimensions: 90x160x28 mm.


6228W

EASYCOM SIMPLEBUS UNIT - WHITE

MAIN FEATURES

Audio system:	Yes
Audio/video system:	Yes
Flush-mounted:	No
Wall-mounted:	Yes
Desk base-mounted:	Yes
Hands-free function:	Yes
Induction loop function:	No
Sensitive Touch technology:	No
Total buttons:	3

FUNCTIONS

Actuator control function:	Yes
Switchboard call function:	Yes
Priority calls:	Yes
Intercom function:	Yes
Selective intercom call:	Yes
Call to multiple addresses:	Yes
Privacy function:	Yes
Doctor:	Yes
Redial:	Yes
Floor door call function:	Yes
Electronic bell:	Yes
Customisable ringtone:	No
Alarm function:	No
Privacy conversation function:	Yes
Key button function:	Yes

HARDWARE SPECIFICATIONS

Customisable housing:	No
-----------------------	----

SETTINGS

Loudspeaker volume control:	Yes
Microphone volume control:	Yes
Ringtone volume control:	Yes

GENERAL DATA

Product height (mm):	160
----------------------	-----



6228W

EASYCOM SIMPLEBUS UNIT - WHITE

GENERAL DATA

Product width (mm):	90
Product depth (mm):	28

COMPATIBILITY

Simplebus Top audio/video system:	Yes
Simplebus 2 audio system:	Yes

TECHNICAL CHARACTERISTICS

Power supply voltage:	22 ÷ 28
Minimum current absorption (mA):	0,7
Maximum current absorption (mA):	400
Microphone:	9,6x9,6mm omni-direction
Loudspeaker:	
IP protection rating:	IP30
Operating temperature (°C):	5 ÷ 40
Product weight (g):	355
Clamps:	L L CFP CFP S- S+



6228W

EASYCOM SIMPLEBUS UNIT - WHITE

ACCESSORIES



1214/2C

VIDEO FILTER FOR SIMPLEBUS COLOUR SYSTEM

Line branch terminal for colour monitors. The terminal must be connected on the riser to be branched towards brackets or telephones.



1256

ACCESSORY - SIMPLEBUS SYSTEM DIGITAL RELAY ACTUATOR

Intelligent Simplebus device for controlling a 12-24 V relay contact. If used in mixed audio/video systems, the actuator relay needs a video filter to be purchased separately. Power supply: 12V AC or 20V DC. Dimensions: 66X85X35 (4 DIN modules).



6212

DESK BASE FOR EASYCOM DOOR-ENTRY PHONE

Stainless steel desk base suitable for all Easycom door-entry phone versions.