



**8451V**

## QUADRA KIT AND WIFI MINI HF, S2



The kit consists of no. 1 external unit Quadra art. 4893M, no. 1 power supply art. 1209, no. 1 monitor Mini hands-free Wi-Fi art. 6741W and no. 1 line termination terminal art. 1216. The kit is pre-programmed and ready to use.

### AWARDS

DESIGN  
MILANO



DESIGN **PLUS**  
awarded by building



**8451V**

## QUADRA KIT AND WIFI MINI HF, S2

### KIT PRODUCTS



#### **4893M** QUADRA ENTRANCE PANEL W/ BUTTONS. 2 WIRES

Quadra series wall-mounted external video entry unit with mechanical buttons. Die-cast aluminium faceplate, wide-angle colour camera and a single LED for nighttime lighting. Indicator LED for call sent, lock-release activated, audio activated and system busy. Adjustment of speaker volume and audio balance. Power supply from bus line. External unit dimensions: 95x195x28 mm.

#### GENERAL DATA

Type	Monoblock
Height (mm)	195
Width (mm)	95
Depth (mm)	23
Product weight (g)	300
Product color	Grey RAL 9006, Black RAL9005
Wall-mounted	Yes

#### COMPATIBLE SYSTEMS

Simplebus 2 audio/video kit with power supply art. 1209	Yes
---	-----

#### AUDIO FEATURES

Microphone	6mm (Ø), Omnidirectional
Loudspeaker	36mm (Ø), 8 Ohm, 1W

#### CAMERA FEATURES

Camera	Colours
Sensor type	1/4" CMOS
Lens optical dimensions (mm)	2.1
Angle of view (H x V - °)	85 x 72
Sensitivity (lux)	0.1 (colour)


**8451V**

## QUADRA KIT AND WIFI MINI HF, S2

### CAMERA FEATURES

Video resolution (H x V - pixel)	648x488
----------------------------------	---------

### ELECTRICAL CHARACTERISTICS

Type of power supply	Power supply from video door entry bus
Supply voltage	33VDC
Maximum absorption (W)	8.25

### HARDWARE FEATURES

Call type	Push-buttons
Type of buttons	Mechanical
Number of push-buttons (n°)	4
Backlight colour	White
Clamps	LL RTE COM DO SE- SE+C NC NO
Number of inputs (n°)	2
Number of outputs (n°)	2
Type of outputs	Open Collector, Relay (C-NO-NC, 10A@12÷24 VAC/VDC)

### SETTINGS

Loudspeaker volume	Yes
Microphone volume	Yes

### ENVIRONMENTAL AND COMPLIANCE FEATURES

IP protection rating	IP54
Vandal Resistant rating (IK code)	IK08
Operating temperature (°C)	-25 ÷ 55
Operating humidity (RH max) (%)	25 ÷ 95
Environmental class	IV
CE certifications	RoHS II - 2011/65/UE (EN 50581:2012), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)

### MAIN FUNCTIONS

**8451V****QUADRA KIT AND WIFI MINI HF, S2**

Door opener	Yes
Number of auxiliary relays (n°)	1
Input for local door release button	Yes
Door open signaling input	Yes

**GENERAL FEATURES**

Type of finishing materials	Polycarbonate, Aluminium alloy
Door release (direct current output)	Yes
Acoustic signalling	Yes
Visual signalling	Yes
Speech synthesis	Yes



**8451V**

## QUADRA KIT AND WIFI MINI HF, S2



### **6741W 2 WIRES MINI HANDSFREE WI-FI DOOR ENTRY MONITOR**

Hands-free Mini Wif-Fi door entry monitor for Simplebus2 system. When used in conjunction with the Comelit app (available to download free of charge from the Google and Apple stores) and/or the voice assistants Alexa/Ecoshow/Google Assistant, it can be used to answer calls directly from your smartphone/tablet/assistants, both locally and remotely. It can be used to enable the "Face recognition" function directly from the app, to automatically - once a person has been recognised - send a lock-release command (enabled by default), trigger an actuator to control a light or additional opening and receive notification when a known individual makes a call. Replacing an old door entry monitor to benefit from all the advantages offered by Wi-Fi technology is no longer problematic: Mini Wi-Fi is actually compatible with all types of Comelit Simplebus 2 video entry phone system and does not require any additional masonry work. Supplied with mounting backplate and riser distribution terminal art. 1214/2C.

#### GENERAL DATA

Height (mm)	160
Width (mm)	115
Depth (mm)	22
Product color	White RAL9003
Type of finishing materials	ABS
Product weight (g)	400
Wall-mounted	Yes
Desk base-mounted	Yes, with a dedicated accessory

#### COMPATIBLE SYSTEMS

Audio/video Simplebus 2 with power supply art. 4888C	Yes
Audio/video Simplebus 2 with power supply art. 1210/1210A	Yes
Simplebus 2 audio/video kit with power supply art. 1209	Yes

#### DISPLAY



**8451V**

**QUADRA KIT AND WIFI MINI HF, S2**

Display size (")	4.3
Aspect Ratio	16:9
Resolution (pixels)	480x272
OSD menu	Yes
Type of display	LCD

**AUDIO FEATURES**

Type	Hands-free
Microphone	6mm (Ø), Omnidirectional
Loudspeaker	36mm (Ø), 40 Ohm, 1W

**ELECTRICAL CHARACTERISTICS**

Type of power supply	Power supply from video door entry bus
Supply voltage	22÷34 VDC (Bus)
Absorption in stand-by (W)	0.1
Stand-by absorption in kit mode (W)	1.9
Maximum absorption (W)	8.1

**HARDWARE FEATURES**

Type of buttons	Capacitive
Service buttons	Lock-release, Answer, Silent (Privacy), Menu, Messages
No. of programmable buttons for additional functions	4
Clamps	L L CFP1 CFP2
Removable terminals	Yes
Number of inputs (n°)	1

**SETTINGS**

Loudspeaker volume	Yes
Ringtone volume	Yes
Screen brightness control	Yes


**8451V**
**QUADRA KIT AND WIFI MINI HF, S2**
**NETWORK AND COMMUNICATION PROTOCOLS**

Type of Wi-Fi connection	IEEE 802.11 b/g/n, 2.4 Ghz, 13 channels
Encryption and authentication method supported	OPEN WPA-PSK networks, TKIP WPA2-PSK, AES WEP 64 bits (5-digit ASCII or 10 hexadecimal codes), WEP 128 bits (13-digit ASCII or 26 hexadecimal codes)
IP address assignment	DHCP
IoT connection to Comelit Cloud	Yes
Firmware update via Comelit Cloud	Yes

**ENVIRONMENTAL AND COMPLIANCE FEATURES**

IP protection rating	IP30
Operating temperature (°C)	5 ÷ 40
Operating humidity (RH max) (%)	25 ÷ 75
Environmental class	I
CE certifications	RoHS II - 2011/65/UE (EN 50581:2012), RED 2014/53/UE (EN 60950-1:2006+A11:2009+A1:2010+A12:2011, +A2:2013, EN 62311:2008, EN 61000-6-1:2007, EN 61000-6-3:2007 + A1:2011, ETSI EN 301 489-1 V2.2.0, ETSI EN 301 489-17 V3.2.0, ETSI EN 300 328 V2.1.1)

**GENERAL FEATURES**

Door opening on call (Doctor)	Yes
Door opener	Yes
Self Activation	Yes
CPS call	Yes
Selective intercom call	Yes
Intercom calls	Yes
Actuator control	Yes
Compatibility with Video Entry Comelit App	Yes
Hands-free function	Yes
Multiple address	Yes
Outside door call input	Yes

**8451V****QUADRA KIT AND WIFI MINI HF, S2****GENERAL FEATURES**

Integration with voice assistants	Yes
Sending alarm calls	Yes
Video memory	Yes
Silent mode (Privacy)	Yes
Face recognition	Yes
Automatic answer (handsfree)	Yes
Door open signaling	Yes
Customisable ringtone	Yes
Date/time display	Yes





**8451V**

## QUADRA KIT AND WIFI MINI HF, S2



### **1209 2-WIRE VIDEO KIT POWER SUPPLY UNIT**

33 VDC power supply unit with overload and short circuit protection devices. It has two separate continuous outputs: one to power the external unit and electric lock, and the other to power the monitor. Input voltage 110-240 VAC. Dimensions: 106x62x89mm (6 DIN modules).

#### MAIN FEATURES

Supply voltage	110÷240
Max. current delivered (A)	1.2
Input connector	Terminal block
Applicable to DIN rail	Yes
Number of DIN modules (n°)	6

#### GENERAL DATA

Height (mm)	62
Width (mm)	106
Depth (mm)	89
Type of finishing materials	Plastic

#### COMPATIBILITY

Kit audio/video system	Yes
------------------------	-----

#### ELECTRICAL SPECIFICATIONS

Maximum power delivered (W)	37
-----------------------------	----



**8451V**

## QUADRA KIT AND WIFI MINI HF, S2



### **1216 SIMPLEBUS2 LINE TERMINATION TERMINAL**

Line termination terminal. To be mounted at the end of the riser, according to the indications given in the technical documentation, to optimise distribution of the signals.

### COMPATIBILITY

Simplebus 2 audio/video system	Yes
--------------------------------	-----

**8451V****QUADRA KIT AND WIFI MINI HF, S2****ACCESSORIES****4793MC CORTEN FACEPLATE FOR QUADRA W/BUTTONS**

Corten color faceplate for Quadra entrance panel with mechanical buttons.

**4793MB BLACK FACEPLATE FOR QUADRA W/BUTTONS**

Black faceplate for Quadra entrance panel with mechanical buttons

**4793MA ALUMINIUM FACEPLATE FOR QUADRA W/BUTTONS**

Aluminium colour faceplate for Quadra entrance panel with mechanical buttons

**4791 Adapter plate for Quadra**

Plate allowing installation of the Quadra external unit in 1- and 2-module flush-mounted boxes by Comelit, Bticino and Urmet. Dimensions 137x236 mm

**4792 RAIN SHIELD FOR QUADRA ENTRANCE PANEL**

Rain shield in painted aluminum for Quadra entrance panel, grey colour. Dimensions (W x H x D): 99 x 210 x 41 mm.

**1217 NAME TAG SHEETS FOR QUADRA ENTRANCE PANEL**

The kit contains 10 sheets of adhesive labels for nameplates

**8451V****QUADRA KIT AND WIFI MINI HF, S2****ACCESSORIES****6732****DESK BASE FOR HANDSFREE MINI MONITOR**

Desk base for desktop conversion of Handsfree Mini monitor.  
Complete with 1x 2 metre cable with RJ45 connector to connect  
monitor terminals to the coupler or domestic series socket.  
Dimensions: 140x190x140mm.

**6720****Access. cables external passage for MINI HF. S2**

Wall support bracket for handsfree Mini monitor allowing thru-routing  
of external cables.

**1405****DIGITAL EXCHANGE 2 QUADRA INPUTS. S2**

Audio/video switching module for audio/video kit systems. For use in  
systems with a maximum of 2 entrances with Quadra series external  
unit. Power supply from bus line. Dimensions: 35x90x58mm (2 DIN  
modules).

**6710****BACKPLATE AND DISTRIBUTION TERMINAL FOR MINI MONITOR**

Wall-mounting or residential series box backplate for MINI monitor,  
/BM versions with handset featuring magnetic induction for hearing  
aid wearers. Also includes riser distribution terminal Art. 1214/2C.  
Dimensions 145x100x4 mm.

**1235A****NAMEPLATE LABEL PRINTING SOFTWARE**

Dedicated software for the creation and printing of nameplate and  
information labels for Ikall, Vandalcom, Quadra and 316 Analog  
entrance panels. Requires use of adhesive labels art.1217, 1218,  
1219 or art.1220. This software is available to download free of  
charge from the Comelit website

**8451V****QUADRA KIT AND WIFI MINI HF, S2****ACCESSORIES****1409****ACCESSORY FOR REMOTE COLOUR CAMERAS, 2-WIRE SYSTEM**

Remote camera module for Simplebus 2 2-wire digital systems. Allows management of up to 3 colour cameras in cyclical sequence from door entry monitors using a dedicated button. 12 Vac or 20 Vdc power supply. Dimensions: 60x85x35 mm (4 DIN modules).

**1404****SIMPLEBUS2 DIGITAL SWITCHING DEVICE**

Audio/video switching module for Simplebus 2 digital systems. To be used in systems with more than one entrance. Power supply from bus line. Dimensions: 60x85x35 mm (4 DIN modules).

**1229A****ADDITIONAL RINGTONE ACCESSORY. S2**

Wall-mounted accessory for additional ringtone for direct connection to 2-wire bus. Allows ringtone selection and adjustment of ringtone volume with privacy function, equipped with dip switches for user code programming, floor door call input terminals and call repeat. Fitted with distribution terminal art. 1214/2C. Dimensions: 125x95x24mm.

**1256****ACCESSORY - SIMPLEBUS SYSTEM DIGITAL RELAY ACTUATOR**

Intelligent Simplebus device for controlling a relay on board (12÷24 VAC/VDC - 10A max). For use and programming of the function required, follow the indications given in the technical documentation. It can be used in Simplebus system. Power supply: 12 VAC or 20 VDC. Dimensions: 66X85X35mm (4 DIN modules). Line branch terminal art. 1214/2C in equipment.