



8501HIM

SING.-FAMILY KIT W/ IKALL METAL & PC INTERCOM VIP H264 SYST.



The kit consists of 1 colour audio/video unit art. 4682HKC, 1 module with 1 button art. 33411M, 1 flush-mounted box art. 3110/1, 1 frame complete with finishing frame art. 3311/1S, 1 power supply unit art. 1595 and 1 PC Intercom software art. 1454K. The kit is pre-programmed and ready to use. The kit can be expanded with other products from the ViP catalogue. Compatible with H.264 video format.

AWARDS

DESIGN
MILANO



8501HIM

SING.-FAMILY KIT W/ IKALL METAL & PC INTERCOM VIP H264 SYST.

KIT PRODUCT



1454K

LOCAL PC DOOR ENTRY MONITOR SOFTWARE VIP

Software on USB stick that allows a PC to be used for answering calls like a door entry monitor. Pre-set for operation with the single-family VIP KIT Art. 8501. For installation and use on a PC wired directly to the system.

COMPATIBILITY - 1454K

Vip system:	Yes
-------------	-----



4894HIM

External unit for VIP kit - Ikall Metal H264

Single-family video door entry external unit for ViP system with Ikall Metal entrance panel. The kit comprises: 1 flush-mounted box Art. 3110/1, 1 silver coloured frame Art. 3311/1S, 1 module with 1 button art. 33411M and 1 colour audio/video unit Art. 4682HKD. The external unit is coded with ViP address 100 and the button on module Art. 33411M sends the call to ViP address 1. Compatible with H264 video format

MAIN FEATURES - 4894HIM

Audio/video system:	Yes
Flush-mounted:	Yes
Type of sensor:	1/3" CCD
Lens size (mm):	3,6
Minimum colour lighting (lux):	0,23
Video resolution (H x V - pixel):	
Video encoding:	H.264
Power supply:	33VDC
Microphone volume control:	Yes
Loudspeaker volume control:	Yes
Operating temperature (°C):	-25 ÷ 55
IP protection rating (IP code):	IP54



1595

33VDC POWER SUPPLY UNIT FOR IKALL ENTRANCE PANEL

Power supply unit with 110-230VAC primary and 33VDC/500 mA continuous output, and 1.2A inrush current for external unit with IKALL entrance panel. Equipped with internal protection against overcurrent and short circuits. Dimensions: 71.7x90x62 mm (4 DIN modules).



8501HIM

SING.-FAMILY KIT W/ IKALL METAL & PC INTERCOM VIP H264 SYST.

MAIN FEATURES - 1595

Supply voltage (VAC):	120÷230
Applicable to DIN rail:	Yes
Number of DIN modules:	4
Max. current delivered (A):	1,2



8501HIM

SING.-FAMILY KIT W/ IKALL METAL & PC INTERCOM VIP H264 SYST.

ACCESSORIES



4895HIM

ADDIT. EXT.UNIT FOR VIP KIT - IKALL METAL. H264

Single-family video door entry external unit for ViP system with Ikall Metal entrance panel. The kit comprises: 1 flush-mounted box Art. 3110/1, 1 silver coloured frame Art. 3311/1S, 1 module with 1 button art. 33411M and 1 colour audio/video unit Art. 4682HKE. The external unit is coded with ViP address 101 and the button on module Art. 33411M sends the call to ViP address 1. Compatible with H.264 video format.



4682HKD

HD COLOR A/V UNIT FOR IKALL KIT. VIP

ViP system audio/video unit complete with colour video camera. Maximum resolution 1280x720 pixels. Recording angle 110° (H) - 80° (V). LED camera lighting. Complete with terminal block and digital audio management system with Echo-cancellation, watertight loudspeaker and electret microphone; loudspeaker volume can be adjusted via software programming. Programmable audiovisual functions for users with disabilities. Standard POE audio/video unit but if necessary 33 Vdc power supply can be used via Art. 1595. Compatible with H.264 video format. Audio/video unit pre-programmed with ViP address 100 and call button with ViP address 1. Dimensions (W x H x D): 102x55x38 mm.



4682HKE

HD A/V UNIT FOR ADDITIONAL KIT ENTRANCE PANEL. VIP

ViP system audio/video unit complete with colour video camera. Maximum resolution 1280x720 pixels. Recording angle 110° (H) - 80° (V). LED camera lighting. Complete with terminal block and digital audio management system with Echo-cancellation, watertight loudspeaker and electret microphone; loudspeaker volume can be adjusted via software programming. Programmable audiovisual functions for users with disabilities. Standard POE audio/video unit but if necessary 33 Vdc power supply can be used via Art. 1595. Compatible with H.264 video format. Audio/video unit pre-programmed with ViP address 101 and call button with ViP address 1. Dimensions (W x H x D): 102x55x38 mm.