



8504H

SING.-FMLY KIT W/VANDALCOM & PC INTERCOM VIP SYST. KIT H.264



VIP

The kit consists of 1 colour audio/video unit art. 4682HKC, 1 module with 1 button art. 3268I/1, 1 flush-mounted box art. 3160/1, 1 frame complete with finishing frame art. 3161/1, 1 power supply unit art. 1595 and 1 PC Intercom software art. 1454K. The kit is pre-programmed and ready to use. The kit can be expanded with other products from the VIP catalogue. Compatible with H.264 video format.



8504H

SING.-FMLY KIT W/VANDALCOM & PC INTERCOM VIP SYST. KIT H.264

KIT PRODUCT

4682HKC



COLOUR A/V UNIT FOR VIP SYSTEM, IKALL SERIES. H264

VIP KIT system audio-video unit with terminal block, complete with mini lens colour camera which is adjustable from the front and LED camera lighting. Complete with terminal block and digital audio management system with Echo-cancelling, watertight loudspeaker and electret microphone, loudspeaker volume adjustable from the front. Dimensions: 102x55x38 mm. Compatible with H.264 video format

MAIN FEATURES - 4682HKC

Audio/video system:	Yes
Camera:	Colours
Video encoding:	H.264
Type of sensor:	1/3" CCD
Minimum illumination (lux):	0,23
Lens size (mm):	3,6
Camera orientation:	Yes
Power supply voltage:	30 ÷ 57
Clamps:	TX- TX+RX- RX+V- V+RTE GND SE COM NC NO
Microphone:	Yes
Microphone volume control:	Yes
Loudspeaker:	Yes
Loudspeaker volume control:	Yes
Operating temperature (°C):	-25 ÷ 55

3268I/1



MODULE FOR A/V UNITS, 1 PUSH-BUTTON, IKALL SERIES

Module made using a double 2.5 mm stainless steel plate. For use with audio/video unit depending on the wiring system used. 1 button. Dimensions 106x106x5.6 mm

MAIN FEATURES - 3268I/1

Backlighting colour:	Lamp
Vandal Resistant rating (IK code):	Yes
Height (mm):	106
Width (mm):	106
Depth (mm):	5,6
Operating temperature (°C):	-25 ÷ 55
Maximum current absorption (mA):	150



8504H

SING.-FMLY KIT W/VANDALCOM & PC INTERCOM VIP SYST. KIT H.264

MAIN FEATURES - 3268/1



3160/1

FLUSH-MOUNTED BOX FOR VANDALCOM ENTRANCE PANEL

Flush-mounted box for Vandalcom entrance panel. 1 module. Dimensions 130x130x58mm

MAIN FEATURES - 3160/1

Vandal Resistant rating (IK code):	Yes
Height (mm):	130
Width (mm):	130
Depth (mm):	58



3161/1

VANDALCOM SERIES FRAME. DARK GREY COLOUR

Made from die-cast aluminium and painted with special dust-resistant paint for outdoor use. Dark grey colour.

1 module. Dimensions 143x143x18 mm

MAIN FEATURES - 3161/1

Vandal Resistant rating (IK code):	Yes
Height (mm):	143
Width (mm):	143
Depth (mm):	18



1595

33VDC POWER SUPPLY UNIT FOR IKALL ENTRANCE PANEL

Power supply unit with 110-230VAC primary and 33VDC/500 mA continuous output, and 1.2A inrush current for external unit with IKALL entrance panel. Equipped with internal protection against overcurrent and short circuits. Dimensions: 71.7x90x62 mm (4 DIN modules).

MAIN FEATURES - 1595

Supply voltage (VAC):	120÷230
Applicable to DIN rail:	Yes

The technical specifications are subject to variations without warning.



8504H

SING.-FMLY KIT W/VANDALCOM & PC INTERCOM VIP SYST. KIT H.264

MAIN FEATURES - 1595

Number of DIN modules:	4
Max. current delivered (A):	1,2



1454K

LOCAL PC DOOR ENTRY MONITOR SOFTWARE VIP

Software on USB stick that allows a PC to be used for answering calls like a door entry monitor. Pre-set for operation with the single-family VIP KIT Art. 8501. For installation and use on a PC wired directly to the system.

COMPATIBILITY - 1454K

Vip system:	Yes
-------------	-----



8504H

SING.-FMLY KIT W/VANDALCOM & PC INTERCOM VIP SYST. KIT H.264

ACCESSORIES

4682HKC



COLOUR A/V UNIT FOR VIP SYSTEM, IKALL SERIES. H264

VIP KIT system audio-video unit with terminal block, complete with mini lens colour camera which is adjustable from the front and LED camera lighting. Complete with terminal block and digital audio management system with Echo-cancelling, watertight loudspeaker and electret microphone, loudspeaker volume adjustable from the front. Dimensions: 102x55x38 mm. Compatible with H.264 video format

3268I/1



MODULE FOR A/V UNITS, 1 PUSH-BUTTON, IKALL SERIES

Module made using a double 2.5 mm stainless steel plate. For use with audio/video unit depending on the wiring system used. 1 button. Dimensions 106x106x5.6 mm

3160/1



FLUSH-MOUNTED BOX FOR VANDALCOM ENTRANCE PANEL

Flush-mounted box for Vandalcom entrance panel. 1 module. Dimensions 130x130x58mm

3161/1



VANDALCOM SERIES FRAME. DARK GREY COLOUR

Made from die-cast aluminium and painted with special dust-resistant paint for outdoor use. Dark grey colour. 1 module. Dimensions 143x143x18 mm

1595



33VDC POWER SUPPLY UNIT FOR IKALL ENTRANCE PANEL

Power supply unit with 110-230VAC primary and 33VDC/500 mA continuous output, and 1.2A inrush current for external unit with IKALL entrance panel. Equipped with internal protection against overcurrent and short circuits. Dimensions: 71.7x90x62 mm (4 DIN modules).

1454K



LOCAL PC DOOR ENTRY MONITOR SOFTWARE VIP

Software on USB stick that allows a PC to be used for answering calls like a door entry monitor. Pre-set for operation with the single-family VIP KIT Art. 8501. For installation and use on a PC wired directly to the system.