



8521

IKALL METAL AND ICONA KIT.VIP H264 SYSTEM



The kit consists of 1 colour audio/video unit art. 4682HKC, 1 module with 1 button art. 33411M, 1 flush-mounted box art. 3110/1, 1 frame complete with finishing frame art. 3311/1S, 1 power supply unit art. 1595, 1 power supply unit art. 1441B, 1 switch art. 1440, 1 Icona monitor art. 6602WK, 1 flush-mounted box art. 6117, 1 wall-mounted bracket art. 6620. The kit is pre-programmed and ready to use. The kit can be expanded with other products from the VIP catalogue. Compatible with H.264 video format.

AWARDS

DESIGN
MILANO





8521

IKALL METAL AND ICONA KIT.VIP H264 SYSTEM

KIT PRODUCT



6602WK

ICONA MONITOR, VIP KIT H264

Flush-mounted (on box art. 6117) or surface-mounted (with bracket art. 6620) colour monitor with 4.3" / 16:9 touch screen, full-duplex audio. Allows adjustment of backlighting intensity, contrast, audio volume and ringtone volume. Equipped as standard with sensitive touch controls for lock-release, audio activation, self-ignition, privacy service and 3 other controls for programmable functions, door open and new message indicator LEDs. Standard floor door call and call repetition management, with alarm and panic inputs and micro-SD card slot. You can customise the ringtone and video memory function with an absent message. Can also be used on standard PoE systems. Dimensions 142.5x147x23mm. Compatible with H.264 video format.

MAIN FEATURES - 6602WK

| | |
|---|---------------|
| Audio system: | No |
| Audio/video system: | Yes |
| Flush-mounted: | Yes |
| Wall-mounted: | Yes |
| Desk base-mounted: | Yes |
| Hands-free function: | Yes |
| Induction loop function: | Yes |
| Type of display: | LCD |
| Display size (inch): | 4,3" 16:9 |
| Touch screen display: | Yes |
| Display resolution HxV (mm): | 480x272 |
| B/W or colour display: | Color |
| Product colour: | White RAL9016 |
| Sensitive Touch technology: | Yes |
| Total buttons: | 9 |
| Comaptibility with Video Entry Comelit App: | No |



4894HIM

External unit for ViP kit - Ikall Metal H264

Single-family video door entry external unit for ViP system with Ikall Metal entrance panel. The kit comprises: 1 flush-mounted box Art. 3110/1, 1 silver coloured frame Art. 3311/1S, 1 module with 1 button art. 33411M and 1 colour audio/video unit Art. 4682HKC. The external unit is coded with ViP address 100 and the button on module Art. 33411M sends the call to ViP address 1. Compatible with H264 video format

MAIN FEATURES - 4894HIM

| | |
|---------------------|----------|
| Audio/video system: | Yes |
| Flush-mounted: | Yes |
| Camera: | |
| Type of sensor: | 1/3" CCD |
| Lens size (mm): | 3,6 |

The technical specifications are subject to variations without warning.



8521

IKALL METAL AND ICONA KIT.VIP H264 SYSTEM

MAIN FEATURES - 4894HIM

| | |
|-----------------------------------|----------|
| Minimum colour lighting (lux): | 0,23 |
| Video resolution (H x V - pixel): | 500x582 |
| Video encoding: | H.264 |
| Power supply: | 33 VDC |
| Microphone volume control: | Yes |
| Loudspeaker volume control: | Yes |
| Operating temperature (°C): | -25 ÷ 55 |
| IP protection rating: | |

1440

NETWORK SWITCH 4 PORT

Floor shunt with one input, one output (10/100 Mb) and 4 shunts (10 MB). Dimensions 66 x 85 x 35 mm



MAIN FEATURES - 1440

| | |
|--------------------------------|---------|
| Product height (mm): | 89 |
| Product width (mm): | 72 |
| Product depth (mm): | 62 |
| Operating temperature (°C): | 5 ÷ 40 |
| RH max operating humidity (%): | 25 ÷ 75 |
| DIN rail mounted: | Yes |
| DIN modules (no.): | 4 |

6117

PLANUX, SMART, ICONA FLUSH BACKBOX

Flush mounted box for Planux, Smart and Icona monitors Dimensions: 132x132x50mm



MAIN FEATURES - 6117

| | |
|----------------------|-----|
| Product height (mm): | 132 |
| Product width (mm): | 132 |
| Product depth (mm): | 50 |



8521

IKALL METAL AND ICONA KIT.VIP H264 SYSTEM

KIT PRODUCT



6620

WALL BRACKET FOR ICONA MONITOR

Wall bracket for Icona monitor. Colour: White. Dimensions: 137X142X12.5 mm.



1441B

30W VIP SYSTEM POWER SUPPLY UNIT

Power supply unit with 110Vac/240Vac input and 48Vdc output. 30W power. DIN bar power supply unit (4 DIN modules). Dimensions: 72x93x56mm

MAIN FEATURES - 1441B

| | |
|----------------------------------|---------|
| Alternating input voltage (VAC): | 110÷240 |
| Number of DIN modules: | 4 |



1595

33VDC POWER SUPPLY UNIT FOR IKALL ENTRANCE PANEL

Power supply unit with 110-230VAC primary and 33VDC/500 mA continuous output, and 1.2A inrush current for external unit with IKALL entrance panel. Equipped with internal protection against overcurrent and short circuits. Dimensions: 71.7x90x62 mm (4 DIN modules).

MAIN FEATURES - 1595

| | |
|----------------------------------|---------|
| Alternating input voltage (VAC): | 120÷230 |
| Output voltage (VDC): | 33 |
| Applicable to DIN rail: | Yes |
| Number of DIN modules: | 4 |
| Max. current delivered (A): | 1,2 |



8521

IKALL METAL AND ICONA KIT.VIP H264 SYSTEM

ACCESSORIES



4895HIM

ADDIT. EXT.UNIT FOR VIP KIT - IKALL METAL. H264

Single-family video door entry external unit for ViP system with Ikall Metal entrance panel. The kit comprises: 1 flush-mounted box Art. 3110/1, 1 silver coloured frame Art. 3311/1S, 1 module with 1 button art. 33411M and 1 colour audio/video unit Art. 4682HKE. The external unit is coded with ViP address 101 and the button on module Art. 33411M sends the call to ViP address 1. Compatible with H.264 video format.



4682HKD

HD COLOR A/V UNIT FOR IKALL KIT. VIP

ViP system audio/video unit complete with colour video camera. Maximum resolution 1280x720 pixels. Recording angle 110° (H) - 80° (V). LED camera lighting. Complete with terminal block and digital audio management system with Echo-cancellation, watertight loudspeaker and electret microphone; loudspeaker volume can be adjusted via software programming. Programmable audiovisual functions for users with disabilities. Standard POE audio/video unit but if necessary 33 Vdc power supply can be used via Art. 1595. Compatible with H.264 video format. Audio/video unit pre-programmed with ViP address 100 and call button with ViP address 1. Dimensions (W x H x D): 102x55x38 mm.



4682HKDE

HD A/V UNIT FOR ADDITIONAL KIT ENTRANCE PANEL. VIP

ViP system audio/video unit complete with colour video camera. Maximum resolution 1280x720 pixels. Recording angle 110° (H) - 80° (V). LED camera lighting. Complete with terminal block and digital audio management system with Echo-cancellation, watertight loudspeaker and electret microphone; loudspeaker volume can be adjusted via software programming. Programmable audiovisual functions for users with disabilities. Standard POE audio/video unit but if necessary 33 Vdc power supply can be used via Art. 1595. Compatible with H.264 video format. Audio/video unit pre-programmed with ViP address 101 and call button with ViP address 1. Dimensions (W x H x D): 102x55x38 mm.



6117

PLANUX, SMART, ICONA FLUSH BACKBOX

Flush mounted box for Planux,Smart and Icona monitors Dimensions: 132x132x50mm



6620

WALL BRACKET FOR ICONA MONITOR

Wall bracket for Icona monitor. Colour: White. Dimensions: 137X142X12.5 mm.



8521

IKALL METAL AND ICONA KIT.VIP H264 SYSTEM

ACCESSORIES



6612

DESK BASE FOR ICONA MONITOR

Adjustable tilt desk base converts the Smart monitor into a desktop version. Complete with 1 x 2 m labelled RJ45 cable for connecting the monitor terminals to the clasp or to a residential series jack. Dimensions: 145x190x120 mm.