

Compact Face Recognition Terminal



Suprema FaceLite is the most compact face recognition terminal providing loads of the world's best features. Powered by Suprema's latest innovation in facial biometrics, FaceLite offers unrivaled matching speed, accuracy, and level of security. With Suprema's patented optic engineering, FaceLite achieves up to 25,000 lx of operating illuminance which in turn, brings all-around confidence regardless of light-ing conditions. Packed in a compact and an ergonomically-designed structure, FaceLite provides exceptional performance and usability for diverse access control and time attendance sites, large or small.



FaceLite Compact Face Recognition Terminal

Features

\bigcirc

Ultra Performance

- Matching Speed: 1:4,000 match/sec
- Group Matching: 1:5,000 match/sec • User Capacity: Max 30,000 users (1:1), 4,000 users (1:N)



Highest Operating Illuminance

- Operating illuminance from 0lx to 25,000lx
- Covers complete darkness to all indoor lighting conditions

\bigcirc

-Ò-

25,000 b

- Enhanced Security
- IR-based Live Face Detection(LFD); Prevent spoofing by printed images and LCDs
- Face template encryption
- \cdot Secured communication with TLS 1.2



Multi RFID Card Reading

- LF(125kHz), HF(13.56MHz) dual-band
- \cdot Reads all card types including Mobile Card (NFC and BLE)



Ergonomics & User Convenience

- Extended height range: 145cm 210cm
- \cdot Improved face enrollment procedure

Model Name	FL-DB
Biometric	Face
RF Options	125kHz EM & 13.56MHz MIFARE, MIFARE Plus, DESFire EV1/EV2*, FeliCa
Mobile Card	NFC, BLE
Max. User	30,000(1:1), 4,000(1:N)
Max. Log	5,000,000
Ethernet	10/100Mbps, auto MDI/MDI-X
RS-485	1ch Host or Slave (Selectable)
Wiegand	1ch Input or Output (Selectable)
TTL	2ch Inputs
Relay	1 Relay
Tamper	Supported
CPU	1.2GHz Quad Core
Memory	8GB Flash + 1GB RAM
Operating Temperature	-20°C ~ 50°C
Dimensions (WxHxD, mm)	80 x 170 x 76
Power	DC 24V
Certificates	CE, FCC, KC, RoHS, REACH, WEEE, BT SIG
	* DESFire EV2 cards are supported by having backward compatibility of DESFire EV1 cards

* DESFire EV2 cards are supported by having backward compatibility of DESFire EV1 cards CSN and smart card functions are compatible with FaceLite.

System Configurations -



Specifications -

Suprema Inc.



17F Parkview Tower, 248, Jeongjail-ro, Bundang-gu, Seongnam-si, Gyeonggi-do, 13554, Republic of Korea T +82 31 783 4502 E sales_sys@supremainc.com www.supremainc.com



For more information about Suprema's global offices, visit the webpage below by scanning the QR code. https://www.supremainc.com/en/about/contact-us.asp

©2021 Suprema Inc. Suprema and identifying product names and numbers herein are registered trade marks of Suprema Inc. All non-Suprema brands and product names are trademarks or registered trademarks of their respective companies. Product appearance, build status and/or specifications are subject to change without notice. [SUPREMA-AHL-FL-EN-REV08]