

CENOVNIK DAHUA CCTV, HDCVI I IP CCTV OPREME

10. Septembar 2019.








Kničaninova br.3; 11000 BEOGRAD







Tel/fax: +381 11 3030840; 3030838

Web: <http://www.boma.rs>; Mail: office@boma.rs

2MP 4u1 kamere, Cooper serija; Sa OSD-om; 2D DNR

Kod	OPIS	VP	MSRP	Slika	
4u1 2MP D/N bullet IC kamera; Cooper serija; Smart IC 20m; Metalno kućište; 3.6mm objektiv; IP67					
HAC-B2A21-0360B	4u1 (analogna, HDCVI, AHD, TVI) 2MP bullet IC kamera; 1/2.7" 2 Megapixels CMOS; Efektivni broj piksela 1920(H) x 1080(V); Rezolucija 1920x1080@25 fps ili 1280x720@25/50 fps; 3.6mm F1.85 fiksni objektiv; Vidni ugao 93°; Opciono 6mm (vidni ugao 54.7°); Osetljivost 0.04Lux/F1.85, 0Lux (IC uključ.); True day/night (ICR); Smart IC LE diode dometa cca. 20m; DWDR; BLC; 2D DNR; OSD; Izbor moda rada putem UTC OSD kontrolera ili sa HCVR uređaja; Prenos signala koaksijalnim kablom 75Ω na dužinama do 500m; Dimenzije 69.8mmx69.8mmx157.6mm; Masa 250g; Alu. kućište; IP67 sertifikovana; Radna temperatura -40°C~+60°C; Napajanje 12Vdc ±30%/2.7W; CE (EN55032, EN55024, EN50130-4)	€ 13,80	€ 23,00	 	Na lageru
4u1 2MP D/N dome IC kamera; Cooper serija; Smart IC 20m; Metalno kućište; 2.8mm objektiv; IP67					
HAC-T2A21-0280B	4u1 (analogna, HDCVI, AHD, TVI) 2MP dome IC kamera; 1/2.7" 2 Megapixels CMOS; Efektivni broj piksela 1920(H) x 1080(V); Rezolucija 1920x1080@25 fps ili 1280x720@25/50 fps; 2.8mm F1.85 fiksni objektiv; Vidni ugao 103°; Opciono 3.6mm ili 6mm (vidni ugao 93° ili 54.7°); Osetljivost 0.04Lux/F1.85, 0Lux (IC uključ.); True day/night (ICR); Smart IC LE diode dometa cca. 20m; DWDR; BLC; 2D DNR; OSD; Izbor moda rada putem UTC OSD kontrolera ili sa HCVR uređaja; Prenos signala koaksijalnim kablom 75Ω na dužinama do 500m; Dimenzije 69.8mmx69.8mmx157.6mm; Masa 250g; Alu. kućište; IP67 sertifikovana; Radna temperatura -40°C~+60°C; Napajanje 12Vdc ±30%/2.7W; CE (EN55032, EN55024, EN50130-4)	€ 14,40	€ 24,00	 	Na lageru
HAC-T2A21-0360B	4u1 (analogna, HDCVI, AHD, TVI) 2MP dome IC kamera; 1/2.7" 2 Megapixels CMOS; Efektivni broj piksela 1920(H) x 1080(V); Rezolucija 1920x1080@25 fps ili 1280x720@25/50 fps; 3.6mm F1.85 fiksni objektiv; Vidni ugao 93°; Opciono 2.8mm ili 6mm (vidni ugao 103° ili 54.7°); Osetljivost 0.04Lux/F1.85, 0Lux (IC uključ.); True day/night (ICR); Smart IC LE diode dometa cca. 20m; DWDR; BLC; 2D DNR; OSD; Izbor moda rada putem UTC OSD kontrolera ili sa HCVR uređaja; Prenos signala koaksijalnim kablom 75Ω na dužinama do 500m; Dimenzije 69.8mmx69.8mmx157.6mm; Masa 250g; Alu. kućište; IP67 sertifikovana; Radna temperatura -40°C~+60°C; Napajanje 12Vdc ±30%/2.7W; CE (EN55032, EN55024, EN50130-4)	€ 14,40	€ 24,00	 	Na lageru
4u1 2MP D/N dome IC kamera; Cooper serija; Smart IC 20m; Kućište od kombinacije aluminijuma i plastike; 2.7-12mm varifokal objektiv; IP67					
HAC-T3A21-VF	4u1 (analogna, HDCVI, AHD, TVI) 2MP dome IC kamera; 1/2.7" 2 Megapixels CMOS; Efektivni broj piksela 1920(H) x 1080(V); Rezolucija 1920x1080@25 fps ili 1280x720@25/50 fps; 2.7~12mm F1.8 objektiv, ručni zum, ručni fokus, fiksni iris; Podesivi vidni ugao 106°~33° horizontalno; Osetljivost 0.04Lux/F1.8, 0Lux (IC uključ.); True day/night (ICR); Smart IC LE diode dometa cca. 30m; DWDR; BLC; 2D DNR; OSD; Izbor moda rada putem UTC OSD kontrolera ili sa HCVR uređaja; Prenos signala koaksijalnim kablom 75Ω na dužinama do 500m; Dimenzije Φ122mmx106mm; Masa 390g; Kućište od kombinacije aluminijuma i plastike; IP67 sertifikovana; Radna temperatura -40°C~+60°C; Napajanje 12Vdc ±30%/4.6W; CE (EN55032, EN55024, EN50130-4)	€ 34,20	€ 57,00	 	Novo! Na lageru
4u1 2MP D/N bullet IC kamera; Cooper serija; Smart IC 30m; Metalno kućište; 2.7-12mm varifokal objektiv; IP67					
HAC-B4A21-VF	4u1 (analogna, HDCVI, AHD, TVI) 2MP bullet IC kamera; 1/2.7" 2 Megapixels CMOS; Efektivni broj piksela 1920(H) x 1080(V); Rezolucija 1920x1080@25 fps ili 1280x720@25/50 fps; 2.7~12mm F1.8 objektiv, ručni zum, ručni fokus, fiksni iris; Podesivi vidni ugao 106°~33° horizontalno; Osetljivost 0.04Lux/F1.8, 0Lux (IC uključ.); True day/night (ICR); Smart IC LE diode dometa cca. 30m; DWDR; BLC; 2D DNR; OSD; Izbor moda rada putem UTC OSD kontrolera ili sa HCVR uređaja; Prenos signala koaksijalnim kablom 75Ω na dužinama do 500m; Dimenzije 209.8mmx90.4mmx90.4mm; Masa 590g; Alu. kućište; IP67 sertifikovana; Radna temperatura -30°C~+60°C; Napajanje 12Vdc ±30%/4.6W; CE (EN55032, EN55024, EN50130-4)	€ 37,80	€ 63,00	 	Novo! Na lageru


2MP 4u1 kamere, S3 Lite serija; Sa OSD-om; 2D DNR

Kod	OPIS	VP	MSRP	Slika	
4u1 2MP D/N dome IC kamera; Lite serija; Smart IC 30m; Metalno kućište; 3.6mm objektiv; IP67					
HAC-HDW1200M-0360B	4u1 (analogna, HDCVI, AHD, TVI) 2MP dome IC kamera; 1/2.7" 2 Megapixels CMOS; Efektivni broj piksela 1920(H) x 1080(V); Rezolucija 1920x1080@25 fps ili 1280x720@25/50 fps; 3.6mm fiksni objektiv; Vidni ugao 89.9°; Opciono 6mm (vidni ugao 59.4°); Osetljivost 0.02Lux/F2.0 (AGC On), 0Lux (IC uključ.); True day/night (ICR); Smart IC SMD LE diode dometa cca. 30m; DWDR; BLC; 2D DNR; OSD; Izbor moda rada putem UTC OSD kontrolera ili sa HCVR uređaja; Prenos signala koaksijalnim kablom 75Ω na dužinama do 500m; Dimenzije Ø93.4mm x 79.7mm; Masa 330g; Metalno kućište; IP67 sertifikovana; Radna temperatura -40°C~+60°C; Napajanje 12VDC/2.8W	€ 15,00	€ 25,00	 	Na lageru
4u1 2MP D/N bullet IC kamera; Lite serija; Smart IC 30m; Metalno kućište; 2.8mm objektiv; IP67					
HAC-HFW1200T-0280B	4u1 (analogna, HDCVI, AHD, TVI) 2MP bullet IC kamera; 1/2.7" 2 Megapixels CMOS; Efektivni broj piksela 1920(H) x 1080(V); Rezolucija 1920x1080@25 fps ili 1280x720@25/50 fps; 2.8mm fiksni objektiv; Vidni ugao 103°; Opciono 3.6mm ili 6mm (vidni ugao 89.9° ili 54.7°); Osetljivost 0.02Lux/F1.85, 0Lux (IC uključ.); True day/night (ICR); Smart IC SMD LE diode dometa cca. 20m; DWDR; BLC; 2D DNR; OSD; Izbor moda rada putem UTC OSD kontrolera ili sa HCVR uređaja; Prenos signala koaksijalnim kablom 75Ω na dužinama do 500m; Dimenzije 176mmx72.4mmx72.5mm; Masa 340g; Metalno kućište; IP67 sertifikovana; Radna temperatura -40°C~+60°C; Napajanje 12VDC/3.2W	€ 15,00	€ 25,00	 	Na lageru
4u1 2MP D/N bullet IC kamera; Lite serija; Smart IC 30m; Metalno kućište; 2.8mm objektiv; Mikrofon; IP67					
HAC-HFW1200T-A-0280B	4u1 (analogna, HDCVI, AHD, TVI) 2MP bullet IC kamera sa mikrofonom; 1/2.7" 2 Megapixels CMOS; Efektivni broj piksela 1920(H) x 1080(V); Rezolucija 1920x1080@25 fps ili 1280x720@25/50 fps; 2.8mm fiksni objektiv; Vidni ugao 103°; Opciono 3.6mm ili 6mm (vidni ugao 89.9° ili 54.7°); Osetljivost 0.02Lux/F1.85, 0Lux (IC uključ.); True day/night (ICR); Smart IC SMD LE diode dometa cca. 30m; Inkorporiran mikrofon; DWDR; BLC; 2D DNR; OSD; Izbor moda rada putem UTC OSD kontrolera ili sa HCVR uređaja; Prenos signala koaksijalnim kablom 75Ω na dužinama do 500m; Dimenzije 176mmx72.4mmx72.5mm; Masa 340g; Metalno kućište; IP67 sertifikovana; Radna temperatura -40°C~+60°C; Napajanje 12VDC/3.2W	€ 19,00	€ 31,67	 	Na lageru
4u1 2MP D/N dome IC kamera; Lite serija; Smart IC 50m; Metalno kućište; 3.6mm objektiv; IP67					
HAC-HDW1200EM-0360B	4u1 (analogna, HDCVI, AHD, TVI) 2MP dome IC kamera; 1/2.7" 2 Megapixels CMOS; Efektivni broj piksela 1920(H) x 1080(V); Rezolucija 1920x1080@25 fps ili 1280x720@25/50 fps; 3.6mm fiksni objektiv; Vidni ugao 89.9°; Opciono 6mm (vidni ugao 59.4°); Osetljivost 0.02Lux/F2.0 (AGC On), 0Lux (IC uključ.); True day/night (ICR); Smart IC LE diode dometa cca. 50m; DWDR; BLC; 2D DNR; OSD; Izbor moda rada putem UTC OSD kontrolera ili sa HCVR uređaja; Prenos signala koaksijalnim kablom 75Ω na dužinama do 500m; Dimenzije Ø106mm x 93.7mm; Masa 440g; Metalno kućište; IP67 sertifikovana; Radna temperatura -40°C~+60°C; Napajanje 12VDC/3.2W	€ 24,00	€ 40,00	 	Na lageru
4u1 2MP D/N bullet IC kamera; Lite serija; Smart IC 80m; Kombinacija plastike i metala; 3.6mm objektiv; Mikrofon; IP67					
HAC-HFW1200TL-A-0360B	4u1 (analogna, HDCVI, AHD, TVI) 2MP bullet IC kamera; 1/2.7" 2 Megapixels CMOS; Efektivni broj piksela 1920(H) x 1080(V); Rezolucija 1920x1080@25 fps ili 1280x720@25/50 fps; 3.6mm fiksni objektiv; Vidni ugao 87.5°; Opciono 2.8mm ili 6mm (vidni ugao 103° ili 54.4°); Osetljivost 0.02Lux/F1.85, 0Lux (IC uključ.); True day/night (ICR); Smart IC LE diode dometa cca. 80m; Inkorporiran mikrofon; DWDR; BLC; 2D DNR; OSD; Izbor moda rada putem UTC OSD kontrolera ili sa XVR uređaja; Prenos signala koaksijalnim kablom 75Ω na dužinama do 500m; Dimenzije 80.2mmx76.2mmx198.9mm; Masa 270g; Kućište od kombinacije metala i plastike; IP67 sertifikovana; Radna temperatura -40°C~+60°C; Napajanje 12VDC/5.3W	€ 25,20	€ 42,00	 	Na lageru
4u1 2MP D/N dome IC kamera; Lite serija; Smart IC 50m; Metalno kućište; 3.6mm objektiv; Mikrofon; IP67					
HAC-HDW1200EM-A-0280B	4u1 (analogna, HDCVI, AHD, TVI) 2MP dome IC kamera sa mikrofonom; 1/2.7" 2 Megapixels CMOS; Efektivni broj piksela 1920(H) x 1080(V); Rezolucija 1920x1080@25 fps ili 1280x720@25/50 fps; 3.6mm fiksni objektiv; Vidni ugao 89.9°; Opciono 6mm (vidni ugao 59.4°); Osetljivost 0.02Lux/F2.0 (AGC On), 0Lux (IC uključ.); True day/night (ICR); Smart IC LE diode dometa cca. 50m; Inkorporiran mikrofon; DWDR; BLC; 2D DNR; OSD; Izbor moda rada putem UTC OSD kontrolera ili sa HCVR uređaja; Prenos signala koaksijalnim kablom 75Ω na dužinama do 500m; Dimenzije Ø106mm x 93.7mm; Masa 440g; Metalno kućište; IP67 sertifikovana; Radna temperatura -40°C~+60°C; Napajanje 12VDC/2.9W	€ 27,60	€ 46,00	 	Na lageru


2MP 4u1 kamere, S3 Lite serija; Sa OSD-om; 2D DNR

Kod	OPIS	VP	MSRP	Slika		
4u1 2MP D/N anti-vandal dome IC kamera; Lite serija; Smart IC 30m; Metalno kućište; 3.6mm objektiv; IP67 i IK10						
HAC-HDBW1200E-0360B	4u1 (analogna, HDCVI, AHD, TVI) 2MP anti-vandal dome IC kamera; 1/2.7" 2 Megapixels CMOS; Efektivni broj piksela 1920(H) x 1080(V); Rezolucija 1920x1080@25 fps ili 1280x720@25/50 fps; 3.6mm fiksni objektiv; Vidni ugao 89.9°; Opciono 6mm (vidni ugao 59.4°); Osetljivost 0.02Lux/F2.0 (AGC On), 0Lux (IC uključ.); True day/night (ICR); Smart IC LE dioda dometa cca. 30m; DWDR; BLC; 2D DNR; OSD; Izbor moda rada putem UTC OSD kontrolera ili sa HCVR uređaja; Prenos signala koaksijalnim kablom 75Ω na dužinama do 500m; Dimenzije Φ109.9mm x 81.0mm; Masa 310g; Metalno kućište; IP67 i IK10 sertifikovana; Radna temperatura -40°C~+60°C; Napajanje 12VDC/2.8W	€ 30,00	€ 50,00	4 u 1 2Mp OSD WDR 2D DNR IP 67 ICR Smart IC LED 30m D-WDR 2D DNR IP 67 ICR Smart IC LED 30m WDR 2D DNR IP 67 ICR Smart IC LED 30m  2MP HDCVI Cruiser Na lageru		


4u1 2MP D/N bullet IC kamera; Lite serija; Smart IC 80m; Metalno kućište; 3.6mm objektiv; IP67

HAC-HFW1200D-0360B	4u1 (analogna, HDCVI, AHD, TVI) 2MP bullet IC kamera; 1/2.7" 2 Megapixels CMOS; Efektivni broj piksela 1920(H) x 1080(V); Rezolucija 1920x1080@25 fps ili 1280x720@25/50 fps; 3.6mm fiksni objektiv; Vidni ugao 89.9°; Opciono 6mm ili 8mm (vidni ugao 59.4° ili 41.4°); Osetljivost 0.02Lux/F2.0 (AGC On), 0Lux (IC uključ.); True day/night (ICR); Smart IC LE diode dometa cca. 80m; DWDR; BLC; 2D DNR; OSD; Izbor moda rada putem UTC OSD kontrolera ili sa HCVR uređaja; Prenos signala koaksijalnim kablom 75Ω na dužinama do 500m; Dimenzije 241.8mmx90.4mmx90.4mm; Masa 640g; Metalno kućište; IP67 sertifikovana; Radna temperatura -40°C~+60°C; Napajanje 12VDC/6.8W	€ 31,80	€ 53,00		Na lageru		
--------------------	--	---------	---------	---	-----------	--	--


4u1 2MP D/N dome IC kamera; Lite serija; Smart IC 60m; Metalno kućište; MZ AF objektiv 2.7-12mm; IP67

HAC-HDW1200T-Z	4u1 (analogna, HDCVI, AHD, TVI) 2MP dome IC True D/N kamera; 1/2.7" 2 Megapixels CMOS; Efektivni broj piksela 1920(H) x 1080(V); Rezolucija 1080P@25/30fps, do 60fps u 720P; 2.7~12mm F1.8 objektiv, motorizovani zum, automatski fokus, fiksni iris; Podesivi vidni ugao 105.9°~33.4°; Osetljivost 0.02Lux/F1.8 (AGC Uključ.), 0Lux (IC Uključ.); True day/night (ICR); Smart IC LE diode dometa cca. 60m; DWDR; 2D DNR; BLC; OSD; Izbor moda rada putem UTC OSD kontrolera ili sa HCVR uređaja; Prenos signala koaksijalnim kablom 75Ω na dužinama do 500m; Dimenzije Φ122mmx104mm; Masa 570g; IP67 sertifikovana; Radna temperatura -30°C~+60°C; Napajanje 12VDC±30%/6.9W	€ 42,60	€ 71,00		Na lageru		
----------------	--	---------	---------	---	-----------	--	--

4u1 2MP anti-vandal dome IC kamera; Smart IC 30m; Metalno kućište; MZ AF objektiv 2.7-12mm; IP67 i IK10

HAC-HDBW1200R-Z	4u1 (analogna, HDCVI, AHD, TVI) 2 megapixels anti-vandal dome IC True D/N kamera; 1/2.7" 2 Megapixels CMOS; Efektivni broj piksela 1920(H) x 1080(V); Rezolucija 1080P@25/30fps, do 60fps u 720P; 2.7~12mm F1.8 objektiv, motorizovani zum, automatski fokus, fiksni iris; Podesivi vidni ugao 105.9°~33.4°; Osetljivost 0.02Lux/F1.8 (AGC Uključ.), 0Lux (IC Uključ.); True day/night (ICR); Smart IC LE diode dometa cca. 30m; DWDR; 2D DNR; BLC; OSD; Izbor moda rada putem UTC OSD kontrolera ili sa HCVR uređaja; Prenos signala koaksijalnim kablom 75Ω na dužinama do 500m; Dimenzije Φ122mmx88.9mm; Masa 440g; IP67 i IK10; Radna temperatura -40°C~+60°C; Napajanje 12VDC/6.3W	€ 44,40	€ 74,00		Na lageru		
-----------------	---	---------	---------	---	-----------	--	--

4u1 2MP D/N bullet IC kamera; Lite serija; Smart IC 60m; Metalno kućište; MZ AF objektiv 2.7-12mm; IP67

HAC-HFW1200R-Z IRE6	4u1 (analogna, HDCVI, AHD, TVI) 2MP bullet IC True D/N kamera; 1/2.7" 2 Megapixels CMOS; Efektivni broj piksela 1920(H) x 1080(V); Rezolucija 1080P@25/30fps, do 60fps u 720P; 2.7~12mm F1.8 objektiv, motorizovani zum, automatski fokus, fiksni iris; Podesivi vidni ugao 105.9°~33.4°; Osetljivost 0.02Lux/F1.8 (AGC Uključ.), 0Lux (IC Uključ.); True day/night (ICR); Smart IC LE diode dometa cca. 60m; DWDR; 2D DNR; BLC; OSD; Izbor moda rada putem UTC OSD kontrolera ili sa HCVR uređaja; Prenos signala koaksijalnim kablom 75Ω na dužinama do 500m; Dimenzije 213mmx90.4mmx90.4mm; Masa 550g; IP67; Radna temperatura -30°C~+60°C; Napajanje 12VDC±30%/12.1W	€ 44,40	€ 74,00		Na lageru		
---------------------	--	---------	---------	---	-----------	--	--

2MP HDCVI i 4u1 kamere, nova S3 Lite serija; Sa OSD-om; 2D DNR; Sa Sony Exmor CMOS-om

Kod	OPIS	VP	MSRP	Slika	
4u1 2MP D/N bullet IC kamera; Lite serija; Smart IC 20m; Metalno kućište; Sony Exmor; 2.8mm objektiv; IP67					
HAC-HFW1220RM-0280B	4u1 (analogna, HDCVI, AHD, TVI) 2MP bullet IC kamera; 1/2.9" 2 Megapixels Sony Exmor CMOS; Efektivni broj piksela 1920(H) x 1080(V); Rezolucija 1920x1080@25 fps ili 1280x720@25/50 fps; 2.8mm fiksni objektiv; Vidni ugao 106°; Opciono 3.6mm ili 6mm (vidni ugao 82.6° ili 51.2°); Osetljivost 0.02Lux/F2.0 (AGC On), 0Lux (IC uključ.); True day/night (ICR); Smart IC LE diode dometa cca. 20m; DWDR; BLC; 2D DNR; OSD; Izbor moda rada putem UTC OSD kontrolera ili sa HCVR uređaja; Prenos signala koaksijalnim kablom 75Ω na dužinama do 500m; Dimenzije 156.3mmx70mmx70mm; Masa 300g; Metalno kućište; IP67; Radna temperatura -40°C~+60°C; Napajanje 12VDC/2.8W	€ 23,00	€ 38,33	4 u 1 2Mp ICR/DNR OSD IP67 SMART IC LED 20m D-WDR 2D DNR DC12V -40°C~+60°C DO ISTAKA ZALTA! 2MP HDCVI  Cannon Na lageru	


2MP HDCVI i 4u1 kamere, nova S3 Lite serija; Sa OSD-om; 2D DNR; Sa Sony Exmor CMOS-om

Kod	OPIS	VP	MSRP		Slika		
4u1 2MP D/N dome IC kamera; Lite serija; Smart IC 20m; Crno metalno kućište; Sony Exmor; 3.6mm objektiv; Mikrofon; IP67							
HAC-HDW1220G-0360B	4u1 (analogna, HDCVI, AHD, TVI) 2MP dome IC kamera sa mikrofonom; 1/2.9" 2 Megapixels Sony Exmor CMOS; Efektivni broj piksela 1920(H) x 1080(V); Rezolucija 1920x1080@25 fps ili 1280x720@25/50 fps; 3.6mm fiksni objektiv; Vidni ugao 82.8°; Osetljivost 0.02Lux/F2.0 (AGC On), 0Lux (IC uključ.); True day/night (ICR); Smart IC LE diode dometa cca. 20m; Inkorporiran mikrofon; DWDR; BLC; 2D DNR; OSD; Izbor moda rada putem UTC OSD kontrolera ili sa HCVR uređaja; Prenos signala koaksijalnim kablom 75Ω na dužinama do 500m; Dimenzije Ø62mmx62mm; Masa 160g; Metalno kućište crne boje; IP67 sertifikovana; Radna temperatura -40°C~+60°C; Napajanje 12VDC/2.9W	€ 29,00	€ 48,33			Na lageru	
4u1 2MP D/N board kamera sa pinhole objektivom; Starlight; True WDR							
HAC-HUM3201B-0280B	4u1 (analogna, HDCVI, AHD, TVI) 2MP bullet IC kamera; 1/2.8" 2 Megapixels Starvis™ CMOS; Efektivni broj piksela 1937(H) x 1097(V); Rezolucija 1920x1080@25 fps ili 1280x720@25/50 fps; 2.8mm fiksni pinhole objektiv; Vidni ugao 103°; Opciono 3.6mm (vidni ugao 92°); Osetljivost 0.05Lux/F2.4 (kolor), 0.005Lux/F2.4 (C/B); Day/night (Elek.); 120dB True WDR; BLC; 2D + 3D DNR; OSD; Izbor moda rada putem UTC OSD kontrolera ili sa XVR uređaja; Prenos signala koaksijalnim kablom 75Ω na dužinama do 500m; Dimenzije 35.5mmx29.9mmx22.1mm; Masa 90g; Radna temperatura -30°C~+60°C; Napajanje 12VDC ±30%/1.2W; CE (EN55032, EN55024, EN50130-4)	€ 44,95	€ 74,92			Na lageru	


2MP HDCVI i 4u1 kamere, Lite Plus serija; Sa OSD-om; 2D DNR; Starlight

Kod	OPIS	VP	MSRP		Slika		
4u1 2MP D/N dome IC kamera; Lite Plus serija; Smart IC 30m; Metalno kućište; Starlight; 2.8mm objektiv; IP67							
HAC-HDW1230M-0280B	4u1 (analogna, HDCVI, AHD, TVI) 2MP bullet IC kamera; 1/2.8" 2 Megapixels Starvis™ CMOS; Efektivni broj piksela 1920(H) x 1080(V); Rezolucija 1920x1080@25 fps ili 1280x720@25/50 fps; 2.8mm F1.6 fiksni objektiv; Vidni ugao 106°; Opciono 3.6mm ili 6mm (vidni ugao 86.9°ili 52.9°); Osetljivost 0.005Lux/F1.6 (AGC On), 0Lux (IC uključ.); True day/night (ICR); Smart IC LE diode dometa cca. 80m; DWDR; BLC; 2D DNR; OSD; Izbor moda rada putem UTC OSD kontrolera ili sa HCVR uređaja; Prenos signala koaksijalnim kablom 75Ω na dužinama do 500m; Dimenzije Ø93.4mmx79.4mm; Masa 270g; IP67 sertifikovana; Radna temperatura -40°C~+60°C; Napajanje 12VDC ±30%/3.5W; CE (EN55032, EN55024, EN50130-4)	€ 22,20	€ 37,00			Na lageru	
4u1 2MP D/N bullet IC kamera; Lite Plus serija; Smart IC 80m; Metalno kućište; Starlight; 3.6mm objektiv; IP67							
HAC-HFW1230D-0360B	4u1 (analogna, HDCVI, AHD, TVI) 2MP bullet IC kamera; 1/2.8" 2 Megapixels Starvis™ CMOS; Efektivni broj piksela 1920(H) x 1080(V); Rezolucija 1920x1080@25 fps ili 1280x720@25/50 fps; 3.6mm F1.6 fiksni objektiv; Vidni ugao 86.9°; Opciono 6mm ili 8mm (vidni ugao 52.9°ili 40.5°); Osetljivost 0.005Lux/F1.6 (AGC On), 0Lux (IC uključ.); True day/night (ICR); Smart IC LE diode dometa cca. 80m; DWDR; BLC; 2D DNR; OSD; Izbor moda rada putem UTC OSD kontrolera ili sa HCVR uređaja; Prenos signala koaksijalnim kablom 75Ω na dužinama do 500m; Dimenzije 241.8mmx90.4mmx90.4mm; Masa 580g; IP67 sertifikovana; Radna temperatura -40°C~+60°C; Napajanje 12VDC ±30%/5.6W; CE (EN55032, EN55024, EN50130-4)	€ 31,00	€ 51,67			Na lageru	
4u1 2MP D/N bullet IC kamera; Lite Plus serija; Smart IC 60m; Metalno kućište; Starlight; MZ AF 2.7-12mm objektiv; IP67							
HAC-HFW1230R-ZIRE6	4u1 (analogna, HDCVI, AHD, TVI) 2MP bullet IC kamera; 1/2.8" 2 Megapixels Starvis™ CMOS; Efektivni broj piksela 1920(H) x 1080(V); Rezolucija 1920x1080@25 fps ili 1280x720@25/50 fps; 2.7~12mm F1.8 objektiv, motorizovani zum, automatski fokus, fiksni iris; Podesivi vidni ugao 101.7°~32.3°; Osetljivost 0.005Lux/F1.6 (AGC On), 0Lux (IC uključ.); True day/night (ICR); Smart IC LE diode dometa cca. 60m; DWDR; BLC; 2D DNR; OSD; Izbor moda rada putem UTC OSD kontrolera ili sa HCVR uređaja; Prenos signala koaksijalnim kablom 75Ω na dužinama do 500m; Dimenzije 213.0mmx90.4mmx90.4mm; Masa 550g; IP67 sertifikovana; Radna temperatura -30°C~+60°C; Napajanje 12VDC ±30%/12.1W; CE (EN55032, EN55024, EN50130-4)	€ 49,00	€ 93,00			Novo! Na lageru	


IoT serija, MotionEye I LinCa modeli

Kod	OPIS	VP	MSRP		Slika		
4u1 2MP bullet IC LinCa kamera sa senzorom temperature i vlažnosti							
HAC-LC1200T-TH	LinCa 4u1 (analogna, HDCVI, AHD, TVI) 2MP bullet IC True D/N kamera sa senzorom temperature i vlažnosti; 1/2.9" 2 Megapixels Sony Exmor CMOS; Efektivni broj piksela 1920(H) x 1080(V); Rezolucija 1920x1080@25 fps ili 1280x720@25/50 fps; 3.6mm fiksni objektiv; Vidni ugao 82.8°; Opciono 2.8mm ili 6mm (vidni ugao 104° ili 51.2°); Osetljivost 0.02Lux/F2.0 (AGC On), 0Lux (IC uklju.); True day/night (ICR); Smart IC LE diode dometa cca. 20m; DWDR; BLC; 2D DNR; OSD; Inkorporiran senzor temperature i vlažnosti - meri opseg -40°C~+60°C, 10-95% RH; Prikaz temperature i vlažnosti; Izbor moda rada putem UTC OSD kontrolera ili sa XVR uređaja; Prenos signala koaksijalnim kablom 75Ω na dužinama do 500m; Dimenzije 176.1x85.4x75.2mm; Masa 400g; IP67; Radna temperatura -40°C~+60°C; Napajanje 12VDC ±30% /3.4W	€ 33,60	€ 56,00			Na lageru	


4u1 2MP D/N kamera sa IC detektorom

HAC-HUM1220A-0360B	4u1 (analogna, HDCVI, AHD, TVI) 2MP kamera sa IC detektorom; 1/2.9" 2MP Sony Exmor CMOS; Efektivni broj piksela 1920(H) x 1080(V); Rezolucija 1920x1080@25 fps ili 1280x720@25/50 fps; 2.8mm fiksni objektiv; Vidni ugao 100.5°; Osetljivost 0.02Lux/F2.0 (kolor), 0.002Lux (C/B); Day/night (Soft.); DWDR; BLC; 2D DNR; OSD; Inkorporiran IC detektor 12x12m, 100°, 19 zona; Tamper zaštita; LED indikacija; Podešavanje osetljivosti u dva nivoa; Pet immunity do 18kg; Nominalna visina montaže 2.2 - 2.5m; Prenos alarmnog signala koaksijalnim kablom (HDCVI alarm); Dim. 120mm x62mm x58mm; Masa 130g; Napajanje 12VDC/0.7W	€ 45,00	€ 75,00			Na lageru	
--------------------	---	---------	---------	---	---	-----------	--


4u1 2MP IC kamera sa IC detektorom za spoljnu montažu

HAC-ME1200B-PIR	4u1 (analogna, HDCVI, AHD, TVI) 2MP bullet IC kamera sa IC detektorom; 1/2.7" 2MP progressive scan; Megapixel objektiv 2.8mm F2.0; Vidni ugao: 112°; Digitalni detektor kretanja, Područje detekcije: 10m, ugao pokrivanja 110°; Osetljivost 0.02Lux/F2.0, (kolor) 0Lux IR uključen; Smart IC LED dometa 20m; LED indikacija alarma; Prenos alarmnog stanja putem koaksijalnog kabla; True day/night (ICR); BLC; HLC; DWDR; 2D; Podržane rezolucije 1080P (1920x1080); Frame rate 25/30fps@1080P, 25/30/50/60fps@720P; IP67 sertifikovan; Opseg radne temperature -10°C~50°C; Dimenzije Ø146.6mmx72.4mmx83mm; Masa 0.23kg; Napajanje 12VDC	€ 25,20	€ 42,00			Na lageru	
-----------------	--	---------	---------	---	---	-----------	--

4MP 4u1 kamere, nova Lite serija; Dahua Missile DSP; Sa OSD-om; 2D DNR;

Kod	OPIS	VP	MSRP		Slika		
4u1 4MP D/N dome IC kamera; Lite serija; Smart IC 20m; Pl. kućište; 2.8mm objektiv							
HAC-HDW1400R-0280B	4u1 (analogna, HDCVI, AHD, TVI) 4MP dome IC kamera; 1/3" 4 Megapixels CMOS; Efektivni broj piksela 2688(H) x 1520(V); Rezolucija 2560x1440@25 fps ili 1920x1080@25fps ili 1280x720@25fps; 2.8mm fiksni objektiv; Vidni ugao 99.7°; Opciono 3.6 ili 6mm (vidni ugao 84.8° ili 52.5°); Osetljivost 0.03Lux/F2.0, 0Lux (IC uklju.); True day/night (ICR); Smart IC SMD LE diode dometa cca. 20m; DWDR; BLC; 2D DNR; OSD; Izbor moda rada putem UTC OSD kontrolera ili sa HCVR uređaja; Prenos signala koaksijalnim kablom 75Ω na dužinama do 500m; Dimenzije Ø85.4mm x 69.1mm; Masa 120g; Radna temperatura -40°C~+60°C; Napajanje 12VDC/3.2W	€ 26,00	€ 43,33			Na lageru	

4u1 4MP D/N dome IC kamera; Lite serija; Smart IC 20m; Metalno kućište; 2.8mm objektiv; IP67

HAC-HDW1400M-0280B	4u1 (analogna, HDCVI, AHD, TVI) 4MP dome IC kamera; 1/3" 4 Megapixels CMOS; Efektivni broj piksela 2688(H) x 1520(V); Rezolucija 2560x1440@25 fps ili 1920x1080@25fps ili 1280x720@25fps; 2.8mm fiksni objektiv; Vidni ugao 99.7°; Opciono 3.6 ili 6mm (vidni ugao 84.8° ili 52.5°); Osetljivost 0.03Lux/F2.0, 0Lux (IC uklju.); True day/night (ICR); Smart IC SMD LE diode dometa cca. 30m; DWDR; BLC; 2D DNR; OSD; Izbor moda rada putem UTC OSD kontrolera ili sa HCVR uređaja; Prenos signala koaksijalnim kablom 75Ω na dužinama do 500m; Dimenzije Ø93.4mmx79.4mm; Masa 280g; IP67 sertifikovana; Radna temperatura -40°C~+60°C; Napajanje 12VDC/3.2W	€ 28,20	€ 47,00			Na lageru	
--------------------	--	---------	---------	---	---	-----------	--

4u1 4MP D/N bullet IC kamera; Lite serija; Smart IC 30m; Metalno kućište; 3.6mm objektiv; IP67

HAC-HFW1400T-0360B	4u1 (analogna, HDCVI, AHD, TVI) 4MP bullet IC kamera; 1/3" 4 Megapixels CMOS; Efektivni broj piksela 2688(H) x 1520(V); Rezolucija 2560x1440@25 fps ili 1920x1080@25fps ili 1280x720@25fps; 3.6mm fiksni objektiv; Vidni ugao 84.8°; Opciono 2.8 ili 6mm (vidni ugao 99.7mm ili 52.5°); Osetljivost 0.03Lux/F2.0, 0Lux (IC uklju.); True day/night (ICR); Smart IC SMD LE diode dometa cca. 30m; DWDR; BLC; 2D DNR; OSD; Izbor moda rada putem UTC OSD kontrolera ili sa HCVR uređaja; Prenos signala koaksijalnim kablom 75Ω na dužinama do 500m; Dimenzije 176mmx72.4mmx72.5mm; Masa 360g; IP67 sertifikovana; Radna temperatura -40°C~+60°C; Napajanje 12VDC/3.2W	€ 29,40	€ 49,00			Na lageru	
--------------------	--	---------	---------	---	---	-----------	--

4MP 4u1 kamere, nova Lite serija; Dahua Missile DSP; Sa OSD-om; 2D DNR;

Kod	OPIS	VP	MSRP		Slika		
4u1 4MP D/N bullet IC kamera; Lite serija; Smart IC 80m; Kućište od komb. Plastike i metala; 3.6mm objektiv; Mikrofon; IP67							
HAC-HFW1400TL-A-0360B	4u1 (analogna, HDCVI, AHD, TVI) 4MP bullet IC kamera; 1/2.7" 4 Megapixels CMOS; Efektivni broj piksela 2560(H) x 1440(V); Rezolucija 2560x1440@25 fps ili 1920x1080@25fps ili 1280x720@25fps; 3.6mm F2.0 fiksni objektiv; Vidni ugao 76.4°; Opciono 2.8mm, 6mm ili 8mm (vidni ugao 97°, 48.6° ili 36.3°); Osetljivost 0.03Lux/F2.0, 0Lux (IC uključ.); True day/night (ICR); Smart IC LE diode dometa cca. 80m; Inkorporiran mikrofon; DWDR; BLC; 2D DNR; OSD; Izbor moda rada putem UTC OSD kontrolera ili sa XVR uređaja; Prenos signala koaksijalnim kablom 75Ω na dužinama do 500m; Dimenzije 80.2mm x76.2mm x198.9mm; Masa 230g; IP67 sertifikovana; Radna temperatura -40°C~+60°C; Napajanje 12VDC±30%/5.6W; CE (EN55032, EN55024, EN50130-4)	€ 31,80	€ 53,00			Na lageru	
4u1 4MP D/N dome IC kamera; Lite serija; Smart IC 50m; Metalno kućište; 2.8mm objektiv; Mikrofon; IP67							
HAC-HDW1400EM-A-0280B	4u1 (analogna, HDCVI, AHD, TVI) 4MP dome IC kamera sa mikrofonom; 1/3" 4 Megapixels CMOS; Efektivni broj piksela 2688(H) x 1520(V); Rezolucija 2560x1440@25 fps ili 1920x1080@25fps ili 1280x720@25fps; 2.8mm fiksni objektiv; Vidni ugao 99.7°; Opciono 3.6 ili 6mm (vidni ugao 84.8° ili 52.5°); Osetljivost 0.03Lux/F2.0, 0Lux (IC uključ.); True day/night (ICR); Smart IC LE dioda dometa cca. 50m; Inkorporiran mikrofon; DWDR; BLC; 2D DNR; OSD; Izbor moda rada putem UTC OSD kontrolera ili sa HCVR uređaja; Prenos signala koaksijalnim kablom 75Ω na dužinama do 500m; Dimenzije 176mmx72.4mmx72.5mm; Masa 360g; IP67 sertifikovana; Radna temperatura -40°C~+60°C; Napajanje 12VDC ±25% /4.1W	€ 34,80	€ 58,00			Na lageru	
4u1 4MP D/N bullet IC kamera; Lite serija; Smart IC 50m; Metalno kućište; 3.6mm objektiv; Mikrofon; IP67							
HAC-HFW1400D-0360B	4u1 (analogna, HDCVI, AHD, TVI) 4MP dome IC kamera; 1/3" 4 Megapixels CMOS; Efektivni broj piksela 2688(H) x 1520(V); Rezolucija 2560x1440@25 fps ili 1920x1080@25fps ili 1280x720@25fps; 3.6mm fiksni objektiv; Vidni ugao 84.8°; Opciono 6mm, 8mm ili 12mm (vidni ugao 52.5°, 32.9° ili 23.6°); Osetljivost 0.03Lux/F2.0, 0Lux (IC uključ.); True day/night (ICR); Smart IC LE diode dometa cca. 80m; DWDR; BLC; 2D DNR; OSD; Izbor moda rada putem UTC OSD kontrolera ili sa HCVR uređaja; Prenos signala koaksijalnim kablom 75Ω na dužinama do 500m; Dimenzije 241.8mmx90.4mmx90.4mm; Masa 590g; IP67 sertifikovana; Radna temperatura -40°C~+60°C; Napajanje 12VDC/5.2W	€ 39,00	€ 65,00			Na lageru	
4u1 4MP D/N dome IC kamera; Lite serija; Smart IC 30m; Metalno kućište; VF objektiv 2.7-13.5mm; IP67							
HAC-HDW1400R-VF	4u1 (analogna, HDCVI, AHD, TVI) 4MP dome IC kamera; 1/3" 4 Megapixels CMOS; Efektivni broj piksela 2688(H) x 1520(V); Rezolucija 2560x1440@25 fps ili 1920x1080@25fps ili 1280x720@25fps; 2.7~13.5mm objektiv, manuelni zum, manuelni fokus, fiksni iris; Podesivi vidni ugao 98°~26°; Osetljivost 0.03Lux/F1.3 (AGC Uključ.), 0Lux (IC Uključ.); True day/night (ICR); Smart IC LE diode dometa cca. 30m; DWDR; BLC; 2D DNR; OSD; Izbor moda rada putem UTC OSD kontrolera ili sa HCVR uređaja; Prenos signala koaksijalnim kablom 75Ω na dužinama do 500m; Dimenzije Φ119mmx97.4mm; Masa 560g; IP67 sertifikovana; Radna temperatura -40°C~+60°C; Napajanje 12VDC/4.6W	€ 53,40	€ 89,00			Na lageru	
4u1 4MP D/N bullet IC kamera; Lite serija; Smart IC 60m; Metalno kućište; VF objektiv 2.7-13.5mm; IP67							
HAC-HFW1400R-VF-IRE6	4u1 (analogna, HDCVI, AHD, TVI) 4MP bullet IC kamera; 1/3" 4 Megapixels CMOS; Efektivni broj piksela 2688(H) x 1520(V); Rezolucija 2560x1440@25 fps ili 1920x1080@25fps ili 1280x720@25fps; 2.7~13.5mm objektiv, manuelni zum, manuelni fokus, fiksni iris; Podesivi vidni ugao 98°~26°; Osetljivost 0.03Lux/F1.3 (AGC Uključ.), 0Lux (IC Uključ.); True day/night (ICR); Smart IC LE diode dometa cca. 60m; DWDR; BLC; 2D DNR; OSD; Izbor moda rada putem UTC OSD kontrolera ili sa HCVR uređaja; Prenos signala koaksijalnim kablom 75Ω na dužinama do 500m; Dimenzije 213.0mm x90.4mmx90.4mm; Masa 630g; IP67 sertifikovana; Radna temperatura -40°C~+60°C; Napajanje 12VDC/7.6W	€ 57,00	€ 95,00			Na lageru	
4u1 4MP D/N bullet IC kamera; Lite serija; Smart IC 60m; Metalno kućište; MZ AF objektiv 2.7-12mm; IP67							
HAC-HFW1400R-Z-IRE6	4u1 (analogna, HDCVI, AHD, TVI) 4MP bullet IC kamera; 1/2.7" 4 Megapixels CMOS; Efektivni broj piksela 2688(H) x 1520(V); Rezolucija 2560x1440@25 fps ili 1920x1080@25fps ili 1280x720@25fps; 2.7~12mm F1.8 objektiv, motorizovani zum, automatski fokus, fiksni iris; Podesivi vidni ugao 92°~29° horizontalno; Osetljivost 0.03Lux/F1.8, 0Lux (IC Uključ.); True day/night (ICR); Smart IC LE diode dometa cca. 60m; DWDR; BLC; 2D DNR; OSD; Izbor moda rada putem UTC OSD kontrolera ili sa HCVR uređaja; Prenos signala koaksijalnim kablom 75Ω na dužinama do 500m; Dimenzije 209.9mmx90.4mmx90.4mm; Masa 550g; IP67 sertifikovana; Radna temperatura -30°C~+60°C; Napajanje 12VDC±30%/11.5W; CE (EN55032, EN55024, EN50130-4)	€ 59,40	€ 99,00			Na lageru	

2.1MP 4u1 kamere, Starlight Pro serija; Sa OSD-OM; 2D+3D DNR; 120dB WDR

Kod	OPIS	VP	MSRP	Slika			
4u1 2.1 Megapixel CMOS True D/N bullet IC kamera sa sa motorizovanim auto-fokus objektivom; Smart IC 60m; WDR 120dB; Starlight							
HAC-HFW2231R-Z IRE6-027135	Starlight 4u1 (analogna, HDCVI, AHD, TVI) 2.1 megapixel bullet IR True D/N kamera sa motorizovanim auto-fokus objektivom; 1/2.8" 2.1 Megapixel Progressive scan CMOS; Efektivni broj piksela 1937(H) x 1097(V); Rezolucija 1920x1080@25 fps ili 1280x720@25fps; 2.7~13.5mm F1.3 objektiv, motorizovani zum, automatski fokus, fiksni iris; Podesivi vidni ugao 102°~29°; Osetljivost 0.005Lux/F1.3, 0Lux (IC uključ.); True day/night (IRC); Smart IC LE diode dometa cca. 60m; 120dB True WDR; 2D + 3D DNR; OSD; Izbor moda rada putem UTC OSD kontrolera ili sa XVR/HCVR uređaja; Prenos signala koaksijalnim kablom 75Ω na dužinama do 500m; IP67 sertifikovana; Dimenzije 213.0mmx90.4mmx90.4mm; Masa 610g; Radna temperatura -40°C~+60°C; Napajanje 12Vdc/10.1W; U kompletu sa nosačem za zidnu montažu, interni prolaz kabla	€ 58,00	€ 96,67	4 u 1 2.1Mp 2.7-13.5mm 120dB WDR 2D+3D DNR DC12V SMART LED 40m OSD IP 67 ICR 60m Auto zoom Auto fokus 102°~29° 120dB WDR IP 67 DC12V DO ISTEKA ZALIHAI 2MP HDCVI  Starlight RASPRODAJA	Na lageru		

4u1 2.1 Megapixel CMOS True D/N bullet IC kamera sa motorizovanim auto-fokus objektivom; Smart IC 60m; WDR 120dB; Starlight

HAC-HFW2231R-Z IRE6-0722	Starlight 4u1 (analogna, HDCVI, AHD, TVI) 2.1 megapixel bullet IR True D/N kamera sa motorizovanim auto-fokus objektivom; 1/2.8" 2.1 Megapixel Progressive scan CMOS; Efektivni broj piksela 1937(H) x 1097(V); Rezolucija 1920x1080@25 fps ili 1280x720@25fps; 7~22mm F1.3 objektiv, motorizovani zum, automatski fokus, fiksni iris; Podesivi vidni ugao 40°~17°; Osetljivost 0.005Lux/F1.3, 0Lux (IC uključ.); True day/night (IRC); Smart IC LE diode dometa cca. 60m; 120dB True WDR; 2D + 3D DNR; OSD; Izbor moda rada putem UTC OSD kontrolera ili sa XVR/HCVR uređaja; Prenos signala koaksijalnim kablom 75Ω na dužinama do 500m; IP67 sertifikovana; Dimenzije 213.0mmx90.4mmx90.4mm; Masa 610g; Radna temperatura -40°C~+60°C; Napajanje 12VDC/10.1W; U kompletu sa nosačem za zidnu montažu, interni prolaz kabla	€ 58,00	€ 96,67		Na lageru		
-----------------------------	---	---------	---------	---	-----------	--	--

4u1 2.1 Megapixel CMOS True D/N anti-vandal dome IC kamera sa motorizovanim auto-fokus objektivom; Smart IC 30m; WDR 120dB; Starlight

HAC-HDBW2231R-Z	Starlight 4u1 (analogna, HDCVI, AHD, TVI) 2.1MP anti-vandal dome IC kamera sa motorizovanim auto-fokus objektivom; 1/2.8" 2.1 Megapixel CMOS; Efektivni broj piksela 1937(H) x 1097(V); Rezolucija 1920x1080@25 fps ili 1280x720@25/50 fps; 2.7~13.5mm F1.3 objektiv, motorizovani zum, automatski fokus, fiksni iris; Podesivi vidni ugao 102°~29°; Osetljivost 0.005Lux/F1.3, 0Lux (IC uključ.); True day/night (IRC); Smart IC LE diode dometa cca. 30m; 120dB True WDR; DWDR; 2D + 3D DNR; OSD; Izbor moda rada putem UTC OSD kontrolera ili sa XVR/HCVR uređaja; Prenos signala koaksijalnim kablom 75Ω na dužinama do 500m; Anti-vandal dome kućište; IP67 & IK10 sertifikovana; Radna temperatura -40°C~+60°C; Dimenzije Ø122mm x 89mm; Masa 470g; Napajanje 12VDC/5.4W	€ 58,00	€ 96,67		Na lageru		
-----------------	--	---------	---------	---	-----------	--	--

2MP 4u1 kamere, Starlight+ Pro serija; Sa OSD-OM; 2D+3D DNR; 120dB WDR

Kod	OPIS	VP	MSRP	Slika		
4u1 2MP dome IC kamera; Smart IC 30m; WDR 120dB; Starlight+						
HAC-HDW2241M-0280B	Starlight+ 4u1 (analogna, HDCVI, AHD, TVI) 2 MP dome IC True D/N WDR kamera; 1/2.8" 2 Megapixels progressive scan CMOS; Efektivni broj piksela 1920(H) x 1080(V); Rezolucija 1920x1080@25 fps ili 1280x720@25/50 fps; 2.8mm F1.6 fiksni objektiv; Vidni ugao 110°; Opciono 3.6 ili 6mm (vidni ugao 86.9° ili 52.8°); Osetljivost 0.004Lux/F1.6, 0Lux (IC uključ.); True day/night (ICR); Smart IC LE diode dometa cca. 30m; 120dB True WDR; 2D + 3D DNR; OSD; Audio ulaz; Broadcast audio kvalitet; Izbor moda rada putem prekidača na kablju kamere, UTC OSD kontrolera, sa XVR/HCVR uređaja; Prenos signala koaksijalnim kablom 75Ω na dužinama do 500m; Dimenzije Ø93.4mmx79.4mm; Masa 300g; Alu. kućište; IP67 sertifikovana; Radna temperatura -40°C~+60°C; Napajanje 12VDC/4.7W	€ 48,00	€ 80,00	4 u 1 2Mp 120dB WDR AUDIO IN DC 12V ICR D/N OSD IP 67 SMARTIC LED 30m 2D+3D DNR -40°C~+60°C 2MP HDCVI Fighter Starlight Na lageru		

2MP 4u1 kamere, Starlight+ Pro serija; Sa OSD-OM; 2D+3D DNR; 120dB WDR

Kod	OPIS	VP	MSRP	Slika		
4u1 2 Megapixela bullet IC kamera; Smart IC 40m; WDR 120dB; Starlight+; Sa mikrofonom						
HAC-HFW2241E-A-0280B	Starlight+ 4u1 (analogna, HDCVI, AHD, TVI) 2 MP bullet IC True D/N WDR kamera sa mikrofonom; 1/2.8" 2 Megapixela progressive scan CMOS; Efektivni broj piksela 1920(H) x 1080(V); Rezolucija 1920x1080@25 fps ili 1280x720@25 fps; 2.8mm F1.6 fiksni objektiv; Vidni ugao 110°; Opciono 3.6 ili 6mm (vidni ugao 86.9° ili 52.8°); Osetljivost 0.004Lux/F1.6, 0Lux (IC uključ.); True day/night (ICR); Smart IC LE diode dometa cca. 40m; 120dB True WDR; 2D + 3D DNR; OSD; Inkorporiran mikrofoni; Audio ulaz; Broadcast audio kvalitet; Izbor moda rada putem prekidača na kablju kamere, UTC OSD kontrolera, sa XVR/HCVR uređaja; Prenos signala koaksijalnim kablom 75Ω na dužinama do 500m; Dimenzije 179.9mmx70mmx70mm; Masa 300g; Alu. kućište; IP67 sertifikovana; Radna temperatura -40°C~+60°C; Napajanje 12VDC/6.7W	€ 52,20	€ 87,00			Na lageru
4u1 2 Megapixela anti-vandal dome IC kamera; Smart IC 20m; WDR 120dB; Starlight+; Sa mikrofonom;						
HAC-HDBW2241F-A-0280B	Starlight+ 4u1 (analogna, HDCVI, AHD, TVI) 2 MP anti-vandal dome IC True D/N WDR kamera sa mikrofonom; 1/2.8" 2 Megapixela progressive scan CMOS; Efektivni broj piksela 1920(H) x 1080(V); Rezolucija 1920x1080@25 fps ili 1280x720@25 fps; 2.8mm F1.6 fiksni objektiv; Vidni ugao 110°; Opciono 3.6 (vidni ugao 86.9°); Osetljivost 0.004Lux/F1.6, 0Lux (IC uključ.); True day/night (ICR); Smart IC LE diode dometa cca. 20m; 120dB True WDR; 2D + 3D DNR; OSD; Inkorporiran mikrofoni; Audio ulaz; Broadcast audio kvalitet; Izbor moda rada putem prekidača na kablju kamere, UTC OSD kontrolera, sa XVR/HCVR uređaja; Prenos signala koaksijalnim kablom 75Ω na dužinama do 500m; Dimenzije Φ106mmx50.3mm; Masa 310g; Alu. kućište; IP67 i IK10 sertifikovana; Radna temperatura -40°C~+60°C; Napajanje 12VDC ±30%/3.6W	€ 50,00	€ 83,33			Na lageru
4u1 2 Megapixela dome IC kamera; Smart IC 50m; WDR 120dB; Starlight+; Sa mikrofonom						
HAC-HDW2241T-A-0280B	Starlight+ 4u1 (analogna, HDCVI, AHD, TVI) 2 MP dome IC True D/N WDR kamera sa mikrofonom; 1/2.8" 2 Megapixela progressive scan CMOS; Efektivni broj piksela 1920(H) x 1080(V); Rezolucija 1920x1080@25 fps ili 1280x720@25 fps; 2.8mm F1.6 fiksni objektiv; Vidni ugao 110°; Opciono 3.6 ili 6mm (vidni ugao 86.9° ili 52.8°); Osetljivost 0.004Lux/F1.6, 0Lux (IC uključ.); True day/night (ICR); Smart IC LE diode dometa cca. 50m; 120dB True WDR; 2D + 3D DNR; OSD; Inkorporiran mikrofoni; Audio ulaz; Broadcast audio kvalitet; Izbor moda rada putem prekidača na kablju kamere, UTC OSD kontrolera, sa XVR/HCVR uređaja; Prenos signala koaksijalnim kablom 75Ω na dužinama do 500m; Dimenzije Φ106mmx99.2mm; Masa 500g; Alu. kućište; IP67 sertifikovana; Radna temperatura -40°C~+60°C; Napajanje 12VDC/5.3W	€ 54,00	€ 90,00			Na lageru
4u1 2 Megapixela bullet IC kamera; Smart IC 80m; WDR 120dB; Starlight+; Sa mikrofonom						
HAC-HFW2241T-18-A-0360B	Starlight+ 4u1 (analogna, HDCVI, AHD, TVI) 2 MP bullet IC True D/N WDR kamera sa mikrofonom; 1/2.8" 2 Megapixela progressive scan CMOS; Efektivni broj piksela 1920(H) x 1080(V); Rezolucija 1920x1080@25 fps ili 1280x720@25 fps; 3.6mm F1.6 fiksni objektiv; Vidni ugao 86.9°; Opciono 6mm (vidni ugao 52.8°); Osetljivost 0.004Lux/F1.6, 0Lux (IC uključ.); True day/night (ICR); Smart IC LE diode dometa cca. 80m; 120dB True WDR; 2D + 3D DNR; OSD; Inkorporiran mikrofoni; Audio ulaz; Broadcast audio kvalitet; Izbor moda rada putem prekidača na kablju kamere, UTC OSD kontrolera, sa XVR/HCVR uređaja; Prenos signala koaksijalnim kablom 75Ω na dužinama do 500m; Dimenzije 244.1mm x 90.4mm x 90.4mm; Masa 500g; Alu. kućište; IP67 sertifikovana; Radna temperatura -40°C~+60°C; Napajanje 12VDC/10.1W	€ 61,80	€ 103,00			Na lageru
4u1 2 Megapixela dome IC kamera; Motorizovani zum, automatski fokus 2.7-13.5mm; Smart IC 60m; WDR 120dB; Starlight+; Sa mikrofonom						
HAC-HDW2241T-Z-A	Starlight+ 4u1 (analogna, HDCVI, AHD, TVI) 2 MP dome IC True D/N WDR kamera sa mikrofonom i motorizovanim zum objektivom; 1/2.8" 2 Megapixela progressive scan CMOS; Efektivni broj piksela 1920(H) x 1080(V); Rezolucija 1920x1080@25 fps ili 1280x720@25 fps; 2.7-13.5 motorizovani zum objektiv (podesivi vidni ugao 108.7°~28.7°); Automatski fokus; Fiksni iris; Osetljivost 0.004Lux/F1.6, 0Lux (IC uključ.); True day/night (ICR); Smart IC LE diode dometa cca. 60m; 120dB True WDR; 2D + 3D DNR; OSD; Inkorporiran mikrofoni; Audio ulaz; Broadcast audio kvalitet; Izbor moda rada putem prekidača na kablju kamere, UTC OSD kontrolera, sa XVR/HCVR uređaja; Prenos signala koaksijalnim kablom 75Ω na dužinama do 500m; Dimenzije Φ122mmx107mm; Masa 590g; Alu. kućište; IP67 sertifikovana; Radna temperatura -30°C~+60°C; Napajanje 12VDC/5.4W	€ 77,40	€ 129,00			Na lageru

4MP HDCVI kamere, PRO serija; Sa OSD-OM; 2D+3D DNR; 120dB WDR

Kod	OPIS	VP	MSRP		Slika		
HDCVI 4 Megapixela CMOS True D/N dome IC kamera sa motorizovanim auto-fokus objektivom; Smart IC 60m; WDR 120dB;							
HAC-HDW2401R-Z	HDCVI 4MP dome IC True D/N WDR kamera sa motorizovanim auto-fokus objektivom; 1/3" 4.1 Megapixela progressive scan CMOS; Efektivni broj piksela 2688(H) x 1520(V); Rezolucija 2560x1440@25fps ili 1920x1080@25fps ili 1280x720@25fps ;2.7~12mm F1.3 objektiv, motorizovani zum, automatski fokus, fiksni iris; Podesivi vidni ugao 98°~26°; Osetljivost 0.01Lux/F1.3, 0Lux (IC uključ.); True day/night (ICR); Smart IC LE diode dometa cca. 60m; 120dB True WDR; 2D + 3D DNR; OSD; HDCVI + kompozitni izlaz (dual); Prenos signala koaksijalnim kablom 75Ω na dužinama do 500m; Dimenzije Φ122mm×104.9mm; Masa 590g; IP67 sertifikovana; Metalno kućište; Radna temperatura -30°C~+60°C; Napajanje 12VDC/8.4W	€ 75,00	€ 125,00			Na lageru	

HDCVI 4 Megapixela CMOS True D/N anti-vandal dome IC kamera sa motorizovanim auto-fokus objektivom; Smart IC 30m; WDR 120dB;

HAC-HDBW2401R-Z	HDCVI 4MP anti-vandal dome IC True D/N WDR kamera sa motorizovanim auto-fokus objektivom; 1/3" 4.1 Megapixela progressive scan CMOS; Efektivni broj piksela 2688(H) x 1520(V); Rezolucija 2560x1440@25fps ili 1920x1080@25fps ili 1280x720@25fps ;2.7~12mm F1.3 objektiv, motorizovani zum, automatski fokus, fiksni iris; Podesivi vidni ugao 98°~26°; Osetljivost 0.01Lux/F1.3, 0Lux (IC uključ.); True day/night (ICR); Smart IC LE diode dometa cca. 30m; 120dB True WDR; 2D + 3D DNR; OSD; HDCVI + kompozitni izlaz (dual); Prenos signala koaksijalnim kablom 75Ω na dužinama do 500m; Dimenzije Φ122mm×88.9mm; Masa 480g; IP67 i IK10 sertifikovana; Metalno kućište; Radna temperatura -30°C~+60°C; Napajanje 12VDC/7.5W	€ 65,00	€ 108,33			Na lageru	
-----------------	--	---------	----------	--	--	-----------	--

5MP 4u1 kamere, Starlight Pro serija; Sa OSD-OM; 2D+3D DNR; 120dB WDR

Kod	OPIS	VP	MSRP		Slika		
4u1 5 Megapixela bullet IC kamera; Smart IC 40m; WDR 120dB; Starlight; Sa mikrofonom							
HAC-HFW2501E-A-0280B	Starlight 4u1 (analogna, HDCVI, AHD, TVI) 5MP bullet IR True D/N kamera sa mikrofonom; 1/2.8" 5 Megapixela CMOS; Efektivni broj piksela 2592(H) x 1944(V); Rezolucija 5MP@20fps, 4MP@25 /30fps, 1920x1080@25/30 fps; 2.8mm F1.6 fiksni objektiv; Vidni ugao 98°; Opciono 3.6 ili 6mm (vidni ugao 79° ili 49.5°); Osetljivost 0.005Lux/F1.6, 0Lux (IC Uključ.); True day/night (IRC); Smart IC LE diode dometa cca. 40m; 120dB True WDR; 2D + 3D DNR; OSD; Inkorporiran mikrofoni; Audio ulaz; Broadcast audio kvalitet; Prenos signala koaksijalnim kablom 75Ω na dužinama do 500m; IP67 sertifikovana; Alu. kućište; Radna temperatura -40°C~+60°C; Dimenzije 179.9mm x70mm x70mm; Masa 490g; Napajanje 12VDC/7W	€ 60,00	€ 100,00			Na lageru	






4u1 5 Megapixela dome IC kamera; Smart IC 50m; WDR 120dB; Starlight+; Sa mikrofonom

HAC-HDW2501T-A-0280B	Starlight 4u1 (analogna, HDCVI, AHD, TVI) 5MP dome IR True D/N kamera sa mikrofonom; 1/2.8" 5 Megapixela CMOS; Efektivni broj piksela 2592(H) x 1944(V); Rezolucija 5MP@20fps, 4MP@25 /30fps, 1920x1080@25/30 fps; 2.8mm F1.6 fiksni objektiv; Vidni ugao 98°; Opciono 3.6 ili 6mm (vidni ugao 79° ili 49.5°); Osetljivost 0.005Lux/F1.6, 0Lux (IC Uključ.); True day/night (IRC); Smart IC LE diode dometa cca. 50m; 120dB True WDR; 2D + 3D DNR; OSD; Inkorporiran mikrofoni; Audio ulaz; Broadcast audio kvalitet; Prenos signala koaksijalnim kablom 75Ω na dužinama do 500m; IP67 sertifikovana; Alu. kućište; Radna temperatura -40°C~+60°C; Dimenzije Φ106mm×99.2mm; Masa 480g; Napajanje 12VDC/7W	€ 61,80	€ 103,00			Na lageru	
----------------------	---	---------	----------	--	--	-----------	--



5MP 4u1 kamere, Starlight Pro serija; Sa OSD-OM; 2D+3D DNR; 120dB WDR

Kod	OPIS	VP	MSRP		Slika		
4u1 5 Megapixela bullet IC kamera; Smart IC 80m; WDR 120dB; Starlight+; Sa mikrofonom							
HAC-HFW2501T-18-A-0360B	Starlight 4u1 (analogna, HDCVI, AHD, TVI) 5MP bullet IR True D/N kamera sa mikrofonom; 1/2.8" 5 Megapixela CMOS; Efektivni broj piksela 2592(H) x 1944(V); Rezolucija 5MP@20fps, 4MP@25 /30fps, 1920x1080@25/30 fps; 3.6mm F1.6 fiksni objektiv; Vidni ugao 79°; Opciono 2.8 ili 6mm (vidni ugao 98° ili 49.5°); Osetljivost 0.005Lux/F1.6, 0Lux (IC Uključ.); True day/night (IRC); Smart IC LE diode dometa cca. 80m; 120dB True WDR; 2D + 3D DNR; OSD; Inkorporiran mikrofoni; Audio ulaz; Broadcast audio kvalitet; Prenos signala koaksijalnim kablom 75Ω na dužinama do 500m; IP67 sertifikovana; Alu. kućište; Radna temperatura -40°C~+60°C; Dimenzije 244.1mmx90.4mmx90.4mm; Masa 750g; Napajanje 12Vdc/10W	€ 69,60	€ 116,00		 Fighter Starlight	Na lageru	
5MP Fisheye IC kamera; Smart IC 10m; WDR 120dB; Starlight; Sa mikrofonom							
HAC-EW2501-0140B	Starlight HDCVI 5MP Fisheye IC kamera; 1/2.8" 5 Megapixela CMOS; Efektivni broj piksela 2592(H) x 1944(V); Rezolucija 5MP@20fps, 4MP@25/30fps; Fiksni objektiv 1.4mm F1.3; Osetljivost 0.005Lux/F1.3 (AGC Uključ.), 0Lux (IC Uključ.); True day/night (IRC); Smart IC LE diode dometa cca. 10m; 120dB True WDR; 2D + 3D DNR; OSD; Inkorporiran mikrofoni; Audio ulaz; Broadcast audio kvalitet; Prenos signala koaksijalnim kablom 75Ω na dužinama do 500m; Kućište od kombinacije plastike i metala; Radna temperatura -30°C~+60°C; Dimenzije Ø126.2mm x 40.6mm; Masa 240g; Napajanje 12Vdc ±30% /7.3W	€ 79,20	€ 132,00		 Fighter Starlight	Novi! Na lageru	
4u1 2 Megapixela dome IC kamera; Motorizovani zum, automatski fokus 2.7-13.5mm; Smart IC 60m; WDR 120dB; Starlight+; Sa mikrofonom							
HAC-HDW2501T-Z-A	Starlight 4u1 (analogna, HDCVI, AHD, TVI) 5MP dome IR True D/N kamera sa motorizovanim auto-fokus objektivom i mikrofonom; 1/2.8" 5 Megapixela CMOS; Efektivni broj piksela 2592(H) x 1944(V); Rezolucija 5MP@20fps, 4MP@25/30fps, 1920x1080@25/30 fps; 2.7~13.5mm F1.3 objektiv, motorizovani zum, automatski fokus, fiksni iris; Podesivi vidni ugao 102°~29°; Osetljivost 0.005Lux/F1.3 (AGC Uključ.), 0Lux (IC Uključ.); True day/night (IRC); Smart IC LE diode dometa cca. 60m; 120dB True WDR; 2D + 3D DNR; OSD; Inkorporiran mikrofoni; Audio ulaz; Broadcast audio kvalitet; Prenos signala koaksijalnim kablom 75Ω na dužinama do 500m; IP67 sertifikovana; Alu. kućište; Radna temperatura -40°C~+60°C; Dimenzije Ø122mm x 107mm; Masa 600g; Napajanje 12Vdc/10W	€ 81,00	€ 135,00		 Fighter Starlight	Na lageru	
4u1 5 Megapixela bullet IC kamera; Motorizovani zum, automatski fokus 2.7-13.5mm; Smart IC 80m; WDR 120dB; Starlight+; Sa mikrofonom							
HAC-HFW2501T-Z-A	Starlight 4u1 (analogna, HDCVI, AHD, TVI) 5MP bullet IR True D/N kamera sa motorizovanim auto-fokus objektivom i mikrofonom; 1/2.8" 5 Megapixela CMOS; Efektivni broj piksela 2592(H) x 1944(V); Rezolucija 5MP@20fps, 4MP@25/30fps, 1920x1080@25/30 fps; 2.7~13.5mm F1.3 objektiv, motorizovani zum, automatski fokus, fiksni iris; Podesivi vidni ugao 102°~29°; Osetljivost 0.005Lux/F1.3 (AGC Uključ.), 0Lux (IC Uključ.); True day/night (IRC); Smart IC LE diode dometa cca. 80m; 120dB True WDR; 2D + 3D DNR; OSD; Inkorporiran mikrofoni; Audio ulaz; Broadcast audio kvalitet; Prenos signala koaksijalnim kablom 75Ω na dužinama do 500m; IP67 sertifikovana; Alu. kućište; Radna temperatura -40°C~+60°C; Dimenzije 244.1mmx90.4mmx90.4mm; Masa 770g; Napajanje 12Vdc/12.4W	€ 92,40	€ 154,00		 Fighter Starlight	Na lageru	






POC HDCVI kamere

Kod	OPIS	VP	MSRP	Slika	
4u1 2MP PoC bullet IC kamera; Lite serija; Smart IC 30m; 2.8mm objektiv; Metalno kućište; IP67; PoC					
HAC-HFW1200S-POC-0280B-S3A	4u1 (analogna, HDCVI, AHD, TVI) 2MP PoC bullet IC kamera; 1/2.7" 2 Megapixels CMOS; Efektivni broj piksela 1920(H) x 1080(V); Rezolucija 1920x1080@25 fps ili 1280x720@25/50 fps; 2.8mm F1.85 fiksni objektiv; Vidni ugao 103°; Opciono 3.6mm ili 6mm (vidni ugao 89.9° ili 54.7°); Osetljivost 0.02Lux/F1.85, 0Lux (IC uključ.); True day/night (ICR); Smart IC LE diode dometa cca. 30m; DWDR; BLC; 2D DNR; OSD; Dimenzije 164.7mmx70mmx71.6mm; Masa 380g; Metalno kućište; IP67 sertifikovana; Radna temperatura -40°C~+60°C; Napajanje POC/12V DC ±25%, 4.2W; CE (EN55032, EN55024, EN50130-4)	€ 29,40	€ 49,00	 PoC	Na lageru
4u1 2MP PoC dome IC kamera; Lite serija; Smart IC 50m; 2.8mm objektiv; Metalno kućište; IP67; PoC					
HAC-HDW1200EM-POC-0280B-S3A	4u1 (analogna, HDCVI, AHD, TVI) 2MP PoC dome IC kamera; 1/2.7" 2 Megapixels CMOS; Efektivni broj piksela 1920(H) x 1080(V); Rezolucija 1920x1080@25 fps ili 1280x720@25/50 fps; 2.8mm F1.85 fiksni objektiv; Vidni ugao 103°; Opciono 3.6mm ili 6mm (vidni ugao 89.9° ili 54.7°); Osetljivost 0.02Lux/F1.85, 0Lux (IC uključ.); True day/night (ICR); Smart IC LE diode dometa cca. 50m; DWDR; BLC; 2D DNR; OSD; Dimenzije Ø106mmx93.7mm; Masa 430g; Metalno kućište; IP67 sertifikovana; Radna temperatura -40°C~+60°C; Napajanje POC/12VDC ±25%, 4.3W; CE (EN55032, EN55024, EN50130-4)	€ 28,80	€ 48,00	 PoC	Na lageru
4u1 4MP PoC bullet IC kamera; Lite serija; Smart IC 30m; 2.8mm objektiv; Metalno kućište; IP67; PoC					
HAC-HFW1400S-POC-0280B-S3A	4u1 (analogna, HDCVI, AHD, TVI) 4MP PoC bullet IC kamera; 1/3" 4 Megapixels CMOS; Efektivni broj piksela 2688(H) x 1520(V); Rezolucija 2560x1440@25 fps ili 1920x1080@25fps ili 1280x720@25fps; 2.8mm fiksni objektiv; Vidni ugao 99.7°; Opciono 3.6 ili 6mm (vidni ugao 84.8° ili 52.5°); Osetljivost 0.03Lux/F2.0, 0Lux (IC uključ.); True day/night (ICR); Smart IC LE diode dometa cca. 30m; DWDR; BLC; 2D DNR; OSD; Dimenzije 164.7mmx70mmx71.6mm; Masa 390g; IP67 sertifikovana; Radna temperatura -40°C~+60°C; Napajanje POC/12VDC ±25%, 4.4W; CE (EN55032, EN55024, EN50130-4)	€ 37,20	€ 62,00	 PoC	Na lageru
4u1 4MP PoC dome IC kamera; Lite serija; Smart IC 50m; 2.8mm objektiv; Metalno kućište; IP67; PoC					
HAC-HDW1400EM-POC-0280B-S3A	4u1 (analogna, HDCVI, AHD, TVI) 4MP PoC dome IC kamera; 1/3" 4 Megapixels CMOS; Efektivni broj piksela 2688(H) x 1520(V); Rezolucija 2560x1440@25 fps ili 1920x1080@25fps ili 1280x720@25fps; 2.8mm fiksni objektiv; Vidni ugao 99.7°; Opciono 3.6 ili 6mm (vidni ugao 84.8° ili 52.5°); Osetljivost 0.03Lux/F2.0, 0Lux (IC uključ.); True day/night (ICR); Smart IC LE diode dometa cca. 50m; DWDR; BLC; 2D DNR; OSD; Dimenzije Ø106mmx93.7mm; Masa 430g; IP67 sertifikovana; Radna temperatura -40°C~+60°C; Napajanje POC/12VDC ±25%, 4.6W; CE (EN55032, EN55024, EN50130-4)	€ 37,20	€ 62,00	 PoC	Na lageru
4u1 2MP PoC anti-vandal dome IC kamera; Pro serija; Starlight; Smart IC 30m; MZ AF 2.7-13.5mm objektiv; Metalno kućište; IP67; IK10; PoC					
HAC-HDBW2231R-Z-POC	Starlight 4u1 (analogna, HDCVI, AHD, TVI) 2.1MP POC anti-vandal dome IC kamera sa motorizovanim auto-fokus objektivom; 1/2.8" 2.1 Megapixels CMOS; Efektivni broj piksela 1937(H) x 1097(V); Rezolucija 1920x1080@25 fps ili 1280x720@25fps; 2.7~13.5mm F1.3 objektiv, motorizovani zum, automatski fokus, fiksni iris; Podesivi vidni ugao 102°~29°; Osetljivost 0.005Lux/F1.3, 0Lux (IC Uključ.); True day/night (IRC); Smart IC LE diode dometa cca. 30m; 120dB True WDR; 2D + 3D DNR; OSD; IP67 i IK10 sertifikovana; Radna temperatura -40°C~+60°C; Dimenzije Ø122mmx88.9mm; Masa 480g; Napajanje POC/12VDC ±25%, 8.8W; CE (EN55032, EN55024, EN50130-4)	€ 72,00	€ 120,00	 PoC Starlight	Na lageru
4u1 2MP PoC bullet IC kamera; Pro serija; Starlight; Smart IC 60m; MZ AF 2.7-13.5mm objektiv; Metalno kućište; IP67; PoC					
HAC-HFW2231R-Z-IRE6-POC	Starlight 4u1 (analogna, HDCVI, AHD, TVI) 2.1MP POC bullet IC kamera sa motorizovanim auto-fokus objektivom; 1/2.8" 2.1 Megapixels CMOS; Efektivni broj piksela 1937(H) x 1097(V); Rezolucija 1920x1080@25 fps ili 1280x720@25fps; 2.7~13.5mm F1.3 objektiv, motorizovani zum, automatski fokus, fiksni iris; Podesivi vidni ugao 102°~29°; Osetljivost 0.005Lux/F1.3, 0Lux (IC Uključ.); True day/night (IRC); Smart IC LE diode dometa cca. 60m; 120dB True WDR; 2D + 3D DNR; OSD; IP67 sertifikovana; Radna temperatura -40°C~+60°C; Dimenzije 213.0mmx90.4mmx90.4mm; Masa 630g; Napajanje POC/12VDC ±25%, 6.8W; CE (EN55032, EN55024, EN50130-4)	€ 72,00	€ 120,00	 PoC Starlight	Na lageru

HDCVI PTZ i speed dome kamere

Kod	OPIS	VP	MSRP	Slika		
HDCVI 2MP Speed dome IC kamera; Lite serija; 12x zoom; IP66; Sa IC LE diodama dometa 100m; Starlight						
SD49212I-HC	HDCVI 2MP 12X zoom speed dome IC kamera; 1/2.8" progressive scan Starvis™ CMOS; Inkorporiran motor zoom auto fokus objektiv f=5.3mm(Wide)~64mm(Tele), F1.6~F3.0 (vidni ugao 58.4°~4.9°); Digitalni zoom do 16x; Osetljivost 0.005Lux/F1.6(color), 0Lux IR On; Inkorporirane IC LE diode dometa do 100m; True Day/Night - motorizovani IR Cut filter; Podržane rezolucije 1920×1080@30 fps ili 1280×720@25/30/50/60 fps; True WDR 120dB; HLC; BLC; 2D i 3D DNR; 2 alamna ulaza/1 relejni izlaz; BNC HDCVI port - prenos signala koaksijalnim kablom 75Ω na dužinama do 500m (audio + video + upravljački signal); Audio ulaz; 300 programabilnih preset-a, 8 grupa, 5 tura, 5 Swing-a; Masking (do 24 zone); Brzina horizontalne rotacije 240°/s maks; 3D pozicioniranje; U IP66 kućištu sa grejačem i ventilatorom ; Dimenzije 160mm (Φ) x 295mm (V); Masa 3kg; Radna temperatura od -40°C do +70°C ; U komp. sa zidnim nosačem; Potrebno napajanje 12VDC 3A	€ 220,00	€ 366,67			Na lageru
HDCVI 2MP Speed dome IC kamera; Lite serija; 25x zoom; IP66; Sa IC LE diodama dometa 100m; Starlight						
SD49225I-HC	HDCVI 2MP 25X zoom speed dome IC kamera; 1/2.8" progressive scan Starvis™ CMOS; Inkorporiran motor zoom auto fokus objektiv f=4.8mm(Wide)~120mm(Tele), F1.6~F4.4 (vidni ugao 62.8°~2.6°); Digitalni zoom do 16x; Osetljivost 0.005Lux/F1.6(color), 0Lux IR On; Inkorporirane IC LE diode dometa do 100m; True Day/Night - motorizovani IR Cut filter; Podržane rezolucije 1920×1080@30 fps ili 1280×720@25/30/50/60 fps; True WDR 120dB; HLC; BLC; 2D i 3D DNR; 2 alamna ulaza/1 relejni izlaz; BNC HDCVI port - prenos signala koaksijalnim kablom 75Ω na dužinama do 500m (audio + video + upravljački signal); Audio ulaz; 300 programabilnih preset-a, 8 grupa, 5 tura, 5 Swing-a; Masking (do 24 zone); Brzina horizontalne rotacije 240°/s maks; 3D pozicioniranje; U IP66 kućištu sa grejačem i ventilatorom ; Dimenzije 160mm (Φ) x 295mm (V); Masa 3kg; Radna temperatura od -40°C do +70°C ; Sa zidnim nosačem; Potrebno napajanje 12VDC 3A	€ 231,00	€ 385,00			Na lageru
HDCVI 2MP Speed dome kamera; Pro serija; 25x zoom; IP66; Sa IC LE diodama dometa 150m; Starlight						
SD59225I-HC	HDCVI 2MP 25X zoom speed dome IC kamera; 1/2.8" Starvis™ progressive scan CMOS; Inkorporiran motor zoom auto fokus objektiv f=4.8mm(Wide)~120.0mm(Tele), F1.6~F4.4 (vidni ugao 59.2°~2.4°); Digitalni zoom do 16x; Osetljivost 0.005Lux/F1.6(color), 0Lux IR On; Inkorporirane IC LE diode dometa do 150m; True Day/Night - motorizovani IR Cut filter; Podržane rezolucije 1920×1080@25 fps ili 1280×720@25/50 fps; True WDR 120dB; HLC; BLC; 2D i 3D DNR; 2 alamna ulaza/1 relejni izlaz; BNC HDCVI port - prenos signala koaksijalnim kablom 75Ω na dužinama do 500m (audio + video + upravljački signal); Audio ulaz; 300 programabilnih preset-a, 8 grupa, 5 tura, 5 Swing-a; Masking (do 24 zone); Brzina horizontalne rotacije 400°/s maks; 3D pozicioniranje; U IP66 kućištu sa grejačem i ventilatorom ; Dimenzije 186mm (Φ) x 309mm (V); Masa 3.5kg; Radna temperatura od -40°C do +70°C ; Sa nap. jedinicom 230VAC/24VAC; U kompletu sa zidnim nosačem	€ 295,20	€ 492,00			Na lageru
HDCVI 2MP Speed dome IC kamera; Pro serija; 30x zoom; IP66; Sa IC LE diodama dometa 150m; Starlight						
SD59230I-HC	HDCVI IR 2 Megapixela 30X zoom speed dome kamera; 1/2.8" Exmor R progressive scan CMOS; Inkorporiran motor zoom auto fokus objektiv f=4.5mm(Wide)~135.0mm(Tele), F1.6~F5.0 (vidni ugao 67.8°~2.4°); Digitalni zoom do 16x; Osetljivost 0.005Lux/F1.6(color), 0Lux IR On; Inkorporirane IC LE diode dometa do 150m; True Day/Night - motorizovani IR Cut filter; Podržane rezolucije 1920×1080@25 fps ili 1280×720@25/50 fps; True WDR 120dB; HLC; BLC; 2D i 3D DNR; 2 alamna ulaza/1 relejni izlaz; BNC HDCVI port - prenos signala koaksijalnim kablom 75Ω na dužinama do 500m (audio + video + upravljački signal); Audio ulaz; 300 programabilnih preset-a, 8 grupa, 5 tura, 5 Swing-a; Masking (do 24 zone); Brzina horizontalne rotacije 400°/s maks; 3D pozicioniranje; U IP66 kućištu sa grejačem i ventilatorom ; Dimenzije 186mm (Φ) x 309mm (V); Masa 3.5kg; Radna temperatura od -40°C do +70°C ; Sa nap. jedinicom 230VAC/24VAC; U kompletu sa zidnim nosačem	€ 463,80	€ 773,00			Na lageru
HDCVI 4MP Speed dome kamera; Pro serija; 30x zoom; IP67; IK10; Sa IC LE diodama dometa 200m						
SD6CE430I-HC	HDCVI 4MP 30X zoom speed dome IC kamera; 1/3" progressive scan CMOS; Inkorporiran motor zoom auto fokus objektiv f=4.5mm(Wide)~135.0mm(Tele), F1.6~F4.4 (vidni ugao 60°~2.2°); Digitalni zoom do 16x; Osetljivost 0.05Lux/F1.6 (kolor), 0Lux IR On; Inkorporirane IC LE diode dometa do 200m; True Day/Night - motorizovani IR Cut filter; Podržane rezolucije 4M@25 fps, 1920×1080@25 fps ili 1280×720@25/50 fps; True WDR 120dB; HLC; BLC; 2D i 3D DNR; 2 alamna ulaza/1 relejni izlaz; BNC HDCVI port - prenos signala koaksijalnim kablom 75Ω na dužinama do 500m (audio + video + upravljački signal); Audio ulaz; RS485; 300 programabilnih preset-a, 8 grupa, 5 tura, 5 Swing-a; Masking (do 24 zone); Brzina horizontalne rotacije 300°/s maks; 3D pozicioniranje; U IP67 kućištu sa grejačem i ventilatorom ; IK10; Dimenzije 209mm (Φ) x 337.4mm (V); Masa 5.8kg; Radna temperatura od -40°C do +70°C ; Sa nap. jedinicom 230VAC/24VAC; U kompletu sa zidnim nosačem	€ 550,00	€ 916,67			Novi Uskoro



IP kamere; EZ-IP serija

Kod	OPIS	VP	MSRP	Slika	
IP bullet IC kamera 2MP; EZ-IP serija; 2.8mm; IC 30m;					
IPC-B1B20-0280B	IP bullet IC kamera 2MP; 1/2.7" progressive scan CMOS (1920x1080 piksela); Osetljivost 0.09Lux /F2.0(kolor), 0Lux (IC aktivan); Smart IC LE diode dometa cca. 30m; Objektiv 2.8mm (Vidni ugao 115°); 3.6mm opciono (87.5°); True D/N funkcija (IRC); BLC/ HLC/ DWDR; 3D DNR; ROI; Masking (do 4 zone); H.265/H.264H/MJPEG(Sub Stream) kompresija; H.265+/H.264+ podrška; Rezolucije 1080P /1.3M /720P /D1 /VGA /CIF; Dual Stream; Do 25/30fps u 2MP i nižim rezolucijama; RJ-45 (10/100Base-T) mrežni port; Protokoli HTTP; TCP; ARP; RTSP; RTP; RTCP; UDP; DHCP; DNS; IPV4; NTP; Multicast; ICMP; TLS Multicast; ICMP; IGMP; TLS; ONVIF Profile S&G; Potrebno napajanje 12VDC ili PoE (802.3af, Class 0); Potrošnja 4.2W; Dimenzije Ø70mmx162.6mm; Kućište od metala i plastike; Masa 0.22kg; IP67; Radna temp. -30°C~+60°C; CE (EN 60950:2000)	€ 30,00	€ 50,00	 	Na lageru
IP bullet IC kamera 2MP; EZ-IP serija; 3.6mm; IC 30m;					
IPC-B1B20-0360B	IP bullet IC kamera 2MP; 1/2.7" progressive scan CMOS (1920x1080 piksela); Osetljivost 0.09Lux /F2.0(kolor), 0Lux (IC aktivan); Smart IC LE diode dometa cca. 30m; Objektiv 3.6mm (Vidni ugao 87.5°); 2.8mm opciono (115°); True D/N funkcija (IRC); BLC/ HLC/ DWDR; 3D DNR; ROI; Masking (do 4 zone); H.265/H.264H/MJPEG(Sub Stream) kompresija; H.265+/H.264+ podrška; Rezolucije 1080P /1.3M /720P /D1 /VGA /CIF; Dual Stream; Do 25/30fps u 2MP i nižim rezolucijama; RJ-45 (10/100Base-T) mrežni port; Protokoli HTTP; TCP; ARP; RTSP; RTP; RTCP; UDP; DHCP; DNS; IPV4; NTP; Multicast; ICMP; TLS Multicast; ICMP; IGMP; TLS; ONVIF Profile S&G; Potrebno napajanje 12VDC ili PoE (802.3af, Class 0); Potrošnja 4.2W; Dimenzije Ø70mmx162.6mm; Kućište od metala i plastike; Masa 0.22kg; IP67; Radna temp. -30°C~+60°C; CE (EN 60950:2000)	€ 30,00	€ 50,00	 	Na lageru
IP bullet IC kamera 4MP; EZ-IP serija; 2.8mm; IC 30m;					
IPC-B1B40-0280B	IP bullet IC kamera 4MP; 1/3" progressive scan CMOS (2560x1440 piksela); Osetljivost 0.09Lux /F2.0(kolor), 0Lux (IC aktivan); Smart IC LE diode dometa cca. 30m; Objektiv 2.8mm (Vidni ugao 101°); 3.6mm opciono (80°); True D/N funkcija (IRC); BLC/ HLC/ DWDR; 3D DNR; ROI; Masking (do 4 zone); H.265/H.264H/MJPEG(Sub Stream) kompresija; H.265+/H.264+ podrška; Rezolucije 4M(2560x1440) /3M(2304x1296) /1080P /1.3M /720P /D1 /VGA /CIF; Dual Stream; Do 20fps u 4M; Do 25/30fps u 2MP i nižim rezolucijama; RJ-45 (10/100Base-T) mrežni port; Protokoli HTTP; TCP; ARP; RTSP; RTP; RTCP; UDP; DHCP; DNS; IPV4; NTP; Multicast; ICMP; TLS Multicast; ICMP; IGMP; TLS; ONVIF Profile S&G; Potrebno napajanje 12VDC ili PoE (802.3af, Class 0); Potrošnja 4.2W; Dimenzije Ø70mmx162.6mm; Kućište od metala i plastike; Masa 0.244kg; IP67; Radna temp. -30°C~+60°C; CE (EN 60950:2000)	€ 41,40	€ 69,00	 	Na lageru
IP dome kamera IC 2MP; EZ-IP serija; 2.8mm; IC 30m;					
IPC-T1B20-0280B	IP dome IC kamera 2MP; 1/2.7" progressive scan CMOS (1920x1080 piksela); Osetljivost 0.09Lux /F2.0(kolor), 0Lux (IC aktivan); Smart IC LE diode dometa cca. 30m; Objektiv 2.8mm (Vidni ugao 115°); 3.6mm opciono (87.5°); True D/N funkcija (IRC); BLC/ HLC/ DWDR; 3D DNR; ROI; Masking (do 4 zone); H.265/H.264H/MJPEG(Sub Stream) kompresija; H.265+/H.264+ podrška; Rezolucije 1080P /1.3M /720P /D1 /VGA /CIF; Dual Stream; Do 25/30fps u 2MP i nižim rezolucijama; RJ-45 (10/100Base-T) mrežni port; Protokoli HTTP; TCP; ARP; RTSP; RTP; RTCP; UDP; DHCP; DNS; IPV4; NTP; Multicast; ICMP; TLS Multicast; ICMP; IGMP; TLS; ONVIF Profile S&G; Potrebno napajanje 12VDC ili PoE (802.3af, Class 0); Potrošnja 4.8W; Dimenzije Ø109mmx85.5mm; Kućište od metala i plastike; Masa 0.24kg; IP67; Radna temp. -30°C~+60°C; CE (EN 60950:2000)	€ 30,00	€ 50,00	 	Na lageru
IP dome kamera IC 2MP; EZ-IP serija; 3.6mm; IC 30m;					
IPC-T1B20-0360B	IP dome IC kamera 2MP; 1/2.7" progressive scan CMOS (1920x1080 piksela); Osetljivost 0.09Lux /F2.0(kolor), 0Lux (IC aktivan); Smart IC LE diode dometa cca. 30m; Objektiv 3.6mm (Vidni ugao 87.5°); 3.6mm opciono (115°); True D/N funkcija (IRC); BLC/ HLC/ DWDR; 3D DNR; ROI; Masking (do 4 zone); H.265/H.264H/MJPEG(Sub Stream) kompresija; H.265+/H.264+ podrška; Rezolucije 1080P /1.3M /720P /D1 /VGA /CIF; Dual Stream; Do 25/30fps u 2MP i nižim rezolucijama; RJ-45 (10/100Base-T) mrežni port; Protokoli HTTP; TCP; ARP; RTSP; RTP; RTCP; UDP; DHCP; DNS; IPV4; NTP; Multicast; ICMP; TLS Multicast; ICMP; IGMP; TLS; ONVIF Profile S&G; Potrebno napajanje 12VDC ili PoE (802.3af, Class 0); Potrošnja 4.8W; Dimenzije Ø109mmx85.5mm; Kućište od metala i plastike; Masa 0.24kg; IP67; Radna temp. -30°C~+60°C; CE (EN 60950:2000)	€ 30,00	€ 50,00	 	Na lageru



IP kamere; EZ-IP serija

Kod	OPIS	VP	MSRP	Slika		
IP dome kamera IC 4MP; EZ-IP serija; 2.8mm; IC 30m;						
IPC-T1B40-0280B	IP dome IC kamera 4MP; 1/3" progressive scan CMOS (2560x1440 piksela); Osetljivost 0.09Lux /F2.0(kolor), 0Lux (IC aktivan); Smart IC LE diode dometa cca. 30m; Objektiv 2.8mm (Vidni ugao 101°); 3.6mm opciono (80°); True D/N funkcija (IRC); BLC/HLC/ DWDR; 3D DNR; ROI; Masking (do 4 zone); H.265/H.264H/MJPEG(Sub Stream) kompresija; H.265+/H.264+ podrška; Rezolucije 4M(2560x1440) /3M(2304x1296) /1080P /1.3M /720P /D1 /VGA /CIF; Dual Stream; Do 20fps u 4M; Do 25/30fps u 2MP i nižim rezolucijama; RJ-45 (10/100Base-T) mrežni port; Protokoli HTTP; TCP; ARP; RTSP; RTP; RTCP; UDP; DHCP; DNS; IPV4; NTP; Multicast; ICMP; TLS Multicast; ICMP; IGMP; TLS; ONVIF Profile S&G; Potrebno napajanje 12VDC ili PoE (802.3af, Class 0); Potrošnja 4.8W; Dimenzije Ø109mmx85.5mm; Kućište od metala i plastike; Masa 0.248kg; IP67; Radna temp. -30°C~+60°C; CE (EN 60950:2000)	€ 41,40	€ 69,00			Na lageru
IP dome IC kamera 2MP; EZ-IP serija; 2.8mm; IC 30m;						
IPC-D2B20-0280B	IP dome IC kamera 2MP; 1/2.7" progressive scan CMOS (1920x1080 piksela); Osetljivost 0.09Lux /F2.0(kolor), 0Lux (IC aktivan); Smart IC LE diode dometa cca. 30m; Objektiv 2.8mm (Vidni ugao 115°); 3.6mm opciono (87.5°); True D/N funkcija (IRC); BLC/HLC/ DWDR; 3D DNR; ROI; Masking (do 4 zone); H.265/H.264H/MJPEG(Sub Stream) kompresija; H.265+/H.264+ podrška; Rezolucije 1080P /1.3M /720P /D1 /VGA /CIF; Dual Stream; Do 25/30fps u 2MP i nižim rezolucijama; RJ-45 (10/100Base-T) mrežni port; Protokoli HTTP; TCP; ARP; RTSP; RTP; RTCP; UDP; DHCP; DNS; IPV4; NTP; Multicast; ICMP; TLS Multicast; ICMP; IGMP; TLS; ONVIF Profile S&G; Potrebno napajanje 12VDC ili PoE (802.3af, Class 0); Potrošnja 5.1W; Dimenzije Ø122mm x 98.1mm; Kućište od plastike; Masa 0.35kg; IP67; Radna temp. -30°C~+60°C; CE (EN 60950:2000)	€ 36,00	€ 60,00			Na lageru
IP dome IC kamera 2MP; EZ-IP serija; 2.8mm; IC 30m;						
IPC-D2B20-0360B	IP dome IC kamera 2MP; 1/2.7" progressive scan CMOS (1920x1080 piksela); Osetljivost 0.09Lux /F2.0(kolor), 0Lux (IC aktivan); Smart IC LE diode dometa cca. 30m; Objektiv 3.6mm (Vidni ugao 87.5°); 2.8mm opciono (115°); True D/N funkcija (IRC); BLC/HLC/ DWDR; 3D DNR; ROI; Masking (do 4 zone); H.265/H.264H/MJPEG(Sub Stream) kompresija; H.265+/H.264+ podrška; Rezolucije 1080P /1.3M /720P /D1 /VGA /CIF; Dual Stream; Do 25/30fps u 2MP i nižim rezolucijama; RJ-45 (10/100Base-T) mrežni port; Protokoli HTTP; TCP; ARP; RTSP; RTP; RTCP; UDP; DHCP; DNS; IPV4; NTP; Multicast; ICMP; TLS Multicast; ICMP; IGMP; TLS; ONVIF Profile S&G; Potrebno napajanje 12VDC ili PoE (802.3af, Class 0); Potrošnja 5.1W; Dimenzije Ø122mm x 98.1mm; Kućište od plastike; Masa 0.35kg; IP67; Radna temp. -30°C~+60°C; CE (EN 60950:2000)	€ 36,00	€ 60,00			Na lageru
IP dome IC kamera 4MP; EZ-IP serija; 2.8mm; IC 30m;						
IPC-D2B40-0280B	IP dome IC kamera 4MP; 1/3" progressive scan CMOS (2560x1440 piksela); Osetljivost 0.09Lux /F2.0(kolor), 0Lux (IC aktivan); Smart IC LE diode dometa cca. 30m; Objektiv 2.8mm (Vidni ugao 101°); 3.6mm opciono (80°); True D/N funkcija (IRC); BLC/HLC/ DWDR; 3D DNR; ROI; Masking (do 4 zone); H.265/H.264H/MJPEG(Sub Stream) kompresija; H.265+/H.264+ podrška; Rezolucije 4M(2560x1440) /3M(2304x1296) /1080P /1.3M /720P /D1 /VGA /CIF; Dual Stream; Do 20fps u 4M; Do 25/30fps u 2MP i nižim rezolucijama; RJ-45 (10/100Base-T) mrežni port; Protokoli HTTP; TCP; ARP; RTSP; RTP; RTCP; UDP; DHCP; DNS; IPV4; NTP; Multicast; ICMP; TLS Multicast; ICMP; IGMP; TLS; ONVIF Profile S&G; Potrebno napajanje 12VDC ili PoE (802.3af, Class 0); Potrošnja 4.4W; Dimenzije Ø122mm x 98.1mm; Kućište od plastike; Masa 0.35kg; IP67; Radna temp. -30°C~+60°C; CE (EN 60950:2000)	€ 46,20	€ 77,00			Na lageru



IP kamere; EZ-IP serija; Sa motorizovanim zum objektivom

Kod	OPIS	VP	MSRP	Slika	
IP bullet IC kamera 2MP; EZ-IP serija; 2.8-12mm MZ AF; IC 40m; Micro SD slot; IP67					
IPC-B2B20-ZS	IP bullet IC kamera 2MP; 1/2.7" progressive scan CMOS (1920x1080 piksela); Osetljivost 0.05Lux /F1.8(kolor), 0Lux (IC aktivan); Smart IC LE diode dometa cca. 40m; Motorizovani zum objektiv 2.8-12mm /F1.8; Vidni ugao od 105° - 33°; Automatski fokus; Fiksni iris; True D/N funkcija (IRC); BLC/ HLC/ DWDR; 3D DNR; ROI; Masking (do 4 zone); H.265/H.264H/MJPEG(Sub Stream) kompresija; H.265+/H.264+ podrška; Rezolucije 1080P /1.3M /720P /D1 /VGA /CIF; Dual Stream; Do 25/30fps u 2MP i nižim rezolucijama; RJ-45 (10/100Base-T) mrežni port; Micro SD slot (do 128GB); Protokoli HTTP; TCP; ARP; RTSP; RTP; RTCP; UDP; DHCP; DNS; IPV4; NTP; Multicast; ICMP; TLS Multicast; ICMP; IGMP; TLS; ONVIF Profile S; Potrebno napajanje 12Vdc ili PoE (802.3af, Class 0); Potrošnja 6.7W; Dimenzije 243.6mmx90.7mmx90.2mm; Kućište od metala i plastike; Masa 0.434kg; IP67; Radna temp. -30°C~+60°C; CE (EN 60950:2000)	€ 69,90	€ 116,50		Na lageru
IP dome IC kamera 2MP; EZ-IP serija; 2.8-12mm MZ AF; IC 40m; Micro SD slot; IP67					
IPC-T2B20-ZS	IP dome IC kamera 2MP; 1/2.7" progressive scan CMOS (1920x1080 piksela); Osetljivost 0.05Lux /F1.8(kolor), 0Lux (IC aktivan); IC LE diode dometa cca. 40m; Motorizovani zum objektiv 2.8-12mm /F1.8; Vidni ugao od 105° - 33°; Automatski fokus; Fiksni iris; True D/N funkcija (IRC); BLC/ HLC/ DWDR; 3D DNR; ROI; Masking (do 4 zone); H.265/H.264H/MJPEG(Sub Stream) kompresija; H.265+/H.264+ podrška; Rezolucije 1080P /1.3M /720P /D1 /VGA /CIF; Dual Stream; Do 25/30fps u 2MP i nižim rezolucijama; RJ-45 (10/100Base-T) mrežni port; Micro SD slot (do 128GB); Protokoli HTTP; TCP; ARP; RTSP; RTP; RTCP; UDP; DHCP; DNS; IPV4; NTP; Multicast; ICMP; TLS Multicast; ICMP; IGMP; TLS; ONVIF Profile S; Potrebno napajanje 12Vdc ili PoE (802.3af, Class 0); Potrošnja 6.8W; Dimenzije Ø122mmx100mm; Kućište od metala i plastike; Masa 0.397kg; IP67; Radna temp. -30°C~+60°C; CE (EN 60950:2000)	€ 69,90	€ 116,50		Na lageru
IP dome IC kamera 2MP; EZ-IP serija; 2.8-12mm MZ AF; IC 30m; Micro SD slot; IP67					
IPC-D2B20-ZS	IP dome IC kamera 2MP; 1/2.7" progressive scan CMOS (1920x1080 piksela); Osetljivost 0.05Lux /F1.8(kolor), 0Lux (IC aktivan); Smart IC LE diode dometa cca. 30m; Motorizovani zum objektiv 2.8-12mm /F1.8; Vidni ugao od 105° - 33°; Automatski fokus; Fiksni iris; True D/N funkcija (IRC); BLC/ HLC/ DWDR; 3D DNR; ROI; Masking (do 4 zone); H.265/H.264H/MJPEG(Sub Stream) kompresija; H.265+/H.264+ podrška; Rezolucije 1080P /1.3M /720P /D1 /VGA /CIF; Dual Stream; Do 25/30fps u 2MP i nižim rezolucijama; RJ-45 (10/100Base-T) mrežni port; Micro SD slot (do 128GB); Protokoli HTTP; TCP; ARP; RTSP; RTP; RTCP; UDP; DHCP; DNS; IPV4; NTP; Multicast; ICMP; TLS Multicast; ICMP; IGMP; TLS; ONVIF Profile S; Potrebno napajanje 12Vdc ili PoE (802.3af, Class 0); Potrošnja 6.8W; Dimenzije Ø122mm x 98.1mm; Kućište od plastike; Masa 0.381kg; IP67; Radna temp. -30°C~+60°C; CE (EN 60950:2000)	€ 69,90	€ 116,50		Na lageru
IP bullet IC kamera 4MP; EZ-IP serija; 2.8-12mm MZ AF; IC 40m; Micro SD slot; IP67					
IPC-B2B40-ZS	IP bullet IC kamera 4MP; 1/3" progressive scan CMOS (2560x1440 piksela); Osetljivost 0.05Lux /F1.8(kolor), 0Lux (IC aktivan); Smart IC LE diode dometa cca. 40m; Motorizovani zum objektiv 2.8-12mm /F1.8; Vidni ugao od 105° - 33°; Automatski fokus; Fiksni iris; True D/N funkcija (IRC); BLC/ HLC/ DWDR; 3D DNR; ROI; Masking (do 4 zone); H.265/H.264H/MJPEG(Sub Stream) kompresija; H.265+/H.264+ podrška; Rezolucije 4M(2560x1440) /3M(2304x1296) /1080P /1.3M /720P /D1 /VGA /CIF; Dual Stream; Do 20fps u 4M; Do 25/30fps u 2MP i nižim rezolucijama; RJ-45 (10/100Base-T) mrežni port; Micro SD slot (do 128GB); Protokoli HTTP; TCP; ARP; RTSP; RTP; RTCP; UDP; DHCP; DNS; IPV4; NTP; Multicast; ICMP; TLS Multicast; ICMP; IGMP; TLS; ONVIF; Napajanje 12Vdc ili PoE (802.3af, Class 0); Potrošnja 6.3W; Dimenzije 243.6mmx90.7mmx90.2mm; Od metala i plastike; Masa 0.434kg; IP67; Radna temp. -30°C~+60°C; CE (EN 60950:2000)	€ 83,90	€ 139,83		Novo! Na lageru
IP dome IC kamera 4MP; EZ-IP serija; 2.8-12mm MZ AF; IC 40m; Micro SD slot; IP67					
IPC-T2B40-ZS-2812	IP dome IC kamera 4MP; 1/3" progressive scan CMOS (2560x1440 piksela); Osetljivost 0.05Lux /F1.8(kolor), 0Lux (IC aktivan); Smart IC LE diode dometa cca. 40m; Motorizovani zum objektiv 2.8-12mm /F1.8; Vidni ugao od 105° - 33°; Automatski fokus; Fiksni iris; True D/N funkcija (IRC); BLC/ HLC/ DWDR; 3D DNR; ROI; Masking (do 4 zone); H.265/H.264H/MJPEG(Sub Stream) kompresija; H.265+/H.264+ podrška; Rezolucije 4M(2560x1440) /3M(2304x1296) /1080P /1.3M /720P /D1 /VGA /CIF; Dual Stream; Do 20fps u 4M; Do 25/30fps u 2MP i nižim rezolucijama; RJ-45 (10/100Base-T) mrežni port; Micro SD slot (do 128GB); Protokoli HTTP; TCP; ARP; RTSP; RTP; RTCP; UDP; DHCP; DNS; IPV4; NTP; Multicast; ICMP; TLS Multicast; ICMP; IGMP; TLS; ONVIF; Napajanje 12Vdc ili PoE (802.3af, Class 0); Potrošnja 6.3W; Dimenzije Ø122mmx100mm; Od metala i plastike; Masa 0.397kg; IP67; Radna temp. -30°C~+60°C; CE (EN 60950:2000)	€ 83,90	€ 139,83		Novo! Na lageru

IP kamere; Lite, nova Lite H.265 i Consumer serija

Kod	OPIS	VP	MSRP	Slika	
IP kamere; Lite H.265 serija 2MP bullet; 2.8mm; IC 30m;					
IPC-HFW1230S-0280B	IP IR bullet kamera 2MP; 1/2.7" progressive scan CMOS (1920x1080 piksela); Osetljivost 0.08Lux /F2.0(kolor), 0Lux (IR aktivan); IR LE diode dometa cca. 30m, Smart IR; Objektiv 2.8mm (Vidni ugao 104°); 3.6mm opciono (92°); True D/N funkcija (IRC); BLC/ HLC/ DWDR; 3D DNR; ROI; Masking (do 4 zone); H.265/H.264H/MJPEG(Sub Stream) kompresija; H.265+/H.264+ podrška; Rezolucije 1080P /1.3M /720P /D1 /VGA /CIF; Dual Stream; Do 25/30fps u 2MP i nižim rezolucijama; RJ-45 (10/100Base-T) mrežni port; Protokoli HTTP; HTTPS; TCP; ARP; RTSP; RTP; RTCP; UDP; SMTP; FTP; DHCP; DNS; DDNS; PPPoE; IPv4/v6; QoS; UPnP; NTP; Bonjour; IEEE 802.1x; Multicast; ICMP; IGMP; TLS; ONVIF, PSIA, CGI; Video analitika - Tripwire, Intrusion; Potrebno napajanje 12VDC ili PoE (802.3af); Potrošnja 5.5W; Dimenzije Ø70mmx164.7mm; Masa 0.38kg; IP67; Radna temp. -30°C~+60°C	€ 49,80	€ 83,00	 H. 265 ONVIF	Na lageru
IP kamere; Lite H.265 serija 2MP bullet; 3.6mm; IC 30m;					
IPC-HFW1230S-0360B	IP IR bullet kamera 2MP; 1/2.7" progressive scan CMOS (1920x1080 piksela); Osetljivost 0.08Lux /F2.0(kolor), 0Lux (IR aktivan); IR LE diode dometa cca. 30m, Smart IR; Objektiv 3.6mm (Vidni ugao 92°); 2.8mm opciono (104°); True D/N funkcija (IRC); BLC/ HLC/ DWDR; 3D DNR; ROI; Masking (do 4 zone); H.265/H.264H/MJPEG(Sub Stream) kompresija; H.265+/H.264+ podrška; Rezolucije 1080P /1.3M /720P /D1 /VGA /CIF; Dual Stream; Do 25/30fps u 2MP i nižim rezolucijama; RJ-45 (10/100Base-T) mrežni port; Protokoli HTTP; HTTPS; TCP; ARP; RTSP; RTP; RTCP; UDP; SMTP; FTP; DHCP; DNS; DDNS; PPPoE; IPv4/v6; QoS; UPnP; NTP; Bonjour; IEEE 802.1x; Multicast; ICMP; IGMP; TLS; ONVIF, PSIA, CGI; Video analitika - Tripwire, Intrusion; Potrebno napajanje 12VDC ili PoE (802.3af); Potrošnja 5.5W; Dimenzije Ø70mmx164.7mm; Masa 0.38kg; IP67; Radna temp. -30°C~+60°C	€ 49,80	€ 83,00	 H. 265 ONVIF	Na lageru
IP kamere; Lite H.265 serija 2MP dome; 2.8mm; IC 30m;					
IPC-HDW1230S-0280B	IP IR dome kamera 2MP; 1/2.7" progressive scan CMOS (1920x1080 piksela); Osetljivost 0.08Lux /F2.0(kolor), 0Lux (IR aktivan); IR LE diode dometa cca. 30m, Smart IR; Objektiv 2.8mm (Vidni ugao 104°); 3.6mm opciono (92°); True D/N funkcija (IRC); BLC/ HLC/ DWDR; 3D DNR; ROI; Masking (do 4 zone); H.265/H.264H/MJPEG(Sub Stream) kompresija; H.265+/H.264+ podrška; Rezolucije 1080P /1.3M /720P /D1 /VGA /CIF; Dual Stream; Do 25/30fps u 2MP i nižim rezolucijama; RJ-45 (10/100Base-T) mrežni port; Protokoli HTTP; HTTPS; TCP; ARP; RTSP; RTP; RTCP; UDP; SMTP; FTP; DHCP; DNS; DDNS; PPPoE; IPv4/v6; QoS; UPnP; NTP; Bonjour; IEEE 802.1x; Multicast; ICMP; IGMP; TLS; ONVIF, PSIA, CGI; Video analitika - Tripwire, Intrusion; Potrebno napajanje 12VDC ili PoE (802.3af); Potrošnja 5.5W; Dimenzije Ø108mmx84.9mm; Masa 0.23kg; IP67; Radna temp. -30°C~+60°C	€ 51,00	€ 85,00	 H. 265 ONVIF	Na lageru
IP kamere; Lite H.265 serija 2MP anti-vandal dome; 2.8mm; IC 30m;					
IPC-HDBW1230E-0280B	IP IR anti-vandal dome kamera 2MP; 1/2.7" progressive scan CMOS (1920x1080 piksela); Osetljivost 0.08Lux /F2.0(kolor), 0Lux (IR aktivan); IR LE diode dometa cca. 30m, Smart IR; Objektiv 2.8mm (Vidni ugao 104°); 3.6mm opciono (92°); True D/N funkcija (IRC); BLC/ HLC/ DWDR; 3D DNR; ROI; Masking (do 4 zone); H.265/H.264H/MJPEG(Sub Stream) kompresija; H.265+/H.264+ podrška; Rezolucije 1080P /1.3M /720P /D1 /VGA /CIF; Dual Stream; Do 25/30fps u 2MP i nižim rezolucijama; RJ-45 (10/100Base-T) mrežni port; Protokoli HTTP; HTTPS; TCP; ARP; RTSP; RTP; RTCP; UDP; SMTP; FTP; DHCP; DNS; DDNS; PPPoE; IPv4/v6; QoS; UPnP; NTP; Bonjour; IEEE 802.1x; Multicast; ICMP; IGMP; TLS; ONVIF, PSIA, CGI; Video analitika - Tripwire, Intrusion; Potrebno napajanje 12VDC ili PoE (802.3af); Potrošnja 5.5W; Dimenzije Ø109.9mm x 81mm; Masa 0.34kg; IP67 i IK10; Radna temp. -30°C~+60°C	€ 54,00	€ 90,00	 H. 265 ONVIF	Na lageru
IP kamere; Lite H.265 serija 2MP anti-vandal dome; 2.8mm; IC 30m; Micro SD slot					
IPC-HDBW1230E-S-0280B	IP IR anti-vandal dome kamera 2MP; 1/2.7" progressive scan CMOS (1920x1080 piksela); Osetljivost 0.08Lux /F2.0(kolor), 0Lux (IR aktivan); IR LE diode dometa cca. 30m, Smart IR; Objektiv 2.8mm (Vidni ugao 104°); 3.6mm opciono (92°); True D/N funkcija (IRC); BLC/ HLC/ DWDR; 3D DNR; ROI; Masking (do 4 zone); H.265/H.264H/MJPEG(Sub Stream) kompresija; H.265+/H.264+ podrška; Rezolucije 1080P /1.3M /720P /D1 /VGA /CIF; Dual Stream; Do 25/30fps u 2MP i nižim rezolucijama; RJ-45 (10/100Base-T) mrežni port; Micro SD slot; Protokoli HTTP; HTTPS; TCP; ARP; RTSP; RTP; RTCP; UDP; SMTP; FTP; DHCP; DNS; DDNS; PPPoE; IPv4/v6; QoS; UPnP; NTP; Bonjour; IEEE 802.1x; Multicast; ICMP; IGMP; TLS; ONVIF, PSIA, CGI; Video analitika - Tripwire, Intrusion; Potrebno napajanje 12VDC ili PoE (802.3af); Potrošnja 5.5W; Dimenzije Ø109.9mm x 81mm; Masa 0.34kg; IP67 i IK10; Radna temp. -30°C~+60°C	€ 58,20	€ 97,00	 H. 265 ONVIF	Na lageru

IP kamere; Lite, nova Lite H.265 i Consumer serija

Kod	OPIS	VP	MSRP	Slika	
IP kamere; Consumer Serija 3MP Cube; Mikrofon, zvučnik, PIR, SD card slot, alarmni izlaz					
IPC-K35A	IP IR cube kamera 3MP; 1/3" progressive scan CMOS; Efektivni broj piksela 2304x1536; Osetljivost 0.78Lux/F2.0(kolor), 0Lux (IR aktivan); IR LE diode dometa cca. 10m; IC detektor dometa 6m; Fiksni objektiv 2.8mm (Vidni ugao 100°); True D/N funkcija (IRC); BLC/ HLC/ DWDR; 3D DNR; Masking (do 4 zone); H.264/ MJPEG kompresija; Rezolucija 3MP/1080P/720P/VGA/QVGA; Do 20fps u 3M rezoluciji; Do 25fps u 1080P i nižim rezolucijama; Protokoli IIPv4/IPv6, HTTP, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS,FTP, QoS; Inkorporiran mikrofon i zvučnik; Micro SD slot (do 128GB); Alarmni ulaz/izlaz; ONVIF; CGI; Easy4ip cloud podrška; U kompletu sa nosačem; Napajanje DC12V ili PoE(802.3af)(class0); Potrošnja 5W; Dimenzije Ø78.5mmx127.8mm; Radna temperatura -10°C~+45°C	€ 67,00	€ 111,67		Na lageru
IP kamere; Lite H.265 serija 4MP bullet; 2.8mm; IC 30m;					
IPC-HFW1431S-0280B	IP IR bullet kamera 4MP; 1/3" progressive scan CMOS (2688x1520 piksela); Osetljivost 0.08Lux /F2.0(kolor), 0Lux (IR aktivan); IR LE diode dometa cca. 30m, Smart IR; Objektiv 2.8mm (Vidni ugao 104°); 3.6mm opciono (87°); True D/N funkcija (IRC); BLC/ HLC; True WDR 120dB; 3D DNR; ROI; Masking (do 4 zone); H.265/H.264H/MJPEG(Sub Stream) kompresija; H.265+/H.264+ podrška; Rezolucije 4M /3M /1080P /1.3M /720P /D1 /VGA /CIF; Dual Stream; Do 20fps u 4MP; Do 25/30fps u 3MP i nižim rezolucijama; RJ-45 (10/100Base-T) mrežni port; Protokoli HTTP; HTTPS; TCP; ARP; RTSP; RTP; RTCP; UDP; SMTP; FTP; DHCP; DNS; DDNS; PPPoE; IPv4/v6; QoS; UPnP; NTP; Bonjour; IEEE 802.1x; Multicast; ICMP; IGMP; TLS; ONVIF, PSIA, CGI; Video analitika - Tripwire, Intrusion; Potrebno napajanje 12VDC ili PoE (802.3af); Potrošnja 5.5W; Dimenzije Ø70mmx164.7mm; Masa 0.38kg; IP67; Radna temp. -30°C~+60°C	€ 75,00	€ 125,00		Na lageru
IP kamere; Lite serija 4MP dome; 2.8mm; IC 30m;					
IPC-HDW1420S-0280B	IP IR dome kamera 4MP; 1/3" progressive scan CMOS; Efektivni broj piksela 2688x1520; Osetljivost 0.1Lux/F2.0(kolor), 0Lux (IR aktivan); IR LE diode dometa cca. 30m; Fiksni objektiv 2.8mm (Vidni ugao 92°); 3.6mm opciono (Vidni ugao 81°); True D/N funkcija (IRC); BLC/ HLC/ DWDR; 3D DNR; Masking (do 4 zone); H.264+/H.264 kompresija; Rezolucije 4MP /3M /1080P /720P /D1 /CIF; Dual Stream; Do 20fps u 4MP; Do 25fps u 3MP i nižim rezolucijama; RJ-45 (10/100Base-T) mrežni port; Protokoli: HTTP; HTTPS, TCP, ARP, RTSP, RTP, DHCP, DNS, DDNS, PPOE, IPv4/v6, QoS, UPnP, NTP, Bonjour, 802.1x, Multicast, ICMP, IGMP; ONVIF; PSIA; CGI; Potrebno napajanje 12VDC ili PoE(802.3af); Potrošnja 6.9W; Dimenzije Ø108mmx84.9mm; IP67 stepen zaštite; Radna temperatura -30°C~+60°C	€ 77,00	€ 128,33		Na lageru
IP kamere; Lite H.265 serija 4MP anti-vandal dome; 2.8mm; IC 30m; Micro SD slot					
IPC-HDBW1431E-0280B	IP IR anti-vandal dome kamera 4MP; 1/3" progressive scan CMOS (2688x1520 piksela); Osetljivost 0.08Lux /F2.0(kolor), 0Lux (IR aktivan); IR LE diode dometa cca. 30m, Smart IR; Objektiv 2.8mm (Vidni ugao 104°); 3.6mm opciono (87°); True D/N funkcija (IRC); BLC/ HLC; True WDR 120dB; 3D DNR; ROI; Masking (do 4 zone); H.265/H.264H/MJPEG(Sub Stream) kompresija; H.265+/H.264+ podrška; Rezolucije 4M /3M /1080P /1.3M /720P /D1 /VGA /CIF; Dual Stream; Do 20fps u 4MP; Do 25/30fps u 3MP i nižim rezolucijama; RJ-45 (10/100Base-T) mrežni port; Protokoli HTTP; HTTPS; TCP; ARP; RTSP; RTP; RTCP; UDP; SMTP; FTP; DHCP; DNS; DDNS; PPPoE; IPv4/v6; QoS; UPnP; NTP; Bonjour; IEEE 802.1x; Multicast; ICMP; IGMP; TLS; ONVIF, PSIA, CGI; Video analitika - Tripwire, Intrusion; Potrebno napajanje 12VDC ili PoE (802.3af); Potrošnja 5.5W; Dimenzije Ø70mmx164.7mm; Masa 0.38kg; IP67 i IK10; Radna temp. -30°C~+60°C	€ 77,40	€ 129,00		Na lageru
IP kamere; Lite H.265 serija 4MP anti-vandal dome; 2.8mm; IC 30m; Micro SD slot					
IPC-HDBW1431E-S-0280B	IP IR anti-vandal dome kamera 4MP; 1/3" progressive scan CMOS (2688x1520 piksela); Osetljivost 0.08Lux /F2.0(kolor), 0Lux (IR aktivan); IR LE diode dometa cca. 30m, Smart IR; Objektiv 2.8mm (Vidni ugao 104°); 3.6mm opciono (87°); True D/N funkcija (IRC); BLC/ HLC; True WDR 120dB; 3D DNR; ROI; Masking (do 4 zone); H.265/H.264H/MJPEG(Sub Stream) kompresija; H.265+/H.264+ podrška; Rezolucije 4M /3M /1080P /1.3M /720P /D1 /VGA /CIF; Dual Stream; Do 20fps u 4MP; Do 25/30fps u 3MP i nižim rezolucijama; RJ-45 (10/100Base-T) mrežni port; Micro SD slot; Protokoli HTTP; HTTPS; TCP; ARP; RTSP; RTP; RTCP; UDP; SMTP; FTP; DHCP; DNS; DDNS; PPPoE; IPv4/v6; QoS; UPnP; NTP; Bonjour; IEEE 802.1x; Multicast; ICMP; IGMP; TLS; ONVIF, PSIA, CGI; Video analitika - Tripwire, Intrusion; Potrebno napajanje 12VDC ili PoE (802.3af); Potrošnja 5.5W; Dimenzije Ø70mmx164.7mm; Masa 0.38kg; IP67 i IK10; Radna temp. -30°C~+60°C	€ 78,60	€ 131,00		Na lageru

IP kamere; Lite, nova Lite H.265 i Consumer serija

Kod	OPIS	VP	MSRP	Slika		
IP kamera; Lite H.265 serija 5MP bullet; 2.8mm; IC 30m;						
IPC-HFW1531S-0280B	IP 5 megapixels bullet IC kamera; 1/2.7" 5MP progressive scan CMOS; Efektivni broj piksela 2592x1944; Osetljivost 0.03Lux/F2.0 (kolor), 0Lux (IC uključ.); Motorizovani IR Cut filter; IR LE diode dometa 30m; Fiksni objektiv 2.8mm / F2.0 (Vidni ugao 96°) ili 3.6mm / F2.0 (Vidni ugao 78°); H.265+/H.265 H.264+/H.264 kompresija; Rezolucija do 5MP (2592x1944); Do 20fps u 2492x1944, Do 30fps u 2048x1536 i nižim rezolucijama; Dual stream; WDR 120dB; HLC; 3D DNR; Masking 4 zone; HTTP; TCP; ARP; RTSP; RTP; UDP; RTCP; SMTP; FTP; DHCP; DNS; DDNS; PPPOE; IPv4/v6; SNMP; QoS; UPnP; NTP; ONVIF, PSIA, CGI; IP67 sertifikovana; Opseg radne temperature -30°C~60°C; Dimenzije Ø70mmx164.7mm; Masa 0,38kg; Napajanje PoE (802.3af) ili 12VDC/4.85W	€ 87,00	€ 145,00		Na lageru	
IP kamera; Lite H.265 serija 5MP anti-vandal dome; 2.8mm; IC 30m;						
IPC-HDBW1531E-0280B	IP 5 megapixels bullet IC kamera; 1/2.7" 5MP progressive scan CMOS; Efektivni broj piksela 2592x1944; Osetljivost 0,03Lux/F2.0 (kolor), 0Lux (IC uključ.); Motorizovani IR Cut filter; IR LE diode dometa 30m; Fiksni objektiv 2.8mm / F2.0 (Vidni ugao 96°) ili 3.6mm / F2.0 (Vidni ugao 78°); H.265+/H.265 H.264+/H.264 kompresija; Rezolucija do 5MP (2592x1944); Do 20fps u 2592x1944, Do 30fps u 2304x1296 i nižim rezolucijama; RJ-45 (10/100Base-T) mrežni port; Dual stream; WDR 120dB; HLC; 3D DNR; Masking 4 zone; HTTP; TCP; ARP; RTSP; RTP; UDP; RTCP; SMTP; FTP; DHCP; DNS; DDNS; PPPOE; IPv4/v6; SNMP; QoS; UPnP; NTP; ONVIF, PSIA, CGI; IP67 sertifikovana; Opseg radne temperature -30°C~60°C; Dimenzije Ø70mmx164.7mm; Masa 0,38kg; Napajanje PoE (802.3af) ili 12VDC/4.85W	€ 87,00	€ 145,00		Na lageru	
IP kamera; Lite H.265 serija 5MP anti-vandal dome; 2.8mm; IC 30m; Micro SD Slot						
IPC-HDBW1531E-S-0280B	IP 5 megapixels bullet IC kamera; 1/2.7" 5MP progressive scan CMOS; Efektivni broj piksela 2592x1944; Osetljivost 0,03Lux/F2.0 (kolor), 0Lux (IC uključ.); Motorizovani IR Cut filter; IR LE diode dometa 30m; Fiksni objektiv 2.8mm / F2.0 (Vidni ugao 96°) ili 3.6mm / F2.0 (Vidni ugao 78°); H.265+/H.265 H.264+/H.264 kompresija; Rezolucija do 5MP (2592x1944); Do 20fps u 2592x1944, Do 30fps u 2304x1296 i nižim rezolucijama; RJ-45 (10/100Base-T) mrežni port; Micro SD slot; Dual stream; WDR 120dB; HLC; 3D DNR; Masking 4 zone; HTTP; TCP; ARP; RTSP; RTP; UDP; RTCP; SMTP; FTP; DHCP; DNS; DDNS; PPPOE; IPv4/v6; SNMP; QoS; UPnP; NTP; ONVIF, PSIA, CGI; IP67 sertifikovana; Opseg radne temperature -30°C~60°C; Dimenzije Ø70mmx164.7mm; Masa 0,38kg; Napajanje PoE (802.3af) ili 12VDC/4.85W	€ 87,60	€ 146,00		Na lageru	
IP kamera; Lite H.265 serija 8MP (4K) bullet; 2.8mm; IC 50m;						
IPC-HFW1831E-0280B	IP IR bullet kamera 8MP (4K); 1/1.8" progressive scan CMOS (3840x2160 piksela); Osetljivost 0.003Lux /F1.6(kolor), 0Lux (IR aktivan); IR LE diode dometa cca. 50m, Smart IR; Objektiv 2.8mm (Vidni ugao 111°); 4mm ili 6mm opciono (87° ili 55°); True D/N funkcija (IRC); BLC/ HLC; True WDR 120dB; 3D DNR; ROI; Masking (do 4 zone); H.265/H.264H/MJPEG(Sub Stream) kompresija; H.265+/H.264+ podrška; Rezolucije 4K /6M /5M /3M /1080P /1.3M /720P /D1 /VGA /CIF; Dual Stream; Do 25/30fps u svim rezolucijama; RJ-45 (10/100Base-T) mrežni port; Protokoli HTTP; HTTPS; TCP; ARP; RTSP; RTP; RTCP; UDP; SMTP; FTP; DHCP; DNS; DDNS; PPPoE; IPv4/v6; QoS; UPnP; NTP; Bonjour; IEEE 802.1x; Multicast; ICMP; IGMP; TLS; ONVIF, PSIA, CGI; Video analitika - Tripwire, Intrusion; Potrebno napajanje 12VDC ili PoE (802.3af); Potrošnja 7.8W; Dimenzije 180mmx70mmx70mm; Masa 0.48kg; IP67; Radna temp. -30°C~+60°C	€ 110,00	€ 183,33		Na lageru	
IP kamera; Lite H.265 serija 8MP (4K) anti-vandal dome; 2.8mm; IC 30m;						
IPC-HDBW1831R-0280B	IP IR anti-vandal dome kamera 8MP (4K); 1/1.8" progressive scan CMOS (3840x2160 piksela); Osetljivost 0.003Lux /F1.6(kolor), 0Lux (IR aktivan); IR LE diode dometa cca. 30m, Smart IR; Objektiv 2.8mm (Vidni ugao 111°); 4mm ili 6mm opciono (87° ili 55°); True D/N funkcija (IRC); BLC/ HLC; True WDR 120dB; 3D DNR; ROI; Masking (do 4 zone); H.265/H.264H/MJPEG(Sub Stream) kompresija; H.265+/H.264+ podrška; Rezolucije 4K /6M /5M /3M /1080P /1.3M /720P /D1 /VGA /CIF; Dual Stream; Do 25/30fps u svim rezolucijama; RJ-45 (10/100Base-T) mrežni port; Protokoli HTTP; HTTPS; TCP; ARP; RTSP; RTP; RTCP; UDP; SMTP; FTP; DHCP; DNS; DDNS; PPPOE; IPv4/v6; QoS; UPnP; NTP; Bonjour; IEEE 802.1x; Multicast; ICMP; IGMP; TLS; ONVIF, PSIA, CGI; Video analitika - Tripwire, Intrusion; Potrebno napajanje 12VDC ili PoE (802.3af); Potrošnja 7.8W; Dimenzije Ø122mmx88.9mm; Masa 0.45kg; IP67 i IK10; Radna temp. -30°C~+60°C	€ 110,00	€ 183,33		Na lageru	

Pinhole IP kamere

Kod	OPIS	VP	MSRP		Slika		
IPC-HUM4231	IP 2MP WDR Pinhole kamera; 1/2.7" 2 Megapixels progressive CMOS; Efektivni broj piksela 1920Hx1080(V); Osetljivost 0.007Lux/F2.4(Color,1/3s,30IRE), 0.04Lux/F2.4(Color,1/30s,30IRE), 0.004Lux/F2.4(B/W,1/3s,30IRE), 0.02Lux/F2.4(B/W,1/30s,30IRE); Soft. dan/noć; Fiksni objektiv 2.8mm F2.4; Vidni ugao 105°; H.265 /H.264 /H.264B /H.264H /MJPEG (Sub Stream) kompresije; Podržane rezolucije 1080P(1920x1080)/ 1.3M(1280x960)/ 720P(1280x720)/ D1(704x576/704x480)/ VGA(640x480)/ CIF(352x288/342x240); Do 25/30fps u 1080P; Triple stream; BLC / HLC / WDR 120dB; 3D DNR; ROI; Detekcija pokreta; Flip; Mirror; Privacy Masking; Video analitika - Tripwire, Intrusion, Object Abandoned/Missing, Face Detection; Ethernet RJ-45 (10/100Base-T) port; Audio ulaz/izlaz; ONVIF, PSIA, CGI; Opseg radne temperature -30°C ~ +60°C; Dimenzije 44.9mm x 57.7mmx34.35mm; Masa 102g; Potrebno napajanje DC12V; Potrošnja do 1.5W	€ 156,00	€ 260,00			Na lageru	

IP WiFi kamere

Kod	OPIS	VP	MSRP		Slika		
-----	------	----	------	--	-------	--	--

IP kamere; Serija 2MP WiFi

IPC-C22	IP IC cube kamera 2MP; 1/2.7" progressive scan CMOS; Efektivni broj piksela 1920x1080; IC LE diode dometa cca. 10m; Fiksni objektiv 2.8mm (Vidni ugao 115°); True D/N funkcija (IRC); BLC/ HLC/ DWDR; 3D DNR; Masking (do 4 zone); H.264/ H.264B/ H.264H/ MJPEG kompresija; Rezolucija/frame rate do 1080P/15FPS; Protokoli IPv4/IPv6, HTTP, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS,FTP, QoS; Inkorporiran mikrofoni i zvučnik; Integriran Wi-Fi (IEEE802.11b/g/n) dometa cca. 30m na otvorenom; Micro SD slot (podržane kartice kapaciteta do 64GB); Micro USB; Easy4ip cloud podrška; U kompletu sa napajanjem jedinicom 5Vdc i nosačem; Potrošnja 2.5W; Dimenzije 120x66x33mm; Radna temperatura -10°C~+45°C	€ 50,00	€ 83,33			Novi Na lageru	
---------	---	---------	---------	--	--	----------------	--

IP kamere; Serija 1.3MP Cube WiFi

IPC-C15	IP IR cube kamera 1.3MP; 1/3" progressive scan CMOS; Efektivni broj piksela 1280x960; Osetljivost 1.96Lux/F1.2(kolor), 0Lux (IR aktivan); IR LE diode dometa cca. 10m; Fiksni objektiv 2.3mm (Vidni ugao 125°); True D/N funkcija (IRC); BLC/ HLC/ DWDR; 3D DNR; Masking (do 4 zone); H.264/ H.264B/ H.264H/ MJPEG kompresija; Rezolucija 1.3MP/720P(1280x720)/ D1(704x576)/ CIF(352x288); Do 25fps u svim rezolucijama; Protokoli IPv4/IPv6, HTTP, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS,FTP, QoS; Inkorporiran mikrofoni i zvučnik; Integriran Wi-Fi (IEEE802.11b/g/n) dometa cca. 30m na otvorenom; Micro SD slot (podržane kartice kapaciteta do 128GB); Micro USB; ONVIF; CGI; Easy4ip cloud podrška; U kompletu sa napajanjem jedinicom 5Vdc i nosačem; Potrošnja 4.5W; Dimenzije 76mmx65mmx107mm; Radna temperatura -10°C~+45°C	€ 50,00	€ 83,33			Na lageru	
---------	---	---------	---------	--	--	-----------	--


IP kamere; Serija 2MP Cube WiFi; H.265

IPC-K26	IP IR cube kamera 2MP; 1/2.9" progressive scan CMOS; Efektivni broj piksela 1920x1080; Osetljivost 0.01Lux/F2.0(kolor), 0Lux (IR aktivan); IR LE diode dometa cca. 10m; IC detektor dometa 6m; Fiksni objektiv 2.8mm (Vidni ugao 106°); True D/N funkcija (IRC); BLC/ HLC/ DWDR; 3D DNR; Masking (do 4 zone); H.265/ H.264 kompresija; Rezolucija 1080P/720P/VGA/QVGA; Do 30fps u 1080P rezoluciji; Protokoli IPv4/IPv6, HTTP, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS,FTP, QoS; Inkorporiran mikrofoni i zvučnik; Integriran Wi-Fi (IEEE802.11b/g/n) dometa cca. 50m na otvorenom; Micro SD slot (podržane kartice kapaciteta do 128GB); Micro USB; Alarmni ulaz/izlaz; ONVIF; CGI; Easy4ip cloud podrška; U kompletu sa napajanjem jedinicom 12Vdc i nosačem; Potrošnja 4.3W; Dimenzije 78.5mmx127.8mm; Radna temperatura -10°C~+45°C	€ 65,00	€ 108,33			Na lageru	
---------	--	---------	----------	--	--	-----------	--

IP kamere; Serija 3MP Cube WiFi

IPC-K35	IP IR cube kamera 3MP; 1/3" progressive scan CMOS; Efektivni broj piksela 2304x1536; Osetljivost 0.01Lux/F2.0(kolor), 0Lux (IR aktivan); IR LE diode dometa cca. 10m; IC detektor dometa 6m; Fiksni objektiv 2.8mm (Vidni ugao 95°); True D/N funkcija (IRC); BLC/ HLC/ DWDR; 3D DNR; Masking (do 4 zone); H.264/ MJPEG kompresija; Rezolucija 3MP/1080P/720P/VGA/QVGA; Do 20fps u 3M rezoluciji; Do 25fps u 1080P i nižim rezolucijama; Protokoli IPv4/IPv6, HTTP, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS,FTP, QoS; Inkorporiran mikrofoni i zvučnik; Integriran Wi-Fi (IEEE802.11b/g/n) dometa cca. 50m na otvorenom; Micro SD slot (podržane kartice kapaciteta do 128GB); Micro USB; Alarmni ulaz/izlaz; ONVIF; CGI; Easy4ip cloud podrška; U kompletu sa napajanjem jedinicom 12Vdc i nosačem; Potrošnja 3W; Dimenzije 68mmx99mmx24mm; Radna temperatura -10°C~+45°C	€ 68,00	€ 113,33			Na lageru	
---------	---	---------	----------	--	--	-----------	--

IP WiFi kamere

Kod	OPIS	VP	MSRP	Slika		
IP kamere; Serija 4MP Cube WiFi; H.265						
IPC-K46	IP IR cube kamera 4MP ; 1/3" progressive scan CMOS; Efektivni broj piksela 2688 x 1520; Osetljivost 0.01Lux/F2.0(kolor), 0Lux (IR aktivan); IR LE diode dometa cca. 10m ; IC detektor dometa 6m ; Fiksni objektiv 2.8mm (Vidni ugao 106°); True D/N funkcija (IRC) ; BLC/ HLC/ DWDR ; 3D DNR ; Masking (do 4 zone) ; H.265/ H.264 kompresija ; Rezolucija 4M/3M/1080P/720P/VGA/QVGA; Do 30fps u 1080P rezoluciji; Protokoli IPv4/IPv6, HTTP, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS,FTP, QoS; Inkorporiran mikrofoni i zvučnik ; Integrisan Wi-Fi (IEEE802.11b/g/n) dometa cca. 50m na otvorenom ; Micro SD slot (podržane kartice kapaciteta do 128GB) ; Video analitika - Human detection ; Micro USB ; Alarmni ulaz/izlaz ; ONVIF ; CGI ; Easy4ip cloud podrška ; U kompletu sa napajačkom jedinicom 12Vdc i nosačem; Potrošnja 4.3W; Dim. Ø78.5mm×127.8mm; Radna temperatura -10°C~+45°C	€ 74,00	€ 123,33			Na lageru
Wi-Fi 2MP IP CMOS True D/N bullet IC kamera; SD Slot; Wi-Fi						
IPC-G26	2MP Wi-Fi IP IC bullet kamera ; 1/2.7" progressive scan CMOS; Efektivni broj piksela 1920x1080; Osetljivost 0.1Lux/F2.0(kolor), 0Lux (IR aktivan); IR LE diode dometa cca. 30m ; Fiksni objektiv 2.8mm (Vidni ugao 112°); 3.6mm opciono (Vidni ugao 88°); True D/N funkcija (IRC) ; BLC/ HLC/ DWDR ; 3D DNR ; Masking (do 4 zone) ; H.265/H.264 kompresija ; Rezolucije 1080P(1920×1080)/ 1.3MP(1280×960)/ 720P(1280×720)/ VGA(640×480)/ QVGA (320×240); Dual Stream; Do 25fps u svim rezolucijama; RJ-45 (10/100Base-T) mrežni port; Mikrofon ; Integrisan Wi-Fi (IEEE802.11b/g/n) ; Dual Antena, 2x2 MIMO ; Micro SD slot (do 128GB) ; ONVIF ; U kompletu sa napajačkom jedinicom 12Vdc i nosačem; Potrošnja 7.5W maks; Dimenzije 60mm x 105mm x 175.5mm; Masa 477g; IP67 stepen zaštite ; Radna temperatura -10°C~+50°C	€ 74,70	€ 124,50			Novi Na lageru
Wi-Fi 4MP IP CMOS True D/N bullet IC kamera; SD Slot; Wi-Fi						
IPC-HFW1435S-W-0280B	4MP Wi-Fi IP IC bullet kamera ; 1/3" progressive scan CMOS; Efektivni broj piksela 1920x1080; Osetljivost 0.1Lux/F2.0(kolor), 0Lux (IR aktivan); IR LE diode dometa cca. 30m ; Fiksni objektiv 2.8mm (Vidni ugao 106°); 3.6mm opciono (Vidni ugao 83°); True D/N funkcija (IRC) ; BLC/ HLC/ DWDR ; 3D DNR ; Masking (do 4 zone) ; H.265/H.264 kompresija ; Rezolucije 1080P(1920×1080)/ 1.3MP(1280×960)/ 720P(1280×720)/ VGA(640×480)/ QVGA (320×240); Dual Stream; Do 20fps u svim rezolucijama; RJ-45 (10/100Base-T) mrežni port; Integrisan Wi-Fi (IEEE802.11b/g/n) dometa cca. 50m ; Micro SD slot (do 128GB) ; Video analitika - Human detection ; Protokoli IPv4/IPv6, HTTP, HTTPS, TCP/IP, UDP, UPnP, ICMP, IGMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS; ONVIF ; CGI ; U kompletu sa napajačkom jedinicom 12Vdc i nosačem; Potrošnja 6.5W; Dimenzije Ø78.5mm×127.8mm; IP67 stepen zaštite ; Radna temperatura -10°C~+50°C	€ 88,00	€ 146,67			Na lageru
Wi-Fi 3MP IP bullet IC kamera; SD Slot; Wi-Fi						
IPC-HFW1320S-W-0280B	Wi-Fi IP IC bullet kamera 3MP ; 1/3" progressive scan CMOS; Efektivni broj piksela 2304x1536; IC LE diode dometa cca. 30m ; Fiksni objektiv 2.8mm (Vidni ugao 100°); 3.6mm opciono (Vidni ugao 77°); True D/N funkcija (IRC) ; BLC/ HLC/ DWDR ; 3D DNR ; Masking (do 4 zone) ; H.264/H.264B/H.264H/MJPEG kompresija ; Rezolucije 3M(2304×1296) /1080P(1920×1080)/ 1.3MP(1280×960) /720P(1280×720) /VGA(640×480) /QVGA (320×240); Dual Stream; Do 20fps u 3M; Do 25/30fps u 1080P i nižim rezolucijama; RJ-45 (10/100Base-T) mrežni port; Integrisan Wi-Fi (IEEE802.11b/g/n) dometa cca. 50m ; Micro SD slot (do 128GB) ; Protokoli IPv4/IPv6, HTTP, HTTPS, TCP/IP, UDP, UPnP, ICMP, IGMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS; ONVIF ; CGI ; Potrebno napajanje 12Vdc; Potrošnja 5.5W; Dimenzije Ø70mm×164.7mm; IP67 stepen zaštite ; Radna temperatura -10°C~+50°C	€ 65,40	€ 109,00			Na lageru

IP WiFi kamere

Kod	OPIS	VP	MSRP	Slika		
Wi-Fi 3MP IP anti-vandal dome IC kamera; SD Slot; Wi-Fi						
IPC-HDBW1320E-W-0280B	Wi-Fi IP IC anti-vandal dome kamera 3MP; 1/3" progressive scan CMOS; Efektivni broj piksela 2304x1536; IC LE diode dometa cca. 30m; Fiksni objektiv 2.8mm (Vidni ugao 100°); 3.6mm opciono (Vidni ugao 77°); True D/N funkcija (IRC); BLC/ HLC/ DWDR; 3D DNR; Masking (do 4 zone); H.264/H.264B/H.264H/MJPEG kompresija; Rezolucije 3M(2304x1296)/1080P(1920x1080)/1.3MP(1280x960)/720P(1280x720)/VGA(640x480)/QVGA (320x240); Dual Stream; Do 20fps u 3M; Do 25/30fps u 1080P i nižim rezolucijama; RJ-45 (10/100Base-T) mrežni port; Integrisan Wi-Fi (IEEE802.11b/g/n) dometa cca. 50m; Micro SD slot (do 128GB); Protokoli IPv4/IPv6, HTTP, HTTPS, TCP/IP, UDP, UPnP, ICMP, IGMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS; ONVIF; CGI; Potrebno napajanje 12VDC; Potrošnja 5.5W; Dimenzije Ø110mmx81mm; IP67 stepen zaštite; IK10; Radna temperatura -10°C~+50°C	€ 65,40	€ 109,00		Ponovo na lageru	
Wi-Fi 2 Megapixela PT kamera; sa IR LE diodama dometa 10m; Sa mikrofonom i zvučnikom; Micro SD slot						
IPC-A26	Wi-Fi IP IC PT dome kamera 2MP; 1/2.9" progressive scan CMOS; Efektivni broj piksela 1920x1080; IR LE diode dometa cca. 10m; Fiksni objektiv 3.6mm (Vidni ugao 84°); Inkorporiran mikrofoni i zvučnik; Micro SD slot (podržane kartice kapaciteta do 128GB); Pan/tilt - opseg horizontalne rotacije 0°~355°, opseg vertikalne rotacije 0°~90°; Digitalni zum do 16X; H.265 / H.264H kompresija; Smart Tracking; Do 25fps u svim rezolucijama; Integrisan Wi-Fi (IEEE802.11b/g/n) dometa cca. 50m; ONVIF Profile S&G, CGI; Napajanje putem priložene jedinice 220VAC/5V 2A; Potrošnja 7W; Dimenzije 94.4mm x 94.4mm x 94mm; Masa 240g; Radna temperatura -10°C~+45°C	€ 102,00	€ 170,00		Na lageru	
Wi-Fi 4 Megapixela PT kamera; sa IR LE diodama dometa 10m; Sa mikrofonom i zvučnikom; Micro SD slot						
IPC-A46	Wi-Fi IP IC PT dome kamera 4MP; 1/3" progressive scan CMOS; Efektivni broj piksela 2688x1520; IR LE diode dometa cca. 10m; Fiksni objektiv 3.6mm (Vidni ugao 83°); Inkorporiran mikrofoni i zvučnik; Micro SD slot (podržane kartice kapaciteta do 128GB); Pan/tilt - opseg horizontalne rotacije 0°~355°, opseg vertikalne rotacije 0°~90°; Digitalni zum do 16X; H.265 / H.264H kompresija; Smart Tracking; Do 20fps u svim rezolucijama; Integrisan Wi-Fi (IEEE802.11b/g/n) dometa cca. 50m; ONVIF Profile S&G, CGI; Napajanje DC 5V 2A; Potrošnja 8W; Dimenzije 94mm x 94mm x 94mm; Masa 240g; Radna temperatura -10°C~+45°C	€ 107,00	€ 178,33		Na lageru	
Wi-Fi 2 Megapixela PTZ anti-vandal dome kamera; 4x zoom; Micro SD slot						
SD22204T-GN-W	Wi-Fi IP 2 Megapixela 4X zoom PTZ kamera; 1/2.7" Progressive scan CMOS; inkorporiran motor zoom auto fokus objektiv f=2.7mm(Wide)~11mm(Tele), F1.6~F2.8 (vidni ugao 112.5°~30°); Digitalni zoom do 16x; Osetljivost 0.05Lux@F1.6 (Color), 0Lux (IR On); True Day/Night - mot. IR Cut filter; IC LE diode dometa cca. 30m; Inkorporiran mikrofoni; H.264+ /H.264 / MJPEG kompresija; Podržane rezolucije 2M/ 720P / D1 / CIF; Frame rate do 25fps u 1080P, do 50fps u 720P; Dual stream; True WDR 120dB; HLC; BLC; 2D i 3D DNR; ROI; Defog; Bit rate 448K ~ 8192Kbps; Micro SD card slot - do 128GB; RJ-45 (10/100Base-T) mrežni port; Integrisan Wi-Fi (IEEE802.11b/g/n) dometa cca. 30m na otvorenom; 300 programabilnih preset-a, 5 grupa, 8 tura; Masking (do 24 zone); Onvif Profile S; Brzina horizontalne rotacije 100°/s maks, opseg 0° ~ 355°; 3D pozicioniranje; Dimenzije Ø132.7mm x 116.5mm; Masa 0.95kg; Radna temperatura od -30°C do +60°C; Potrebno napajanje 12VDC/13W	€ 129,60	€ 216,00		Na lageru	
Wi-Fi 2 Megapixela PTZ dome kamera; 4x zoom; Sa IR LE diodama 30m; Inkorporiran mikrofoni; Micro SD slot						
SD29204T-GN-W	Wi-Fi IP IC 2 Megapixela 4X zoom PTZ kamera; 1/2.7" Progressive scan CMOS; inkorporiran motor zoom auto fokus objektiv f=2.7mm(Wide)~11mm(Tele), F1.6~F2.8 (vidni ugao 112.5°~30°); Digitalni zoom do 16x; Osetljivost 0.05Lux@F1.6 (Color), 0Lux (IR On); True Day/Night - mot. IR Cut filter; IC LE diode dometa cca. 30m; Inkorporiran mikrofoni; H.264+ /H.264 / MJPEG kompresija; Podržane rezolucije 2M/ 720P / D1 / CIF; Frame rate do 25fps u 1080P, do 50fps u 720P; Dual stream; True WDR 120dB; HLC; BLC; 2D i 3D DNR; ROI; Defog; Bit rate 448K ~ 8192Kbps; Micro SD card slot - do 128GB; RJ-45 (10/100Base-T) mrežni port; Integrisan Wi-Fi (IEEE802.11b/g/n) dometa cca. 30m na otvorenom; 300 programabilnih preset-a, 5 grupa, 8 tura; Masking (do 24 zone); Onvif Profile S; Brzina horizontalne rotacije 100°/s maks, opseg 0° ~ 355°; 3D pozicioniranje; Dimenzije Ø132.7mm x 116.5mm; Masa 0.95kg; Radna temperatura od -30°C do +60°C; Potrebno napajanje 12VDC/13W	€ 166,20	€ 277,00		Uskoro	


IP kamere; Lite H.265 serija sa vari-fokal ili motorizovanim auto-fokus objektivom

Kod	OPIS	VP	MSRP		Slika		
IP 2MP bullet IC kamera; Lite serija; Smart IC 60m; Metalno kućište; MZ AF objektiv 2.7-13.5mm; IP67; Starlight; Micro SD slot							
IPC-HFW2231T-ZS	IP 2MP bullet IC kamera sa motorizovanim zum objektivom; 1/2.8" 2MP progressive scan Starvis™ CMOS; Efektivni broj piksela 1920X1080; Osetljivost 0.006Lux/F1.4 (kolor), 0Lux (IC uključ.); Motorizovani IR Cut filter; IC LE diode dometa 60m; Motorizovani zum objektiv 2.7-13.5mm /F1.4; Vidni ugao od 106° - 29°; Automatski fokus; Fiksni iris; H.265+/H.265/H.264+/H.264/MJPEG kompresija; Rezolucija do 1920x1080; Do 25/30fps u 1920x1080 i svim nižim rezolucijama; Dual stream; WDR 120dB; HLC; BLC; 3D DNR; ROI; Masking 4 zone; HTTP; HTTPS; TCP; ARP; RTSP; RTP; RTCP; UDP; SMTP; FTP; DHCP; DNS; DDNS; PPPoE; IPv4/v6; QoS; UPnP; NTP; Bonjour; IEEE 802.1x; Multicast; ICMP; IGMP; TLS; ONVIF Profile S&G, API; Video analitika - Tripwire, Intrusion; Micro SD slot (do 128GB); IP67 sertifikovana, IK10 opciono; Opseg radne temperature -30°C~60°C; Dimenzije 244.1mm x79xmm x75.9mm; Masa 0.815kg; Napajanje PoE+ (IEEE 802.3af, Class 4) ili 12VDC, 14W; CE (EN 60950:2000)	€ 109,20	€ 182,00		H. 265 Starlight ONVIF	Na lageru	
IP 2MP anti-vandal dome IC kamera; Lite serija; Smart IC 30m; Metalno kućište; MZ AF objektiv 2.7-13.5mm; IP67; IK10; Starlight; Micro SD slot							
IPC-HDBW2231R-ZS	IP 2MP anti-vandal dome IC kamera sa motorizovanim zum objektivom; 1/2.8" 2MP progressive scan Starvis™ CMOS; Efektivni broj piksela 1920X1080; Osetljivost 0.006Lux/F1.4 (kolor), 0Lux (IC uključ.); Motorizovani IR Cut filter; IC LE diode dometa 30m; Motorizovani zum objektiv 2.7-13.5mm /F1.4; Vidni ugao od 106° - 29°; Automatski fokus; Fiksni iris; H.265+/H.265/H.264+/H.264/MJPEG kompresija; Rezolucija do 1920x1080; Do 25/30fps u 1920x1080 i svim nižim rezolucijama; Dual stream; WDR 120dB; HLC; BLC; 3D DNR; ROI; Masking 4 zone; HTTP; HTTPS; TCP; ARP; RTSP; RTP; RTCP; UDP; SMTP; FTP; DHCP; DNS; DDNS; PPPoE; IPv4/v6; QoS; UPnP; NTP; Bonjour; IEEE 802.1x; Multicast; ICMP; IGMP; TLS; ONVIF Profile S&G, API; Video analitika - Tripwire, Intrusion; Micro SD slot (do 128GB); IP67 i IK10 sertifikovana; Opseg radne temperature -30°C~60°C; Dimenzije 122mmx88.9mm; Masa 0.4kg; Napajanje PoE (802.3af, Class 0) ili 12VDC, 9W; CE (EN 60950:2000)	€ 109,20	€ 182,00		H. 265 Starlight ONVIF	Na lageru	
IP 4MP bullet IC kamera; Lite serija; Smart IC 60m; Metalno kućište; MZ AF objektiv 2.7-13.5mm; IP67; Micro SD slot							
IPC-HFW2431T-ZS	IP 4MP bullet IC kamera sa motorizovanim zum objektivom; 1/3" 4MP progressive scan CMOS; Efektivni broj piksela 2688X1520; Osetljivost 0.03Lux/F1.4 (kolor), 0Lux (IC uključ.); Motorizovani IR Cut filter; IC LE diode dometa 60m; Motorizovani zum objektiv 2.7-13.5mm /F1.4; Vidni ugao od 104° - 28°; Automatski fokus; Fiksni iris; H.265+/H.265/H.264+/H.264/MJPEG kompresija; Rezolucija do 4MP (2688x1520); Do 20fps u 4MP rezoluciji; Do 25/30fps u 3MP i svim nižim rezolucijama; Dual stream; WDR 120dB; HLC; BLC; 3D DNR; ROI; Masking 4 zone; HTTP; HTTPS; TCP; ARP; RTSP; RTP; RTCP; UDP; SMTP; FTP; DHCP; DNS; DDNS; PPPoE; IPv4/v6; QoS; UPnP; NTP; Bonjour; IEEE 802.1x; Multicast; ICMP; IGMP; TLS; ONVIF Profile S&G, API; Video analitika - Tripwire, Intrusion; Micro SD slot (do 128GB); IP67 sertifikovana, IK10 opciono; Opseg radne temperature -30°C~60°C; Dimenzije 244.1mm x79xmm x75.9mm; Masa 0.815kg; Napajanje PoE+ (IEEE 802.3af, Class 4) ili 12VDC, 14W; CE (EN 60950:2000)	€ 120,00	€ 200,00		H. 265 ONVIF	Na lageru	
IP 4MP anti-vandal dome IC kamera; Lite serija; Smart IC 30m; Metalno kućište; MZ AF objektiv 2.7-13.5mm; IP67; IK10; Micro SD slot							
IPC-HDBW2431R-ZS	IP 4MP anti-vandal dome IC kamera sa motorizovanim zum objektivom; 1/3" 4MP progressive scan CMOS; Efektivni broj piksela 2688X1520; Osetljivost 0.03Lux/F1.4 (kolor), 0Lux (IC uključ.); Motorizovani IR Cut filter; IC LE diode dometa 30m; Motorizovani zum objektiv 2.7-13.5mm /F1.4; Vidni ugao od 104° - 28°; Automatski fokus; Fiksni iris; H.265+/H.265/H.264+/H.264/MJPEG kompresija; Rezolucija do 4MP (2688x1520); Do 20fps u 4MP rezoluciji; Do 25/30fps u 3MP i svim nižim rezolucijama; Dual stream; WDR 120dB; HLC; BLC; 3D DNR; ROI; Masking 4 zone; HTTP; HTTPS; TCP; ARP; RTSP; RTP; RTCP; UDP; SMTP; FTP; DHCP; DNS; DDNS; PPPoE; IPv4/v6; QoS; UPnP; NTP; Bonjour; IEEE 802.1x; Multicast; ICMP; IGMP; TLS; ONVIF Profile S&G, API; Video analitika - Tripwire, Intrusion; Micro SD slot (do 128GB); IP67 i IK10 sertifikovana; Opseg radne temperature -30°C~60°C; Dimenzije 122mmx88.9mm; Masa 0.4kg; Napajanje PoE (IEEE 802.3af, Class 0) ili 12VDC, 9W; CE (EN 60950:2000)	€ 118,20	€ 197,00		H. 265 ONVIF	Na lageru	

IP kamere; Lite H.265 serija sa vari-fokal ili motorizovanim auto-fokus objektivom

Kod	OPIS	VP	MSRP		Slika	
IP 4MP dome IC kamera; Lite serija; Smart IC 60m; Metalno kućište; MZ AF objektiv 2.7-13.5mm; IP67; Micro SD slot						
IPC-HDW2431R-ZS	IP 4MP dome IC kamera sa motorizovanim zum objektivom; 1/3" 4MP progressive scan CMOS; Efektivni broj piksela 2688X1520; Osetljivost 0.03Lux/F1.4 (kolor), 0Lux (IC uključ.); Motorizovani IR Cut filter; IC LE diode dometa 60m; Motorizovani zum objektiv 2.7-13.5mm /F1.4; Vidni ugao od 104° - 28°; Automatski fokus; Fiksni iris; H.265+/H.265/H.264+/H.264/MJPEG kompresija; Rezolucija do 4MP (2688x1520); Do 20fps u 4MP rezoluciji; Do 25/30fps u 3MP i svim nižim rezolucijama; Dual stream; WDR 120dB; HLC; BLC; 3D DNR; ROI; Masking 4 zone; HTTP; HTTPS; TCP; ARP; RTSP; RTP; RTCP; UDP; SMTP; FTP; DHCP; DNS; DDNS; PPPoE; IPv4/v6; QoS; UPnP; NTP; Bonjour; IEEE 802.1x; Multicast; ICMP; IGMP; TLS; ONVIF Profile S&G, API; Video analitika - Tripwire, Intrusion; Micro SD slot (do 128GB); IP67 sertifikovana, IK10 opciono; Opseg radne temperature -30°C~60°C; Dimenzije Φ122mm x 102mm; Masa 0.6kg; Napajanje PoE (IEEE 802.3af, Class 0) ili 12Vdc, 9.5W; CE (EN 60950:2000)	€ 117,00	€ 195,00		 H. 265 ONVIF	Na lageru
IP 5MP bullet IC kamera; Lite serija; Smart IC 60m; Metalno kućište; MZ AF objektiv 2.7-13.5mm; IP67; Micro SD slot						
IPC-HFW2531T-ZS	IP 5MP bullet IC kamera sa motorizovanim zum objektivom; 1/2.7" 5MP progressive scan CMOS; Efektivni broj piksela 2592X1944; Osetljivost 0.02Lux/F1.6 (kolor), 0Lux (IC uključ.); Motorizovani IR Cut filter; IC LE diode dometa 60m; Motorizovani zum objektiv 2.7-13.5mm /F1.4; Vidni ugao od 95° - 27°; Automatski fokus; Fiksni iris; H.265+/H.265/H.264+/H.264/MJPEG kompresija; Rezolucija do 5MP (2592x1944); Do 15fps u 5MP rezoluciji; Do 25/30fps u 3MP i nižim rezolucijama; Dual stream; WDR 120dB; HLC; BLC; 3D DNR; ROI; Masking 4 zone; HTTP; HTTPS; TCP; ARP; RTSP; RTP; RTCP; UDP; SMTP; FTP; DHCP; DNS; DDNS; PPPoE; IPv4/v6; QoS; UPnP; NTP; Bonjour; IEEE 802.1x; Multicast; ICMP; IGMP; TLS; ONVIF Profile S&G, API; Video analitika - Tripwire, Intrusion; Micro SD slot (do 128GB); IP67 sertifikovana, IK10 opciono; Opseg radne temperature -30°C~60°C; Dimenzije 244.1mm x79xmm x75.9mm; Masa 0.815kg; Napajanje PoE+ (IEEE 802.3at, Class 4) ili 12Vdc, 15W; CE (EN 60950:2000)	€ 138,60	€ 231,00		 H. 265 ONVIF	Na lageru
IP 5MP anti-vandal dome IC kamera; Lite serija; Smart IC 30m; Metalno kućište; MZ AF objektiv 2.7-13.5mm; IP67; IK10; Micro SD slot						
IPC-HDBW2531R-ZS	IP 5MP anti-vandal dome IC kamera sa motorizovanim zum objektivom; 1/2.7" 5MP progressive scan CMOS; Efektivni broj piksela 2592X1944; Osetljivost 0.02Lux/F1.6 (kolor), 0Lux (IC uključ.); Motorizovani IR Cut filter; IC LE diode dometa 60m; Motorizovani zum objektiv 2.7-13.5mm /F1.4; Vidni ugao od 95° - 27°; Automatski fokus; Fiksni iris; H.265+/H.265/H.264+/H.264/MJPEG kompresija; Rezolucija do 5MP (2592x1944); Do 15fps u 5MP rezoluciji; Do 25/30fps u 3MP i nižim rezolucijama; Dual stream; WDR 120dB; HLC; BLC; 3D DNR; ROI; Masking 4 zone; HTTP; HTTPS; TCP; ARP; RTSP; RTP; RTCP; UDP; SMTP; FTP; DHCP; DNS; DDNS; PPPoE; IPv4/v6; QoS; UPnP; NTP; Bonjour; IEEE 802.1x; Multicast; ICMP; IGMP; TLS; ONVIF Profile S&G, API; Video analitika - Tripwire, Intrusion; Micro SD slot (do 128GB); IP67 i IK10 sertifikovana; Opseg radne temperature -30°C~60°C; Dimenzije 244.1mm x79xmm x75.9mm; Masa 0.815kg; Napajanje PoE (IEEE 802.3af, Class 0) ili 12Vdc, 9.5W; CE (EN 60950:2000)	€ 136,80	€ 228,00		 H. 265 ONVIF	Na lageru
IP 8MP bullet IC kamera; Lite serija; Smart IC 60m; Metalno kućište; MZ AF objektiv 3.7-11mm; IP67; Micro SD slot						
IPC-HFW2831T-ZS	IP 8MP bullet dome IC kamera sa motorizovanim zum objektivom; 1/1.8" 8MP progressive scan CMOS; Efektivni broj piksela 3840X2160; Osetljivost 0.004Lux/F1.9 (kolor), 0Lux (IC uključ.); Motorizovani IR Cut filter; IC LE diode dometa 60m; Motorizovani zum objektiv 3.7-11mm /F1.9; Vidni ugao od 112° - 46°; Automatski fokus; Fiksni iris; H.265+/H.265/H.264+/H.264/MJPEG kompresija; Rezolucija do 4K (3840x2160); Do 25fps u svim rezoluciji; Dual stream; WDR 120dB; HLC; BLC; 3D DNR; ROI; Masking 4 zone; HTTP; HTTPS; TCP; ARP; RTSP; RTP; RTCP; UDP; SMTP; FTP; DHCP; DNS; DDNS; PPPoE; IPv4/v6; QoS; UPnP; NTP; Bonjour; IEEE 802.1x; Multicast; ICMP; IGMP; TLS; ONVIF Profile S&G, API; Video analitika - Tripwire, Intrusion; Micro SD slot (do 128GB); IP67 i IK10; Opseg radne temperature -30°C~60°C; Dimenzije φ122mmx88.9mm; Masa 0.49kg; Napajanje PoE (IEEE 802.3af, Class 0) ili 12Vdc, 10.9W; CE (EN 60950:2000)	€ 170,00	€ 283,33		 H. 265 ONVIF	Na lageru

IP kamere; Lite H.265 serija sa vari-fokal ili motorizovanim auto-fokus objektivom

Kod	OPIS	VP	MSRP	Slika			
IP 8MP anti-vandal dome IC kamera; Lite serija; Smart IC 30m; Metalno kućište; MZ AF objektiv 3.7-11mm; IP67; IK10; Micro SD slot							
IPC-HDBW2831R-ZS	IP 8MP anti-vandal dome IC kamera sa motorizovanim zum objektivom; 1/1.8" 8MP progressive scan CMOS; Efektivni broj piksela 3840X2160; Osetljivost 0.004Lux/F1.9 (kolor), 0Lux (IC uključ.); Motorizovani IR Cut filter; IC LE diode dometa 30m; Motorizovani zum objektiv 3.7-11mm /F1.9; Vidni ugao od 112° - 46°; Automatski fokus; Fiksni iris; H.265+/H.265/H.264+/H.264/MJPEG kompresija; Rezolucija do 4K (3840x2160); Do 25fps u svim rezoluciji; Dual stream; WDR 120dB; HLC; BLC; 3D DNR; ROI; Masking 4 zone; HTTP; HTTPS; TCP; ARP; RTSP; RTP; RTCP; UDP; SMTP; FTP; DHCP; DNS; DDNS; PPPoE; IPv4/v6; QoS; UPnP; NTP; Bonjour; IEEE 802.1x; Multicast; ICMP; IGMP; TLS; ONVIF Profile S&G, API; Video analitika - Tripwire, Intrusion; Micro SD slot (do 128GB); IP67 i IK10; Opseg radne temperature -30°C~60°C; Dimenzije φ122mm×88.9mm; Masa 0.49kg; Napajanje PoE (IEEE 802.3af, Class 0) ili 12VDC, 10.9W; CE (EN 60950:2000)	€ 170,00	€ 283,33			Na lageru	

IP Kamere; Eco Savvy 3.0 i Eco Savvy 3.0 ePoE serija

Kod	OPIS	VP	MSRP	Slika		
IP 2MP anti-vandal dome IC kamera; Eco Savvy 3 ePoE serija; Smart IC 30m; Objektiv 2.8mm; IP67; IK10; Starlight						
IPC-HDBW4231E-ASE-0280B	IP 2MP anti-vandal dome IC kamera; 1/2.8" 2MP progressive scan Starvis™ CMOS; Efektivni broj piksela 1920x1080; Osetljivost 0.007Lux/F1.6 (kolor), 0Lux (IC uključ.); Motorizovani IR Cut filter; Smart IR LE diode dometa 30m; Fiksni objektiv 2.8mm /F1.6; Vidni ugao od 110° ; Opciono objektiv 3.6mm ili 6mm (vidni ugao 87° ili 52°); H.265+ /H.265 /H.264+ /H.264 kompresija ; Rezolucija do 1080P (1920x1080); Do 60fps u svim rezolucijama; Bit rate 24~9472Kbps; Triple stream; WDR 120dB; HLC; BLC; 3D DNR; ROI; Analitika - Tripwire, Intrusion, Abandoned/Missing Object, Face detect ; Masking; IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, 802.1x; Alarmni ulaz/izlaz; Audio ulaz/izlaz; Micro SD slot (podržane kartice kapaciteta do 128GB); ONVIF, PSIA, CGI; IP67 i IK10 sertifikat; Opseg radne temperature -30°C~60°C ; Dimenzije Φ109.9mmx81mm; Masa 0.41kg; Napajanje PoE (802.3af) ili 12VDC, 5W maks; ePoE Kompatibilna	€ 81,60	€ 136,00			Na lageru
IP 2MP anti-vandal dome IC kamera; Eco Savvy 3 serija; Smart IC 20m; Objektiv 2.8mm; IP67; IK10; Starlight; Mikrofon						
IPC-HDBW4231F-AS-0280B	IP 2MP anti-vandal dome IC kamera; 1/2.8" 2MP progressive scan STARVIS CMOS; Efektivni broj piksela 1920x1080; Osetljivost 0.009Lux/F2.0 (kolor), 0Lux (IC uključ.); Motorizovani IR Cut filter; Smart IR LE diode dometa 20m; Fiksni objektiv 2.8mm /F2.0; Vidni ugao od 110° ; Opciono objektiv 3.6mm ili 6mm (vidni ugao 87° ili 51°); H.265+ /H.265 /H.264+ /H.264 kompresija ; Rezolucija do 1080P (1920x1080); Do 60fps u svim rezolucijama; Bit rate 24~9472Kbps; Triple stream; WDR 120dB; HLC; BLC; 3D DNR; ROI; Analitika - Tripwire, Intrusion, Abandoned/Missing Object, Face detect ; Detekcija pokreta; Masking 4 zone; IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, 802.1x; Ugrađen mikrofoni; Micro SD slot (podržane kartice kapaciteta do 128GB); ONVIF, PSIA, CGI; IP67 i IK10 sertifikovana; Opseg radne temperature -30°C~60°C ; Dimenzije Φ106mmx50.3mm; Masa 0.4kg; Napajanje PoE (802.3af, Class 0) ili 12VDC/4.5W	€ 88,80	€ 148,00			Na lageru
IP 2MP dome IC kamera; Eco Savvy 3 ePoE serija; Smart IC 50m; Objektiv 2.8mm; IP67; Starlight; Mikrofon						
IPC-HDW4231EM-ASE-0280B	IP 2MP dome IC kamera; 1/2.8" 2MP progressive scan Starvis™ CMOS; Efektivni broj piksela 1920x1080; Osetljivost 0.007Lux/F1.6 (kolor), 0Lux (IC uključ.); Motorizovani IR Cut filter; Smart IR LE diode dometa 50m; Fiksni objektiv 2.8mm /F1.6; Vidni ugao od 110° ; Opciono objektiv 3.6mm ili 6mm (vidni ugao 87° ili 52°); H.265+ /H.265 /H.264+ /H.264 kompresija ; Rezolucija do 1080P (1920x1080); Do 60fps u svim rezolucijama; Bit rate 24~9472Kbps; Triple stream; WDR 120dB; HLC; BLC; 3D DNR; ROI; Analitika - Tripwire, Intrusion, Abandoned/Missing Object, Face detect ; Masking; IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, 802.1x; Ugrađen mikrofoni; Micro SD slot (podržane kartice kapaciteta do 128GB); ONVIF, PSIA, CGI; IP67 sertifikat; Opseg radne temperature -30°C~60°C ; Dimenzije Φ106mmx93.7mm; Masa 0.47kg; Napajanje PoE (802.3af) ili 12VDC, 5.5W maks; ePoE Kompatibilna	€ 93,60	€ 156,00			Na lageru



IP Kamere; Eco Savvy 3.0 ePoE serija

Kod	OPIS	VP	MSRP		Slika		
IP 2MP bullet IC kamera; Eco Savvy 3 ePoE serija; Smart IC 80m; Objektiv 3.6mm; IP67; IK10; Starlight							
IPC-HFW4231T-ASE-0360B	IP 2MP bullet IC kamera; 1/2.8" 2MP progressive scan Starvis™ CMOS; Efektivni broj piksela 1920x1080; Osetljivost 0.009Lux/F2.0 (kolor), 0Lux (IC uključ.); Motorizovani IR Cut filter; Smart IC LE diode dometa 80m; Fiksni objektiv 3.6mm /F1.6; Vidni ugao od 87°; Opciono objektiv 6mm, 8mm ili 12mm (vidni ugao 52°, 41° ili 26°); H.265+ /H.265 /H.264+ /H.264 kompresija; Rezolucija do 1080P (1920x1080); Do 60fps u svim rezolucijama; Bit rate 24~9472Kbps; Triple stream; WDR 120dB; HLC; BLC; 3D DNR; ROI; Analitika - Tripwire, Intrusion, Abandoned/Missing Object, Face detect; Masking; IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, 802.1x; Alarmni ulaz/izlaz; Audio ulaz/izlaz; Micro SD slot (podržane kartice kapaciteta do 128GB); ONVIF, PSIA, CGI; IP67 i IK10 sertifikat; Opseg radne temperature -30°C~60°C; Dimenzije 244.1mmx79mmx75.9mm; Masa 0.815kg; Napajanje PoE (802.3af) ili 12VDC, 12W maks; ePoE Kompatibilna	€ 90,60	€ 151,00			Na lageru	
IP 4MP anti-vandal dome IC kamera; Eco Savvy 3 ePoE serija; Smart IC 30m; Objektiv 2.8mm; IP67; IK10							
IPC-HDBW4431E-ASE-0280B	IP 4MP anti-vandal dome IC kamera; 1/3" 4MP progressive scan CMOS; Efektivni broj piksela 2688x1520; Osetljivost 0.06Lux/F1.6 (kolor), 0Lux (IC uključ.); Motorizovani IR Cut filter; Smart IC LE diode dometa 30m; Fiksni objektiv 2.8mm /F1.6; Vidni ugao od 104°; Opciono objektiv 3.6mm ili 6mm (vidni ugao 83° ili 55°); H.265+ /H.265 /H.264+ /H.264 kompresija; Rezolucija do 4MP (2688x1520); Do 30fps u svim rezolucijama; Bit rate 24~10240Kbps; Triple stream; WDR 120dB; HLC; 3D DNR; ROI; Analitika - Tripwire, Intrusion, Abandoned/Missing Object, Face detect; Detekcija pokreta; Masking; IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, 802.1x; Alarmni ulaz/izlaz; Audio ulaz/izlaz; Micro SD slot (podržane kartice kapaciteta do 128GB); ONVIF, PSIA, CGI; IP67 i IK10 sertifikovana; Opseg radne temperature -30°C~60°C; Dimenzije Φ109.9mmx81mm; Masa 0.41kg; Napajanje PoE - IEEE802.3af ili 12VDC, 5W maks; ePoE Kompatibilna	€ 101,40	€ 169,00			Na lageru	
IP 4MP dome IC kamera; Eco Savvy 3 ePoE serija; Smart IC 50m; Objektiv 2.8mm; IP67							
IPC-HDW4431EM-ASE-0280B	IP 4MP anti-vandal dome IC kamera; 1/3" 4MP progressive scan CMOS; Efektivni broj piksela 2688x1520; Osetljivost 0.06Lux/F1.6 (kolor), 0Lux (IC uključ.); Motorizovani IR Cut filter; IC LE diode dometa 50m; Fiksni objektiv 2.8mm /F1.6; Vidni ugao od 104°; Opciono objektiv 3.6mm ili 6mm (vidni ugao 83° ili 55°); H.265+ /H.265 /H.264+ /H.264 kompresija; Rezolucija do 4MP (2688x1520); Do 30fps u svim rezolucijama; Bit rate 24~10240Kbps; Triple stream; WDR 120dB; HLC; 3D DNR; ROI; Analitika - Tripwire, Intrusion, Abandoned/Missing Object, Face detect; Detekcija pokreta; Masking; IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, 802.1x; Ugrađen mikrofoni; Micro SD slot (podržane kartice kapaciteta do 128GB); ONVIF, PSIA, CGI; IP67 sertifikovana; Opseg radne temperature -30°C~60°C; Dimenzije Φ106mmx93.7mm; Masa 0.47kg; Napajanje PoE - IEEE802.3af ili 12VDC, 5.5W maks; ePoE Kompatibilna	€ 101,40	€ 169,00			Na lageru	
IP 4MP bullet IC kamera; Eco Savvy 3 ePoE serija; Smart IC 80m; Objektiv 3.6mm; IP67							
IPC-HFW4431T-ASE-0360B	IP 4MP bullet IC kamera; 1/3" 4MP progressive scan CMOS; Efektivni broj piksela 2688x1520; Osetljivost 0.08Lux/F2.0 (kolor), 0Lux (IC uključ.); Motorizovani IR Cut filter; Smart IR LE diode dometa 80m; Fiksni objektiv 3.6mm /F1.6; Vidni ugao od 87°; Opciono objektiv 6mm, 8mm ili 12mm (vidni ugao 55°, 38° ili 12°); H.265+ /H.265 /H.264+ /H.264 kompresija; Rezolucija do 4MP (2688x1520); Do 25/30fps u svim rezolucijama; Bit rate 24~10240Kbps; Triple stream; WDR 120dB; HLC; 3D DNR; ROI; Analitika - Tripwire, Intrusion, Abandoned/Missing Object, Face detect; Detekcija pokreta; Masking; HTTP; HTTPS; TCP; ARP; RTSP; RTP; UDP; SMTP; FTP; DHCP; DNS; DDNS; PPPOE; IPv4/v6; QoS; UPnP; NTP; Bonjour; 802.1x; Multicast; ICMP; IGMP; SNMP; Alarmni ulaz/izlaz; Audio ulaz/izlaz; Micro SD slot (do 128GB); ONVIF, PSIA, CGI; IP67; IK10; Opseg radne temperature -30°C~60°C; Dimenzije 244.1mmx79mmx75.9mm; Masa 0.815kg; Napajanje PoE (IEEE802.3af, Class 0) ili 12VDC/10.1W	€ 93,60	€ 156,00			Na lageru	

IP Kamere; Eco Savvy 3.0 ePoE serija

Kod	OPIS	VP	MSRP	Slika		
IP 2MP anti-vandal dome Full Color kamera; Eco Savvy 3 ePoE serija; Objektiv 3.6mm; IP67						
IPC-HDBW4239R-ASE-NI-0360B	IP 2MP anti-vandal dome Full-color kamera; 1/2.8" 2MP progressive scan Starvis™ CMOS; Efektivni broj piksela 1920x1080; Osetljivost 0.001Lux/F1.0 (kolor); Fiksni objektiv 3.6mm /F1.0; Vidni ugao od 87°; Opciono objektiv 6mm (vidni ugao 54°); H.265+ /H.265 /H.264+ /H.264/MJPEG kompresija; Rezolucija do 1080P (1920x1080); Do 25/30fps u svim rezolucijama; Bit rate 14~9984Kbps; Triple stream; WDR 120dB; HLC; BLC; 3D DNR; ROI; Analitika - Tripwire, Intrusion, Abandoned/Missing Object, Face detect; Masking; HTTP; HTTPS; TCP; ARP; RTSP; RTP; RTCP; UDP; PPPOE; IEEE802.1X; SMTP; SNMP; FTP; DHCP; DNS; DDNS; PPPoE; IPV4/V6; QoS; UPnP; NTP; Bonjour; IEEE 802.1X; Multicast; ICMP; IGMP; TLS; SSH; NFS; Alarmni ulaz/izlaz; Audio ulaz/izlaz; Micro SD slot (do 128GB); ONVIF, PSIA, CGI; IP67 i IK10 sertifikat; Opseg radne temperature -30°C~60°C; Dimenzije Φ122.9mmx88.9mm; Masa 0.44kg; Napajanje PoE (802.3af) ili 12VDC, 3.7W maks; ePoE Kompatibilna; CE (EN 60950:2000)	€ 117,00	€ 195,00			Na lageru
IP 2MP bullet Full Color kamera; Eco Savvy 3 ePoE serija; Objektiv 3.6mm; IP67						
IPC-HFW4239T-ASE-NI-0360B	IP 2MP bullet Full-color kamera; 1/2.8" 2MP progressive scan Starvis™ CMOS; Efektivni broj piksela 1920x1080; Osetljivost 0.001Lux/F1.0 (kolor); Fiksni objektiv 3.6mm /F1.0; Vidni ugao od 87°; Opciono objektiv 6mm (vidni ugao 54°); H.265+ /H.265 /H.264+ /H.264/MJPEG kompresija; Rezolucija do 1080P (1920x1080); Do 25/30fps u svim rezolucijama; Bit rate 14~9984Kbps; Triple stream; WDR 120dB; HLC; BLC; 3D DNR; ROI; Analitika - Tripwire, Intrusion, Abandoned /Missing Object, Face detect; Masking; HTTP; HTTPS; TCP; ARP; RTSP; RTP; RTCP; UDP; PPPOE; IEEE802.1X; SMTP; SNMP; FTP; DHCP; DNS; DDNS; PPPoE; IPV4/V6; QoS; UPnP; NTP; Bonjour; IEEE 802.1X; Multicast; ICMP; IGMP; TLS; SSH; NFS; Alarmni ulaz/izlaz; Audio ulaz/izlaz; Micro SD slot (do 128GB); ONVIF, PSIA, CGI; IP67 i IK10 sertifikat; Opseg radne temperature -30°C~60°C; Dimenzije 244.1mmx79mmx75.9mm; Masa 0.815kg; Napajanje PoE (802.3af) ili 12VDC, 4W maks; ePoE Kompatibilna; CE (EN 60950:2000)	€ 117,00	€ 195,00			Na lageru
IP 6MP dome IC kamera; Eco Savvy 3 ePoE serija; Smart IC 50m; Objektiv 2.8mm; IP67; Starlight						
IPC-HDW4631EM-ASE-0280B	IP 6 megapixels WDR dome IR True D/N kamera sa mikrofonom; 1/2.9" 6MP progressive scan Starvis CMOS; Efektivni broj piksela 3072x2048; Osetljivost 0.04Lux/F1.6 (kolor), 0Lux (IC uključ.); Motorizovani IR Cut filter; IR LE diode dometa 50m; Fiksni objektiv 2.8mm /F1.6; Vidni ugao od 98°, opciono 3.6mm (Vidni ugao 69°); H.265+ /H.265 /H.264+ /H.264 kompresija; Rezolucija do (3072x2048); Do 20fps u (3072x2048), do 30fps u 4MP i svim nižim rezolucijama; Bit rate 24~10240Kbps; Triple stream; WDR 120dB; HLC; BLC; 3D DNR; ROI; Analitika - Tripwire, Intrusion, Abandoned/Missing Object, Face detect; Masking; IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, 802.1x; Ugrađen mikrofoni; Micro SD slot (podržane kartice kapaciteta do 128GB); ONVIF, PSIA, CGI; IP67 sertifikat; Opseg radne temperature -30°C~60°C; Dimenzije Φ106mmx93.7mm; Masa 0.47kg; Napajanje PoE (802.3af) ili 12VDC/6W	€ 118,20	€ 197,00			Na lageru
IP 6MP anti-vandal dome IC kamera; Eco Savvy 3 ePoE serija; Smart IC 30m; Objektiv 2.8mm; IP67; IK10; Starlight						
IPC-HDBW4631E-ASE-0280B	IP 6MP anti-vandal dome IC kamera; 1/2.9" 6MP progressive scan Starvis CMOS; Efektivni broj piksela 3072x2048; Osetljivost 0.04Lux/F1.6 (kolor), 0Lux (IC uključ.); Motorizovani IR Cut filter; IR LE diode dometa 50m; Fiksni objektiv 2.8mm /F1.6; Vidni ugao od 98°, opciono 3.6mm (Vidni ugao 69°); H.265+ /H.265 /H.264+ /H.264 kompresija; Rezolucija do (3072x2048); Do 20fps u (3072x2048), do 30fps u 4MP i svim nižim rezolucijama; Bit rate 24~10240Kbps; Triple stream; WDR 120dB; HLC; BLC; 3D DNR; ROI; Analitika - Tripwire, Intrusion, Abandoned/Missing Object, Face detect; Masking; IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, 802.1x; Ugrađen mikrofoni; Micro SD slot (podržane kartice kapaciteta do 128GB); ONVIF, PSIA, CGI; IP67 i IK10 sertifikat; Opseg radne temperature -30°C~60°C; Dimenzije Φ106mmx93.7mm; Masa 0.47kg; Napajanje PoE (802.3af) ili 12VDC/6W	€ 122,40	€ 204,00			Na lageru


IP Kamere; Eco Savvy 3.0 ePoE serija

Kod	OPIS	VP	MSRP	Slika		
IP 6MP bullet IC kamera; Eco Savvy 3 ePoE serija; Smart IC 80m; Objektiv 2.8mm; IP67; Starlight						
IPC-HFW4631T-ASE-0280B	IP 6 megapixela WDR bullet IR True D/N kamera; 1/2.9" 6MP progressive scan Starvis CMOS; Efektivni broj piksela 3072x2048; Osetljivost 0.04Lux/F1.6 (kolor), 0Lux (IC uključ.); Motorizovani IR Cut filter; IR LE diode dometa 80m; Fiksni objektiv 2.8mm /F1.6; Vidni ugao od 98°, opciono 3.6mm (Vidni ugao 69°) ili 6mm (Vidni ugao 48°); H.265+ /H.265 /H.264+ /H.264 kompresija; Rezolucija do (3072x2048); Do 20fps u (3072x2048), do 30fps u 4MP i svim nižim rezolucijama; Bit rate 24~10240Kbps; Triple stream; WDR 120dB; HLC; 3D DNR; ROI; Analitika - Tripwire, Intrusion, Abandoned/Missing Object, Face detect; Masking; IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, 802.1x; Audio ulaz/izlaz; Alarmni ulaz/izlaz; Micro SD slot (podržane kartice kapaciteta do 128GB); ONVIF, PSIA, CGI; IP67 i IK10 sertifikovana; Opseg radne temperature -30°C~60°C; Dimenzije Φ244,1mmx79mmx75.9mm; Masa 0.815kg; Napajanje PoE (802.3af) ili 12VDC/11W	€ 127,80	€ 213,00	  Na lageru		
IP 8MP anti-vandal dome IC kamera; Eco Savvy 3 ePoE serija; Smart IC 30m; Objektiv 2.8mm; IP67; IK10; Starlight						
IPC-HDBW4831E-ASE-0280B	IP 8 megapixela anti-vandal dome IR D/N kamera; 1/2.5" 8MP progressive Starvis™ CMOS; Efektivni broj piksela 3840x2160; Osetljivost 0.06Lux/F1.6 (kolor), 0Lux (IC uključ.); Motorizovani IR Cut filter; Smart IR LE diode dometa 30m; Fiksni objektiv 2.8mm /F1.6; Vidni ugao od 112°; Opciono objektiv 4mm (vidni ugao 88°); H.265+ /H.265 /H.264+ /H.264 kompresija; Rezolucija do 4K/8MP (3840x2160); Do 15fps u 4K rezoluciji; Bit rate 24~10240Kbps; Triple stream; WDR 120dB; HLC; 3D DNR; ROI; Analitika - Tripwire, Intrusion, Abandoned/Missing Object, Face detect; Detekcija pokreta; Masking; IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, 802.1x; Alarmni ulaz/izlaz; Audio ulaz/izlaz; Micro SD slot (podržane kartice kapaciteta do 128GB); ONVIF, PSIA, CGI; IP67 i IK10 sertifikovana; Opseg radne temperature -30°C~60°C; Dimenzije Φ109.9mmx81mm; Masa 0.41kg; Napajanje PoE - IEEE802.3af ili 12VDC, 5.5W maks; ePoE Kompatibilna	€ 153,00	€ 255,00	  Na lageru		
IP 8MP dome IC kamera; Eco Savvy 3 ePoE serija; Smart IC 50m; Objektiv 2.8mm; IP67; Starlight						
IPC-HDW4831EM-ASE-0280B	IP 8 megapixela dome IR D/N kamera; 1/2.5" 8MP progressive Starvis™ CMOS; Efektivni broj piksela 3840x2160; Osetljivost 0.06Lux/F1.6 (kolor), 0Lux (IC uključ.); Motorizovani IR Cut filter; Smart IR LE diode dometa 50m; Fiksni objektiv 2.8mm /F1.6; Vidni ugao od 112°; Opciono objektiv 4mm (vidni ugao 88°); H.265+ /H.265 /H.264+ /H.264 kompresija; Rezolucija do 4K/8MP (3840x2160); Do 15fps u 4K rezoluciji; Bit rate 24~10240Kbps; Triple stream; WDR 120dB; HLC; 3D DNR; ROI; Analitika - Tripwire, Intrusion, Abandoned/Missing Object, Face detect; Detekcija pokreta; Masking; IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, 802.1x; Ugrađen mikrofoni; Micro SD slot (podržane kartice kapaciteta do 128GB); ONVIF, PSIA, CGI; IP67 i IK10 sertifikovana; Opseg radne temperature -30°C~60°C; Dimenzije Φ106mmx93.7mm; Masa 0.47kg; Napajanje PoE - IEEE802.3af ili 12VDC, 6W maks; ePoE Kompatibilna	€ 153,00	€ 255,00	  Na lageru		
IP 8MP bullet IC kamera; Eco Savvy 3 ePoE serija; Smart IC 80m; Objektiv 2.8mm; IP67; Starlight						
IPC-HFW4831T-ASE-0280B	IP 8 megapixela dome IR D/N kamera; 1/2.5" 8MP progressive Starvis™ CMOS; Efektivni broj piksela 3840x2160; Osetljivost 0.06Lux/F1.6 (kolor), 0Lux (IC uključ.); Motorizovani IR Cut filter; Smart IR LE diode dometa 80m; Fiksni objektiv 2.8mm /F1.6; Vidni ugao od 112°; Opciono objektiv 4mm (vidni ugao 88°); H.265+ /H.265 /H.264+ /H.264 kompresija; Rezolucija do 4K/8MP (3840x2160); Do 15fps u 4K rezoluciji; Bit rate 24~10240Kbps; Triple stream; WDR 120dB; HLC; 3D DNR; ROI; Analitika - Tripwire, Intrusion, Abandoned/Missing Object, Face detect; Detekcija pokreta; Masking; IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, 802.1x; Alarmni ulaz/izlaz; Audio ulaz/izlaz; Micro SD slot (podržane kartice kapaciteta do 128GB); ONVIF, PSIA, CGI; IP67 i IK10 sertifikovana; Opseg radne temperature -30°C~60°C; Dimenzije 244.1mmx79mmx75.9mm; Masa 0.815kg; Napajanje PoE - IEEE802.3af ili 12VDC, 11W maks; ePoE Kompatibilna	€ 157,80	€ 263,00	  Na lageru		

IP Kamere; Eco-Savvy 3.0 serija ePoE

Kod	OPIS	VP	MSRP	Slika		
2 Megapixela IP CMOS True D/N IR bullet; Motor zum objektiv, auto-fokus, auto iris; Audio ulaz/izlaz; Alarmni ulaz/izlaz; Micro SD card slot; IP67						
IPC-HFW5231E-ZE	IP 2 megapixela bullet IR D/N kamera; 1/2.8" 2 Megapixel progressive Starvis™ CMOS; Efektivni broj piksela 1920x1080; Motorizovani zum objektiv 2.7mm~13.5mm (5x optički zoom, vidni ugao 101°~31°, F1.4); Automatski fokus; Automatski iris; Osetljivost 0.006Lux/F1.4 (kolor), 0Lux (IC uključ.); Smart IR LE diode dometa 50m; True day/night (ICR); True WDR (120dB); BLC; HLC; 3D DNR; Analitika - Tripwire, Intrusion, Abandoned/Missing; Face detection; H.265+/H.265/H.264+/H.264 kompresije; Triple stream; Podržane rezolucije do 1080P(1920x1080); Do 60fps u svim rezolucijama; HTTP; HTTPS; TCP; ARP; RTSP; RTP; UDP; SMTP; FTP; DHCP; DNS; DDNS; PPPOE; IPv4/v6; QoS; UPnP; NTP; Bonjour; 802.1x; Multicast; ICMP; IGMP; SNMP; ONVIF, PSIA, CGI; RJ-45 (10/100Base-T) Ethernet port; Audio ulaz/izlaz; Alarmna 2 ulaza/izlaza; Analogni video izlaz (BNC); Micro SD Slot, Max 128GB; Dim. 273.2 mm x 95mmx96.4mm; Masa 1.07kg; IP67 i IK10 sertifikati; Radna temp. -30°C~60°C; Napajanje 12VDC ili PoE (802.3af), 12.95W; ePoE kompatibilna	€ 166,20	€ 277,00	 2Mp 2.7-13.5mm Motor zum auto fokus SD CARD SLOT -30°C~60°C TRIPWIRE, INTRUSION, ABANDONED/MISSING, SCENE CHANGE, AUDIO & FACE DETECTION SMART ICR LED 50m 120dB WDR AUDIO IN/OUT Vandal IP 67 DC 12V PSE 2MP IP H. 265 ePoE ECO-SAVVY ONVIF Starlight	Na lageru	
2 Megapixela IP CMOS True D/N IR anti-vandal dome; motor zum objektiv, auto-fokus, auto iris; Audio ulaz/izlaz; Alarmni ulaz/izlaz; Micro SD card slot; IP67						
IPC-HDBW5231E-ZE	IP 2 megapixela anti-vandal dome IR D/N kamera; 1/2.8" 2 Megapixel progressive Starvis™ CMOS; Efektivni broj piksela 1920x1080; Motorizovani zum objektiv 2.7mm~13.5mm (5x optički zoom, vidni ugao 101°~31°, F1.4); Automatski fokus; Automatski iris; Osetljivost 0.006Lux/F1.4 (kolor), 0Lux (IC uključ.); Smart IR LE diode dometa 50m; True day/night (ICR); True WDR (120dB); BLC; HLC; 3D DNR; Analitika - Tripwire, Intrusion, Abandoned/Missing; Face detection; H.265+/H.265/H.264+/H.264 kompresije; Triple stream; Podržane rezolucije do 1080P (1920x1080); Do 60fps u svim rezolucijama; HTTP; HTTPS; TCP; ARP; RTSP; RTP; UDP; SMTP; FTP; DHCP; DNS; DDNS; PPPOE; IPv4/v6; QoS; UPnP; NTP; Bonjour; 802.1x; Multicast; ICMP; IGMP; SNMP; ONVIF, PSIA, CGI; RJ-45 (10/100Base-T) Ethernet port; Audio ulaz/izlaz; Alarmna 2 ulaza/izlaza; Analogni video izlaz (BNC); Micro SD Slot, Max 128GB; Dim. Ø159.1mmx117.9mm; Masa 0.95kg; IP67 i IK10 sertifikati; Radna temp. -30°C~60°C; Napajanje 12VDC/24VAC ili PoE (802.3af), 15W maks; ePoE kompatibilna	€ 166,20	€ 277,00	 2Mp 2.7-13.5mm Motor zum auto fokus SD CARD SLOT -30°C~60°C TRIPWIRE, INTRUSION, ABANDONED/MISSING, SCENE CHANGE, AUDIO & FACE DETECTION SMART ICR LED 50m 120dB WDR AUDIO IN/OUT Vandal IP 67 DC 12V PSE 2MP IP H. 265 ePoE ECO-SAVVY ONVIF Starlight	Na lageru	
4 Megapixela IP CMOS True D/N IR bullet; Motor zum objektiv, auto-fokus, auto iris; Audio ulaz/izlaz; Alarmni ulaz/izlaz; Micro SD card slot; IP67						
IPC-HFW5431E-ZE	IP 4 megapixela bullet IR True D/N kamera; 1/3" 4MP progressive scan CMOS; Efektivni broj piksela 2688x1520; Motorizovani zum objektiv sa automatskim fokusom i irisom, 2.7mm~13.5mm F1.4; Podesivi vidni ugao od 106°~31°; Automatski fokus; Automatski iris; Osetljivost 0.03Lux/F1.4 (kolor), 0Lux (IC uključ.); Smart IR LE diode dometa 50m; True day/night (ICR); True WDR (120dB); BLC; HLC; 3D DNR; Analitika - Tripwire, Intrusion, Scene change, Face detect; H.265+/H.265/H.264+/H.264 kompresija; Triple stream; Rezolucija do 4MP (2688x1520); Do 25/30fps u svim rezolucijama; Bit rate 16K ~ 10Mbps; Detekcija pokreta; Masking; IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour; ONVIF, PSIA, CGI; Micro SD slot (do 128GB); Audio ulaz/izlaz; 2x alarmni ulaz, 1x relejni izlaz; IP67 i IK10 sertifikovana; Opseg radne temperature -30°C~60°C; Dimenzije 273.2mmx95.0mmx95.0mm; Masa 1.11kg; Napajanje PoE - IEEE802.3af ili 12VDC, 12.95W maks; ePoE kompatibilna	€ 183,60	€ 306,00	 4Mp 2.7-13.5mm Motor zum auto fokus SD CARD SLOT Vandal IP 67 TRIPWIRE, INTRUSION, ABANDONED/MISSING, SCENE CHANGE, AUDIO & FACE DETECTION SMART ICR LED 50m 120dB WDR AUDIO IN/OUT IP 67 DC 12V PSE 4MP IP H. 265 ePoE ECO-SAVVY ONVIF	Na lageru	
4MP IP anti-vandal dome IC kamera; motor zum objektiv, auto-fokus, auto iris; Audio ulaz/izlaz; Alarmni ulaz/izlaz; Micro SD card slot; IP67						
IPC-HDBW5431E-ZE	IP 4MP WDR anti-vandal dome IC kamera; 1/3" 4MP progressive scan CMOS; Efektivni broj piksela 2688x1520; Osetljivost 0.03Lux/F1.4 (kolor), 0Lux (IC uključ.); Motorizovani IR Cut filter; IR LE diode dometa 50m; Motorizovani zum objektiv sa automatskim fokusom i irisom, 2.7mm~13.5mm F1.4; Podesivi vidni ugao od 106°~31°; H.265+/H.265/H.264+/H.264 kompresija; Rezolucija do 4MP (2688x1520); Do 25/30fps u svim rezolucijama; Bit rate 14~9984Kbps; Triple stream; WDR 120dB; HLC; 3D DNR; ROI; Analitika - Tripwire, Intrusion, Object Abandoned /Missing, Face detectio; Detekcija pokreta; Masking; HTTP; HTTPS; TCP/IP; ARP; RTSP; RTP; UDP; SMTP; FTP; DHCP; DNS; DDNS; PPPOE; IPv4/v6; QoS; UPnP; NTP; Bonjour; 802.1x; Multicast; ICMP; IGMP; SNMP; ONVIF, PSIA, CGI; Micro SD slot (do 128GB); Kompozitni video izlaz; Audio ulaz/izlaz; Alarmni ulaz/izlaz; IP67 i IK10 sertifikovana; Opseg radne temperature -30°C~60°C; Dimenzije Ø159mmx117.9mm; Masa 0.95kg; Napajanje PoE - (IEEE802.3at, Class 4) ili 12VDC/24VAC 15W; ePoE kompatibilna	€ 183,60	€ 306,00	 4Mp 2.7-13.5mm Motor zum auto fokus SD CARD SLOT Vandal IP 67 TRIPWIRE, INTRUSION, ABANDONED/MISSING, SCENE CHANGE, AUDIO & FACE DETECTION SMART ICR LED 50m 120dB WDR AUDIO IN/OUT IP 67 DC 12V PSE 4MP IP H. 265 ePoE ECO-SAVVY ONVIF	Na lageru	

IP Kamere; Eco-Savvy 3.0 serija ePoE

Kod	OPIS	VP	MSRP		Slika		
IP 6MP IC bullet kamera; Eco Savvy 3 ePoE serija; MZ AF 2.7-13.5mm objektiv; Audio i alarmni I/O; Micro SD card slot; IP67; IK10							
IPC-HFW5631E-ZE	IP 6MP bullet IC kamera; 1/2.9" 6MP Starvis™ progressive scan CMOS; Efektivni broj piksela 3072x2048; Motorizovani zum objektiv sa automatskim fokusom i irisom, 2.7mm~13.5mm F1.4; Podesivi vidni ugao od 91°~27° horizontalno; Automatski fokus; Automatski iris; Osetljivost 0.03Lux/F1.4 (kolor), 0Lux (IC uključ.); Smart IC LE diode dometa 50m; True day/night (ICR); True WDR (120dB); BLC; HLC; 3D DNR; ROI; Analitika - Tripwire, Intrusion, Object Abandoned/Missing, Face detection; H.265+/H.265 /H.264+ /H.264 kompresija; Triple stream; Rezolucija do 6MP (3072x2048); Do 20fps u PMP rezoluciji; Do 25/30fps u 4MP i nižim rezolucijama; Bit rate 16K ~ 10Mbps; Detekcija pokreta; Masking ;HTTP; HTTPS; TCP; ARP; RTSP; RTP; UDP; SMTP;FTP; DHCP; DNS; DDNS; PPPOE; IPv4/v6; QoS;UPnP;NTP; Bonjour; 802.1x; Multicast; ICMP; IGMP; SNMP ONVIF,PSIA,CGI; Micro SD slot (do 128GB); Audio ulaz/izlaz; 2x alarmni ulaz, 1x alarmni izlaz; IP67 i IK10 sertifikovana; Opseg radne temperature -30°C~60°C; Dimenzije 273.2mmx95.0mmx95.0mm; Masa 1.11kg; Napajanje PoE - IEEE802.3af ili 12VDC, 12.95W maks; ePoE kompatibilna	€ 207,00	€ 345,00		 H.265 Starlight ePoE ECO-SAVVY ONVIF	Na lageru	↓
IP 6MP IC bullet kamera; Eco Savvy 3 ePoE serija; MZ AF 2.7-13.5mm objektiv; Audio i alarmni I/O; Micro SD card slot; IP67; IK10							
IPC-HDBW5631E-ZE	IP 6MP anti-vandal dome IC kamera; 1/2.9" 6MP Starvis™ progressive scan CMOS; Efektivni broj piksela 3072x2048; Motorizovani zum objektiv sa automatskim fokusom i irisom, 2.7mm~13.5mm F1.4; Podesivi vidni ugao od 91°~27° horizontalno; Automatski fokus; Automatski iris; Osetljivost 0.03Lux/F1.4 (kolor), 0Lux (IC uključ.); Smart IC LE diode dometa 50m; True day/night (ICR); True WDR (120dB); BLC; HLC; 3D DNR; ROI; Analitika - Tripwire, Intrusion, Object Abandoned/Missing, Face detection; H.265+/H.265 /H.264+ /H.264 kompresija; Triple stream; Rezolucija do 6MP (3072x2048); Do 20fps u PMP rezoluciji; Do 25/30fps u 4MP i nižim rezolucijama; Bit rate 16K ~ 10Mbps; Detekcija pokreta; Masking ;HTTP; HTTPS; TCP; ARP; RTSP; RTP; UDP; SMTP;FTP; DHCP; DNS; DDNS; PPPOE; IPv4/v6; QoS;UPnP;NTP; Bonjour; 802.1x; Multicast; ICMP; IGMP; SNMP ONVIF,PSIA,CGI; Micro SD slot (do 128GB); Audio ulaz/izlaz; 2x alarmni ulaz, 1x alarmni izlaz; IP67 i IK10 sertifikovana; Opseg radne temperature -30°C~60°C; Dimenzije 273.2mmx95.0mmx95.0mm; Masa 1.11kg; Napajanje PoE - IEEE802.3af ili 12VDC, 12.95W maks; ePoE kompatibilna	€ 207,00	€ 345,00		 H.265 Starlight ePoE ECO-SAVVY ONVIF	Na lageru	↓
IP 2MPbox kamera; Eco Savvy 3 serija; 30X zum objektiv; Audio i alarmni I/O; Micro SD card slot; IP67; IK10							
SDZ2030S-N	2MP 30x Starlight Zoom Network kamera; 1/2.8" 2Megapixel Exmor R CMOS; Efektivni broj piksela 1920x1080; RAM/ROM - 512M/128M; Osetljivost 0.005Lux@F1.6 (kolor), 0.005Lux@F1.6 (c/b); Objektiv 4.5mm - 135mm, F1.6 - F4.4; Vidni ugao 67,8°-2,4°; 30x optički zoom, 16x digitalni zoom; IVS: Tripwire, Intrusion, Abandoned/Missing, Face Detection; Video kompresija H.265 /H.264 /MJPEG; Rezolucija 1080P(1920x1080)/ 1.3M(1280x960)/ 720P(1280x720)/ D1(704x576/704x480)/ CIF(352x288/352x240); Frame Rate: Main Stream 1080P/720P (1-50/60fps), 1.3M (1-25/30fps) - Sub Stream1 D1/CIF (1-25/30fps) - Sub Stream2 1080P/1.3M/720P/D1/ CIF (1 ~ 25/30fps); Bit Rate H.265/H.264: 448K ~ 8192Kbps, MJPEG: 5120K ~10240Kbps; BLC; HLC; WDR (120dB); Ultra DNR (2D/3D); Motion Detection; EIS; Defog; Masking do 24 zone; Audio kompresija G.711a/G.711mu/AAC/G.722 /G.726 /G.729 /MPEG2-L2; Ethernet RJ-45 (10/100Base-T); Protokol IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, 802.1x; ONVIF, PSIA, CGI; Micro SD slot (do 128GB); 1x RS485, 1x RS232; Audio ulaz/izlaz; 2x alarmni ulaz/1 izlaz; Kompozitni video izlaz (BNC); Napajanje DC12V/1.5A, PoE(802.3af); Potrošnja 10W; Radna temperatura -40°C do 70°C; Dimenzije 160x70x70mm; Masa 1kg		€ 716,00		 NEW H.265 Starlight ePoE ONVIF	Novo! Na lageru	

IP Kamere; Ultra serija

Kod	OPIS	VP	MSRP		Slika		
Bullet 3MP WDR, sa analitikom, 3X zoom, IR 50m, audio in/out, alarm in/out, analog out, SD card slot							
IPC-HFW8331E-Z	3MP IR bullet WDR Smart kamera; 1/2.8" 3 Megapixel progressive scan STARVIS CMOS; Broj efektivnih piksela: 2048x1536; Motorizovani zum 2.7mm~13.5mm (5x optički zoom, vidni ugao 101°~31°, F1.4); Automatski fokus; Automatski iris; Osetljivost 0.005Lux/F1.4 (kolor), 0Lux (IC uključ.); Smart IR LE diode dometa 50m; True day/night (ICR); WDR (140dB); HLC; 3D DNR; Defog; EIS: Analitika - Tripwire, Intrusion, Missing/Abandoned, Face detect; People counting; Heat Map; H.265+/H.265/H.264+/H.264 kompresija; Triple stream; Podržane rezolucije 3MP(2048x1536) / 1080P(1920x1080) / 1.3M(1280x960) / 720P(1280x720) / D1(704x576/704x480) / VGA(640x480)/ CIF (352x288 /342x240); Do 60fps u svim rezolucijama; HTTP; HTTPS; TCP; ARP; RTSP; RTP; UDP; SMTP; FTP; DHCP; DNS; DDNS; PPPOE; IPv4/v6; QoS; UPnP; NTP; Bonjour; 802.1x; Multicast; ICMP; IGMP; SNMP; ONVIF, PSIA, CGI; RJ-45 (100/1000Base-T) Ethernet port; Audio ulaza/izlaz; Alarm 2 ulaza/1 izlaz; Micro SD slot (do 128GB); Dimenzije 273.2mm x 95mm x 96.4mm; Masa 1.12kg; IP67 i IK10 sertifikati; Opseg radne temperature -40°C~60°C; Napajanje DC12V/13W, PoE+ (802.3at Class 4)	€ 315,00	€ 525,00		 H. 265 Starlight	Na lageru	
Dome 3MP WDR, sa analitikom, 3X zoom, IR 50m, audio in/out, alarm in/out, analog out, SD card slot							
IPC-HDBW8331E-ZH	IP 3 megapixels WDR anti-vandal IR True D/N kamera; 1/2.8" 3MP progressive scan Starvis CMOS; Efektivni broj piksela 2048x1536; Osetljivost 0.005Lux/F1.4 (kolor), 0Lux (IC uključ.); Motorizovani IR Cut filter; IR LE diode dometa 50m; Motorizovani zum objektiv sa automatskim fokusom i irisom, 2.7mm~12mm F1.4; Podesivi vidni ugao od 87°~31°; H.265/H.264/MJPEG kompresija; Rezolucija do 3M (2048x1536); Do 30fps u svim rezolucijama; Bit rate 40K ~ 10Mbps; Triple stream; WDR 140dB; HLC; BLC; 3D DNR; ESI; ROI; Analitika - Tripwire, Intrusion, Scene change, Missing/Abandoned; Audio detect; Face detect; Intelligent function; People counting; Heat map; Masking; IPv4/IPv6, HTTP; HTTPS; SSL; TCP/IP; UDP; UPnP; ICMP; IGMP; SNMP; RTSP; RTP; SMTP; NTP; DHCP; DNS; PPPOE; DDNS; FTP; IP Filter; QoS; Bonjour; ONVIF,PSIA,CGI; Micro SD slot (do 128GB); Kompozitni video izlaz; Audio ulaz/izlaz; 2x Alarmni ulaz, 1x relejni izlaz; IP67 i IK10 sertifikati; Opseg radne temperature -40°C~60°C; Dimenzije Ø159mmx117.9mm; Masa 0.96kg; Napajanje PoE+(802.3at Class 4) ili 12VDC/24VAC 18W	€ 315,00	€ 525,00		 H. 265 Starlight	Na lageru	
Bullet 3MP WDR, sa analitikom, 5X zoom, IR 100m, audio in/out, alarm in/out, analog out, SD card slot							
IPC-HFW8331E-ZS	3MP IR bullet WDR kamera; 1/2.8" 3 Megapixel progressive scan STARVIS CMOS; Broj efektivnih piksela 2048x1536; Motorizovani zum objektiv sa automatskim fokusom i irisom, 7mm~35mm F1.4; Podesivi vidni ugao od 32°~11°; Osetljivost 0.005Lux/F1.4 (kolor), 0Lux (IC uključ.); Smart IR LE diode dometa 100m; True day/night (ICR); WDR (140dB); HLC; BLC; 3D DNR; Defog; EIS: Analitika - Tripwire, Intrusion, Missing/Abandoned, Face detect; People counting; Heat Map; H.265+/H.265/H.264+/H.264 kompresija; Triple stream; Podržane rezolucije 3MP(2048x1536) / 1080P(1920x1080) / 1.3M (1280x960) / 720P(1280x720) / D1 (704x576 /704x480) / VGA (640 x480) / CIF (352x288 /342x240); do 60fps u svim rezolucijama; HTTP; HTTPS; TCP; ARP; RTSP; RTP; UDP; SMTP; FTP; DHCP; DNS; DDNS; PPPOE; IPv4/v6; QoS; UPnP; NTP; Bonjour; 802.1x; Multicast; ICMP; IGMP; SNMP; ONVIF, PSIA, CGI; RJ-45 (100/1000Base-T) Ethernet port; Audio ulaz/izlaz; Alarm 2 ulaza/1 izlaz; Micro SD slot (do 128GB); Dimenzije 273.2mm x 95mm x 96.4mm; Masa 1.12kg; IP67 i IK10 sertifikati; Opseg radne temperature -40°C~60°C; Napajanje DC12V/13W, PoE+ (802.3at Class 4)	€ 332,00	€ 553,33		 H. 265 Starlight	Na lageru	
Bullet 12MP, 4X zoom, IR 50m, audio in/out, alarm in/out, analog out, SD card slot							
IPC-HFW81230E-ZE	12MP (4K real time) IR bullet kamera; 1/1.7" 12 Megapixel Exmor CMOS 4000(H)x3000(V); Motorizovani zum 4.1mm~16.4mm (4x optički zoom, vidni ugao 85°~35°, F1.53); Automatski fokus; Osetljivost 0.02Lux/F1.53 (kolor), 0Lux (IC uključ.); Smart IR LE diode dometa 50m; True day/night (ICR); SSA; DWDR; HLC; 3D DNR; ROI; Defog; EIS; Analitika - Tripwire, Intrusion, Object Abandoned/Missing; Napredna analitika: Face Detection, People Counting, Heat Map; H.265/H.264 kompresija; Triple stream; Podržane rezolucije do 12MP(4000x3000); Do 20fps u 12MP; Do 25fps u 4K i nižim rezolucijama; HTTP; HTTPS; TCP; ARP; RTSP; RTP; UDP; SMTP; FTP; DHCP; DNS; DDNS; PPPOE; IPv4/v6; QoS; UPnP; NTP; Bonjour; 802.1x; Multicast; ICMP; IGMP; SNMP; ONVIF, PSIA, CGI; RJ-45 (10/100Base-T) Ethernet port; Audio ulaz/izlaz; Alarmni ulaz/izlaz; Micro SD Slot, Max 128GB; Dim. 273.2 x 95.0 x 96.4mm; Masa 1.12kg; IP67; Radna temp. -40°C~60°C; Napajanje DC12V/13W, PoE (802.3at, Class 4)		€ 782,00		 H. 265 ONVIF	Uskoro	

Panoramske kamere

Kod	OPIS	VP	MSRP	Slika		
Panoramska IP kamera 5MP sa mikrofonom, SD card slotom i Heat Map funkcijom						
IPC-EB5531	Panoramska kamera 5MP; 1/2.7" 5MP progressive scan CMOS; Megapixel objektiv 1.4mm F1.6; Osetljivost 0.02Lux/F1.6 (kolor), 0.05Lux/F2.6 (C/B); Day/night (Soft.); True WDR 120dB; HLC; BLC; 3D DNR; ROI; H.265+/H.265/H.264+/H.264 kompresija; Dual stream; Podržane rezolucije do 5M(2592x1944); Frame rate do 25 fps u 5MP, do 30fps u 3M i nižim rezolucijama; Micro SD slot (do 128GB); Inkorporiran mikrofoni; IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour; ONVIF,PSIA,CGI; IP67 i IK08 sertifikovana; Opseg radne temperature -30°C~60°C; Dimenzije Φ110mmx56mm; Masa 0.38kg; Napajanje PoE - IEEE802.3af ili 12VDC/3.4W	€ 142,20	€ 237,00			Na lageru
Panoramska IP kamera 6MP, IR 10m, IP67, SD card slotom i Heat Map funkcijom						
IPC-EBW8630	Panoramska kamera 6MP; 1/1.8" 6MP progressive scan STARVIS CMOS; Megapixel objektiv 1.7mm F2.0; Osetljivost 0.002Lux/F2.0, 0Lux IC uključ; Smart IC LED dometa 10m; True day/night (ICR); DWDR; HLC; BLC; 3D DNR; H.265/H.264 kompresija; Triple stream; p modova rada + 4 VR moda; Podržane rezolucije 6M(3072x2048)/CIF(352x240); Frame rate do 25/30fpsu svim rezolucijama; Micro SD slot (do 128GB); Audio ulaz/izlaz, Ugrađen mikrofoni; Alarmni 2 ulaza/2 izlaza; HTTP; HTTPS; TCP; ARP; RTSP; RTP; UDP; SMTP; FTP; DHCP; DNS; DDNS; PPPOE; IPv4/v6; QoS; UPnP; NTP; Bonjour; 802.1x; Multicast; ICMP; IGMP; SNMP; ONVIF, PSIA, CGI IP67 i IK10 sertifikovana; Opseg radne temperature -30°C~60°C; Dimenzije Φ149.8mmx50.7mm; Masa 0,58kg; Napajanje PoE - IEEE802.3af ili 12VDC/12W	€ 400,00	€ 666,67			Na lageru
Panoramska IP kamera 12MP, IR 10m, IP67, SD card slotom i Heat Map funkcijom						
IPC-EBW81230	Panoramska kamera 12MP; 1/1.7" 12MP progressive scan STARVIS CMOS; Megapixel objektiv 1.98mm F2.8; Osetljivost 0.001Lux/F2.8, 0Lux IC uključ; Smart IC LED dometa 10m; True day/night (ICR); DWDR; HLC; BLC; 3D DNR; H.265/H.264 kompresija; Triple stream; 9 modova rada + 4 VR moda; Podržane rezolucije 12M(4000x3000)/CIF(352x240); Frame rate 12MP 1~25fps/1080P/(1 ~ 25/30fps); Micro SD slot (do 128GB); Audio ulaz/izlaz; Alarmni 2 ulaza/2 izlaza; HTTP; HTTPS; TCP; ARP; RTSP; RTP; UDP; SMTP; FTP; DHCP; DNS; DDNS; PPPOE; IPv4/v6; QoS; UPnP; NTP; Bonjour; 802.1x; Multicast; ICMP; IGMP; SNMP; ONVIF, PSIA, CGI IP67 i IK10 sertifikovana; Opseg radne temperature -30°C~60°C; Dimenzije Φ149.8mmx47.7mm; Masa 0,58kg; Napajanje PoE - IEEE802.3af ili 12VDC/12W	€ 391,80	€ 653,00			Na lageru

AI IP KAMERE

Kod	OPIS	VP	MSRP	Slika			
2X 1.3MP kamera za brojanje posetilaca							
IPC-HD4140X-3D	AI IP kamera za brojanje posetilaca; 2X 1/3" 1.3MP progressive scan Starvis™ CMOS; 2.1mm F2.2 objektiv, vidni ugao 109.5° horizontalno; 2.8mm objektiv opciono, vidni ugao 89° horizontalno; Podržava brojanje nakon prelaska definisane linije i regionalno brojanje uz filter protiv "motanja u sceni" i visinski filter; H.265+ /H.264+ /H.265 /H.264 /H.264B /MJPEG kompresija; Triple stream; Podržane rezolucije 1.3M(1280x960) /720P(1280x720)/ D1(704x576/704x480) / VGA(640x480); Do 25/30fps u punoj rezoluciji; Bitrate (H.265) 512~ 3072Kbps; Elektronski D/N; BLC / HLC /DWDR; 3D DNR; ROI; Masking; RJ-45 (10/100Base-T) mrežni port; Ugrađen mikrofoni; RS485 port; Alarmni ulaz/izlaz; HTTP; HTTPS; TCP; ARP; RTSP; RTP; UDP; RTCP; SMTP; FTP; DHCP; DNS; DDNS; PPPOE; IPv4/v6; QoS; UPnP; NTP; Bonjour; IEEE 802.1x; Multicast; ICMP; IGMP; SNMP; TLS; ONVIF Profile S&G, API; Metalno kućište; IP54 stepen zaštite; Radna temperatura -10°C ~ +45°C; Dimenzije 162.1mm x76mm x37.8mm; Masa 0.3kg; Napajanje 12VDC ili PoE (IEEE 802.3af, Class 0); CE (EN 60950:2000)		€ 431,00	2x1.3Mp PEOPLE COUNTING D-WDR 3D DNR SOFTEN SD CARD SLOT AUDIO IN/OUT Alarm in/out DC 12V PoE ONVIF	Na lageru		

AI IP KAMERE

Kod	OPIS	VP	MSRP		Slika		
2MP danti-vandal dome IC kamera; AI serija							
IPC-HDBW8241E-Z	IP 2MP AI anti-vandal dome IC kamera; 1/2.8" progressive scan CMOS; Efektivni broj piksela 1920x1080; Osetljivost 0.006Lux/F1.6 (kolor), 0Lux (IC uključ.); Motorizovani IR Cut filter; IR LE diode dometa 50m; Motorizovani zum objektiv sa automatskim fokusom i irisom, 2.7mm~13.5mm F1.6; Podesivi vidni ugao od 107°~32° horizontalno; H.265 /H.264 /H.264B /H.264H /MJPEG(sub stream) kompresija; Rezolucija do 1080P; Do 50/60fps u svim rezolucijama; Bit rate 14 ~ 10240Kbps; Triple stream; WDR 140dB; HLC; BLC; 3D DNR; EIS; ROI; AI People counting funkcije: Line crossing people counting, Region people counting, Loitering filter; AI Perimeter Protection fukcije: Tripwire, Intrusion (Human &Vehicle classification); HTTP; HTTPS; TCP; ARP; RTSP; RTP; UDP; RTCP; SMTP; FTP; DHCP; DNS; DDNS; PPPOE; IPv4/v6; QoS; UPnP; NTP; Bonjour; IEEE 802.1x; Multicast; ICMP; IGMP;SNMP;TLS; ONVIF, API; Micro SD slot (do 128GB); Kompozitni video izlaz; Audio ulaz/izlaz; Alarmni ulaz/izlaz; IP67 i IK10 sertifikati; Opseg radne temperature -30°C~60°C; Dimenzije Φ159.1mm ×117.9mm; Masa 1.06kg; Napajanje PoE+ (802.3at Class 4) ili 12Vdc/24VAc 16.4W; CE (EN 60950:2000)		€ 580,00			Novo! Na lageru	
2X 3MP kamera za brojanje posetilaca							
IPC-HDW8341X-3D	AI IP kamera za brojanje posetilaca; 2X 1/2.8" 3MP progressive scan Starvis™ CMOS; 2.8mm F1.8 objektiv, vidni ugao 106.31° horizontalno; 3.6mm objektiv opciono, vidni ugao 78.5° horizontalno; Smart IC LE diode dometa 10m; Osetljivost 0.009Lux/F1.8 (Color,1/3s,30IRE), 0.08Lux/F1.8 (Color,1/30s,30IRE), 0Lux (IC uključ.); Podržava brojanje nakon prelaska definisane linije i regionalno brojanje uz filter protiv "motanja u sceni" i visinski filter; H.265+ /H.264+ /H.265 /H.264H /MJPEG kompresija; Triple stream; Podržane rezolucije 3MP(2048x1536)/ 1080P(1920x1080)/ 1.3M(1280x960)/ 720P(1280x720)/ D1(704x576/704x480) / VGA(640x480)/ CIF(352x288/342x240); Do 25fps u punoj rezoluciji; Bitrate (H.265) 80~ 6144Kbps; True D/N (ICR); BLC / HLC /DWDR; 3D DNR; ROI; Masking; RJ-45 (100/1000Base-T) mrežni port; Ugrađen mikrofoni; 2x Alarmni ulaz/2x izlaz; 2x audio ulaz/1 audio izlaz; HTTP; HTTPS; TCP; ARP; RTSP; RTP; UDP; RTCP; SMTP; FTP; DHCP; DNS; DDNS; PPPOE; IPv4/v6; QoS; UPnP; NTP;Bonjour; IEEE 802.1x; Multicast; ICMP; IGMP; SNMP; TLS; ONVIF Profile S&G, API; Metalno kućište; IP67 stepen zaštite; Radna temperatura -30°C ~ +60°C; Dimenzije 204mmx78mmx62mm; Masa 0.8kg; Napajanje 12Vdc ili PoE (IEEE 802.3af, Class 0); CE (EN 60950:2000)		€ 798,00			Na lageru	
Kamera za prepoznavanje lica							
IPC-HF8242F-FR	AI IP box kamera za prepoznavanje lica; 1/1.8" Starvis™ 2MP progressive scan CMOS; Osetljivost 0.001Lux/F1.2 (kolor,1/3s,30IRE), 0.0005Lux/F1.2 (C/B,1/3s,30IRE); C/CS Mount; Prepoznavanje lica sa do 5 baza sa do 10.000 fotografija; Prepoznavanje do 6 atributa (godine, pol, raspoloženje, naočare, maska, brkovi); H.265+ /H.264+ /H.265 /H.264H /MJPEG kompresija; Triple stream; Podržane rezolucije 1080P(1920x1080)/ 1.3M(1280x960)/ 720P(1280x720)/ D1(704x576/704x480) / VGA(640x480)/ CIF(352x288/342x240); Do 50/60fps u punoj rezoluciji; Bitrate (H.265) 14~ 6144Kbps; True D/N (ICR); BLC / HLC / WDR 120dB / SSA; 3D DNR; ROI; EIS; Defog; Masking; RJ-45 (100/1000Base-T) mrežni port; Ugrađen mikrofoni; 2x Alarmni ulaz/2x izlaz; 2x audio ulaz/1 audio izlaz; 12Vdc 165mA izlaz; RS485 port; Analogni video izlaz; HHTTP; HTTPS; TCP; ARP; RTSP; RTP; UDP; RTCP; SMTP; FTP; DHCP; DNS; DDNS; PPPOE; IPv4/v6; QoS; UPnP; NTP; Bonjour; IEEE 802.1x; Multicast; ICMP; IGMP; SNMP; TLS; ONVIF Profile S&G, API; Dimenzije 161.6mm x85.5mm x74.0mm; Masa 0.8kg; Masa 0.78kg; Napajanje 12Vdc/24VAc ili PoE (IEEE 802.3af, Class 0), 10W; Bez Objektiva; CE (EN 60950:2000)		€ 1.270,00			Na lageru	
PLZ20C0-D	Auto-iris (DC) objektiv; Za kamere rezolucije do 12MP; 1/1.7"; F1.5; CS Mount; Ručni fokus; Ručni zum; Podesivi vidni ugao 109°(horizontalno) do 28.5°(H); Dimenzije φ54mmx82.8mm; Masa 270g	€ 111,00	€ 185,00				

AI IP KAMERE

Kod	OPIS	VP	MSRP	Slika		
Kamera za prepoznavanje registarskih tablica						
ITC237-PW1B-IRZ	IP 2MP ANPR IC kamera; Ugrađen ANPR algoritam; Podržava prepoznavanje i snapshot registarske tablice, overview snapshot i snimanje; Ugrađena Bela lista sa do 10.000 unosa; Rele za kontrolu rampe/barijere; Ulaz za okidanje prepoznavanja induktivnom petljom; Okidanje video detekcijom; Podržava prepoznavanje sa distance 3~8m u jednoj traci; 1/2.8" 2MP progressive scan Starvis™ CMOS; Efektivni broj piksela 1920x1080; Motorizovani zum objektiv 2.7mm~12mm (4.4x optički zoom, vidni ugao 101°~36° horizontalno, F1.6); Automatski fokus; Osetljivost 0.005Lux/F1.6 (kolor), 0Lux (IC uključ.); Smart IR LE diode dometa 3~8m; True day/night (ICR); True WDR (140dB); BLC; HLC; 3D DNR; H.265 /H.264M /H.264H /H.264B /MJPEG kompresije; Dual stream; Podržane rezolucije do 1080P (1920x1080); Do 25/30fps u svim rezolucijama; IPv4/IPv6, HTTP, TCP/IP, UDP, NTP, DHCP, DNS; ONVIF, CGI, SDK; RJ-45 (100/1000Base-T) Ethernet port; Audio ulaz/izlaz; 2 alarmna ulaza/izlaza; Analogni video izlaz (BNC); Micro SD Slot (maks. 64GB); Dim. 273.3mm × 94.8mm ×94.8mm; Masa 1.12kg; IP67 i IK10 sertifikati; Radna temp. -40°C~60°C; Napajanje 12VDC ili PoE (802.3af), 12W maks		€ 599,00			Na lageru
AI Kamera za prepoznavanje registarskih tablica						
ITC215-PW4I-IRLZF27135	AI IP bullet kamera za prepoznavanje registarskih tablica; 1/2.8" 2MP progressive scan CMOS; Osetljivost 0.005Lux/F1.3 (kolor), 0Lux (IC uključ.); IC LE diode dometa do 12m; Motorizovani zum objektiv 2.7-13.5mm F1.3 (5X optički zum), automatski fokus, automatski (DC) iris; Podesivi vidni ugao 119°~ 32° horizontalno; Prepoznavanje registarskih tablica sa daljine 3~8m; Deep Learning algoritam za prepoznavanje u samoj kameri; Sa podrškom za detekciju i klasifikaciju vozila (veličina, boja) i smeru kretanja; Snapshot registarske tablice, overview snapshot i snimanje; Ugrađena Bela lista sa do 10.000 unosa; Rele za kontrolu rampe/barijere; Ulaz za okidanje prepoznavanja induktivnom petljom; Podržava i okidanje video detekcijom; True day/night (ICR); True WDR; 3D DNR; H.265/H.264M/H.264H/H.264B kompresije; Dual stream; Podržane rezolucije do 1080P (1920x1080); Do 25/30fps u svim rezolucijama; IPv4/IPv6, HTTP, TCP/IP, UDP, NTP, DHCP, DNS; ONVIF, CGI, SDK; RJ-45 (100/1000Base-T) Ethernet port; Audio ulaz/izlaz; 2 RS485 porta; 3 alarmna ulaza/izlaza; Micro SD Slot (maks. 64GB); Dim. 297mm × 124mm ×108mm; Masa 1.9kg; IP67 sertifikati; Radna temp. -30°C~65°C; Napajanje 12VDC ili PoE +(802.3at), 24W maks; CE		€ 650,00			Na lageru
Termalna + IP / hibridna bullet kamera						
TPC-BF2120	Termalna mini hibridna bullet kamera Termalna kamera: Uncooled VOx Microbolometer rezolucije 160(H)x120(V); Veličina piksela 12um; Termalna osetljivost (NETD) <50mK@f/1.1; Spektralni opseg 7~14um; Podešavanje Brightness /Sharpness /ROI /AGC /FFC/3D DNR; 14 paleta prikaza (Whitehot /Blackhot /Ironrow /Icefire /Fusion /Rainbow /Globow /Iconbow1 /Iconbow2, ...); Objektiv 1mm; Vidni ugao H: 56° /V: 44°; 2MP kamera vidljivi spektar: 1/2.8" 2MP CMOS; 1944(H) x1092(V) piksela; Osetljivost 0.005Lux@F1.8 (kolor), 0.0005Lux@F1.8 (C/B); 0Lux (IC uključ.); IC dometa 35m; Fiksni objekti 4mm F2.1; Vidni ugao H: 86.2° /V: 45.9°; True D/N (ICR); BLC/HLC/WDR; ROI; Ultra DNR; Defog; H.264/MJPEG kompresija; Glavni stream za termalnu kameru 1280x960 (default)/720P@1~25/30fps; Glavni stream za 2MP kameru: 1080P (default)/720P@1~25/30fps; Bit Rate CBR/VBR, 640 ~ 8192Kbps; Tripwire, Intrusion, Object Abandon/Missing, Fire detection & alarm, Image Fusion; RJ-45 (10/100Base-T) mrežni port; Pv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPoE, DDNS, FTP, IP Filter, QoS, Bonjour, 802.1x; ONVIF Profile S & G, PSIA, CGI; Audio ulaz/izlaz; 2x Alarmni ulaz/1x izlaz; Kompozitni video izlaz (BNC); RS485; IP67; Napajanje 12Vdc/PoE do 12W; Metalno kućište; Dimenzije 238.6mm × 90.4mm× 90.4mm; Masa 1kg;		€ 1.280,00			Na lageru

IP PTZ i Speed dome kamere

Kod	OPIS	VP	MSRP		Slika	
2MP mini PTZ dome kamera; Lite serija; 4x zoom;						
SD22204T-GN	IP 2MP 4X zoom PTZ kamera; 1/2.7" Progressive scan CMOS; Inkorporiran motor zoom auto fokus objektiv f=2.7mm(Wide)~11mm(Tele), F1.6~F2.8 (vidni ugao 112.5°~30°); Digitalni zoom do 16x; Osetljivost 0.05Lux@F1.6 (Color), 0.005Lux/F1.6(B/W); True Day/Night - mot. IR Cut filter; H.264+ / H.264 / MJPEG kompresija; Podržane rezolucije 2M/ 720P / D1 / CIF; Frame rate do 25fps u 1080P, do 50fps u 720P; Triple stream; True WDR 120dB; HLC; BLC; 2D i 3D DNR; Defog; ROI; Bit rate 448K ~ 8192Kbps; Micro SD card slot - do 128GB; RJ-45 (10/100Base-T) mrežni port; 300 programabilnih preset-a, 5 grupa, 8 tura; Masking (do 24 zone); Onvif Profile S; Brzina horizont. rotacije 100°/s maks, opseg 0° ~ 355°; 3D pozicioniranje; Dimenzije Ø122mm x 89mm; Masa 0.66kg; IP66 stepen zaštite; IK10 otpornost; Radna temperatura od -30°C do +60°C; Potrebno napajanje 12VDC/10W ili PoE	€ 120,60	€ 201,00			Na lageru
2MP mini PTZ dome kamera; Lite serija; 4x zoom; Sa IC LE diodama 30m; Inkorporiran mikrofoni						
SD29204T-GN	IP 2MP 4X zoom PTZ IC kamera; 1/2.7" Progressive scan CMOS; Inkorporiran motor zoom auto fokus objektiv f=2.7mm(Wide)~11mm(Tele), F1.6~F2.8 (vidni ugao 112.5°~39°); Digitalni zoom do 16x; Osetljivost 0.05Lux@F1.6 (Color), 0.005Lux/F1.6(B/W), 0Lux (IR On); True Day/Night - mot. IR Cut filter; IC LE diode dometa cca. 30m; Inkorporiran mikrofoni; H.264+ / H.264 / MJPEG kompresija; Podržane rezolucije 2M/ 720P / D1 / CIF; Frame rate do 25fps u 1080P, do 50fps u 720P; Dual stream; True WDR 120dB; HLC; BLC; 2D i 3D DNR; ROI; Defog; Bit rate 448K-8Mbps; Micro SD card slot - do 64GB; RJ-45 (10/100Base-T) mrežni port; 300 programabilnih preset-a, 5 grupa, 8 tura; Masking (do 24 zone); Onvif Profile S; Brzina horizontalne rotacije 100°/s maks, opseg 0° ~ 355°; 3D pozicioniranje; Dimenzije Ø132.7mm x 116.5mm; Masa 0.95kg; Radna temperatura od -30°C do +60°C; Potrebno napajanje 12VDC/13W ili PoE	€ 157,20	€ 262,00			Na lageru
2MP Speed dome kamera; Lite serija; 12x zoom; IP67; IK10; Starlight						
SD40212T-HN	IP 2MP 12X zoom speed dome kamera; 1/2.8" progressive scan Starvis CMOS; Inkorporiran motor zoom auto fokus objektiv f=5.3mm(Wide)~64mm(Tele), F1.6~F4.4 (vidni ugao 58.2°~64°); Digitalni zoom do 16x; Osetljivost 0.005Lux/F1.6(color), 0.0005Lux@F1.6 (B/W); True Day/Night (IRC); H.265+/H.265/H.264+/H.264 kompresija; Podržane rezolucije 1080P/720P/D1/CIF; Frame rate do 25/30fps za 1080p rezoluciju; Triple stream; True WDR 120dB; HLC; BLC; 2D i 3D DNR; ROI; Defog; EIS; Analitika - Tripwire, Intrusion, Abandoned/Missing Object Detection, Face Detection; Auto Tracking; Bit rate 448K ~ 8192Kbps; Micro SD card slot - 256GB maks.; 2 alarmna ulaza/1 relejni izlaz; RJ-45 (10/100Base-T) mrežni port; Audio ulaz/izlaz; 300 preset-a, 8 grupa, 5 tura, 5 Swing-a; Masking (do 24 zone); Brzina horizontalne rotacije 500°/s maks; 3D pozicioniranje; U IP66 kućištu sa grejačem i ventilatorom; IK10; Dimenzije Ø186(mm) x 234(mm); Masa 2.3kg; Radna temp. od -40°C do +60°C; Napajanje 24VAC/1.5A ili PoE+; Sa zidnim nosačem i transformatorom	€ 258,60	€ 431,00			Na lageru
2MP Speed dome kamera; Lite serija; 25x zoom; IP66; Sa IC LE diodama dometa 100m; Sa analitikom; Starlight						
SD49225T-HN	IP 2MP 25X zoom speed dome IC kamera; 1/2.8" progressive scan Exmor R CMOS; Inkorporiran motor zoom auto fokus objektiv f=4.8mm(Wide)~120.0mm(Tele), F1.6~F4.4 (vidni ugao 59.1°~2.4°); Digitalni zoom do 16x; Osetljivost 0.005Lux/F1.6(color); 0Lux IR On; IC LE diode dometa do 100m; True Day/Night (IRC); H.265 / H.264 / MJPEG kompresija; Podržane rezolucije 1080P/720P/D1/CIF; Frame rate do 50fps za 1080p rezoluciju; Do 50fps za 720p rezoluciju; Triple stream; True WDR 120dB; HLC; BLC; 2D i 3D DNR; ROI; Defog; Analitika - Tripwire, Intrusion, Abandoned/Missing Object Detection, Face Detection; Bit rate 448K ~ 8192Kbps; Micro SD card slot - 128GB maks.; 2 alarmna ulaza/1 relejni izlaz; RJ-45 (10/100Base-T) mrežni port; Audio ulaz/izlaz; 300 preset-a, 8 grupa, 5 tura, 5 Swing-a; Masking (do 24 zone); Brzina horizontalne rotacije 240°/s maks; 3D pozicioniranje; U IP66 kućištu sa grejačem i ventilatorom; Dimenzije 160mm (Ø) x 295mm (V); Masa 4kg; Radna temp. od -40°C do +70°C; Potrebno napajanje 12Vdc/3A ili PoE+; Sa zidnim nosačem	€ 297,00	€ 495,00			Na lageru

IP PTZ i Speed dome kamere

Kod	OPIS	VP	MSRP		Slika		
2MP Speed dome kamera; Pro serija; 25x zoom; IP67; IK10; Sa analitikom; Starlight; Auto Tracking							
SD50225U-HNI	IP 2MP 25X zoom speed dome kamera; 1/2.8" progressive scan Exmor R CMOS; Inkorporiran motor zoom auto fokus objektiv f=4.8mm(Wide)~120.0mm(Tele), F1.6~F4.4 (vidni ugao 59.1°~2.4°); Digitalni zoom do 16x; Osetljivost 0.005Lux/F1.6(color), 0.0005Lux@F1.6 (B/W); True Day/Night (IRC); H.265 /H.264 /MJPEG kompresija; Podržane rezolucije 1080P/720P/D1/CIF ; Frame rate do 50fps za 1080p rezoluciju; Do 50fps za 720p rezoluciju; Triple stream; True WDR 120dB; HLC; BLC; 2D i 3D DNR; ROI; Defog; EIS; Analitika - Tripwire, Intrusion, Abandoned/Missing Object Detection, Face Detection; Auto Tracking; Bit rate 448K ~ 8192Kbps; Micro SD card slot - 128GB maks.; 2 alamna ulaza/1 relejni izlaz; RJ-45 (10/100Base-T) mrežni port; Audio ulaz/izlaz; 300 preset-a, 8 grupa, 5 tura, 5 Swing-a; Masking (do 24 zone); Brzina horizontalne rotacije 500°/s maks; 3D pozicioniranje; U IP67 kućištu sa grejačem i ventilatorom; IK10; Dimenzije Φ186(mm) x 253(mm); Masa 2.5kg; Radna temp. od -40°C do +60°C; Napajanje 24VAc/1.5A ili PoE+ ; Sa zidnim nosačem i transformatorom	€ 304,20	€ 507,00			Na lageru	
2MP Speed dome kamera; Pro serija; 25x zoom; IP66; Sa IC LE diodama dometa 150m; Sa analitikom; Starlight; Auto Tracking							
SD59225U-HNI	IP 2MP 25X zoom speed dome IC kamera; 1/2.8" progressive scan Exmor R CMOS; Inkorporiran motor zoom auto fokus objektiv f=4.8mm(Wide)~120.0mm(Tele), F1.6~F4.4 (vidni ugao 59.2°~2.4°); Digitalni zoom do 16x; Osetljivost 0.005Lux/F1.6(color); 0Lux IR On; IC LE diode dometa do 150m; True Day/Night (IRC); H.265/H.264/MJPEG kompresija; Podržane rezolucije 1080P/1.3MP/720P/D1/CIF ; Frame rate do 50fps za sve rezolucije; Triple stream; WDR 120dB; HLC; BLC; 2D i 3D DNR; ROI; DIS; Defog; Analitika - Tripwire, Intrusion, Abandoned/Missing Object Detection; Auto Tracking; Bit rate 32K-8Mbps; Micro SD card slot - 128GB maks.; 2 alamna ulaza/1 relejni izlaz; RJ-45 (10/100Base-T) mrežni port; Audio ulaz/izlaz; 300 preset-a, 8 grupa, 5 tura, 5 Swing-a; Masking (do 24 zone); Brzina horizontalne rotacije 400°/s maks; 3D pozicioniranje; U IP66 kućištu sa grejačem i ventilatorom; Dimenzije 186mm (Φ) x 309mm (V); Masa 3.5kg; Radna temp. od -40°C do +70°C; Sa zidnim nosačem; Sa napajanjem 230VAc/24VAc; Prihvata i PoE + napajanje;	€ 369,60	€ 616,00			Na lageru	
2MP Speed dome kamera; Pro serija; 30x zoom; IP66; Sa IC LE diodama dometa 150m; Sa analitikom; Starlight; Auto Tracking							
SD59230U-HNI	IP 2MP 30X zoom speed dome IC kamera; 1/2.8" progressive scan Exmor R CMOS; Inkorporiran motor zoom auto fokus objektiv f=4.5mm(Wide)~135.0mm(Tele), F1.6~F4.4 (vidni ugao 67.8°~2.4°); Digitalni zoom do 16x; Osetljivost 0.005Lux/F1.6(color); 0Lux IR On; IC LE diode dometa do 150m; True Day/Night (IRC); H.265/H.264/MJPEG kompresija; Podržane rezolucije 1080P/1.3MP/720P/D1/CIF ; Frame rate do 50fps za sve rezolucije; Triple stream; WDR 120dB; HLC; BLC; 2D i 3D DNR; ROI; DIS; Defog; Analitika - Tripwire, Intrusion, Abandoned/Missing Object Detection; Auto Tracking; Bit rate 32K-8Mbps; Micro SD card slot - 128GB maks.; 2 alamna ulaza/1 relejni izlaz; RJ-45 (10/100Base-T) mrežni port; Audio ulaz/izlaz; 300 preset-a, 8 grupa, 5 tura, 5 Swing-a; Masking (do 24 zone); Brzina horizontalne rotacije 400°/s maks; 3D pozicioniranje; U IP66 kućištu sa grejačem i ventilatorom; Dimenzije 186mm (Φ) x 309mm (V); Masa 3.5kg; Radna temp. od -40°C do +70°C; Sa zidnim nosačem; Sa napajanjem 230VAc/24VAc; Prihvata i PoE + napajanje;	€ 553,80	€ 923,00			Na lageru	
4MP Speed dome kamera; Pro serija; 30x zoom; IP66; Sa IC LE diodama dometa 100m; Sa analitikom; Auto Tracking							
SD59430U-HNI	IP 4MP 30X zoom speed dome IC kamera; 1/3" progressive scan CMOS; Inkorporiran motor zoom auto fokus objektiv f=4.5mm(Wide)~135.0mm(Tele), F1.6~F4.4 (vidni ugao 60°~2.2°); Digitalni zoom do 16x; Osetljivost 0.05Lux/F1.6(color); 0Lux IR On; IR LE diode dometa do 100m; True Day/Night (IRC); H.265/H.264/MJPEG kompresija; Podržane rezolucije 4MP /3MP /1080P /1.3MP /720P /D1 /CIF ; Frame rate do 30fps u 4MP; Do 60fps u 1080P; Triple stream; WDR 120dB; HLC; BLC; 2D i 3D DNR; ROI; DIS; Defog; Analitika - Tripwire, Intrusion, Abandoned/Missing Object Detection; Auto Tracking; Bit rate 32K-8Mbps; Micro SD card slot - 128GB maks.; 2 alamna ulaza/1 relejni izlaz; RJ-45 (10/100Base-T) mrežni port; Audio ulaz/izlaz; 300 preset-a, 8 grupa, 5 tura, 5 Swing-a; Masking (do 24 zone); Brzina horizontalne rotacije 400°/s maks; 3D pozicioniranje; U IP66 kućištu sa grejačem i ventilatorom; Dimenzije 186mm (Φ) x 309mm (V); Masa 3.5kg; Radna temp. od -40°C do +70°C; Sa zidnim nosačem; Sa napajanjem 230VAc/24VAc; Prihvata i PoE + napajanje;	€ 628,20	€ 1.047,00			Na lageru	


IP PTZ i Speed dome kamere

Kod	OPIS	VP	MSRP	Slika	
2MP Speed dome kamera; Pro serija; 45x zoom; IP67 i IK10; Sa IC LE diodama dometa 250m; Sa analitikom; Starlight; Auto Tracking					
SD6CE245U-HNI	IP 2MP 45X zoom speed dome IC kamera; 1/2.8" progressive scan Starvis™ CMOS; Inkorporiran motor zoom auto fokus objektiv f=3.95mm(Wide)~177.7mm(Tele), F1.6~F4.95 (vidni ugao 70.3°~1.8°); Digitalni zoom do 16x; Osetljivost 0.005Lux/F1.6(color); 0Lux IR On; IC LE diode dometa do 250m; True Day/Night (IRC); H.265+/H.265/H.264+/ H.264 kompresija; Podržane rezolucije 1080P /1.3MP /720P /D1 /CIF ; Frame rate do 50/60fps za sve rezolucije; Triple stream; WDR 120dB; HLC; BLC; 2D i 3D DNR; ROI; DIS; Defog; Analitika - Tripwire, Intrusion, Abandoned/Missing Object Detection; Auto Tracking; Bit rate 32K-8Mbps; Micro SD card slot - 128GB maks.; 7 alamnih ulaza/1 izlaz; RJ-45 (10/100Base-T) mrežni port; Audio ulaz/izlaz; Kompozitni video izlaz (BNC); RS485; 300 preset-a, 8 grupa, 5 tura, 5 Swing-a; Masking (do 24 zone); Brzina horizontalne rotacije 300°/s maks; 3D pozicioniranje; U metalnom IP67 kućištu sa grejačem i ventilatorom; IK10; Dimenzije 209mm (Φ) x 337.4mm (V); Masa 5.8kg; Radna temp. od -40°C do +70°C; Sa zidnim nosačem; Sa napajanjem 230VAc/24VAc; Prihvata i PoE + napajanje;	€ 696,00	€ 1.160,00	 2MP 45X Zoom 120dB WDR Defog ROI, EIS AUDIO IN/OUT 30P/SEC Alarm In/Out SD CARD SLOT AUTO TRACKING 40°C~70°C SMART LED 250m ICR 0.1μm 120dB WDR 24P/SEC IP 67 24V Hi PoE H. 265 Starlight ONVIF	Uskoro
2MP Speed dome kamera; Ultra serija; 40x zoom; IP67; Sa IR LE diodama dometa 450m; Sa brisačem; Sa analitikom; Starlight; Auto Tracking					
SD8A240VI-HNI	IP 2MP 40X zoom speed dome IC kamera sa brisačem; 1/1.8" progressive scan Starvis™ CMOS; Inkorporiran motor zoom auto fokus objektiv f=5.6mm(Wide)~223mm(Tele), F1.4~F4.8 (vidni ugao 63.9°~2.0°); Digitalni zoom do 16x; Osetljivost 0.002Lux/F1.4(color); 0Lux IR On; IR LE diode dometa do 450m; Brisač prednjeg stakla; True Day/Night (IRC); H.265+/H.265/H.264+/ H.264 kompresija; Podržane rezolucije 1080P /1.3MP /720P /D1 /CIF ; Frame rate do 25/30fps za sve rezolucije; Triple stream; WDR 120dB; HLC; BLC; 2D i 3D DNR; ROI; DIS; Defog; Analitika - Tripwire, Intrusion, Abandoned/Missing Object Detection; Face Detection, Heat Map; Auto Tracking; Bit rate 32K-8Mbps; Micro SD card slot - 256GB maks.; 7 alamnih ulaza/2 izlaza; RJ-45 (10/100Base-T) mrežni port; Audio ulaz/izlaz; Kompozitni video izlaz (BNC); RS485; 300 preset-a, 8 grupa, 5 tura, 5 Swing-a; Masking (do 24 zone); Brzina horizontalne rotacije 240°/s maks; 3D pozicioniranje; U metalnom IP67 kućištu sa grejačem i ventilatorom; Dimenzije Φ262mm x 415.6mm; Masa 8.5kg; Radna temp. od -40°C do +70°C; Sa zidnim nosačem; Sa napajanjem 230VAc/24VAc; Prihvata i Hi PoE	€ 1.190,00	€ 1.983,33	 2MP 40X Zoom 120dB WDR Defog ROI, EIS AUDIO IN/OUT 24P/SEC Alarm In/Out SD CARD SLOT IP 67 24V Hi PoE SMART LED 450m ICR 0.1μm SMART WIPER 24P/SEC IP 67 24V Hi PoE H. 265 Starlight ONVIF	Uskoro
8MP / 4K Speed dome kamera; 40x zoom; IP67; Sa IR LE diodama dometa 450m; Sa brisačem; Sa analitikom; Starlight; Auto Tracking					
SD8A840VI-HNI	IP 8MP / 4K 40X zoom speed dome IC kamera sa brisačem; 1/1.8" progressive scan Starvis™ CMOS; Inkorporiran motor zoom auto fokus objektiv f=5.6mm(Wide)~223mm(Tele), F1.4~F4.8 (vidni ugao 60.6°~1.8°); Digitalni zoom do 16x; Osetljivost 0.002Lux/F1.4(color); 0Lux IR On; IC LE diode dometa do 450m; Brisač prednjeg stakla; True Day/Night (IRC); H.265+/H.265/H.264+/ H.264 kompresija; Podržane rezolucije 4K/ 1080P /1.3MP /720P /D1 /CIF ; Frame rate do 25/30fps za sve rezolucije; Triple stream; WDR 120dB; HLC; BLC; 2D i 3D DNR; ROI; DIS; Defog; Analitika - Tripwire, Intrusion, Abandoned/Missing Object Detection; Face Detection, Heat Map; Auto Tracking; Bit rate 32K-8Mbps; Micro SD card slot - 256GB maks.; 7 alamnih ulaza/2 izlaza; RJ-45 (10/100Base-T) mrežni port; Audio ulaz/izlaz; Kompozitni video izlaz (BNC); RS485; 300 preset-a, 8 grupa, 5 tura, 5 Swing-a; Masking (do 24 zone); Brzina horizontalne rotacije 240°/s maks; 3D pozicioniranje; U metalnom IP67 kućištu sa grejačem i ventilatorom; Dimenzije Φ262mm x 415.6mm; Masa 8.5kg; Radna temp. od -40°C do +70°C; Sa zidnim nosačem; Sa napajanjem 230VAc/24VAc; Prihvata i Hi PoE	€ 1.330,00	€ 2.216,67	 8MP 40X Zoom 120dB WDR Defog ROI, EIS AUDIO IN/OUT 24P/SEC Alarm In/Out SD CARD SLOT IP 67 24V Hi PoE SMART LED 450m ICR 0.1μm SMART WIPER 24P/SEC IP 67 24V Hi PoE H. 265 Starlight ONVIF	Uskoro
2MP PTZ kamera; 45x zoom; IP68; Sa IR LE diodama dometa 350m; Sa brisačem; Sa analitikom; Starlight; Auto Tracking					
PTZ19245U-IRB-N	IP 2MP 45X zoom PTZ IC kamera sa brisačem; 1/2.8" progressive scan Starvis™ CMOS; Inkorporiran motor zoom auto fokus objektiv f=3.95mm(Wide)~177.7mm(Tele), F1.6~F4.95 (vidni ugao 70.3°~1.8°); Digitalni zoom do 16x; Osetljivost 0.005Lux@F1.6 (kolor), 0.0005Lux@F1.6 (C/B); 0Lux IR On; IR LE diode dometa do 350m; Pametni brisač prednjeg stakla; True Day/Night (IRC); H.265+/H.265/H.264+/ H.264 kompresija; Podržane rezolucije 1080P /1.3MP /720P /D1 /CIF ; Frame rate do 50/60fps za sve rezolucije; Triple stream; WDR 120dB; HLC; BLC; 2D i 3D DNR; ROI; DIS; Defog; Analitika - Tripwire, Intrusion, Abandoned/Missing Object Detection; Face Detection, Heat Map; Auto Tracking; Bit rate 32K-8Mbps; Micro SD card slot - 256GB maks.; 7 alamnih ulaza/2 izlaza; RJ-45 (10/100Base-T) mrežni port; Audio ulaz/izlaz; Kompozitni video izlaz (BNC); RS485; 300 preset-a, 8 grupa, 5 tura, 5 Swing-a; Masking (do 24 zone); Brzina horizontalne rotacije 120°/s maks; 3D pozicioniranje; U metalnom IP68 kućištu sa grejačem i ventilatorom; NEMA 4X; Dimenzije Φ262mm x 415.6mm; Masa 8.5kg; Radna temp. od -50°C do +70°C; Sa napajanjem 230VAc/24VAc 5A; Prihvata i Hi PoE napajanje; CE: EN55032/EN55024/EN50130-4		€ 2.870,00	 2MP 45X Zoom 120dB WDR Defog ROI, EIS AUDIO IN/OUT 120/SEC Alarm In/Out SD CARD SLOT IP 68 24V Hi PoE SMART LED 350m ICR 0.1μm SMART WIPER 120/SEC IP 68 24V Hi PoE H. 265 Starlight ONVIF	Na lageru




4-kanalni tribridi i penta-brid

Kod	OPIS	VP	MSRP		Slika		
4+1 kanalni penta-brid, 100fps@1080N, mini metalno kućište, 1X audio ulaz/izlaz, 1X SATA, HDMI + VGA, network							
XVR1B04	4+1 kanalni stand-alone penta-brid DVR (analog + HDCVI + AHD + TVI + IP); H.265/H.264 video kompresija; AAC (samo za kanal 1), G.711A, G.711U, PCM audio kompresija; 4 video ulaza; VGA izlaz; HDMI izlaz; 1 audio ulaz/1 izlaz; USB x2 (USB 2.0) - za lokalni backup i miš; Rezolucija/frame rate za snimanje po kameri 1080N/720P/960H/D1/CIF (1~25/30fps) ; Rezolucija prikaza 1280×720 do 1920×1080; Dual stream; 1 SATA port - HDD do 6TB; Network port 10/100Mbps; CMS software (Smart PSS); Web pristup; Software za iOS i Android; P2P podrška; Podrška 1 dodatnu IP kameru (rezolucija do 2MP, bitrate do 20Mbps) ili do 5 IP kamera; Dimenzije Cooper 1U, 197mm×192mm×41mm (W×D×H); Masa 0.54kg; Napajanje 110-240VAc preko pril. adaptera 12VDC 1.5A	€ 37,20	€ 62,00			Na lageru	
4+2 kanalni penta-brid, 60fps@4M-N/1080P, plast. kućište, 1X audio ulaz/izlaz, 1X SATA, HDMI + VGA, network							
XVR5104C-X1	4+2 kanalni stand-alone penta-brid DVR (analog + HDCVI + AHD + TVI + IP); H.265+/H.265/H.264+/H.264 video kompresija; AAC (samo za kanal 1), G.711A, G.711U, PCM audio kompresija; 4 video ulaza; VGA izlaz; HDMI izlaz; 1 audio ulaz/1 izlaz; USB x2 (USB 2.0) - za lokalni backup i miš; RS485; Rezolucija/frame rate za snimanje po kameri, za prvi kanal 5M-N(1~10fps); Za ostale kanale: 4M-N/1080P(1~15fps); 1080N/720P/960H/D1/CIF (1~25/30fps) ; Rezolucija prikaza 1280×720 ili do 1920×1080 (HDMI); Dual stream; 1 SATA port - HDD do 10TB; Network port 10/100Mbps; CMS software (Smart PSS); Web pristup; Software za iOS i Android; P2P podrška; Podrška do 2 dodatne IP kamere (rezolucija do 6MP, bitrate do 24Mbps) ili do 6 IP kamera; Dimenzije Smart 1U, 205mm×211mm×45mm (W×D×H); Masa 0.5kg; Napajanje 110-240VAc preko pril. adaptera 12VDC 2A; POS podrška; Podrška HDCVI audio i alarm; Smart Fan; Reset taster na ploči; Broadcast audio kvalitet	€ 55,20	€ 92,00			Na lageru	
4+2 kanalni penta-brid, 60fps@4M-N/1080P, metalno kućište, 1X audio ulaz/izlaz, 1X SATA, RS485, HDMI + VGA, network							
XVR5104HS-X1	4+2 kanalni stand-alone penta-brid DVR (analog + HDCVI + AHD + TVI + IP); H.265+/H.265/H.264+/H.264 video kompresija; AAC (samo za kanal 1), G.711A, G.711U, PCM audio kompresija; 4 video ulaza; VGA izlaz; HDMI izlaz; 1 audio ulaz/1 izlaz; USB x2 (USB 2.0) - za lokalni backup i miš; RS485; Rezolucija/frame rate za snimanje po kameri, za prvi kanal 5M-N(1~10fps); Za ostale kanale: 4M-N/1080P(1~15fps); 1080N/720P/960H/D1/CIF (1~25/30fps) ; Rezolucija prikaza 1280×720 ili do 1920×1080 (HDMI); Dual stream; 1 SATA port - HDD do 10TB; Network port 10/100Mbps; CMS software (Smart PSS); Web pristup; Software za iOS i Android; P2P podrška; Podrška do 2 dodatne IP kamere (rezolucija do 6MP, bitrate do 24Mbps) ili do 6 IP kamera; Dimenzije Compact 1U, 260×236×48mm (W×D×H); Masa 0.9kg; Napajanje 110-240VAc preko pril. adaptera 12VDC 2A; POS podrška; Podrška HDCVI audio i alarm; Smart Fan; Reset taster na ploči; Broadcast audio kvalitet	€ 64,80	€ 108,00			Na lageru	
4+2 kanalni penta-brid, 100fps@1080P, 60fps@4MP, metalno kućište, 1X audio ulaz/izlaz, 1X SATA, RS485, HDMI + VGA, network							
XVR5104HS-4KL-X	4+2 kanalni stand-alone penta-brid DVR (analog + HDCVI + AHD + TVI + IP); H.265+/H.265/H.264+/H.264 video kompresija; AAC (samo za kanal 1), G.711A, G.711U, PCM audio kompresija; 4 video ulaza; VGA izlaz; HDMI izlaz; 1 audio ulaz/1 izlaz; USB x2 (USB 2.0) - za lokalni backup i miš; RS485; Rezolucija/frame rate za snimanje po kameri, za prvi kanal 4K(1~7fps); 5MP(1~12fps); 4MP/ 3MP(1~15fps); Za ostale kanale: 4K-N(1~7fps), 4MP/3MP(1~15fps); 4M-N/1080P/720P/960H/D1/CIF (1~25/30fps) ; Rezolucija prikaza 1280×720 ili do 3840×2160 (HDMI); Dual stream; 1 SATA port - HDD do 10TB; Network port 10/100Mbps; CMS software (Smart PSS); Web pristup; Software za iOS i Android; P2P podrška; Podrška do 2 dodatne IP kamere (rezolucija do 8MP, bitrate do 24Mbps) ili do 6 IP kamera; Dimenzije Compact 1U, 260×236×48mm; Masa 0.9kg; Napajanje 110-240VAc preko pril. adaptera 12VDC 2A; POS podrška; Podrška HDCVI audio i alarm; Smart Fan; Reset taster na ploči; Broadcast audio kvalitet	€ 90,00	€ 150,00		 	Na lageru	

4-kanalni tribridi i penta-brid

Kod	OPIS	VP	MSRP		Slika		
4+4 kanalni penta-brid, 100fps@1080P, 60fps@4MP, metalno kućište, 4X audio ulaz/1 izlaz, 1X SATA, alarmni ulazi/izlazi, RS485, HDMI + VGA, network							
XVR7104HE-4KL-X	4+4 kanalni stand-alone penta-brid DVR (analog + HDCVI + AHD + TVI + IP); H.265+/H.265/H.264+/H.264 video kompresija; AAC (samo za kanal 1), G.711A, G.711U, PCM audio kompresija; 4 video ulaza; VGA izlaz; HDMI izlaz; 4 audio ulaza/1 izlaz; 8 alarmnih ulaza/3 relejna izlaza; USB x2 (USB 2.0) - za lokalni backup i miš; RS485; Rezolucija/frame rate za snimanje po kameri, za prvi kanal 4K(1~7fps); 5MP(1~12fps); 4MP/ 3MP(1~15fps); Za ostale kanale: 4K-N(1~7fps), 4MP/3MP(1~15fps); 4M-N/1080P/720P/960H/D1/CIF (1~25/30fps) ; Rezolucija prikaza 1280x720 ili do 2560x1440 (HDMI); Dual stream; 1 SATA port - HDD do 10TB; Network port 10/100Mbps; CMS software (Smart PSS); Web pristup; Software za iOS i Android; P2P podrška; Podržava do 4 dodatne IP kamere (rezolucija do 8MP, bitrate do 32Mbps) ili do 8 IP kamera; Dimenzije Mini 1U, 325mmx255mmx55mm (WxDxH); Masa 1.2kg; Napajanje 110-240VAc preko pril. adaptera 12Vdc 2A; POS podrška; Podržava HDCVI audio i alarm; Smart Fan; Reset taster na ploči; Broadcast audio kvalitete; Do 4 kanala analitike	€ 145,00	€ 241,67			Na lageru	
4+4 kanalni penta-brid, 100fps@4MP, 60fps@4K, plastično kućište, 1 audio ulaz/izlaz, 1X SATA, RS485, HDMI + VGA, network							
XVR7104E-4KL-B-X	4+4 kanalni stand-alone penta-brid DVR (analog + HDCVI + AHD + TVI + IP); H.265+/H.265/H.264+/H.264 video kompresija; AAC (samo za kanal 1), G.711A, G.711U, PCM audio kompresija; 4 video ulaza; VGA izlaz; HDMI izlaz; USB x3 (USB 2.0 x2 i USB 3.0 x1) - za lokalni backup i miš; RS485; Rezolucija/frame rate za snimanje po kameri: 4K(1~15fps); 6MP/5MP(1~20fps); 4MP/3MP/1080P/720P/960H/D1/CIF (1~25/30fps); Rezolucija prikaza 1920x1080 ili do 3840x2160 (HDMI); Dual stream; 1 SATA port - HDD do 10TB; Network port 10/100/1000Mbps; CMS software (Smart PSS); Web pristup; Software za iOS i Android; P2P podrška; Podržava do 4 dodatne IP kamere (rezolucija do 8MP, bitrate do 32Mbps) ili do 8 IP kamera; Dimenzije elegant 1U, 260mmx150mmx87,5mm (WxDxH); Masa 1.2kg; Napajanje 110-240VAc preko pril. adaptera 12Vdc 5A; Izlaz za napajanje kamera; Ugrađena pomoćna baterija; IoT i POS podrška; Podržava HDCVI audio i alarm; Smart Fan; Reset taster na ploči; Broadcast audio kvalitete; Do 4 kanala analitike	€ 189,60	€ 316,00			Na lageru	
4+2 kanalni tribrid, 60fps@4K, 100fps@4MP, metalno kućište, RS485, 1X audio ulaz/izlaz, 2X SATA, HDMI + VGA, network							
HCVR7204AN-4K	4+2 kanalni stand-alone tribridni DVR (analog + HDCVI + IP); H.264 i H.264+/G.711 kompresija; 4 video ulaza; VGA izlaz; HDMI izlaz; 1 audio ulaz/1 izlaz; USB x2 (1 USB 2.0 , 1 USB 3.0) - za lokalni backup i miš; RS485; Rezolucija/frame rate za snimanje po kameri 4K(1~15fps), 4MP /1080P /720P /960H /D1 /HD1 /BCIF /CIF /QCIF (1~25/30fps); Rezolucija prikaza 720x576 ili do 3840x2160 (HDMI); Dual stream; 2 SATA porta - za do 2 SATA HDD do 8TB (do 16TB ukupno); Network port 10/100/1000Mbps; CMS software (Smart PSS); Web pristup; Software za iOS i Android; P2P podrška; Podržava do 2 dodatne IP kamere (rezolucija do 8MP, bitrate do 24Mbps) ili do 6 IP kamera; Dimenzije 1U, 375mmx287mmx53mm (WxDxH); Masa 2.35kg; Napajanje 110-240VAc preko pril. adaptera 12Vdc 4A	€ 170,00	€ 283,33			Na lageru	




8-kanalni tribridi i penta-brid

Kod	OPIS	VP	MSRP		Slika		
8+2 kanalni penta-brid, 130fps@1080N & 720P, mini metalno kućište, 1X audio ulaz/izlaz, 1X SATA, HDMI + VGA, network							
XVR1B08	8+2 kanalni stand-alone penta-brid DVR (analog + HDCVI + AHD + TVI + IP); H.265+/H.265/H.264+/H.264 video kompresija; AAC (samo za kanal 1), G.711A, G.711U, PCM audio kompresija; 8 video ulaza; VGA izlaz; HDMI izlaz; 1 audio ulaz/1 izlaz; USB x2 (USB 2.0) - za lokalni backup i miš; Rezolucija/frame rate za snimanje po kameri, za prvi kanal 1080N/720P(1~25/30fps); Za ostale kanale: 1080N/720P(1~15fps); 960H/D1/CIF (1~25/30fps) ; Rezolucija prikaza 1280×720 ili do 1920×1080 (HDMI); Dual stream; 1 SATA port - HDD do 6TB; Network port 10/100Mbps; CMS software (Smart PSS); Web pristup; Software za iOS i Android; P2P podrška; Podrška do 2 dodatne IP kamere (rezolucija do 6MP, bitrate do 40Mbps) ili do 10 IP kamera; Dimenzije Cooper 1U, 197mm×192mm×41mm (W×D×H); Masa 0.54kg; Napajanje 110-240VAc preko pril. adaptera 12Vdc 1.5A	€ 54,60	€ 91,00			Na lageru	
8+4 kanalni penta-brid, 120fps@4M-N/1080P, plast. kućište, 1X audio ulaz/izlaz, 1X SATA, HDMI + VGA, network							
XVR5108C-X	8+4 kanalni stand-alone penta-brid DVR (analog + HDCVI + AHD + TVI + IP); H.265+/H.265/H.264+/H.264 video kompresija; AAC (samo za kanal 1), G.711A, G.711U, PCM audio kompresija; 8 video ulaza; VGA izlaz; HDMI izlaz; 1 audio ulaz/1 izlaz; USB x2 (USB 2.0) - za lokalni backup i miš; RS485; Rezolucija/frame rate za snimanje po kameri, za prvi i drugi kanal 5M-N(1~10fps); Za ostale kanale: 4M-N/1080P(1~15fps); 1080N/720P/960H/D1/CIF (1~25/30fps) ; Rezolucija prikaza 1280×720 ili do 1920×1080 (HDMI); Dual stream; 1 SATA port - HDD do 10TB; Network port 10/100Mbps; CMS software (Smart PSS); Web pristup; Software za iOS i Android; P2P podrška; Podrška do 4 dodatne IP kamere (rezolucija do 6MP, bitrate do 48Mbps) ili do 12 IP kamera; Dimenzije Smart 1U, 205mm×211mm×45mm (W×D×H); Masa 0.5kg; Napajanje 110-240VAc preko pril. adaptera 12Vdc 2A; POS podrška; Podrška HDCVI audio i alarm; Reset taster na ploči; Broadcast audio kvalitet	€ 80,40	€ 134,00			Na lageru	
8+4 kanalni penta-brid, 120fps@4M-N/1080P, metalno kućište, 1X audio ulaz/izlaz, 1X SATA, RS485, HDMI + VGA, network							
XVR5108HS-X	8+4 kanalni stand-alone penta-brid DVR (analog + HDCVI + AHD + TVI + IP); H.265+/H.265/H.264+/H.264 video kompresija; AAC (samo za kanal 1), G.711A, G.711U, PCM audio kompresija; 8 video ulaza; VGA izlaz; HDMI izlaz; 1 audio ulaz/1 izlaz; USB x2 (USB 2.0) - za lokalni backup i miš; RS485; Rezolucija/frame rate za snimanje po kameri, za prvi i drugi kanal 5M-N(1~10fps); Za ostale kanale: 4M-N/1080P(1~15fps); 1080N/720P/960H/D1/CIF (1~25/30fps) ; Rezolucija prikaza 1280×720 ili do 1920×1080 (HDMI); Dual stream; 1 SATA port - HDD do 10TB; Network port 10/100Mbps; CMS software (Smart PSS); Web pristup; Software za iOS i Android; P2P podrška; Podrška do 4 dodatne IP kamere (rezolucija do 6MP, bitrate do 48Mbps) ili do 12 IP kamera; Dimenzije Compact 1U, 260×236×48mm (W×D×H); Masa 0.9kg; Napajanje 110-240VAc preko adaptera 12Vdc 2A; POS podrška; Podrška HDCVI audio i alarm; Smart Fan; Reset taster na ploči; Broadcast audio kvalitet	€ 90,00	€ 150,00			Na lageru	
8+4 kanalni penta-brid, 200fps@1080P, 120fps@4MP, metalno kućište, 1X audio ulaz/izlaz, 1X SATA, RS485, HDMI + VGA, network							
XVR5108HS-4KL-X	8+4 kanalni stand-alone penta-brid DVR (analog + HDCVI + AHD + TVI + IP); H.265+/H.265/H.264+/H.264 video kompresija; AAC (samo za kanal 1), G.711A, G.711U, PCM audio kompresija; 8 video ulaza; VGA izlaz; HDMI izlaz; 1 audio ulaz/1 izlaz; USB x2 (1x USB 2.0 i 1x USB 3.0) - za lokalni backup i miš; RS485; Rezolucija/frame rate za snimanje po kameri: 4K(1~7fps); 6MP(1~10fps); 5MP(1~12fps); 4MP/3MP(1~15fps); 4M-N/ 1080P/ 720P/ 960H/ D1 /CIF (1~ 25 /30fps); Rezolucija prikaza 1280×720 ili do 3840×2160 (HDMI); Dual stream; 1 SATA port - HDD do 10TB; Network port 10/100/1000Mbps; CMS software (Smart PSS); Web pristup; Software za iOS i Android platforme; P2P podrška; Podrška do 4 dodatne IP kamere (rezolucija do 8MP, bitrate do 48Mbps) ili do 12 IP kamera; Dimenzije Compact 1U, 260mm×236mm×48mm (W×D×H); Masa 0.9kg; Napajanje 110-240VAc preko adaptera 12Vdc 2A; POS podrška; Podrška HDCVI audio i alarm; Smart Fan; Reset taster na ploči; Broadcast audio kvalitet	€ 135,00	€ 225,00		 	Na lageru	

8-kanalni tribridi i penta-brid

Kod	OPIS	VP	MSRP		Slika		
8+4 kanalni penta-brid, 200fps@1080P, 120fps@4MP, metalno kućište, 1X audio ulaz/izlaz, 2X SATA, RS485, HDMI + VGA, network							
XVR5208AN-4KL-X	8+4 kanalni stand-alone penta-brid DVR (analog + HDCVI + AHD + TVI + IP); H.265+ /H.265 /H.264+ /H.264 video kompresija; AAC (samo za kanal 1), G.711A, G.711U, PCM audio kompresija; 8 video ulaza; VGA izlaz; HDMI izlaz; 1 audio ulaz/1 izlaz; USB x2 (1x USB 2.0 i 1x USB 3.0) - za lokalni backup i miš; RS485; Rezolucija/frame rate za snimanje po kameri: 4K(1~7fps); 6MP(1~10fps); 5MP(1~12fps); 4MP/3MP(1~15fps); 4M-N /1080P /720P /960H /D1 /CIF (1~25 /30fps); Rezolucija prikaza 1280x720 ili do 3840x2160 (HDMI); Dual stream; 2 SATA porta - HDD do 10TB; Network port 10/100/1000Mbps; CMS software (Smart PSS); Web pristup; Software za iOS i Android platforme; P2P podrška; Podržava do 4 dodatne IP kamere (rezolucija do 8MP, bitrate do 48Mbps) ili do 12 IP kamera; Dimenzije 1U, 375mm x287mm x53mm (WxDxH); Masa 1.5kg; Napajanje 110-240VAc preko pril. adaptera 12Vdc 4A; POS podrška; Podržava HDCVI audio i alarm; Smart Fan; Reset taster na ploči; Broadcast audio kvalitet	€ 160,00	€ 266,67			Na lageru	
8+8 kanalni penta-brid, 200fps@1080P, 120fps@4MP, metalno kućište, 8X audio ulaz/1 izlaz, 1X SATA, alarmni ulazi/izlazi, RS485, HDMI + VGA, network							
XVR7108HE-4KL-X	8+8 kanalni stand-alone penta-brid DVR (analog + HDCVI + AHD + TVI + IP); H.265+/H.265/H.264+/H.264 video kompresija; AAC (samo za kanal 1), G.711A, G.711U, PCM audio kompresija; 8 video ulaza; VGA izlaz; HDMI izlaz; 8 audio ulaza/1 izlaz; 8 alarmnih ulaza/3 relejna izlaza; USB x2 (1x USB 2.0 i 1x USB 3.0) - za lokalni backup i miš; RS485; Rezolucija/frame rate za snimanje po kameri: 4K(1~7fps); 6MP(1~10fps); 5MP(1~12fps); 4MP/3MP(1~15fps); 4M-N/1080P/720P/960H/D1/CIF(1~25/30fps) ; Rezolucija prikaza 1920x1080 ili do 3840x2160 (HDMI); Dual stream; 1 SATA port - HDD do 10TB; Network port 10/100/1000Mbps; CMS software (Smart PSS); Web pristup; Software za iOS i Android; P2P podrška; Podržava do 8 dodatne IP kamere (rezolucija do 8MP, bitrate do 64Mbps) ili do 16 IP kamera; Dimenzije Mini 1U, 325mm x255mm x55mm (WxDxH); Masa 1.2kg; Napajanje 110-240VAc preko ad. 12Vdc 2A; POS podrška; Podržava HDCVI audio i alarm; Smart Fan; Reset t.na ploči; Broadcast audio kvalitet; Do 4 kanala analitike	€ 172,00	€ 286,67			Na lageru	
8+8 kanalni penta-brid, 200fps@1080P, 120fps@4MP, metalno kućište, 4X audio ulaz/1 izlaz, 2X SATA, RS485, HDMI + VGA, network							
XVR7208A-4KL-X	8+8 kanalni stand-alone penta-brid DVR (analog + HDCVI + AHD + TVI + IP); H.265+/H.265/H.264+/H.264 video kompresija; AAC (samo za kanal 1), G.711A, G.711U, PCM audio kompresija; 8 video ulaza; VGA izlaz; HDMI izlaz; 4 audio ulaza/1 izlaz; 8 alarmnih ulaza/3 relejna izlaza; USB x2 (1x USB 2.0 i 1x USB 3.0) - za lokalni backup i miš; RS485; Rezolucija/frame rate za snimanje po kameri: 4K(1~7fps); 6MP(1~10fps); 5MP(1~12fps); 4MP/3MP(1~15fps); 4M-N /1080P /720P /960H /D1 /CIF (1~25/ 30fps) ; Rezolucija prikaza 1920x1080 ili do 3840x2160 (HDMI); Dual stream; 2 SATA port - HDD do 10TB; Network port 10/100/1000Mbps; CMS software (Smart PSS); Web pristup; Software za iOS i Android platforme; P2P podrška; Podržava do 8 dodatne IP kamere (rezolucija do 8MP, bitrate do 64Mbps) ili do 16 IP kamera; Dimenzije 1U, 375mm x287mm x53mm (WxDxH); Masa 1.7kg; Napajanje 110-240VAc preko ad. 12Vdc 5A; POS podrška; Podržava HDCVI audio i alarm; Smart Fan; Reset na ploči; Broadcast audio kvalitet; Do 4 kanala analitike	€ 215,00	€ 358,33			Na lageru	
8+8 kanalni penta-brid, 120fps@4MP, 56fps@4K, plastično kućište, 1 audio ulaz/izlaz, 1X SATA, RS485, HDMI + VGA, network							
XVR7108E-4KL-B-X	8+8 kanalni stand-alone penta-brid DVR (analog + HDCVI + AHD + TVI + IP); H.265+/H.265/H.264+/H.264 video kompresija; AAC (samo za kanal 1), G.711A, G.711U, PCM audio kompresija; 8 video ulaza; VGA izlaz; HDMI izlaz; USB x3 (USB 2.0 x2 i USB 3.0 x1) za lokalni backup i miš; RS485; Rezolucija/frame rate za snimanje po kameri: 4K(1~7fps); 6MP(1~10fps); 5MP(1~12fps); 4MP/3MP(1~15fps); 4M-N/1080P/720P/960H/D1/CIF (1~25/30fps); Rezolucija prikaza 1920x1080 ili do 3840x2160 (HDMI); Dual stream; 1 SATA port - HDD do 10TB; Network port 10/100/1000Mbps; CMS software (Smart PSS); Web pristup; Software za iOS i Android; P2P podrška; Podržava do 8 dodatnih IP kamere (rezolucija do 8MP, bitrate do 64Mbps) ili do 16 IP kamera; Dimenzije Elegant 1U, 260mm x150mm x87,5mm (WxDxH); Masa 1.4kg; Napajanje 110-240VAc preko adaptera 12Vdc 5A; Izlaz za napajanje kamera; Ugrađena pomoćna baterija; IoT i POS podrška; Podržava HDCVI audio i alarm; Reset taster na ploči; Broadcast audio kvalitet; Do 4 kanala analitike	€ 190,00	€ 316,67			Na lageru	

16-kanalni penta-brid

Kod	OPIS	VP	MSRP	Slika	
16+8 kanalni penta-brid, 240fps@4MP, 112fps@4K, metalno kućište, 1X audio ulaz/izlaz, 1X SATA, RS485, HDMI + VGA, network					
XVR5116H-4KL-X	16+8 kanalni stand-alone penta-brid DVR (analog + HDCVI + AHD + TVI + IP); H.265+ /H.265 /H.264+/ H.264 video kompresija; AAC (samo za kanal 1), G.711A, G.711U, PCM audio kompresija; 16 video ulaza; VGA izlaz; HDMI izlaz; 1 audio ulaz/1 izlaz; USB x2 (1x USB 2.0 i 1x USB 3.0) - za lokalni backup i miš; RS485; Rezolucija/frame rate za snimanje po kameri: 4K(1~7fps); 6MP(1~10fps); 5MP(1~12fps); 4MP/3MP(1~15fps); 4M-N /1080P /720P /960H /D1 /CIF(1~25/30fps); Rezolucija prikaza 1280×720 ili do 3840×2160 (HDMI); Dual stream; 1 SATA port - HDD do 10TB; Network port 10/100/1000Mbps; CMS software (Smart PSS); Web pristup; Software za iOS i Android; P2P podrška; Podrška do 8 dodatne IP kamere (rezolucija do 8MP, bitrate do 64Mbps) ili do 24 IP kamera; Dimenzije Mini 1U, 325mm ×255mm ×55mm (W×D×H); Masa 1.2kg; Napajanje 110-240VAc preko adaptera 12Vdc 3A; POS podrška; Podrška HDCVI audio i alarm; Smart Fan; Reset taster na ploči; Broadcast audio kvalitet	€ 199,00	€ 331,67	 	Na lageru
16+8 kanalni penta-brid, 240fps@4MP, 112fps@4K, metalno kućište, 1X audio ulaz/izlaz, 1X SATA, RS485, HDMI + VGA, network					
XVR5216AN-4KL-X	16+8 kanalni stand-alone penta-brid DVR (analog + HDCVI + AHD + TVI + IP); H.265+/H.265/H.264+/H.264 video kompresija; AAC (samo za kanal 1), G.711A, G.711U, PCM audio kompresija; 16 video ulaza; VGA izlaz; HDMI izlaz; 1 audio ulaz/1 izlaz; USB x2 (1x USB 2.0 i 1x USB 3.0) - za lokalni backup i miš; RS485; Rezolucija/frame rate za snimanje po kameri: 4K(1~7fps); 6MP(1~10fps); 5MP(1~12fps); 4MP/3MP(1~15fps); 4M-N/1080P/720P/960H/D1/CIF(1~25/30fps); Rezolucija prikaza 1280×720 ili do 3840×2160 (HDMI); Dual stream; 2 SATA port - HDD do 10TB; Network port 10/100/1000Mbps; CMS software (Smart PSS); Web pristup; Software za iOS i Android; P2P podrška; Podrška do 8 dodatne IP kamere (rezolucija do 8MP, bitrate do 64Mbps) ili do 24 IP kamera; Dimenzije 1U, 375mm ×287mm ×53mm (W×D×H); Masa 1.7kg; Napajanje 110-240VAc preko adaptera 12Vdc 5A; POS podrška; Podrška HDCVI audio i alarm; Smart Fan; Reset taster na ploči; Broadcast audio kvalitet	€ 220,00	€ 366,67	 	Na lageru
16+16 kanalni penta-brid, 240fps@4MP, 112fps@4K, metalno kućište, 4X audio ulaz/1 izlaz, 2X SATA, RS485, HDMI + VGA, network					
XVR7216A-4KL-X	16+16 kanalni stand-alone penta-brid DVR (analog + HDCVI + AHD + TVI + IP); H.265+ /H.265/ H.264+/ H.264 video kompresija; AAC (samo za kanal 1), G.711A, G.711U, PCM audio kompresija; 16 video ulaza; VGA izlaz; HDMI izlaz; 4 audio ulaza/1 izlaz; USB x2 (1x USB 2.0 i 1x USB 3.0) - za lokalni backup i miš; RS485; Rezolucija/frame rate za snimanje po kameri: 4K(1~7fps); 6MP(1~10fps); 5MP(1~12fps); 4MP/3MP(1~15fps); 4M-N /1080P /720P /960H /D1 /CIF (1~ 25 /30fps); Rezolucija prikaza 1920×1080 ili do 3840×2160 (HDMI); Dual stream; 2 SATA port - HDD do 10TB; Network port 10/100/1000Mbps; CMS software (PSS i PSS Smart); Web pristup; Software za iOS i Android; P2P podrška; Podrška do 16 dodatne IP kamere (rezolucija do 8MP, bitrate do 128Mbps) ili do 24 IP kamere; Dimenzije 1U, 375mm×287mm×53mm (W×D×H); Masa 1.8kg; Napajanje 110-240VAc preko adaptera 12Vdc 5A; POS podrška; Podrška HDCVI audio i alarm; Smart Fan; Reset taster na ploči; Broadcast audio kvalitet; Do 4 kanala analitike	€ 275,00	€ 458,33	 	Na lageru
16+16 kanalni penta-brid, 240fps@4MP, 112fps@4K, metalno kućište, 4X audio ulaz/1 izlaz, 4X SATA, RS232, RS485, RS422, 2xHDMI + VGA+BNC, network					
XVR7416L-4KL-X	16+16 kanalni stand-alone penta-brid DVR (analog + HDCVI + AHD + TVI + IP); H.265+ /H.265 /H.264+ /H.264 video kompresija; AAC (samo za kanal 1), G.711A, G.711U, PCM audio kompresija; 16 video ulaza; VGA izlaz (do 1080p); 2X HDMI izlaz; BNC kompozitni izlaz; 4 audio ulaza/1 izlaz; USB x3 (2x USB 2.0 i 1x USB 3.0) - za lokalni backup i miš; RS232; RS485; RS422; Rezolucija/frame rate za snimanje po kameri: 4K(1~7fps); 6MP(1~10fps); 5MP(1~12fps); 4MP/3MP(1~15fps); 4M-N /1080P /720P /960H /D1 /CIF(1~25/30fps); Rezolucija prikaza 1280×720 ili do 3840×2160 (HDMI); Dual stream; 4 SATA port - HDD do 10TB; eSATA port; Network port 10/100/1000Mbps; CMS software (Smart PSS); Web pristup; Software za iOS i Android; P2P podrška; Podrška do 16 dodatnih IP kamera (rezolucija do 12MP, ukupni bitrate do 128Mbps); POS podrška; Dimenzije 1.5U, 440mm ×417mm ×76mm (W×D×H), rek montaža; Masa 4,8kg; Napajanje 110-240VAc	€ 415,00	€ 691,67	 	Na lageru

16-kanalni penta-brid

Kod	OPIS	VP	MSRP	Slika		
16+16 kanalni penta-brid, 240fps@4MP, 112fps@4K, metalno kućište, 16X audio ulaz/1 izlaz, 8X SATA, RS232, RS485, RS422, 2xHDMI + VGA, network						
XVR7816S-4KL-X	16+16 kanalni stand-alone penta-brid DVR (analog + HDCVI + AHD + TVI + IP); H.265+ /H.265 /H.264+ /H.264 video kompresija; AAC (samo za kanal 1), G.711A, G.711U, PCM audio kompresija; 16 video ulaza; VGA izlaz (do 1080p); 2X HDMI izlaz; BNC kompozitni izlaz; 16 audio ulaza/1 izlaz; USB x4 (2x USB 2.0 i 2x USB 3.0) - za lokalni backup i miš; RS232; RS485; RS422; 16 alarmnih ulaza/6 relejnih izlaza; Rezolucija/frame rate za snimanje po kameri: 4K(1~7fps); 6MP(1~10fps); 5MP(1~12fps); 4MP/3MP(1~15fps); 4M-N/1080P/720P/960H/D1/CIF(1~25/30fps); Rezolucija prikaza 1280x720 ili do 3840x2160 (HDMI); Dual stream; 8 SATA port - HDD do 10TB; eSATA port; 2x Network port 10/100/1000Mbps; CMS software (Smart PSS); Web pristup; Software za iOS i Android; P2P podrška; Podržava do 16 dodatnih IP kamera (rezolucija do 12MP, ukupni bitrate do 128Mbps); POS podrška; Dimenzije 2U, 440mmx455mmx95mm (WxDxH), rek montaža; Masa 6,9kg; Napajanje 110-240VAC	€ 555,00	€ 777,00	  	Na lageru	

32 kanalni penta-brid, 480fps@1080P, metalno kućište, 1X audio ulaz/1 izlaz, 2X SATA, RS485, HDMI + VGA + BNC, network

XVR5232AN-X	32 kanalni stand-alone penta-brid DVR (analog + HDCVI + AHD + TVI + IP); H.265+ /H.265 /H.264+ /H.264 video kompresija; AAC (samo za kanal 1), G.711A, G.711U, PCM audio kompresija; 32 video ulaza; VGA izlaz (do 1080p); HDMI izlaz; BNC kompozitni izlaz; 1 audio ulaza/1 izlaz; USB x2 (1x USB 2.0 i 1x USB 3.0) - za lokalni backup i miš; RS485; Rezolucija/frame rate za snimanje po kameri, za prvi i drugi kanal 5M-N (1~10fps); Za ostale kanale: 4M-N/1080P(1~15fps); 1080N/720P/960H/D1/CIF(1~25/30fps); Rezolucija prikaza do 1920x1080 (VGA) ili do 3840x2160 (1x HDMI); Dual stream; 2 SATA port - HDD do 10TB; eSATA port; Network port 10/100/1000Mbps; CMS software (Smart PSS); Web pristup; Software za iOS i Android; P2P podrška; Podržava do 32 IP kamere (rezolucija do 6MP, bitrate do 128Mbps); Dimenzije 1U, 375mmx287mmx53mm (WxDxH); Masa 2kg; Napajanje 110-240VAC preko adaptera 12VDC 5A; POS podrška; Podržava HDCVI audio i alarm; Smart Fan; Reset taster na ploči; Broadcast audio kvalitet	€ 275,00	€ 458,33	 	Na lageru	
-------------	---	----------	----------	--	-----------	--



32 kanalni penta-brid, 480fps@1080P, metalno kućište, 4X audio ulaz/1 izlaz, alarmni ulazi/izlazi, 4X SATA, RS232, RS485, RS422, 2xHDMI + VGA, network

XVR5432L-X	32 kanalni stand-alone penta-brid DVR (analog + HDCVI + AHD + TVI + IP); H.265+/H.265/H.264+/H.264 video kompresija; AAC (samo za kanal 1), G.711A, G.711U, PCM audio kompresija; 32 video ulaza; VGA izlaz (do 1080p); 2X HDMI izlaz; BNC kompozitni izlaz; 4 audio ulaza/1 izlaz; 16 alarmnih ulaza/6 relejnih izlaza; USB x3 (1x USB 2.0 i 2x USB 3.0) - za lokalni backup i miš; RS232; RS485; RS422; Rezolucija/frame rate za snimanje po kameri, za prvi i drugi kanal 5M-N (1~10fps); Za ostale kanale: 4M-N/1080P(1~15fps); 1080N/720P/960H/D1/CIF(1~25/30fps); Rezolucija prikaza 1920x1080 (VGA i 1x HDMI) ili do 3840x2160 (1x HDMI); Dual stream; 4 SATA port - HDD do 10TB; eSATA port; Network port 10/100/1000Mbps; CMS software (Smart PSS); Web pristup; Software za iOS i Android; P2P podrška; Podržava do 32 IP kamere (rezolucija do 8MP, ukupni bitrate do 128Mbps); Dimenzije 1.5U, 440mmx417mmx76mm (WxDxH), rek montaža; Masa 5kg; Napajanje 110-240VAC; POS podrška; Podržava HDCVI audio i alarm; Smart Fan; Reset taster na ploči; Broadcast audio kvalitet	€ 415,00	€ 691,67	 	Na lageru	
------------	---	----------	----------	---	-----------	--

32 kanalni penta-brid, 480fps@1080P, metalno kućište, 16X audio ulaz/1 izlaz, alarmni ulazi/izlazi, 8X SATA, RS232, RS485, RS422, 2xHDMI + VGA, 2x network

XVR5832S-X	32 kanalni stand-alone penta-brid DVR (analog + HDCVI + AHD + TVI + IP); H.265+/H.265/H.264+/H.264 video kompresija; AAC (samo za kanal 1), G.711A, G.711U, PCM audio kompresija; 32 video ulaza; VGA izlaz (do 1080p); 2X HDMI izlaz; BNC kompozitni izlaz; 16 audio ulaza/1 izlaz; 16 alarmnih ulaza/6 relejnih izlaza; USB x4 (2x USB 2.0 i 2x USB 3.0) - za lokalni backup i miš; RS232; RS485; RS422; Rezolucija/frame rate za snimanje po kameri, za prvi i drugi kanal 5M-N (1~10fps); Za ostale kanale: 4M-N/1080P(1~15fps); 1080N/720P/960H/D1/CIF(1~25/30fps); Rezolucija prikaza 1920x1080 (VGA i 1x HDMI) ili do 3840x2160 (1x HDMI); Dual stream; 8 SATA port - HDD do 10TB; eSATA port; 2x Network port 10/100/1000Mbps; CMS software (Smart PSS); Web pristup; Software za iOS i Android; P2P podrška; Podržava do 32 IP kamere (rezolucija do 8MP, ukupni bitrate do 128Mbps); Dimenzije 2U, 440mmx455mmx95mm (WxDxH), rek montaža; Masa 7kg; Napajanje 110-240VAC; POS podrška; Podržava HDCVI audio i alarm; Smart Fan; Reset taster na ploči; Broadcast audio kvalitet	€ 535,00	€ 891,67	 	Na lageru	
------------	---	----------	----------	--	-----------	--





PoC DVR-ovi

Kod	OPIS	VP	MSRP		Slika		
PoC 8+4 kanalni penta-brid, 200fps@1080P, 120fps@4MP, metalno kućište, 1X audio ulaz/izlaz, 1X SATA, RS485, HDMI + VGA, network							
XVRS108H-4KL-X-8P	PoC (Power over Coax) 8+4 kanalni stand-alone penta-brid DVR (analog + HDCVI + AHD + TVI + IP); H.265+/H.265/H.264+/H.264 video kompresija; AAC (samo za kanal 1), G.711A, G.711U, PCM audio kompresija; 8 video ulaza; VGA izlaz; HDMI izlaz; 1 audio ulaz/1 izlaz; USB x2 (1x USB 2.0 i 1x USB 3.0) - za lokalni backup i miš; RS485; Rezolucija/frame rate za snimanje po kameri: 4K(1~7fps); 6MP(1~10fps); 5MP(1~12fps); 4MP/3MP(1~15fps); 4M-N/1080P/720P/960H/D1/CIF(1~25/30fps); Rezolucija prikaza 1280×720 ili do 3840×2160 (HDMI); Dual stream; 1 SATA port - HDD do 10TB; Network port 10/100/1000Mbps; CMS software (Smart PSS); Web pristup; Software za iOS i Android platforme; P2P podrška; Napaja kamere ukupne snage do 48W - do 8 PoC kamera Lite serije ili 4 PoC kamere Pro serije; Podržava do 4 dodatne IP kamere (rezolucija do 8MP, bitrate do 48Mbps) ili do 12 IP kamera; Dimenzije Mini 1U, 325mm ×255mm ×55mm (W×D×H); Masa 1.35kg; Napajanje 110-240VAc preko pril. adaptera 53Vdc; POS podrška; Podržava HDCVI audio i alarm; Smart Fan; Reset taster na ploči; Broadcast audio kvalitet	€ 165,00	€ 275,00		 		
PoC 16+8 kanalni penta-brid, 240fps@4MP, 112fps@4K, metalno kućište, 1X audio ulaz/izlaz, 1X SATA, RS485, HDMI + VGA, network							
XVRS216AN-4KL-X-16P	16+8 kanalni stand-alone penta-brid DVR (analog + HDCVI + AHD + TVI + IP); H.265+/H.265/H.264+/H.264 video kompresija; AAC (samo za kanal 1), G.711A, G.711U, PCM audio kompresija; 16 video ulaza; VGA izlaz; HDMI izlaz; BNC kompozitni izlaz; 1 audio ulaz/1 izlaz; USB x2 (1x USB 2.0 i 1x USB 3.0) - za lokalni backup i miš; RS485; Rezolucija/frame rate za snimanje po kameri: 4K(1~7fps); 6MP(1~10fps); 5MP(1~12fps); 4MP/3MP(1~15fps); 4M-N /1080P /720P /960H /D1 /CIF (1~25/30fps); Rezolucija prikaza 1280×720 ili do 3840×2160 (HDMI); Dual stream; 2 SATA port - HDD do 10TB; Network port 10/100/1000Mbps; CMS software (Smart PSS); Web pristup; Software za iOS i Android; P2P podrška; Napaja kamere ukupne snage do 96W - do 16 PoC kamera Lite serije ili 8 PoC kamera Pro serije; Podržava do 8 dodatne IP kamere (rezolucija do 8MP, bitrate do 64Mbps) ili do 24 IP kamera; Dimenzije 1U, 375mm ×287mm ×53mm (W×D×H); Masa 1.7kg; Napajanje 110-240VAc preko adaptera 54Vdc; POS podrška; Podržava HDCVI audio i alarm; Smart Fan; Reset taster na ploči; Broadcast audio kvalitet	€ 310,00	€ 516,67		 		

HD Network video rekorderi serije 2XXX-S2 i serije 2XXX-4KS2

Kod	OPIS	VP	MSRP	Slika		
NVR serije EZ-IP, 4-kanalni, 1X SATA						
NVR1B04	HD Network video rekorder; Za do 4 IP kamere; Podržane rezolucije snimanja 8MP/ 6Mp/ 5Mp/ 4Mp/ 3Mp/ 1080P/ 720P/ D1; ONVIF, CGI, SDK; HDMI izlaz (do 3840x2160); VGA; Multi screen prikaz 1/4 kamere; Podržane kompresije H.265+/H.264+; Dual Stream; Dolazni bit rate do 80Mbps; 1x RJ-45 port (10/100Mbps); 2 porta USB2.0 - kontrola mišem i backup; 1 SATA port - do 1 HDD (6TB maks.); Napajanje preko eksterne napajalčke jedinice 230VAc/12VDC 2A; Dimenzije Smart 1U, 204.6mmx204.6mmx45.2mm (ŠxDxV); Masa 0.43kg; CMS software (Smart PSS); Web pristup; Software za iOS i Android; P2P podrška	€ 37,80	€ 63,00		Na lageru	
NVR serije EZ-IP, 4-kanalni, 1X SATA						
NVR1B08	HD Network video rekorder; Za do 8 IP kamere; Podržane rezolucije snimanja 8MP/ 6Mp/ 5Mp/ 4Mp/ 3Mp/ 1080P/ 720P/ D1; ONVIF, CGI, SDK; HDMI izlaz (do 3840x2160); VGA; Multi screen prikaz 1/4/8/9 kamere; Podržane kompresije H.265+/H.264+; Dual Stream; Dolazni bit rate do 80Mbps; 1x RJ-45 port (10/100Mbps); 2 porta USB2.0 - kontrola mišem i backup; 1 SATA port - do 1 HDD (6TB maks.); Napajanje preko eksterne napajalčke jedinice 230VAc/12VDC 2A; Dimenzije Smart 1U, 204.6mmx204.6mmx45.2mm (ŠxDxV); Masa 0.43kg; CMS software (Smart PSS); Web pristup; Software za iOS i Android; P2P podrška	€ 42,60	€ 71,00		Na lageru	
NVR serije 2XXX-4KS2, 4-kanalni, 1X SATA						
NVR2104HS-4KS2	HD Network video rekorder; Za do 4 IP kamere; Podržane rezolucije snimanja 8MP/ 6Mp/ 5Mp/ 4Mp/ 3Mp/ 1080P/ 720P/ D1; ONVIF 2.4, CGI, SDK; HDMI izlaz (do 3840x2160); VGA; Multi screen prikaz 1/4 kamere; Podržane kompresije H.265/H.264; Dual Stream; Dolazni bit rate do 80Mbps; 1x RJ-45 port (10/100Mbps); 2 porta USB2.0 - kontrola mišem i backup; 1 SATA port - do 1 HDD (6TB maks.); Napajanje preko eksterne napajalčke jedinice 230VAc/12VDC 2A; Dimenzije Compact 1U, 260mmx224.9mmx47.6mm (ŠxDxV); Masa 0.8kg; CMS software (Smart PSS); Web pristup; Software za iOS i Android; P2P podrška	€ 54,00	€ 90,00		Na lageru	
NVR serije 2XXX-4KS2, 8-kanalni, 1X SATA						
NVR2108HS-4KS2	HD Network video rekorder; Za do 8 IP kamera; Podržane rezolucije snimanja 8MP/ 6Mp/ 5Mp/ 4Mp/ 3Mp/ 1080P/ 720P/ D1; ONVIF 2.4, CGI, SDK; HDMI izlaz (do 3840x2160); VGA; Multi screen prikaz 1/4/8/9 kamera; Podržane kompresije H.265/H.264; Dual Stream; Dolazni bit rate do 80Mbps; 1x RJ-45 port (10/100Mbps); 2 porta USB2.0 - kontrola mišem i backup; 1 SATA port - do 1 HDD (6TB maks.); Napajanje preko eksterne napajalčke jedinice 230VAc/12VDC 2A; Dimenzije Compact 1U, 260mmx224.9mmx47.6mm (ŠxDxV); Masa 0.8kg; CMS software (Smart PSS); Web pristup; Software za iOS i Android; P2P podrška	€ 64,20	€ 107,00		Na lageru	
NVR serije 2XXX-4KS2, 4-kanalni sa 4X PoE, 1X SATA						
NVR2104HS-P-4KS2	HD Network video rekorder; Za do 4 IP kamere; Podržane rezolucije snimanja 8MP/ 6Mp/ 5Mp/ 4Mp/ 3Mp/ 1080P/ 720P/ D1; ONVIF 2.4, CGI, SDK; HDMI izlaz (do 3840x2160); VGA; Multi screen prikaz 1/4 kamere; Podržane kompresije H.265/H.264; Dual Stream; Dolazni bit rate do 80Mbps; 1x RJ-45 port (10/100Mbps); 2 porta USB2.0 - kontrola mišem i backup; 1 SATA port - do 1 HDD (6TB maks.); Napajanje preko eksterne napajalčke jedinice 230VAc/48VDC 1.25A; Dimenzije Compact 1U, 260mmx224.9mmx47.6mm (ŠxDxV); Masa 0.8kg; CMS software (Smart PSS); Web pristup; Software za iOS i Android; P2P podrška; Sa 4 PoE (IEEE802.3at/af) mrežna porta; Do 25.5W po portu; Do 50W ukupno	€ 89,40	€ 149,00		Na lageru	
NVR serije 2XXX-S2, 8-kanalni sa 8X PoE, 1X SATA						
NVR2108HS-8P-S2	HD Network video rekorder; Za do 8 IP kamera; Podržane rezolucije snimanja 6Mp/ 5Mp/ 4Mp/ 3Mp/ 1080P/ 720P/ D1; ONVIF 2.4, CGI; HDMI izlaz (do 1080P); VGA; Multi screen prikaz 1/4/8/9 kamera; Podržane kompresije H.264 i H.264+; Dual Stream; Bit rate za snimanje do 80Mbps; 1x RJ-45 port (10/100Mbps); 2 porta USB2.0 - kontrola mišem i backup; 1 SATA port - do 1 HDD (6TB maks.); Napajanje preko eksterne napajalčke jedinice 230VAc/48VDC 2A; Dimenzije Compact 1U, 260mmx224.9mmx47.6mm (ŠxDxV); Masa 0.8kg; CMS software (Smart PSS); Web pristup; Software za iOS i Android; P2P podrška; Sa 8 PoE (IEEE802.3at/af) mrežnih portova	€ 100,00	€ 166,67		Na lageru	

HD Network video rekorderi serije NVR4XXX-4KS2

Kod	OPIS	VP	MSRP		Slika		
NVR-ovi serije NVR41XXH, 4-kanalni, 1X SATA							
NVR4104HS-4KS2	HD Network video rekorder; Za do 4 IP kamere; Podržane rezolucije snimanja 8Mp/ 6Mp/ 5MP/ 4MP/ 3MP/ 1080P/ 1.3MP/ 720P; ONVIF; HDMI izlaz (do 3840x2160); VGA; Multi screen prikaz 1/4 kamere; Podržane kompresije H.265 i H.264; Dual Stream; Bit rate za snimanje do 80Mbps; 1x RJ-45 port (10/100Mbps); 2 USB porta - zadnji + prednji USB2.0 - kontrola mišem i backup; 1 SATA porta (6TB maks.); Napajanje 12V 2A; Dimenzije Compact 1U, 260mmx224.9mmx47.6mm(ŠxDxV); Masa 0,8kg; CMS software (PSS i PSS Smart); Web pristup; Software za Win Mobile, iPhone i Android platforme; Besplatan Dahua DDNS; P2P podrška;	€ 70,80	€ 118,00			Na lageru	
NVR-ovi serije NVR41XXH, 8-kanalni, 1X SATA							
NVR4108HS-4KS2	HD Network video rekorder; Za do 8 IP kamere; Podržane rezolucije snimanja 8Mp/ 6Mp/ 5MP/ 4MP/ 3MP/ 1080P/ 1.3MP/ 720P; ONVIF; HDMI izlaz (do 3840x2160); VGA; Multi screen prikaz 1/4/8 kamere; Podržane kompresije H.265 i H.264; Dual Stream; Bit rate za snimanje do 80Mbps; 1x RJ-45 port (10/100Mbps); 2 USB porta - zadnji + prednji USB2.0 - kontrola mišem i backup; 1 SATA porta (6TB maks.); Napajanje 12V 2A; Dimenzije Compact 1U, 260mmx224.9mmx47.6mm(ŠxDxV); Masa 0,8kg; CMS software (PSS i PSS Smart); Web pristup; Software za Win Mobile, iPhone i Android platforme; Besplatan Dahua DDNS; P2P podrška;	€ 87,00	€ 145,00			Na lageru	
NVR-ovi serije NVR41XXH, 16-kanalni, 1X SATA							
NVR4116HS-4KS2	HD Network video rekorder; Za do 16 IP kamere; Podržane rezolucije snimanja 8Mp/ 6Mp/ 5MP/ 4MP/ 3MP/ 1080P/ 1.3MP/ 720P; ONVIF; HDMI izlaz (do 3840x2160); VGA; Multi screen prikaz 1/4/8/9/16 kamere; Podržane kompresije H.265 i H.264; Dual Stream; Bit rate za snimanje do 80Mbps; 1x RJ-45 port (10/100Mbps); 2 USB porta - zadnji + prednji USB2.0 - kontrola mišem i backup; 1 SATA porta (6TB maks.); Napajanje 12V 2A; Dimenzije Compact 1U, 260mmx224.9mmx47.6mm(ŠxDxV); Masa 0,8kg; CMS software (PSS i PSS Smart); Web pristup; Software za Win Mobile, iPhone i Android platforme; Besplatan Dahua DDNS; P2P podrška;	€ 99,60	€ 166,00			Na lageru	
NVR-ovi serije NVR41XX-4KS2, 4-kanalni sa 4X PoE, 1X SATA							
NVR4104HS-P-4KS2	HD Network video rekorder sa integrisanim 4-portnim PoE switch-em; Za do 4 IP kamere; Podržane rezolucije snimanja 8Mp/ 6Mp/ 5MP/ 4MP/ 3MP/ 1080P/ 1.3MP/ 720P; ONVIF; HDMI izlaz (do 3840x2160); VGA; Multi screen prikaz 1/4 kamere; Podržane kompresije H.265 i H.264; Dual Stream; Bit rate za snimanje do 80Mbps; 1x RJ-45 port (10/100Mbps) + 4x 10/100Mbps PoE (IEEE802.3af) porta; PoE budžet do 25.5W po portu, 50W ukupno; 2 USB porta - zadnji + prednji USB2.0 - kontrola mišem i backup; 1 SATA porta (6TB maks.); Napajanje 48V 1.5A; Dimenzije Compact 1U, 260mmx224.9mmx47.6mm(ŠxDxV); Masa 0,8kg; CMS software (PSS i PSS Smart); Web pristup; Software za Win Mobile, iPhone i Android platforme; Besplatan Dahua DDNS; P2P podrška;	€ 114,60	€ 191,00			Na lageru	
NVR-ovi serije NVR42XX-4KS2, 8-kanalni, 2X SATA							
NVR4208-4KS2	HD Network video rekorder; Za do 8 IP kamere; Podržane rezolucije snimanja 8Mp/ 6Mp/ 5MP/ 4MP/ 3MP/ 1080P/ 1.3MP/ 720P; ONVIF 2.4; HDMI izlaz (do 3840x2160); VGA; Multi screen prikaz 1/4/8/9 kamere; Podržane kompresije H.265/H.264; Dual Stream; Bit rate za snimanje do 200Mbps; 6 alarmnih ulaza; 2 relejna izlaza; RJ-45 port (10/100M/1000M); 2 USB porta - USB 3.0 + USB2.0 - kontrola mišem i backup; 2 SATA III porta - do 2 HDD-a (12TB maks.); Audio ulaz/izlaz; Napajanje 12Vdc 4A; Dimenzije 1U, 375mmx327.5mmx53mm (ŠxDxV); Masa 2.7kg; CMS software (PSS i PSS Smart); Web pristup; Software za Win Mobile, iPhone i Android platforme; Besplatan Dahua DDNS; P2P podrška	€ 110,40	€ 184,00			Na lageru	
NVR-ovi serije NVR42XX-4KS2, 16-kanalni, 2X SATA							
NVR4216-4KS2	HD Network video rekorder; Za do 16 IP kamere; Podržane rezolucije snimanja 8Mp/ 6Mp/ 5MP/ 4MP/ 3MP/ 1080P/ 1.3MP/ 720P; ONVIF 2.4; HDMI izlaz (do 3840x2160); VGA; Multi screen prikaz 1/4/8/9/16 kamere; Podržane kompresije H.265/H.264; Dual Stream; Bit rate za snimanje do 200Mbps; 6 alarmnih ulaza; 2 relejna izlaza; RJ-45 port (10/100M/1000M); 2 USB porta - USB 3.0 + USB2.0 - kontrola mišem i backup; 2 SATA III porta - do 2 HDD-a (12TB maks.); Audio ulaz/izlaz; Napajanje 12Vdc 4A; Dimenzije 1U, 375mmx327.5mmx53mm (ŠxDxV); Masa 2.7kg; CMS software (PSS i PSS Smart); Web pristup; Software za Win Mobile, iPhone i Android platforme; Besplatan Dahua DDNS; P2P podrška	€ 125,40	€ 209,00			Na lageru	

HD Network video rekorderi serije NVR4XXX-4KS2

Kod	OPIS	VP	MSRP		Slika			
NVR-ovi serije NVR42XX-XXP-4KS2, 8-kanalni sa 8X PoE, 2X SATA								
NVR4208-8P-4KS2	HD Network video rekorder sa integrisanim 8-portnim PoE switch-em; Za do 8 IP kamera; Podržane rezolucije snimanja 8Mp/ 6Mp/ 5MP/ 4MP/ 3MP/ 1080P/ 1.3MP/ 720P; ONVIF 2.4; HDMI izlaz (do 3840x2160); VGA; Multi screen prikaz 1/4/8/9 kamera; Podržane kompresije H.265/H.264; Dual Stream; Bit rate za snimanje do 200Mbps; 4 alarmna ulaza; 2 relejna izlaza; RJ-45 port (10/100M/1000M) + 8x 10/100Mbps PoE (IEEE802.3at) porta; Do 25.5W na jednom portu, 80W ukupno; 2 USB porta - USB 3.0 + USB2.0 - kontrola mišem i backup; 2 SATA III porta - do 2 HDD-a (12TB maks.); Audio ulaz/izlaz; Napajanje 220VAc do 89.6W; Dimenzije 1U, 375mmx275mmx56mm (ŠxDxV); Masa 1.65kg; CMS software (PSS i PSS Smart); Web pristup; Software za Win Mobile, iPhone i Android platforme; Besplatan Dahua DDNS; P2P podrška	€ 186,00	€ 310,00	8x VIDEO REC 200Mbps ANR P2P Corridor PLUS & PLAY H.265 /H.264 Do 8MP 4K 1080P/VGA Alarm In/out 12TB Maks. 2x USB (2.0 3.0) 8x PoE Class 3			Na lageru	

NVR-ovi serije NVR42XX-XXP-4KS2, 16-kanalni sa 16X PoE, 2X SATA

NVR4216-16P-4KS2	HD Network video rekorder sa integrisanim 16-portnim PoE switch-em; Za do 16 IP kamera; Podržane rezolucije snimanja 8Mp/ 6Mp/ 5MP/ 4MP/ 3MP/ 1080P/ 1.3MP/ 720P; ONVIF 2.4; HDMI izlaz (do 3840x2160); VGA; Multi screen prikaz 1/4/8/9/16 kamera; Podržane kompresije H.265/H.264; Dual Stream; Bit rate za snimanje do 200Mbps; 6 alarmnih ulaza; 2 relejna izlaza; RJ-45 port (10/100M/1000M) + 16x 10/100Mbps PoE (IEEE802.3at) porta; Do 25.5W na jednom portu, 130W ukupno; 2 USB porta - USB 3.0 + USB2.0 - kontrola mišem i backup; 2 SATA III porta - do 2 HDD-a (12TB maks.); Audio ulaz/izlaz; Napajanje 220VAc do 143.2W; Dimenzije 1U, 375mmx275mmx56mm (ŠxDxV); Masa 2.7kg; CMS software (PSS i PSS Smart); Web pristup; Software za Win Mobile, iPhone i Android platforme; Besplatan Dahua DDNS; P2P podrška	€ 255,00	€ 425,00				Na lageru	
------------------	---	----------	----------	---	---	---	-----------	--



NVR-ovi serije NVR44XX-XXP-4KS2, 16-kanalni sa 16X PoE, 4X SATA, rek montaža

NVR4416-16P-4KS2	16-kanalni HD Network video rekorder sa integrisanim 16-portnim PoE switch-em; Za do 16 IP kamera; Podržane rezolucije snimanja 8Mp, 6Mp, 5Mp, 3Mp, 1080P, 1.3Mp, 720P, ...; ONVIF; HDMI izlaza (do 3840x2160); VGA; Multi screen prikaz 1/4/8/9/16 kamera; Podržane kompresije H.265/H.264; Dual Stream; Bit rate za snimanje do 200Mbps; 16 alarmnih ulaza; 6 relejnih izlaza; 1x RJ-45 port (10/100M/1000M) + 16x 10/100Mbps PoE (IEEE802.3at) porta; Do 25.5W na jednom portu, 150W ukupno; 2 USB porta - USB 3.0 + USB2.0 - kontrola mišem i backup; 4 SATA porta - do 4 HDD-a (24TB maks.); RS232 port; RS485 port; Audio ulaz/izlaz; Napajanje 220VAc 163.7W Maks.; Dimenzije 1.5U, 440mmx411.1mmx76mm(ŠxDxV); Masa 4.7g; CMS software (PSS i PSS Smart); Web pristup; Software za Win Mobile, iPhone i Android platforme; Besplatan Dahua DDNS; P2P podrška; Easy4IP podrška	€ 325,20	€ 542,00				Na lageru	
------------------	--	----------	----------	---	---	---	-----------	--

HD Network video rekorderi serije NVR5XXX-4KS2

Kod	OPIS	VP	MSRP		Slika		
NVR-ovi serije NVR52XX-4KS2, 16-kanalni, 2X SATA							
NVR5216-4KS2	16-kanalni HD Network video rekorder; Podržane rezolucije snimanja 12Mp/ 8Mp/ 6Mp/ 5Mp/ 4Mp/ 3Mp/ 1080P / 720P/ D1; ONVIF 2.4; HDMI izlaza (do 3840x2160); VGA; Multi screen prikaz do 16 kamera; Dekoding do 16 kanala @1080P H.265/H.264; Podržane kompresije H.265/H.264/MJPEG/MPEG4; Dual Stream; Bit rate za snimanje do 320Mbps; 4 alarmna ulaza; 2 relejna izlaza; RJ-45 port (10/100M/1000M); 2 USB porta - prednji USB 2.0 + zadnji USB 3.0 - kontrola mišem i backup; 2 SATA porta - do 2 HDD-a (12TB maks.); RS232 port; Napajanje 220VAc 16.7W; Dimenzije 1U, 375mmx282mmx56mm(ŠxDxV); Masa 1.6kg; CMS software (PSS i PSS Smart); Web pristup; Software za Win Mobile, iPhone i Android platforme; Besplatan Dahua DDNS; P2P podrška	€ 195,00	€ 325,00	OLD 16x VIDEO REC 320Mbps ANR P2P Corridor H.265/ H.264/ MJPEG 4K Alarm In/out 12TB Maks. 2x USB (2.0 3.0) RS232	4K UHD  H. 265 ONVIF	Na lageru	

HD Network video rekorderi serije NVR5XXX-4KS2

Kod	OPIS	VP	MSRP	Slika		
NVR-ovi serije NVR52XX-4KS2, 32-kanalni, 2X SATA						
NVR5232-4KS2	32-kanalni HD Network video rekorder; Podržane rezolucije snimanja 12Mp/ 8Mp/ 6Mp/ 5Mp/ 4Mp/ 3Mp/ 1080P / 720P/ D1; ONVIF 2.4; HDMI izlaza (do 3840x2160); VGA; Multi screen prikaz do 36 kamera; Dekodiranje do 16 kanala @1080P H.265/H.264; Podržane kompresije H.265/H.264/MJPEG/MPEG4; Dual Stream; Bit rate za snimanje do 320Mbps; 4 alarmna ulaza; 2 relejna izlaza; RJ-45 port (10/100M/1000M); 2 USB porta - prednji USB 2.0 + zadnji USB 3.0 - kontrola mišem i backup; 2 SATA porta - do 2 HDD-a (12TB maks.); RS232 port; Napajanje 220VAC 16.7W; Dimenzije 1U, 375mmx282mmx56mm(ŠxDxV); Masa 1.6kg; CMS software (PSS i PSS Smart); Web pristup; Software za Win Mobile, iPhone i Android platforme; Besplatan Dahua DDNS; P2P podrška	€ 239,40	€ 399,00			Na lageru
NVR-ovi serije NVR52XX-4KS2E, 8-kanalni, 8X PoE (ePoE), 2X SATA						
NVR5208-8P-4KS2E	8-kanalni HD Network video rekorder sa integrisanim 8-portnim PoE switch-em; Podržane rezolucije snimanja 12Mp/ 8Mp/ 6Mp/ 5Mp/ 4Mp/ 3Mp/ 1080P / 720P/ D1; ONVIF 2.4; HDMI izlaza (do 3840x2160); VGA; Multi screen prikaz do 1/4/9 kamera; Dekodiranje do 8 kanala @1080P H.265/H.264; Podržane kompresije H.265/H.264/MJPEG/MPEG4; Dual Stream; Bit rate za snimanje do 320Mbps; 4 alarmna ulaza; 2 relejna izlaza; RJ-45 port (10/100M/1000M); 2 USB porta - prednji USB 2.0 + zadnji USB 3.0 - kontrola mišem i backup; 2 SATA porta - do 2 HDD-a (20TB maks.); RS232 port; RS485; 8 PoE portova (IEEE802.3af/at); Do 25.5W po portu, 130W ukupno; Podržava ePoE i EoC na svim portovima; 1 mrežni RJ-45 Port (10/100/1000Mbps); Napajanje 220VAC 15.2W za NVR i do 130W za PoE; Dimenzije 1U, 375mm x 326.5mm x 53mm (ŠxDxV); Masa neto 2.7kg; CMS software (PSS i PSS Smart); Web pristup; Software za Win Mobile, iPhone i Android platforme; Besplatan Dahua DDNS; P2P podrška	€ 334,20	€ 557,00			Na lageru
NVR-ovi serije NVR52XX-4KS2E, 16-kanalni, 8X PoE (ePoE), 2X SATA						
NVR5216-8P-4KS2E	16-kanalni HD Network video rekorder sa integrisanim 8-portnim PoE switch-em; Podržane rezolucije snimanja 12Mp/ 8Mp/ 6Mp/ 5Mp/ 4Mp/ 3Mp/ 1080P / 720P/ D1; ONVIF 2.4; HDMI izlaza (do 3840x2160); VGA; Multi screen prikaz do 1/4/9/16 kamera; Dekodiranje do 16 kanala @1080P H.265/H.264; Podržane kompresije H.265/H.264/MJPEG/MPEG4; Dual Stream; Bit rate za snimanje do 320Mbps; 4 alarmna ulaza; 2 relejna izlaza; RJ-45 port (10/100M/1000M); 2 USB porta - prednji USB 2.0 + zadnji USB 3.0 - kontrola mišem i backup; 2 SATA porta - do 2 HDD-a (20TB maks.); RS232 port; RS485; 8 PoE portova (IEEE802.3af/at); Do 25.5W po portu, 130W ukupno; Podržava ePoE i EoC na svim portovima; 1 mrežni RJ-45 Port (10/100/1000Mbps); Napajanje 220VAC 15.2W za NVR i do 130W za PoE; Dimenzije 1U, 375mm x 326.5mm x 53mm (ŠxDxV); Masa neto 2.7kg; CMS software (PSS i PSS Smart); Web pristup; Software za Win Mobile, iPhone i Android platforme; Besplatan Dahua DDNS; P2P podrška	€ 354,60	€ 591,00			Na lageru
NVR-ovi serije NVR42XX-4KS2, 32-kanalni, 4X SATA, rek montaža						
NVR5432-4KS2	32-kanalni HD Network video rekorder; Podržane rezolucije snimanja 12Mp/ 8Mp/ 6Mp/ 5Mp/ 4Mp/ 3Mp/ 1080P / 720P/ D1; ONVIF 2.4; 2 HDMI izlaza (1 do 3840x2160 i drugi do 1080P); VGA; Multi screen prikaz do 36 kamera; Dekodiranje do 16 kanala @1080P H.265/H.264; Podržane kompresije H.265/H.264/MJPEG/MPEG4; Dual Stream; Bit rate za snimanje do 320Mbps; 16 alarmnih ulaza; 6 relejnih izlaza; 2x RJ-45 port (10/100M/1000M); 3 USB porta - prednji USB 2.0 + 2x zadnji USB 3.0 - kontrola mišem i backup; 4 SATA porta - do 4 HDD-a (24TB maks.); eSATA port (do 16TB eksterno); RS232 port; Napajanje 220VAC 16.7W; Dimenzije 1,5U, 440mm x413mmx75mm(ŠxDxV); Masa 4.65kg; CMS software (PSS i PSS Smart); Web pristup; Software za Win Mobile, iPhone i Android platforme; Besplatan Dahua DDNS; P2P podrška	€ 356,40	€ 594,00			Na lageru
NVR-ovi serije NVR52XX-4KS2, 24-kanalni, 2X SATA, 24X PoE						
NVR5224-24P-4KS2	24-kanalni HD Network video rekorder sa integrisanim 24-portnim PoE switch-em; Za do 24 IP kamera; Podržane rezolucije snimanja 12Mp/ 8Mp/ 6Mp/ 5Mp/ 4Mp/ 3Mp/ 1080P/ 1.3MP/ 720P; ONVIF 2.4; HDMI izlaz (do 3840x2160); VGA; Multi screen prikaz 1/4/8/9/16/25 kamera; Podržane kompresije Smart H.265+/H.265/Smart H.264+/H.264/MJPEG; Dual Stream; Dolazni bit rate do 320Mbps; 4 alarmna ulaza; 2 relejna izlaza; RJ-45 port (10/100M/1000M) + 24x 10/100Mbps PoE 24 ports (IEEE802.3af/at) porta; Do 25.5W na jednom portu, 210W ukupno; 2 USB porta - USB 3.0 + USB2.0 - kontrola mišem i backup; 2 SATA III porta - do 2 HDD-a (16TB maks.); Audio ulaz/izlaz; Napajanje 220VAC do 16W za sam NVR; Dimenzije 1U, 440mmx419.96mmx43.65mm (ŠxDxV); Sa priborom za montažu u rek; Masa 4.5kg; CMS software (PSS i PSS Smart); Web pristup; Software za Win Mobile, iPhone i Android platforme; Besplatan Dahua DDNS; P2P podrška	€ 464,40	€ 774,00			Na lageru

HD Network video rekorderi serije NVR5XXX-4KS2

Kod	OPIS	VP	MSRP		Slika			
NVR-ovi serije NVR54XX-4KS2, 24-kanalni, 4X SATA, 24X PoE								
NVR5424-24P-4KS2	24-kanalni HD Network video rekorder sa integrisanim 24-portnim PoE switch-em; Za do 24 IP kamera; Podržane rezolucije snimanja 12Mp/ 8Mp/ 6Mp/ 5MP/ 4MP/ 3MP/ 1080P/ 1.3MP/ 720P; ONVIF 2.4; 2x HDMI izlaz (do 3840x2160); VGA; Multi screen prikaz 1/4/8/9/16/25 kamera; Podržane kompresije Smart H.265+/H.265/Smart H.264+/H.264/MJPEG; Dual Stream; Dolazni bit rate do 320Mbps; 16 alarmnih ulaza; 6 relejnih izlaza; RJ-45 port (10/100M/1000M) + 24x 10/100Mbps PoE 24 ports (IEEE802.3af/at) porta; Do 25.5W na jednom portu, 210W ukupno; 3 USB porta - 2x USB 3.0 + USB2.0 - kontrola mišem i backup; 4 SATA III porta - do 4 HDD-a (24TB maks.); Audio ulaz/izlaz; Napajanje 220VAc do 18W za sam NVR; Dimenzije 1.5U, 440mm x 413.3mm x 76mm (ŠxDxV); Sa priborom za montažu u rek; Masa 4.7kg; CMS software (PSS i PSS Smart); Web pristup; Software za Win Mobile, iPhone i Android platforme; Besplatan Dahua DDNS; P2P podrška	€ 553,80	€ 923,00			Na lageru		

HD Network video rekorderi serije NVR608-XX-4KS2

Kod	OPIS	VP	MSRP		Slika		
NVR608-32-4KS2	32-kanalni HD Network video rekorder; Za do 32 IP kamera; Podržane rezolucije snimanja 12MP, 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, 720P, 960H, D1, CIF, QCIF, VGA; ONVIF 2.4; 2x HDMI izlaz (do 3840x2160); VGA; Multi screen prikaz 1/4/8/9/16/25/36 kamera na HDMI 1; Do 16 kamera na HDMI 2; Podržane kompresije H.265/H.264/MJPEG; Dual Stream; Bit rate: Dolazni do 384Mbps, odlazni do 384Mbps, za snimanje do 256Mbps; 16 alarmnih ulaza; 8 relejnih izlaza; 2x RJ-45 port (10/100M/1000M); 4 USB porta - USB 3.0 + 3x USB2.0 - kontrola mišem i backup; eSATA port; 8 SATA III portova - do 8 HDD-a (48TB maks.); Integrisan RAID kontroler - RAID 0/1/5/6/10/50/60 podrška; Global HDD hot-spare podrška; Podržava N+M hot standby; RS232 port; RS485 port; Audio ulaz/izlaz; Napajanje 220Va 40W maks; Dimenzije 2U, 440mm x 451.08mm x 94.85mm(ŠxDxV); Masa 9kg; CMS software (PSS i PSS Smart); Web pristup; Software za Win Mobile, iPhone i Android platforme; Besplatan Dahua DDNS; P2P podrška	€ 470,00	€ 783,33			Na lageru	
NVR608-64-4K	64-kanalni HD Network video rekorder; Za do 64 IP kamera; Podržane rezolucije snimanja 12MP, 8MP, 6MP, 5MP, 3MP, 1080P, 720P, 960H, D1, CIF, QCIF, VGA; ONVIF 2.4; 2x HDMI izlaz (do 3840x2160); VGA; Multi screen prikaz 1/4/8/9/16/25/36 kamera na HDMI 1; Do 16 kamera na HDMI 2; Podržane kompresije H.264/MPEG4; Dual Stream; Bit rate: Dolazni do 384Mbps, odlazni do 384Mbps, za snimanje do 256Mbps; 16 alarmnih ulaza; 8 relejnih izlaza; 2x RJ-45 port (10/100M/1000M); 4 USB porta - USB 3.0 + 3x USB2.0 - kontrola mišem i backup; eSATA port; 8 SATA III portova - do 8 HDD-a (48TB maks.); Integrisan RAID kontroler - RAID 0/1/5/6/10/50/60 podrška; Global HDD hot-spare podrška; Podržava N+M hot standby; RS232 port; RS485 port; Audio ulaz/izlaz; Napajanje 220Va 40W Maks; Dimenzije 2U, 486mmx454,9mmx91mm(ŠxDxV); Masa 9kg; CMS software (PSS i PSS Smart); Web pristup; Software za Win Mobile, iPhone i Android platforme; Besplatan Dahua DDNS; P2P podrška	€ 850,00	€ 1.416,67			Na lageru	
NVR608-128-4KS2	128-kanalni HD Network video rekorder; Za do 128 IP kamera; Podržane rezolucije snimanja 12MP, 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, 720P, 960H, D1, CIF, QCIF, VGA; ONVIF 2.4; 2x HDMI izlaz (do 3840x2160); VGA; Multi screen prikaz 1/4/8/9/16/25/36 kamera na HDMI 1; Do 16 kamera na HDMI 2; Podržane kompresije H.265/H.264/MJPEG; Dual Stream; Dolazni bit-rate do 384Mbps; 16 alarmnih ulaza; 8 relejnih izlaza; 2x RJ-45 port (10/100M/1000M); 4 USB porta - 2x USB 3.0 + 2x USB2.0 - kontrola mišem i backup; eSATA port; 8 SATA III portova - do 8 HDD-a (64TB maks.); Integrisan RAID kontroler - RAID 0/1/5/6/10/50/60 podrška; Global HDD hot-spare podrška; Podržava N+M hot standby; RS232 port; RS485 port; Audio ulaz/izlaz; Napajanje 220Va 20W maks; Dimenzije 2U, 444mm x 457.08mm x 95mm(ŠxDxV); Masa 9kg neto; CMS software (PSS i PSS Smart); Web pristup; Software za iOS i Android platforme; Besplatan Dahua DDNS; P2P podrška; EN55022, EN55024, EN50130-4, EN60950-1	€ 925,00	€ 1.541,67			Na lageru	

Instrumenti i programatori

Kod	OPIS	VP	MSRP		Slika		
PFM820	Programator za HDCVI kamere Cannon/S3 serije; Izbor moda rada - analogni/HDCVI/AHD/TVI; Potrebne 2 AAA baterije; Dimenzije 90mmx41mmx21mm	€ 10,20	€ 17,00			Na lageru	
PFM906	Univerzalni instrument za analogne, HDCVI, TVI, AHD, SDI i IP instalacije; 7" touch-screen rezolucije 1920x1200 ; HDMI ulaz; HDMI izlaz; PoE, 12VDC 2A i USB 5V 2A izlazi; 37Wh litijum jon polimer baterija (10 sati normalnog rada); TDR (za mrežne i koaksijalne kablove); Optički VFL (Visual Fault Locator); Optički OPM (Optical Power Meter); Digitalni multimetar; 3x 10/100M RJ45 mrežni port; 2x video ulaz (SDI, HDCVI/TVI/AHD/CVBS), 1x video izlaz; 1x TDR, 1x OPM, 1x VLS, 1x RS485, 1x 12VDC ulaz (punjenje), 1x HDMI izlaz, 1x HDMI ulaz, 1x audio ulaz, 1x audio izlaz, 1x Micro SD; Podrška Dahua i ONVIF IP kamerame rezolucije do 4K; Podrška HDCVI/ AHD/ TVI/ CVBS kamere rezolucije do 2560x1440; Podrška SDI kamere do 60fps 1080p; RS485 port sa podrškom za preko 30 protokola (PELCO-D/P, Samsung, Panasonic, ...); Mrežni alati (IP address scan, Ping test, bandwidth test, port flashing, DHCP server); Funkcija lampe; Kalkulator; Snimanje sa analognih/IP kamera; Snimanje podsetnika; Ugrađen WiFi (2.4GHz); 8GB interne memorije; Podrška SD do 32GB; Opseg radne temperature -10°C~+55°C; Dimenzije 270mm x160mm x46mm; Masa neto 0.95kg	€ 505,80	€ 562,00			Na lageru	

Tastature

Kod	OPIS	VP	MSRP		Slika		
NKB1000	Mrežna upravljačka tastatura sa džojstikom; sa LC displejom 75.2mm x 33.85mm; Upravljanje Dahua DVR-ovima, NVR-ovima, speed-dome kamerama sa Dahua, Pelco-P i Pelco-D protokolom, Dahua IP Speed dome kamerama, Dahua IP koderima/dekoderima i Dahua Smart PSS software-om; Sa twist-to-zoom džojstikom; RJ-45,RS232,RS485,RS422 i USB konekcija; Mogućnost vezivanja slave tastatura; sa napajanjem 220VAC/12Vdc; dimenzije 330mmx160(140)mmx37.5(21)mm (WxDxH); masa 2,5Kg	€ 170,00	€ 283,33	3-axis USB CONTROL RJ-45 port LINUX		Na lageru	
NKB5000-F	Mrežna upravljačka tastatura sa džojstikom; Sa 10.1" TFT LCD touch screen (1280x800); Upravljanje Dahua DVR-ovima, NVR-ovima, PTZ kamerama, Dahua IP koderima/dekoderima i CMS software-om; Sa twist-to-zoom džojstikom; 2x RJ-45 port (10/100/1000M)), Wi-Fi; 2x USB3.0, 2x USB2.0; Wi-Fi (2.4GHz); RS485; 2X RS232; RS422; 4xHDMI; Audio ulaz/izlaz; 4x alarmni ulaz/4x alarmni izlaz; Dual-core Braswell CPU; Embedded LINUX 4.2.0; Dekodiranje do 16CH@2MP(30fps); Dimenzije 425mmx194mmx59mm; Masa 3.73kg; Napajanje 12Vdc 4A; Sa dodatnom mini tastaturom	€ 943,20	€ 1.572,00	3-axis USB CONTROL 2xRJ-45 port 4x HDMI Wi-Fi DUAL-CORE CPU LINUX		Na lageru	

Dekoderi

Kod	OPIS	VP	MSRP		Slika		
NVD0905DH-4I-4K	Ultra-HD mrežni video dekođer; Dekodiranje H.265/H.264/MJPEG/MPEG4/MPEG2 stream-ova rezolucije do 12MP; Dekodiranje PCM/G711/AAC audio stream-ova; Ulazi: 2x HDMI i 2x DVI-I input; Izlazi: 9x HDMI; Podrška 1/4/9/16 slika na svakom od izlaza; Performansa dekodiranja po grupi od tri HDMI izlaza: 3CH@12MP /4CH@4K /16CH@1080P /27CH@720P/ 48CH@D1; Ukupna performansa dekodiranja 9CH@12MP /12CH@4K /48CH@1080P /81CH@720P /144CH@D1; Do 3840x2160 na prvim 6 HDMI izlaza, do 2560x1600 na poslednja 3 izlaza; 2x RJ45 mrežni port (10M/100M/1000M); 3x RS232(1 DB9, 2 RJ45); 1x RS485; 4x alarmni ulaz/4x izlaz; Napajanje 100-240VAC 70W maks; Dimenzije 1.5U, 440x408x70mm; Rek montaža; Masa 4.8kg;	€ 1.092,00	€ 1.820,00			Na lageru	


Monitori

Kod	OPIS	VP	MSRP		Slika		
DHL22-F600-S	22" profesionalni monitor za 24/7 upotrebu; Vidljiva dijagonala 21.5"; Odnos stranica 16:9; LED; Rezolucija 1920 x 1080; Osvetljaj 200cd/m²; Kontrast 1000:1; Ugao gledanja 178°/178° (vertikalno/ horizontalno); Odziv 15ms; Ulazi: VGA(D-Sub)×1 /HDMI×1 /Audio×1; Inkorporirani zvučnici; Vesa 75x75mm; Dimenzije 502.8×299.8×47.6mm; Masa 3.2kg; Nap. 220VAc 25W	€ 135,00	€ 225,00	1080p HDMI/VGA 178 24/7 VESA 15ms		Na lageru	
LM22-L200	22" profesionalni monitor za 24/7 upotrebu; Vidljiva dijagonala 21.5"; Odnos stranica 16:9; LED; Rezolucija 1920 x 1080; Osvetljaj 200cd/m²; Kontrast 1000:1; Ugao gledanja 178°/178° (vertikalno/ horizontalno); Odziv 5ms; Ulazi: 1 HD (podržava HDCVI, HDTVI, AHD, CVBS), 1 VGA, 1 HDMI, 1 BNC, 1 Audio; Izlazi: 1 HD (podržava HDCVI, HDTVI, AHD, CVBS); Inkorporirani zvučnici; Vesa 100x100mm; Dimenzije 516.60 x316.70 x51.20mm; Masa 5kg; Napajanje 240VAc 30W	€ 173,00	€ 288,33	1080p HDMI/VGA 178 24/7 VESA 5ms HDCVI HDTVI AHD CVBS		Na lageru	
DHL24-F600	24" profesionalni monitor za 24/7 upotrebu; Vidljiva dijagonala 23.8"; Odnos stranica 16:9; LED; Rezolucija 1920 x 1080; Osvetljaj 250cd/m²; Kontrast 1000:1; Ugao gledanja 178°/178° (vertikalno/ horizontalno); Odziv 14ms; Ulazi: VGA(D-Sub)×1 /HDMI×1 /Audio×1; Inkorporirani zvučnici; Vesa 75x75mm; Dimenzije 553.2×328.1×48.5mm; Masa 3.8kg; Napajanje 240VAc 30W	€ 156,00	€ 260,00	1080p HDMI/VGA 178 24/7 VESA 5ms		Na lageru	
DHL27-F600	27" profesionalni monitor za 24/7 upotrebu; Vidljiva dijagonala 27"; Odnos stranica 16:9; LED; Rezolucija 1920 x 1080; Osvetljaj 250cd/m²; Kontrast 1000:1; Ugao gledanja 178°/178° (vertikalno/ horizontalno); Odziv 14ms; Ulazi: VGA(D-Sub)×1 /HDMI×1 /Audio×1; Inkorporirani zvučnici; Dimenzije 627×366.5×32.1mm; Masa 4.2kg; Napajanje 240VAc 27W	€ 190,00	€ 316,67	1080p HDMI/VGA 178 24/7 VESA 5ms 14ms		Na lageru	
DHL32-F600	32" profesionalni monitor za 24/7 upotrebu; Vidljiva dijagonala 31.5"; Odnos stranica 16:9; LED; Rezolucija 1920 x 1080; Osvetljaj 300cd/m²; Kontrast 1200:1; Ugao gledanja 178°/178° (vertikalno/horizontalno); Odziv 5ms; Ulazi: VGA(D-Sub)×1 /HDMI×2 / Display Port (DP) x1 /Audio×1; Inkorporirani zvučnici; Vesa 100x100; Dimenzije 731.2mm x435.6mm x79.2mm; Masa 5.4kg; Napajanje 220VAc 52W	€ 280,00	€ 466,67	1080p HDMI/VGA 178 24/7 VESA 5ms		Na lageru	
DHL43-F600	43" profesionalni monitor za 24/7 upotrebu; Vidljiva dijagonala 42.5"; Odnos stranica 16:9; LED; Rezolucija 1920 x 1080; Osvetljaj 350cd/m²; Kontrast 1200:1; Ugao gledanja 178°/178° (vertikalno/ horizontalno); Odziv 5ms; Ulazi: VGA(D-Sub)×1 /HDMI×1 /Audio×1; Inkorporirani zvučnici; Vesa 200x200; Dimenzije 967mm x561mm x86mm; Masa 7.7kg; Napajanje 220VAc 58W	€ 385,00	€ 641,67	1080p HDMI/VGA 178 24/7 VESA 5ms		Na lageru	
LM43-S400	43" 4K profesionalni monitor za 24/7 upotrebu; Odnos stranica 16:9; LED; Rezolucija 3840 x 2160; Osvetljaj 450cd/m²; Kontrast 4000:1; Ugao gledanja 178°/178° (vertikalno/ horizontalno); Odziv 8ms; 3D COMB filter i 3D Noise Reduction; Ultra tanak okvir 8mm; Ulazi: DP 1.2a×1, HDMI 2.0×2, VGA(D-Sub)×1, USB multimedia×1, Audio×1, RJ45(RS232)×1; Izlazi: RJ45(RS232)×1; Inkorporirani zvučnici 2x 5W; Vesa 400x400; Metalno kućište; Dimenzije 960.7×550.7×65.0mm; Neto masa 16.6kg; Napajanje 220VAc 105W; U kompletu sa nosačem za zidnu montažu i HDMI kablom; Opciono nosač za stonu montažu	€ 840,00	€ 1.400,00	4K HDMI/VGA 178 24/7 VESA 8ms Metal housing		PP	
LM49-S400	49" 4K profesionalni monitor za 24/7 upotrebu; Odnos stranica 16:9; LED; Rezolucija 3840 x 2160; Osvetljaj 450cd/m²; Kontrast 4700:1; Ugao gledanja 178°/178° (vertikalno/ horizontalno); Odziv 8ms; 3D COMB filter i 3D Noise Reduction; Ultra tanak okvir 8mm; Ulazi: DP 1.2a×1, HDMI 2.0×2, VGA(D-Sub)×1, USB multimedia×1, Audio×1, RJ45(RS232)×1; Izlazi: RJ45(RS232)×1; Inkorporirani zvučnici 2x 5W; Vesa 400x400; Metalno kućište; Dimenzije 1091.5×623.2×65.0mm ; Neto masa 20.5kg; Napajanje 220VAc 145W; U kompletu sa nosačem za zidnu montažu i HDMI kablom; Opciono nosač za stonu montažu	€ 980,00	€ 1.633,33	4K HDMI/VGA 178 24/7 VESA 8ms Metal housing		PP	
LM55-S400	55" 4K profesionalni monitor za 24/7 upotrebu; Odnos stranica 16:9; LED; Rezolucija 3840 x 2160; Osvetljaj 450cd/m²; Kontrast 5500:1; Ugao gledanja 178°/178° (vertikalno/ horizontalno); Odziv 6ms; 3D COMB filter i 3D Noise Reduction; Ultra tanak okvir 8mm; Ulazi: DP 1.2a×1, HDMI 2.0×2, VGA(D-Sub)×1, USB multimedia×1, Audio×1, RJ45(RS232)×1; Izlazi: RJ45(RS232)×1; Inkorporirani zvučnici 2x 5W; Vesa 400x400; Metalno kućište; Dimenzije 1227.2×699.6×65.0mm ; Neto masa 25.2kg; Napajanje 220VAc 170W; U kompletu sa nosačem za zidnu montažu i HDMI kablom; Opciono nosač za stonu montažu	€ 1.120,00	€ 1.866,67	4K HDMI/VGA 178 24/7 VESA 6ms Metal housing		PP	

Video Wall segmenti i oprema

Kod	OPIS	VP	MSRP		Slika		
LS460UCM-EF	46" Monitor za video wall; Industrijski DID LCD panel; Za 24/7 upotrebu u kontrolnim centrima; Ultra tanak okvir - 3.5mm od okvira-do-okvira (2.3mm na levoj i gornjoj margini, 1.2mm na desnoj i donjoj margini); Sa Splicing funkcijom do 4x4 displeja; Rezolucija 1920 x 1080; Direct LED pozadinsko osvetljenje; Osvetljaj 500cd/m²; Kontrast 1200:1; Ugao gledanja 178°/178°; Odziv 8ms; MTBF 50.000h; Ulazi VGA(D-Sub)×1, CVBS(BNC)×1, DVI-D×1, HDMI×1, RS232(RJ45)×1, USB×2, Audio in×1, IR×1; Izlazi: CVBS×1, RS232(RJ45)×1, HDMI×2, VGA×1, Audio out×1; Napajanje 90~264VAC 110W maks; Dimenzije 1022.0×576.6×107.3mm; Neto masa 21kg; VESA 600×400mm; Podržava upravljanje putem RS232 konekcije		€ 1.770,00			Novi Lager	
FS-A046FUS-B	Zidni nosač; Za LS460UCM-EF video wall segment;					PP	
LS460-WS	Zidni nosač sa mehanizmom za izbacivanje; Za LS460UCM-EF video wall segment;					Lager	

Digital Signage monitori

Kod	OPIS	VP	MSRP		Slika		
LDV55-SAI200	55" samostojeći Digital Signage monitor; Industrijski IPS panel A+ klase; 5mm kaljeno zaštitno staklo; Odnos 9:16; Rezolucija 1080×1920; 16.7 miliona boja (8 bitni); Osvetljaj 400nits; Kontrast 1200:1; Ugao gledanja 178°/178°; Odziv 8ms; Za 24/7 upotrebu; RJ45 mrežni interface; WiFi; RS232; 2x USB 2.0; Zvučnici 2x 2W; Cortex-A7 1.5GHz Quad Core CPU; RAM 1GB(2GB opciono); Skladište 8GB; Multimedia - mp4, avi, mov, asf, wmv, rm, rmvb, mkv, jpg, jpeg, gif, bmp, png, mp3, wma, wav, pdf; OS Android 4.4 (Android 5.1 opciono); Podržava Dahau MPS software (upravljanje sa do 20 DS monitora besplatno); Kapacitet dekodiranja 1ch@4K ili 4ch@1080P; Sa daljinskim upravljačem; Dimenzije 2068.3 ×788.3 ×63.6mm; Masa 108.4kg; Napajanje 100 240VAc (+/- 10%), 50/60Hz, 59.3W		€ 2.523,00			Novi Lager	

HDD-ovi

Kod	OPIS	VP	MSRP		Slika		
ST1000VX001	HDD 1TB; Seagate/Dahua SkyHawk surveillance serija; projektovan za upotrebu u DVR-ovima i NVR-ovima; Za 24/7 aplikacije sa do 32 HD kamere; 1.000.000 sati MTBF; 3.5", 1TB, 64MB cache, SATA 6Gb/s	€ 42,00	€ 70,00			Na lageru	Novo
ST2000VX007	HDD 2TB; Seagate/Dahua SkyHawk Lite surveillance serija; projektovan za upotrebu u DVR-ovima i NVR-ovima; Za 24/7 aplikacije; 3.5", 2TB, 64MB cache, SATA 6Gb/s	€ 52,00	€ 86,67				
ST2000VX003	HDD 2TB; Seagate/Dahua SkyHawk surveillance serija; projektovan za upotrebu u DVR-ovima i NVR-ovima; Za 24/7 aplikacije sa do 32 HD kamere; 1.000.000 sati MTBF; 3.5", 2TB, 64MB cache, SATA 6Gb/s	€ 57,00	€ 95,00				
ST3000VX006	HDD 3TB; Seagate/Dahua SkyHawk surveillance serija; projektovan za upotrebu u DVR-ovima i NVR-ovima; Za 24/7 aplikacije sa do 32 HD kamere; 1.000.000 sati MTBF; 3.5", 3TB, 64MB cache, SATA 6Gb/s	€ 68,00	€ 113,33				
ST4000VX000	HDD 4TB; Seagate/Dahua SkyHawk surveillance serija; projektovan za upotrebu u DVR-ovima i NVR-ovima; Za 24/7 aplikacije sa do 32 HD kamere; 1.000.000 sati MTBF; 3.5", 4TB, 64MB cache, SATA 6Gb/s, R/V (Rotational Vibration) Sensor; Pogodan za primenu u multi-drive RAID konfiguracijama	€ 94,00	€ 156,67				
ST6000VX003	HDD 6TB; Seagate/Dahua SkyHawk surveillance serija; projektovan za upotrebu u DVR-ovima i NVR-ovima; Za 24/7 aplikacije sa do 32 HD kamere; 1.000.000 sati MTBF; 3.5", 6TB, 128MB cache, SATA 6Gb/s, R/V (Rotational Vibration) Sensor; Pogodan za primenu u multi-drive RAID konfiguracijama	€ 152,00	€ 253,33				
ST6000VX001	HDD 6TB; Seagate/Dahua SkyHawk surveillance serija; projektovan za upotrebu u DVR-ovima i NVR-ovima; Za 24/7 aplikacije sa do 64 HD kamere; 1.000.000 sati MTBF; 3.5", 6TB, 256MB cache, SATA 6Gb/s, R/V (Rotational Vibration) Sensor; Pogodan za primenu u multi-drive RAID konfiguracijama	€ 158,00	€ 263,33			Novo	
ST8000VX0002	HDD 8TB; Seagate/Dahua SkyHawk surveillance serija; projektovan za upotrebu u DVR-ovima i NVR-ovima; Za 24/7 aplikacije sa do 64 HD kamere; 1.000.000 sati MTBF; 3.5", 8TB, 256MB cache, SATA 6Gb/s, R/V (Rotational Vibration) Sensor; Pogodan za primenu u multi-drive RAID konfiguracijama	€ 199,00	€ 331,67				

Micro SD kartice

Kod	OPIS	VP	MSRP		Slika		
PFM110	Micro SD memorijska kartica kapaciteta 16GB ; Class 10 , UHS-I (reading speed: 90MB/s, writing speed: 20MB/s); TLC flash (triple level cell flash)	€ 7,20	€ 8,00			Lager	
PFM111	Micro SD memorijska kartica kapaciteta 32GB ; Class 10 , UHS-I (reading speed: 90MB/s, writing speed: 20MB/s); TLC flash (triple level cell flash)	€ 13,50	€ 15,00			Lager	
PFM112	Micro SD memorijska kartica kapaciteta 64GB ; Class 10 , UHS-I (reading speed: 90MB/s, writing speed: 20MB/s); TLC flash (triple level cell flash)	€ 25,20	€ 28,00			Lager	

Mrežna oprema

Kod	OPIS	VP	MSRP		Slika		
PFS3005-5GT	5-portni gigabitni switch; 5x 10/100/1000 Base-T; Switching Capacity 10G; Packet Forwarding Rate 7.44Mpps; Dimenzije 100mm×64mm×25mm; Masa 170g	€ 16,00	€ 26,67			Lager	
PFS3008-8GT	8-portni gigabitni switch; 8x 10/100/1000 Base-T; Switching Capacity 16G; Packet Forwarding Rate 11.9Mpps; Dimenzije 186mm×106mm×33mm; Masa 508g	€ 28,00	€ 46,67			Lager	
PFS3024-24GT	24-portni gigabitni switch; 24x 10/100/1000 Base-T; Switching Capacity 48G; Packet Forwarding Rate 35.7Mpps; Dimenzije 294mm x 178mm x 44mm; Masa 1.43kg	€ 94,20	€ 157,00			Novi	
PFS3005-4P-58	PoE 4-portni switch; 1x 10/100 Base-T; 4x 10/100 Base-T (PoE); PoE budžet 58W; Do 30W po portu maksimalno; U skladu sa IEEE802.3af i IEEE802.3at; MAC auto study and aging, MAC address list capacity 1K; Dva moda rada - Default i Extend (Default -kao standardni switch, Extend - PoE portovi se ponašaju kao 10Mbps portovi sa dometom do 250m i komuniciraju sa Uplink portom) ; Napajanje jedinica 220VAc/51VDC; Radna temperatura -10°C~50°C; Dim. 100mm×100mm×26mm; Masa 259g	€ 28,00	€ 46,67			Lager	
PFS3006-4ET-60	PoE 4-portni switch; 2x 10/100Mbps Uplink; 4x 10/100 Base-T (PoE); PoE budžet 60W; Do 60W na portu 1; Do 30W na portovima 2-4; U skladu sa IEEE802.3af, IEEE802.3at i Hi-PoE; Napajanje jedinica 220VAc/48-57VDC; Radna temperatura -10°C~55°C; Dim. 130mm×85mm×26mm; Masa 300g	€ 30,00	€ 50,00			Na lageru	
PFS3008-8ET-60	8-portni switch sa 4 PoE porta; 4x 10/100 Base-T (PoE) + 4x 10/100 Base-T; PoE budžet 60W; Do 60W na portu 1; Do 30W na portovima 2-4; U skladu sa IEEE802.3af, IEEE802.3at i Hi-PoE; Napajanje jedinica 220VAc/48-57VDC; Radna temperatura -10°C~55°C; Dim. 190mm×100mm×30mm; Masa 480g	€ 39,00	€ 65,00			Na lageru	
PFS3009-8ET-96	PoE 8-portni switch; 1x 10/100 Base-T; 8x 10/100 Base-T (PoE); PoE budžet 96W; Do 60W po portu maksimalno (Port 1); U skladu sa IEEE802.3af i IEEE802.3at i Hi-PoE; Switching Capacity 1.8Gbps; Packet Forwarding Rate 1.34Mpps; Packet Buffer Memory 768K; MAC auto study and aging; MAC address list capacity 2K; MDI/MDIX self-adaptation; Napajanje jedinica 220VAc/48-57VDC; Radna temperatura -10°C~50°C; Dim. 190mm× 100mm× 30mm; Masa 480g	€ 43,00	€ 71,67			Na lageru	
PFS3008-8GT-60	8-portni gigabitni switch sa 4 PoE porta; 4x 10/100/1000 Base-T (PoE) + 4x 10/100/1000 Base-T; PoE budžet 60W; Do 60W na portu 1; Do 30W na portovima 2-4; U skladu sa IEEE802.3af, IEEE802.3at i Hi-PoE; Napajanje jedinica 220VAc/48-57VDC; Radna temperatura -10°C~55°C; Dim. 190mm×100mm×30mm; Masa 490g	€ 48,00	€ 80,00			Novi	
PFS3010-8ET-96	PoE 8-portni switch; 2x 10/100/1000 Base-T; 8x 10/100 Base-T (PoE); PoE budžet 96W; Do 60W po portu maksimalno (Port 1); U skladu sa IEEE802.3af i IEEE802.3at i Hi-PoE; Switching Capacity 5.6Gbps; Packet Forwarding Rate 4.17Mpps; Packet Buffer Memory 4MB; MAC auto study and aging; MAC address list capacity 16K; MDI/MDIX self-adaptation; Napajanje jedinica 220VAc/48-57VDC; Radna temperatura -10°C~50°C; Dim. 190mm× 100mm× 30mm; Masa 490g	€ 50,00	€ 83,33			Na lageru	

Mrežna oprema

Kod	OPIS	VP	MSRP		Slika		
PFS3106-4P-60	Industrijski PoE 4-portni switch; 1x 100/1000 Base-x; 1x 10/100/1000 Base-T; 4x 10/100 Base-T (PoE); PoE budžet 60W; Do 30W po portu maksimalno; U skladu sa IEEE802.3af i IEEE802.3at; MAC auto study and aging, MAC address list capacity 8K; Napajačka jedinica 220VAc/53VDC; Radna temperatura -30°C~65°C; Dimenzije 150mm×100mm×30mm; Masa 480g	€ 48,00	€ 80,00			Na lageru	
PFS3110-8P-96	Industrijski PoE 8-portni switch; 1x 100/1000 Base-x; 1x 10/100/1000 Base-T; 8x 10/100 Base-T (PoE); PoE budžet 93W; Do 30W po portu maksimalno; U skladu sa IEEE802.3af i IEEE802.3at; MAC auto study and aging, MAC address list capacity 8K; Napajačka jedinica 220VAc/53VDC; Radna temperatura -30°C~65°C; Dimenzije 150mm×100mm×42mm; Masa 540g	€ 69,00	€ 115,00			Na lageru	
PFS3211-8GT-120	Industrijski PoE 8-portni switch; 2x 100/1000 Base-x; 1x 10/100/1000 Base-T; 8x 10/100/1000 Base-T (PoE); PoE budžet 120W; Do 60W po portu maksimalno; U skladu sa IEEE802.3af, IEEE802.3at i Hi-PoE; Switching Capacity 33Gbps; Packet Forwarding Rate 16.37Mpps; Napajačka jedinica 220VAc/53VDC; Radna temperatura -30°C~65°C; Dimenzije 150mm×110mm×42mm; Masa 620g	€ 154,80	€ 258,00			Novi!	
PFS4206-4P-96	Industrijski Layer 2 upravljivi PoE 4-portni switch; 2x 1000 Base-X (SFP); ; 1X 10/100/1000 Base-T (Hi-PoE/PoE+/PoE); 3X 10/100 Base-T (PoE+/PoE); PoE budžet 96W; Do 30W po portu maksimalno; U skladu sa IEEE802.3af, IEEE802.3at i Hi-PoE; MAC auto study and aging, MAC address list capacity 8K; Switching Capacity 6.8Gbps; 802.1Q Standard VLAN; Ring network: Support private fast ring network, recovery time <=50ms; Podržava Spanning Tree, STP/RSTP; Podržava Loop Detection; Napajačka jedinica 220VAc/48-57VDC; Radna temperatura -30°C~65°C; Dimenzije 150mm×100mm×30mm; Masa 480g	€ 76,00	€ 126,67			Na lageru	
PFS4206-4P-120	Industrijski Layer 2 upravljivi PoE 4-portni switch; 2x 1000 Base-X (SFP); ; 1X 10/100/1000 Base-T (Hi-PoE/PoE+/PoE); 3X 10/100 Base-T (PoE+/PoE); PoE budžet 120W; Do 30W po portu maksimalno; U skladu sa IEEE802.3af, IEEE802.3at i Hi-PoE; MAC auto study and aging, MAC address list capacity 8K; Switching Capacity 6.8Gbps; 802.1Q Standard VLAN; Ring network: Support private fast ring network, recovery time <=50ms; Podržava Spanning Tree, STP/RSTP; Podržava Loop Detection; Napajačka jedinica 220VAc/48-57VDC; Radna temperatura -30°C~65°C; Dimenzije 150mm×100mm×30mm; Masa 480g	€ 85,80	€ 143,00			Novi! Na lageru	
PFL2106-4ET-96	Industrijski ePoE 4-portni switch; Podržava ePoE do 800m dužine uz kompatibilne Dahua proizvode; 1x 100/1000 Base-X; 1x 10/100/1000 Base-T; 4*10/100 Base-T; PoE budžet 96W; Do 60W po portu maksimalno (Port 4); Do 30W po portu za portove 1-3; Switching Capacity 6.8Gbps; Packet Forwarding Rate 3.57Mpps; Napajačka jedinica 220VAc/48-57VDC; Radna temperatura -30°C~65°C; Dimenzije 150mm×100mm×30mm; Masa 480g	€ 85,00	€ 141,67			Na lageru	
LR2218-16ET-240	ePoE 16-portni switch; Podržava ePoE do 800m dužine uz kompatibilne Dahua proizvode; Layer 2 web upravljivi; Podržava EPoE na portovima 1-8; Podržava ePoE kompatibilne EOC uređaje na portovima 1-8; 2x 10/100/1000 Base-T; 2x 1000 Base-X (Combo); 16x 10/100 Base-T (PoE); PoE budžet 240W; Do 60W po portu maksimalno (Port 1 i 2); Do 30W za ostale portove; Switching Capacity 8.8Gbps; Packet Forwarding Rate 5.36Mpps; Napajanje 100-240VAc; Radna temperatura -30°C~65°C; Dimenzije 440mm x300mm x44mm; Masa 3.12kg	€ 205,00	€ 341,67			Na lageru	
LR2226-24ET-360	ePoE 24-portni switch; Podržava ePoE do 800m dužine uz kompatibilne Dahua proizvode; Layer 2 web upravljivi; Podržava EPoE na portovima 1-8; Podržava ePoE kompatibilne EOC uređaje na portovima 1-8; 2x 10/100/1000 Base-T; 2x 1000 Base-X (Combo); 24x 10/100 Base-T (PoE); PoE budžet 360W; Do 60W po portu maksimalno (Port 1 i 2); Do 30W za ostale portove; Switching Capacity 8.8Gbps; Packet Forwarding Rate 6.55Mpps; Napajanje 100-240VAc; Radna temperatura -30°C~65°C; Dimenzije 440mm x300mm x44mm; Masa 3.12kg	€ 265,00	€ 441,67			Na lageru	
PFS3117-16ET-135	16-portni PoE switch; 1x 10/100/1000 Base-T (Combo); 1x 1000 Base-X (Combo); 16x 10/100 Base-T (PoE); PoE budžet 135W; Do 60W po portu maksimalno (za port 1 i 2); U skladu sa IEEE802.3af, IEEE802.3at i HiPoE; 4 moda rada - Default, Isolation, CCTV i Extender Mode; Switching Capacity 5.2G; Packet Forwarding Rate 3.87Mpps; Napajanje 220VAc; Radna temperatura -10°C~55°C; Dim. 1U 340mm x200mm x43mm;	€ 154,20	€ 257,00			Na lageru	

Mrežna oprema

Kod	OPIS	VP	MSRP		Slika		
PFS3125-24ET-190	24-portni PoE switch; 1x 10/100/1000 Base-T (Combo); 1x 1000 Base-X (Combo); 24x 10/100 Base-T (PoE); PoE budžet 190W; Do 60W po portu maksimalno (za port 1 i 2); U skladu sa IEEE802.3af, IEEE802.3at i HiPoE; 4 moda rada - Default, Isolation, CCTV i Extender Mode; Switching Capacity 6.8G; Packet Forwarding Rate 5.06Mpps; Napajanje 220VAc; Radna temperatura -10°C~55°C; Dim. 1U 340mm x200mm x43mm;	€ 190,80	€ 318,00			Na lageru	
PFS4218-16ET-190	Layer 2 upravljivi 16-portni PoE switch; 2x 10/100/1000 Base-T (Combo); 2x 1000 Base-X (Combo); 16x 10/100 Base-T (PoE); PoE budžet 190W; Do 60W po portu maksimalno (za port 1 i 2); U skladu sa IEEE802.3af, IEEE802.3at i HiPoE; Switching Capacity 8.8G; Packet Forwarding Rate 5.36Mpps; Podržava spanning tree protocol STP/RSTP; Napajanje 220VAc; Radna temperatura -10°C~55°C; Dim. 1U 440mm x300mm x44mm; Masa 3.51g	€ 165,00	€ 275,00			Na lageru	
PFS4218-16ET-240	Layer 2 upravljivi 16-portni PoE switch; 2x 10/100/1000 Base-T (Combo); 2x 1000 Base-X (Combo); 16x 10/100 Base-T (PoE); PoE budžet 240W; Do 60W po portu maksimalno (za port 1 i 2); U skladu sa IEEE802.3af, IEEE802.3at i HiPoE; Switching Capacity 8.8G; Packet Forwarding Rate 5.36Mpps; Podržava spanning tree protocol STP/RSTP; Napajanje 220VAc; Radna temperatura -10°C~55°C; Dim. 1U 440mm x300mm x44mm; Masa 3.51g	€ 189,60	€ 316,00			Na lageru	
PFS4226-24ET-240	Layer 2 upravljivi 24-portni PoE switch; 2x 10/100/1000 Base-T (Combo); 2x 1000 Base-X (Combo); 24x 10/100 Base-T (PoE); PoE budžet 240W; Do 60W po portu maksimalno (za port 1 i 2); U skladu sa IEEE802.3af, IEEE802.3at i HiPoE; Switching Capacity 8.8G; Packet Forwarding Rate 6.66Mpps; Podržava spanning tree protocol STP/RSTP; Napajanje 220VAc; Radna temperatura -10°C~55°C; Dim. 1U 440mm x300mm x44mm; Masa 3.51g	€ 195,00	€ 325,00			Na lageru	
PFS4226-24ET-360	Layer 2 upravljivi 24-portni PoE switch; 2x 10/100/1000 Base-T (Combo); 2x 1000 Base-X (Combo); 24x 10/100 Base-T (PoE); PoE budžet 360W; Do 60W po portu maksimalno (za port 1 i 2); U skladu sa IEEE802.3af, IEEE802.3at i HiPoE; Switching Capacity 8.8G; Packet Forwarding Rate 6.66Mpps; Podržava spanning tree protocol STP/RSTP; Napajanje 220VAc; Radna temperatura -10°C~55°C; Dim. 1U 440mm x300mm x44mm; Masa 3.51g	€ 225,00	€ 375,00			Na lageru	
PFS4228-24P-370	Layer 2 upravljivi 24-portni Gigabitni PoE switch; 2x 10/100/1000 Base-T; 2x 1000 Base-X; 24x 10/100/1000 Base-T (PoE); PoE budžet 370W; Do 30W po portu maksimalno; U skladu sa IEEE802.3af i IEEE802.3at; Switching Capacity 24.8G; Packet Forwarding Rate 9.52Mpps; Podržava spanning tree protocol STP/RSTP; Napajanje 220VAc; Radna temperatura -10°C~55°C; Dim. 1U 442mm x263mm x44.5mm; Masa 3.73g	€ 400,00	€ 666,67			Na lageru	
PFS4428-24GT-370	Layer 2 upravljivi 24-portni Gigabitni PoE switch; 4x 1000 Base-X; 24x 10/100/1000 Base-T (PoE); PoE budžet 370W; Do 30W po portu maksimalno; U skladu sa IEEE802.3af i IEEE802.3at; Switching Capacity 56Gbps; Packet Forwarding Rate 41.66Mpps; Podržava spanning tree protocol STP/RSTP; Napajanje 220VAc; Radna temperatura -10°C~55°C; Dim. 1U 440mm x260mm x44mm; Masa 3.85kg	€ 400,00	€ 666,67			Na lageru	
S3000-16X	16-portni Fiber switch; 16x 100Mbps SFP fiber port; 2x 1000Mbps Combo port; U skladu sa IEEE802.3, IEEE802.3u, IEEE802.3ab/z i IEEE802.3X; Podržava WEB, SNMP (v1/v2c), link aggregation, Port isolation, speed limit, mirroring, 802.1Q VLAN, Anti-MAC address flooding; Napajanje 220VAc; Radna temperatura -10°C~55°C; Dimenzije 1U 440mmx43.5mmx300mm; Masa 3.5g	€ 275,00	€ 458,33			Na lageru	
PFS5424-24T	Multi layer upravljivi 24-portni gigabitni switch; 24x 10/100/1000Mbps self-adaptive porta; 4x 1000Mbps Combo port; Backplane bandwidth 128Gbps; Packet forward rate 35.7Mpps; MAC entry 8K; VLAN entry 4K; Pasivno hlađenje; Napajanje 220VAc; Radna temperatura -25°C~55°C; Dimenzije 1U 440mmx300mmx44mm	€ 430,00	€ 716,67			Na	
PFS5924-24X	L2+ upravljivi 24-portni gigabitni switch; 1000M SFP port x 16; Combo 1000BASE-T/SFP port x 8; Konzolni port; Switching Capacity 350Gbps; Packet forward rate 35.7Mpps; Port-based VLAN; 802.1Q Standard VLAN; MAC-based VLAN; Protocol-based VLAN; Spanning Tree - STP, RSTP, MSTP; Napajanje 220VAc; Radna temperatura -25°C~55°C; Dimenzije 1U 440(L)x285(W)x44.5(H)mm; Masa 5kg; Napajanje 220VAc 50W	€ 500,00	€ 833,33			Na lageru	

Mrežna oprema

Kod	OPIS	VP	MSRP		Slika		
PFT1300	PoE ekstender; 1x 10/100 Base-T PoE ulazni port; 1x 10/100 Base-T PoE port za konekciju kamere; 1x 10/100 Base-T PoE port ka sledećem uređaju; Kaskadno vezivanje do 2 ekstendera u kombinaciji sa PFT1200 High PoE Injectorom na početku niza; Potrošnja ≤3W; Dimenzije 79mm×52mm×23mm; Masa 57g; Nazidna montaža ili montaža na DIN šinu	€ 20,00	€ 33,33			Lager	
TAM1GT1GT-30	PoE+ Midspan; 1x10/100/1000 Base-T port ulazni port; 1x 10/100/1000 Base-T PoE ka kameri ili ekstenderu; 30W PoE; LED indikacija stanja; 220VAc napajanje; Dimenzije 132.3mm×60mm×33mm; Masa 250g; Nazidna montaža	€ 23,00	€ 38,33			Lager	
PFT1200	High PoE Midspan; 1x10/100/1000 Base-T port ulazni port; 1x 10/100/1000 Base-T PoE ka kameri ili ekstenderu; 60W PoE; LED indikacija stanja; 220VAc napajanje; Dimenzije 150mm×70mm×39mm; Masa 390g; Nazidna montaža	€ 34,00	€ 56,67			Lager	
PFT3910	Industrijski SFP modul; 155Mbps; Single mode-mode 1310/1550nm; Single fiber bi-directional transmission; 20km; LC konektor; Radna temperatura -40°C~85°C	€ 20,00	€ 33,33			Lager	
PFT3920	Industrijski SFP modul; 155Mbps; Single mode-mode 1550/1310nm; Single fiber bi-directional transmission; 20km; LC konektor; Radna temperatura -40°C~85°C	€ 23,00	€ 38,33			Lager	
PFT3950	Industrijski SFP modul; 1.25Gbps; Multi-mode 850nm; Double fiber; 500m; LC konektori; Radna temperatura -40°C~85°C;	€ 22,00	€ 36,67			Lager	
PFT3960	Industrijski SFP modul; 1.25Gbps; Single mode-mode 1310/1550nm; Single fiber bi-directional transmission; 20km; LC konektor; Radna temperatura -40°C~85°C	€ 24,00	€ 40,00			Lager	
PFT3970	Industrijski SFP modul; 1.25Gbps; Single mode-mode 1550/1310nm; Single fiber bi-directional transmission; 20km; LC konektor; Radna temperatura -40°C~85°C	€ 36,00	€ 60,00			Lager	

Dodatna oprema; Adapteri i nosači za analogne, IP i HDCVI kamere

Kod	OPIS	VP	MSRP		Slika		
PFA100	Adapter ploča za montažu kamere na zidni ili plafonski nosač; Dimenzije Φ150.8mm x 37mm; Aluminijum; Nosivost 3kg; Masa 0.21kg	€ 4,50	€ 7,50			Lager	
PFA101	Adapter ploča za montažu kamere na zidni ili plafonski nosač; Dimenzije Φ159mm x 35mm; Aluminijum; Nosivost 3kg; Masa 0.24kg	€ 4,50	€ 7,50			Lager	
PFA103	Adapter ploča za montažu kamere na zidni ili plafonski nosač; Dimenzije Φ133mm x 37mm; Aluminijum; Nosivost 3kg; Masa 0.13kg	€ 4,50	€ 7,50			Lager	
PFA12A	Kutija za smeštaj kablova i konektora; Od plastike; Masa 100g; Nosivost 3kg; Dimenzije 210.9mmx97.5mmx35mm	€ 3,00	€ 5,00			Lager	
PFA121-V2	Kutija za smeštaj kablova i konektora; Od aluminijuma; Masa 500g; Nosivost 3kg; Dimenzije 134mm(L) x 134mm(W) x 53.5mm(H)	€ 10,00	€ 16,67			Lager	

Dodatna oprema; Adapteri i nosači za analogne, IP i HDCVI kamere

Kod	OPIS	VP	MSRP		Slika		
PFA122-V2	Kutija za smeštaj kablova i konektora; Za nazidnu montažu; Od aluminijuma; Masa 500g; Nosivost 3kg; Dimenzije 134mm(L) x 134mm(W) x 53.5mm(H)	€ 10,00	€ 16,67			Lager	
PFA130-E	Adapter za nazidnu montažu; Od aluminijuma; Masa 350g; Nosivost 3kg; Dimenzije Ø124mmx41mm	€ 7,00	€ 11,67			Lager	
PFA13A-E	Adapter za nazidnu montažu; Od aluminijuma; Masa 160g; Nosivost 1kg; Dimenzije Ø 96.8mm x 93.5mm (V)	€ 4,50	€ 7,50			Lager	
PFA13B	Adapter za nazidnu montažu; Od aluminijuma; Masa 160g; Nosivost 1kg; Dimenzije Ø 96.8mm x 93.5mm (V)	€ 4,50	€ 7,50			Lager	
PFA132	Adapter za nazidnu montažu; Od aluminijuma; Masa 600g; Nosivost 3kg; Dimenzije 155mm x 155mm x 39mm	€ 10,50	€ 17,50			Lager	
PFA134 (135)	Adapter za nazidnu montažu; Od aluminijuma; Masa 220g; Nosivost 1kg; Dimenzije Ø 90mm x 35mm (V)	€ 4,50	€ 7,50			Lager	
PFA136	Adapter za nazidnu montažu; Od aluminijuma; Masa 180g; Nosivost 1kg; Dimenzije Ø 110mm x 33.5mm (V)	€ 4,50	€ 7,50			Lager	
PFA137	Adapter za nazidnu montažu; Od aluminijuma; Masa 180g; Nosivost 1kg; Dimenzije Ø 122mm x 28.5mm (V)	€ 4,50	€ 7,50			Lager	
PFA139	Adapter za nazidnu montažu; Od aluminijuma; Masa 160g; Nosivost 1kg; Dimenzije Ø 108mm x 33.8mm (V)	€ 4,50	€ 7,50			Lager	
G3/4" water joint	Kablovska uvodnica za upotrebu s Dahua kutijama i adapterima	€ 1,00	€ 1,67			Lager	
PFA120	Back box za montažu speed dome kamera; Od aluminijuma; Dimenzije 115.0mmx160.0mmx38.8mm; Nosivost 7kg; Masa 0.53kg	€ 7,00	€ 11,67			Lager	
PFA140	Kutija za smeštaj kablova, konektora i napojne jedinice; Pogodna za montažu dodatne opreme speed dome kamera; Konstrukcija od livenog aluminijuma; Masa 1,7kg; nosivost do 8kg; Dimenzije 297mmx 248mm x 107mm; IP66 stepen zaštite; U kompletu sa kablovskim uvodnicama; Pogodna za montažu na zid, na stub uz dodatni adapter PFA150 ili na ugao objekta uz dodatni adapter PFA151	€ 50,00	€ 83,33			Lager	
PFA150	Adapter za montažu kamere na stub; Odgovara speed dome kamerama montiranim zidni nosač; Dimenzije 130.4mm x 170mm x 45mm; Pogodan za stubove Ø80-130mm; Masa 1kg; Nosivost 10kg	€ 11,00	€ 18,33			Lager	
PFA151	Adapter za montažu zidnog nosača na ugao; Dimenzije 243mm x 170mm x 138mm; Masa 1,7kg; Nosivost 10kg; Odgovara speed dome kamerama montiranim zidni nosač, i fisknim kamerama	€ 12,50	€ 20,83			Lager	

Dodatna oprema; Adapteri i nosači za analogne, IP i HDCVI kamere

Kod	OPIS	VP	MSRP		Slika		
PFA152-E	Adapter za montažu kamere na stub; Odgovara kamerama montiranim na adaptere PFA130, PFA131, PAA121, PFA122; Dimenzije 117.5mm x 87mm x 21mm; Pogodan za stubove ø80-130mm; Masa 200g; Nosivost 3kg	€ 7,00	€ 11,67			Lager	
PFA200W	Adapter za montažu dome kamera na zid sa zaštitom od padavina; Dimenzije 129.3mm x127mm x147mm; Masa 250g	€ 7,00	€ 11,67			Lager	
PFB121W	Nosač za zidnu montažu box i bullet kamera; Aluminijum; Dimenzije 58mm x 88mm x 190.5mm; Masa 0.24kg; Nosivost 1kg;	€ 5,00	€ 8,33			Lager	
PFB202W	Nosač za zidnu montažu; Od aluminijuma; Masa 0,57kg; Nosivost 1kg; Dimenzije 160mm(W) x 122mm(H) x 76mm(D); Za kamere SD22204I-GC, SD22204T-GN(-W)	€ 6,00	€ 10,00			Lager	
PFB203W	Nosač za zidnu montažu; Od aluminijuma; Masa 0,5kg; Nosivost 1kg; Dimenzije 160mm(W) x 120mm(H) x 76mm(D)	€ 6,00	€ 10,00			Lager	
PFB204W	Nosač za zidnu montažu; Od aluminijuma; Masa 1kg; Nosivost 1kg; Dimenzije 160mm(W) x 122mm(H) x 76mm(D)	€ 6,00	€ 10,00			Lager	
PFB200C	Adapter za montažu u spuštenu plafon; Dimenzije Ø166.0mm x 75.8mm; Nosivost 1kg; Masa 0.32kg;	€ 10,00	€ 16,67			Lager	
PFB201C	Adapter za montažu u spuštenu plafon; Dimenzije Ø211.0mm x 88.0mm; Nosivost 1.5kg; Masa 0.61kg; Za kamere serije HDBW5121 /5220 /5221 /5231 /5421 /5431 /5830/ 8231 /8331 /81200 /81230E-Z i HDBW3231E-Z	€ 11,00	€ 18,33			Lager	
PFB210W	Nosač za zidnu montažu; Od aluminijuma; Masa 0.93kg; Nosivost 3kg; Dimenzije 229.7mm x168.7mm x113.2mm	€ 14,00	€ 23,33			Lager	
PFB300C	Nosač za plafonsku montažu speed dome i dome kamera; Dimezije Ø133.6mm x 235.5mm; Navoj G1 1/2"; Masa 0,75kg; Nosivost 7kg	€ 12,00	€ 20,00			Lager	
PFB302S-V2	Zidni nosač; Konstrukcija od livenog aluminijuma; Dimenzije134mm x 134mm x 187.5mm; Nosivost 3kg; Masa 0.7kg; Koristi se uz adaptere PFA100, PFA101 i PFA104	€ 12,00	€ 20,00			Lager	
PFB602W	Zidni nosač; Konstrukcija od livenog aluminijuma; Dimenzije 109mm x 300mm x 82mm; Nosivost 3kg; Masa 0.7kg; Koristi se uz IPC HFW5221EP-Z-IRA	€ 9,50	€ 15,83			Lager	

Kod	OPIS	VP	MSRP		Slika		
PFH610N-H	Kućište kamere za spoljnu montažu; Stepen zaštite IP66; Bočno otvaranje; Inkorporiran grejač i ventilator; Dimenzije 404mm(L) x 164mm(W) x 132mm(H); Korisne dimenzije 255mm(L) x 90mm(W) x 83mm(H); Dimenzije prednjeg prozora 100(L) x 80(W); Masa 2,4kg; Potrebno napajanje 24VAc 3A	€ 54,00	€ 90,00			DU	
PFH610N-IR	Kućište kamere za spoljnu montažu sa IC LE diodama dometa do 100m; Stepen zaštite IP66; Bočno otvaranje; Inkorporiran grejač i ventilator; Dimenzije 404mm(L) x 164mm(W) x 132mm(H); Korisne dimenzije 255mm(L) x 90mm(W) x 83mm(H); Dimenzija prednjeg prozora Ø50mm; Masa 2,7kg; Potrebno napajanje 24VAc 5A	€ 116,00	€ 193,33			DU	
PFB603W	Nosač kućišta za zidnu ili plafonsku montažu; Od livenog aluminijuma; Masa 990g; Nosivost 3kg; Dimenzije 314mm x 250mm x Ø133mm	€ 7,00	€ 11,67			DU	
PFB600W	Nosač kućišta za zidnu montažu; Od livenog aluminijuma; Masa 270g; Nosivost 3kg; Dimenzije 70mm x 90mm x 193mm	€ 14,00	€ 23,33			DU	

Dodatna oprema; Primo-predajnici

Kod	OPIS	VP	MSRP		Slika		
PFM800-E	Pasivni primo-predajnik HDCVI signala po upredenoj parici; Domet 400m za 720P ili 250m za 1080P HDCVI signal; Kompatibilan sa HDCVI/AHD/TVI/CVBS; Potiskivanje šuma (CMRR) od min. 60dB; Inkorporirna transientna zaštita; Sa muškim BNC konektorom i "push" terminalima; Cena je za par	€ 3,00	€ 5,00			Lager	
PFM800-4K	Pasivni primo-predajnik HDCVI signala po upredenoj parici; Model za 720P/1080P/4MP/5MP/4K rezolucije; Domet 400m za 720P, 250m za 1080P HDCVI signal i 200m za 4MP/5MP/4K HDCVI signal; Kompatibilan sa HDCVI/AHD/TVI/CVBS; Potiskivanje šuma (CMRR) od min. 60dB; Inkorporirna transientna zaštita; Sa muškim BNC konektorom i "push" terminalima; Cena je za par	€ 4,50	€ 7,50			Lager	

Dodatna oprema; Primo-predajnici i zaštite

Kod	OPIS	VP	MSRP		Slika		
PFM801-4MP	Primo-predajnik HDCVI signala i napajanja po UTP kablju; Maksimalni domet 300m; Ulaz 24Vdc ili 36Vdc i HDCVI signal; Izlaz 12Vdc 8W maksimalno i HDCVI signal; Potiskivanje šuma (CMRR) od min. 60dB; Inkorporirna transientna zaštita; Sa muškim BNC konektorom, muškim/ženskim napojnim i RJ45 konektorima; Cena je za par	€ 8,00	€ 13,33			Lager	
PFM809	16-kanalni pasivni primo-predajnik HDCVI signala po upredenoj parici; Domet 400m za 720P ili 250m za 1080P HDCVI signal; Potiskivanje šuma (CMRR) od min. 60dB; Inkorporirna transientna zaštita; Sa 16 ženskih BNC konektora; sa klemama i RJ45 konektorima za parice; Dimenzije 430mmx100mmx44.5mm (1U), rek montaža; Masa 1250g	€ 42,00	€ 70,00			Lager	
PFM790	HDCVI napajački izolator; Sprečava smetnje izazvane napajanjem; Dimenzije 108mmx22mmx20mm	€ 6,00	€ 10,00			Lager	
PFM791	HD video izolator; Sprečava smetnje izazvane razlikom u potencijalu uzemljenja; Dimenzije 42mm x22.5mm x16mm	€ 5,40	€ 9,00			Lager	



Dodatna oprema; PoC i ekstenzeri

Kod	OPIS	VP	MSRP		Slika		
PoC							
PFM810-4K	Primo-predajnik HDCVI signala i napajanja po koaksijalnom kablu; Maksimalni domet 400m; Ulaz 24VDC ili 36VDC i HDCVI signal; Izlaz 12VDC 8W maksimalno i HDCVI signal; Potiskivanje šuma (CMRR) od min. 60dB; Inkorporirna transientna zaštita; Sa muškim BNC konektorom, muskim/ženskim napojnim i ženskim BNC konektorima; Cena je za par	€ 18,00	€ 30,00			Lager	
Ethernet over coax							
LR1002	Ethernet over Coax ePoE pasivni adapter; 1X RJ45 10/100Mbps port, 1x BNC; Radi samo u kombinaciji sa ePoE switch-evina i ePoE IP kamerama; Domet po RG9 kablu 400m/100Mbps, 1000m/10Mbps; U skladu sa IEEE802.3, IEEE802.3u; Radna temperatura -40°C-60°C; Dimenzije 56mm×27mm×21mm; Masa 28.3g	€ 7,80	€ 13,00			Lager	
LR1002-1ET	Ethernet over Coax adapter; 1x 10/100 Mbps Base-TX; 1x BNC; Dometi za RG59B/U kabl: 400m/100Mbps, 1000m/10Mbps; Potrošnja <2W; U skladu sa IEEE802.3af i IEEE802.3at; U skladu sa IEEE802.3, IEEE802.3u, IEEE802.3x; Radna temperatura -30°C-65°C; Dimenzije 79mm×52mm×23mm; Masa 61g; Predajnik	€ 20,40	€ 34,00			Lager	
LR1002-1EC	Ethernet over Coax adapter; 1x 10/100 Mbps Base-TX; 1x BNC; Dometi za RG59B/U kabl: 400m/100Mbps, 1000m/10Mbps; Potrošnja <2W; U skladu sa IEEE802.3af i IEEE802.3at; U skladu sa IEEE802.3, IEEE802.3u, IEEE802.3x; Radna temperatura -30°C-65°C; Dimenzije 79mm×52mm×23mm; Masa 61g; Prijemnik	€ 20,40	€ 34,00			Lager	
Dodatni alarmni modul za DVR-ove							
ARB1606	Alarmni ulazno/izlazni modul za DVR uređaje; 16 alarmnih ulaza/6 alarmnih izlaza; Dodavanje modula putem RS485 konekcije; 2 bitno adresiranje; Dimenzije 97.68mm×90.3mm×33mm	€ 22,00	€ 36,67			Lager	
HDCVI video konvertor							
TP2105	HDCVI video konvertor; Ulaz 1x HDCVI (BNC); Izlaz 1x HDCVI (BNC), 1x CVBS (BNC), 1x HDMI, 1x VGA; 1x RS485 port; Dimenzije 162mm×136.4mm×30mm; Masa 200g; Radna temperatura -10°C ~55°C; Napajanje 12VDC 1A;	€ 53,00	€ 88,33			Lager	
Dodatna oprema; Ekstenderi							
Kod	OPIS	VP	MSRP		Slika		
VGA Ekstender							
PFM710	Pasivni VGA ekstender; Prenos signala do 75m po UTP kablu; Podržava VGA, SVGA, XGA, WSXGA i UXGA rezolucije; 1KV prenaponska zaštita; Dimenzije 88mm×64mm×25mm (iste su za predajnik i prijemnik); Masa 110g (iste je za predajnik i prijemnik); Alu. kućište; Pasivni	€ 31,80	€ 53,00			Lager	
HDMI Ekstender							
PFM700-E	HDMI ekstender; Prenos HD signala do 60m po UTP kablu; Podržava 1080P/ 1080i/ 720P/ 576P/ 576i/ 480P/ 480i rezolucije; HDMI 1.3 kompatibilan; Podržava prenos IC daljinske kontrole; 1KV prenaponska zaštita; Loop trough HDMI ulaz na predajniku; Dimenzije 79.5mm×68mm×16.5mm (iste su za predajnik i prijemnik); Masa 133g (iste je za predajnik i prijemnik); Alu. kućište; Sa napajačkom jedinicom 5VDC (napaja se samo predajnik); Potrošnja 3W (po uređaju)	€ 62,40	€ 104,00			Lager	

Dodatna oprema; Napojne jedinice, mikrofoni i HDCVI baluni

Kod	OPIS	VP	MSRP		Slika		
Mikrofoni							
AM-002	Audio modul - mikrofoni; Potrebno napajanje 12VDC/10mA; Pokrivanje do 100m ² ; U pl. kućištu dimenzija 39.5x31x16mm	€ 5,00	€ 8,33			Lager	
Napojne jedinice							
PFM321D-EN	Dahua napojna jedinica 220VAc/ 12VDC 1A ; Dimenzije 84mmx41mmx26mm; Masa 150g	€ 4,00	€ 6,67			Lager	
PFM320D-015	Dahua napojna jedinica 220VAc/ 12VDC 1.5A ; Radna temperatura 30°C~+70°C; Dimenzije 77.3mmx51.9mmx30.0mm; Masa 95g; Pogodna za montažu u kutije PFA121 i PFA122; Priključne klemme za 220VAc/12Vdc	€ 5,50	€ 9,17			Lager	
S024-1A120200HE	Dahua napojna jedinica 220VAc/ 12VDC 2A ; Utičnog tipa	€ 5,00	€ 8,33			Lager	
PFM320D-EN	Dahua napojna jedinica 220VAc/ 12VDC 2A ; Dimenzije 104mmx45mmx33mm; Masa 170g; Pogodna za montažu u kutija PFA121 i PFA122	€ 5,50	€ 9,17			Lager	
PFM300	Dahua napojna jedinica 220VAc/ 12VDC 2A ; Dimenzije 88mmx37mmx138mm; Masa 160g; Radna temperatura -30°C~+70°C; Prostor za smeštaj konekcija i baluna; Za nazidnu montažu; Od V-0 negorive sive plastike	€ 6,00	€ 10,00			Lager	
SUN-1200300B1	Dahua napojna jedinica 220VAc/ 12VDC 3A ; Dimenzije 84mmx41mmx26mm; Masa 150g	€ 7,00	€ 11,67			Lager	
PFM322	Dahua napojna jedinica 220VAc/ 12VDC 2.8A - 4 izlaza po 0,7A ; Dimenzije 148mmx70mmx31mm; Masa 210g	€ 11,00	€ 18,33			Lager	
PVPS12V5A	Napojna jedinica 220VAc/ 12VDC 5A	€ 10,00	€ 16,67			Lager	
PFM340-5CH	Dahua Napojna jedinica 90~260VAc/ 12VDC 4A ; 5 izlaza sa osiguračkom zaštitom; Zaštita od prenapona, kratkog spoja i preopterećenja; LED indikacija prisustva 220V i LED indikacija rada pojedinačnih izlaza; Do 2.5A po izlazu; U metalnom kućištu 165x165x50mm; masa 0.85 kg	€ 27,50	€ 45,83			Lager	
PFM341-9CH	Dahua Napojna jedinica 90~260VAc/ 12VDC 5A ; 9 izlaza sa osiguračkom zaštitom; Zaštita od prenapona, kratkog spoja i preopterećenja; LED indikacija prisustva 220V i LED indikacija rada pojedinačnih izlaza; Do 2.5A po izlazu; U metalnom kućištu 165x165x50mm; masa 0.9 kg	€ 33,00	€ 55,00			Lager	
BPS12-09-10	Napojna jedinica 90~260VAc/ 12VDC 10A ; 9 izlaza sa osiguračkom zaštitom; Regulacija izlaznog napona u opsegu od 11-13VDC; Zaštita od prenapona, kratkog spoja i preopterećenja; U metalnom kućištu	€ 30,00	€ 50,00			Lager	
BPS12-18-15	Napojna jedinica 90~260VAc/ 12VDC 15A ; 18 izlaza sa osiguračkom zaštitom; Regulacija izlaznog napona u opsegu od 11-13VDC; Zaštita od prenapona, kratkog spoja i preopterećenja; U metalnom kućištu	€ 38,00	€ 63,33			Lager	
BPS12-18-20	Napojna jedinica 90~260VAc/ 12VDC 20A ; 18 izlaza sa osiguračkom zaštitom; Regulacija izlaznog napona u opsegu od 11-13VDC; Zaštita od prenapona, kratkog spoja i preopterećenja; U metalnom kućištu	€ 41,00	€ 68,33			Lager	
PFM920I-5EUN	Dahua CAT5E OFC (Oxygen Free Copper) kabl; PVC izolacija; Pakovanje 305m; Dimenzije pakovanja 360x 360x 220mm; Masa 8.6kg	€ 51,00	€ 85,00			Lager	
PFM930-59N	Dahua RG59B/U koaksijalni kabl; 99.99% OFC (oxygen free copper); PVC izolacija; Pakovanje 200m; Dimenzije pakovanja 662mm x337mm x467mm; Masa 7.2kg	€ 40,00	€ 66,67			Lager	

Kablovi i konektori

Kod	OPIS	VP	MSRP		Slika		
CBRG59 2x075 100m	Kombo kabl, koaksijalni + napajački; RG59+2x0.75mm, CU, pun bakar, kotur od 100m	€ 30,00	€ 50,00			Lager	
CBRG59 2x075 300m	Kombo kabl, koaksijalni + napajački; RG59+2x0.75mm, CU, pun bakar, kotur od 300m	€ 88,00	€ 146,67			Lager	
RG59 100m CCA	RG59 kabla; Kotur od 100m; CCA	€ 10,00	€ 16,67			Lager	
CBRG59 2x075 100m CCA	Kombo kabl, koaksijalni + napajački; RG59+2x0.75mm, CCA, kotur od 100m	€ 19,00	€ 31,67			Lager	
CBRG59 2x075 305m CCA	Kombo kabl, koaksijalni + napajački; RG59+2x0.75mm, CCA, kotur od 305m	€ 58,00	€ 96,67			Lager	
DG01	DC Napojni konektor muški	€ 0,20	€ 0,33			Lager	
DG02	DC Napojni konektor ženski	€ 0,20	€ 0,33			Lager	
DC-101N	Konektor napajanja; Provodnici sa jedne strane, DC napojni konektor muški sa druge strane	€ 0,22	€ 0,37			Novo	
DC-102N	Konektor napajanja; Provodnici sa jedne strane, DC napojni konektor ženski sa druge strane	€ 0,22	€ 0,37			Novo	
DC-102R	Razdelnik napajanja za dve kamere	€ 0,70	€ 1,17			Lager	
DC-104R	Razdelnik napajanja za četiri kamere	€ 1,00	€ 1,67			Lager	
DC-108R	Razdelnik napajanja za osam kamera	€ 1,30	€ 2,17			Lager	
BNC-L105-59	BNC konektor krimp; Za kabl RG59	€ 0,25	€ 0,42			Lager	

Napomena: Sve cene su bez PDV-a. Obračunavamo prodajni kurs naše poslovne banke.